

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI - 110001

No.F6/DFS/MS/GH/2024/ 25.5

Dated: 25/06/2024

FIRE SAFETY CERTIFICATE

Certified that the D. Suites Guest House located at 3311-41, Gali Hari Mandir, Pahar ganj, New Delhi comprised of Ground floor (02 guest rooms + reception), 1st floor to 3rd floor (05 guest rooms at each floor), 4th floor not in use as per affidavit dated 26.12.2019 total 17 guest rooms up to third floor only was earlier granted FSC by this department vide letter No. F6/DFS/MS/GH/2021/126 dated 08/03/21. Now, the premises was re-inspected by the officer concerned of this department on 18/06/24 in the presence of Manager and found that the said guest house building has deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Residential, Sub Division-A-1 Ground floor (02 guest rooms + reception), 1st floor to 3rd floor (05 guest rooms at each floor), total 17 guest rooms up to third floor only and valid up to 31.03.2027 from the date of issue in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued ... 25 06 2024.... New Delhi by.

DIRECTOR Delhi Fire Service

Copy to:-

 The Commissioner, North MCD, Civic Centre, New Delhi. To kindly ensure the occupancy as detailed above and deviation if any.

 The Addl. Commissioner of Police (Lic), First Floor, P.S. Defence Colony New Delhi. ID No. 2024060108585 dated 03/06/24.

3. The Manager, D. Suites Guest House at 3311-14, Gali Hari Mandir, Pahar Ganj, New Delhi.

Condition for the validity of fire safety certificate

- All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.

3. The trained fire fighting staff should be available round the clock.

- The compliance with regards to electrical installation, structural stability, set back area, occupancy and any deviation in construction etc. shall be verified from authority concerned.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. The means of escape shall be kept unobstructed / unlocked for unhindered evacuation in case of an emergency.
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".
- 9. Any flammable material for interior decoration is prohibited.

INSPECTION REPORT

1. Name & address of the building D Suites Guest House, 3311-14, Gali Hari

2. Type of occupancy:- Mandir, Pahar Ganj, New Delhi.

Gr. + 04 Upper floors (total 17 Guest roo

Gr. + 04 Upper floors (total 17 Guest rooms)
Ground floor (02 guest rooms + reception), 1st
Floor to3rd floor (05 guest rooms at each floor).

4th floor not in use as per affidavit of applicant Dated 26.12.2019

3. Type of case:- Renewal

4. Details of previous FSC:- F6/DFS/MS/GH/2021/126 dated 08/03/21.

5. Fire safety directives No.6. Date of inspection:18/06/24

7. Name of the inspecting officer:- Sh. Ravinder Singh (ADO/CC)

8. Name & designation of officer

From the building side:- Manager 9. Year of construction:- 2013

10. Applicant's letter No:- ID No. 2024060108585 dated 03/06/24.

S.No.	Minimum Standards on fire Prevention and fire safety U/R 33	Requirement/ Existing fire safety arrangements	Provided at site	Old Case Remarks MR/NMR		
1.	Access to Building					
	1) Road width	N/A	06 mtr.	N/A		
	2) Gate width	N/A	N/A	N/A		
	3)Width of internal road	N/A	N/A	N/A		
2.	Number, Width Type & Arrangement of Exits					
68	A. Number of staircases					
	1. Upper floors	01 No.	01 No.	MR		
	2. Basements	N/A	N/A	N/A		
	B. Width of staircase			IVA		
	1. Upper floors	1.5 mtr.	1.5 Mtr.	MR		
	2. Basements	N/A	N/A	N/A		
	C. Protection of exits			14/21		
	1. Fire check door	N/A	N/A	N/A		
	2. Pressurization	N/A	N/A	N/A		
	D. No. of continuous staircase to terrace	01	01	MR		
	E. Width of corridor	N/A	N/A	N/A		
	F. Door size	1.0 mtr.	1.0 mtr.	MR		
3.	Compartmentation	a.o ma.	IVIK			
	1) Fire check door	N/A	N/A	27/4		
	2) Sealing of electrical shafts	N/A	N/A	N/A		
	3) Fire rating of shaft door	N/A	N/A	N/A		
	4) Water curtain	N/A	N/A	N/A		
	5) Fire Dampers	N/A	N/A	N/A		
4.	Smoke Management System					
	1) Basements	NA	N/A	T		
	2) Upper floors	12 ACPH	Natural / Exaust	N/A		
			fan	MR		
5.	Fire Extinguishers					
	1) Total numbers	10 Nos.	12 Nos.	100		
	2) Types	ABC & CO2	ABC & CO2	MR MR		



	3) ISI marking		Provided	M	
	3) ISI marking	Required	Piovided		
6.	First-Aid Hose Reel		1		
	1) Total number of eachfloor	01	01	MR	
	2) Length of hose reel hose	30 mtr.	30 mtr.	MR	
п	3) Nozzle diameter	05 mm	05 mm	MR	
7.	Automatic Fire Detection & Alarming System				
	1) Type of detectors CO Type	Required	Provided	MR	
	2) Location of main panel	Gr. floor	Provided	MF	
	3) Location of repeater panel	N/A	N/A	N/A	
	4) Alternate source of power	Required	Provided	MR	
4.1	5) Hooter's Location	Gr. floor	Provided	MF	
8.	MOEFA	N/A	Provided	MF	
9.	Public Address System	N/A	Provided	MR	
10.	Automatic Sprinkler System N/A Provided				
	1) Basement	N/A	N/A	N/A	
	2) Upper floors	N/A	N/A	N/A	
	Sprinkler above false ceiling	N/A	N/A	N/A	
11.	Internal Hydrants				
	1) Size of riser/down-comer	N/A	N/A	N/A	
	2) Number of hydrants per floor	N/A	N/A	N/A	
12.20	3) Hose box	N/A	N/A	N/A	
12.	Yard Hydrants				
	1) Total number of hydrants	N/A	N/A	N/A	
12	2) Hose box	N/A	N/A	N/A	
13.	Pumping Arrangement			14/2	
	1) Ground level	N/A	N/A	NI/	
	a) Discharge of main pump	N/A	N/A	N/A	
	b) Head of main pump	N/A	N/A	N/	
	c) Number of main pump	N/A	N/A	N/A	
	d) Jockey pump out put	N/A	N/A	N/A	
	e) Jockey pump head	N/A	N/A	N/A	
	f) Stand by pump output	N/A	N/A	N/A	
	g) Stand by pump head	N/A	N/A	N/A	
	h) Auto starting/Manual stopping	N/A	N/A	N/A	
	2) Terrace level	I THE TAX I ST			
	a) Discharge of pump	450 LPM	450 LPM	MI	
	b) Head of pump	30 mtr.	30 mtr.	MI	
	c) Power supply	Required	Provided	MI	
14.	d) Auto starting of pump	Deguined	Provided		
1.44.	Captive Water Storage for F	ire Fighting	- 10 11404	M	
	capacity	N/A	N/A	N/	
	a) Draw-off connection	N/A	N/A	NT.	
	b) Fire service inlet	N/A	N/A	N/	
		-	14/17	N/	
	c) Access to tank	Required	Provided	M	

	d) Over head tank capacity	5,000 ltr.	5,000 ltr.	MR
15.	Exit Signage.	Required	Provided	MR
16.	Provision of Lifts.			
	a) Pressurization of lift shaft	N/A	N/A	N/A
	b) Pressurization of lift lobby	N/A	N/A	N/A
	c) Communication in lift car	N/A	N/A	N/A
	d) Fireman's switch	N/A	N/A	N/A
	e) Lift signage	N/A	N/A	N/A
17.	Stand by Power Supply	Required	Provided	MR
18.	Refuge Area	N/A	N/A	N/A
	Total area location	N/A	N/A	N/A
19.	Fire Control Room	N/A	N/A	N/A
	a) Detector system	N/A	N/A	N/A
	b) Flow switch panel	N/A	N/A	N/A
	c) PA system panel	N/A	N/A	N/A
	d) Battery backup	N/A	N/A	N/A
	e) Building floor plan	N/A	N/A	N/A
20.	Special Fire Protection Sys Risk, if any: ABC & CO2	MR		

The fire protection systems provided in the building were randomly tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules, if agreed, we may renew the FSC issued vide letter no. F6/DFS/MS/GH/2021/126 dated 08/03/21, under rule 35(6) of the Delhi Fire Service Rules 2010. Accordingly, DFA is put up for kind perusal and signature please.

Signature of the Inspecting Officer

Name: - Rawinder Singh

Designation: - ADO (CC)