C-2



GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: NEW DELHI - 110001



No F 6 / DFS / MS / 2024 / School/WZ/ 590

Dated 3706 2024

FIRE SAFETY CERTIFICATE

Certified that the C.K. Nair Public School located at Gandhi Ashram, Narela, Delhi110040 comprised of Ground floor only was issued FSC by this department vide letter No F6
/DFS/MS/School/2018/1330 dated 06.06.2018. The premises was re-inspected by the officer
concerned of this department on 19.06.2024 in the presence of Sh. Ashok Kumar (Manager), and
observed that all the fire prevention and fire safety arrangements as provided in the premises
found in good working condition. The premises have deemed complied with requirements of
circular issued by Director of Education letter no 3298-3398 dated 01.03.2011 and the building/
premise is fit for occupancy Group B Educational with effect from ________ for a
period of three years, subject to compliance of the conditions mentioned below:

Issued on .. 2. 71.06 / 2024 at New Delhi by

Director
Ph. 011-23414000

Copy to:-

1. The Director, Education, Government of NCT of Delhi. Old Sect. Delhi-110054

2. The Principal, C.K. Nair Public School located at Gandhi Ashram, Narela, Delhi-110040.

Conditions for the validity of Fire Safety Certificate:

1. All the fire safety arrangement provided there-in shall be maintained in good working conditions at all times.

2. Loss of life or property due to non functional fire safety measure shall be at the responsibility of the management.

3. The trained fire fighting staff should be available round the clock.

 Any deviation with regard to the construction etc shall be verified by the concerned building sanctioning agency.

5. This certificate cannot be treated in any case for regularizations of unauthorized construction.

6. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director of Form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six months prior to its expiry".

7. The owner / occupier shall submit a declaration every year in form "K" provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on <u>WWW.dfs.Delhigovt.nic.in</u>

8. All the means of escape shall be kept free of any obstruction all the time to evacuate the occupant, in a safe manner, in the event of emergency.

INSPECTION REPORT C.K. Nair Public School located at Gandhi Ashram, Narela, Delhi- 40. Name & address of the building: : Educational 2. Type of Occupancy Ground floor only 3. Building Comprised of Renewal 4. Type of Case F6/DFS/MS/School/2018/1330 dated 06/06/2018 5. Details of Previous NOC DOE circular No. 3298-3398 dated 01/03/2011 6. Fire Safety directives letter No : 7. Date of inspection R.K.Sinha, ADO (BW) 8. Name of Inspecting Officer 9. Name and designation of officers Sh. Ashok Kumar (Manager) From the building side 1997 10. Year of Construction CKNPS/NRL/2024/30 dated 04/06/2024 11. Applicant's letter No. Remarks Provided at site DOE Minimum Standards on fire S. MR/NMR Requirement prevention and fire safety U/R 33 No. Access to building MR Provided 6 m Road width MR(old case) 1.5 m 4.5 m Gate width NA NA NA Width of internal road Number, Wilth, Type & Arrangement of Exits 2. Number of staircases NA NA NA Upper Floors NA NA NA Basements Width of staircases NA NA NA Upper Floor NA NA NA Basements Protection of exits NA NA NA Fire check door NA NA NA Pressurization No. of continuous staircases to NA NA NA terrace NA NA NA Width of Corridor MR 1 m 1 m Door Size Compartmentation NA NA NA Fire check doo NA NA NA Sealing of electrical shafts NA NA NA Fire Rating of shaft door NA NA NA Water Curtain NA NA NA Fire Dampers Smoke Management System NA NA Basements Required Naturally Ventilated Upper floors Fire Extinguishers 03 03 MR Total numbers Provided ABC Type MR Types IS marking Required Provided MR First-Aid Hose Reels Total numbers on each floor NA NA NA NA Length of hose reel hose NA NA Nozzle diameter NA NA NA Automatic fire detection and alarming system Type of detectors NA NA NA Location of Main Panel NA NA NA

NA

NA

NA

NA

NA

NA

NA

NA

NA

3.

4.

5.

Location of Repeater Panel

Alternate source of power

Hooters' Location

| 102 | | - 1 |
|-----|------|-----|
| AJ | 1 | 13 |
| r | - 11 | - |

| | | 10-15 | 194 | 1 |
|-----------|---|----------|----------|----------------|
| 8. | MOEFA | NA | NA | N A |
| 9. | Public Address System | NA NA | NA | NA |
| 10. | Automatic Sprinkler System | | | |
| | -p | | | NA |
| | Basement | NA | NA NA | NA NA |
| | Ground Floor | NA | NA NA | NA |
| | Sprinkler above false ceiling | NA | NA | |
| 11. | Internal Hydrants | | | |
| | Size of riser/down-comer | NA NA | NA | NA |
| | Number of hydrants per floor | NA NA | NA | NA |
| | Hose Box | NA | NA | . NA |
| 12. | Yard Hydrants | | | |
| | | T NA T | NA | NA |
| | Total number of hydrants | NA NA | NA NA | NA |
| 13. | Hose Box Pumping Arrangements | IVA | **** | |
| (V 472 P) | | | | |
| | Ground Level | NA | NA · | NA |
| | Discharge of main Pump | NA NA | NA NA | NA |
| | Head of Main pump | | W 00000 | |
| | Number of main pumps | NA | NA | NA |
| | Jockey Pump out put | NA | NA | NA |
| | Jockey pump head | NA | NA | NA |
| | Standby Pump out put | NA NA | NA | NA NA |
| | Standby Pump Head | NA | NA | NA NA |
| | Auto Starting/Manual Stopping | NA | NA | NA |
| | Pump House Access | NA | NA | NA |
| | Terrace level | | | |
| | Discharge of pump | NA | NA | NA |
| | Head of the pump | NA | NA | NA |
| | Power Supply | NA | NA | NA |
| | Auto Starting of pump | NA | NA | NA |
| 14. | Captive Water Storage for fire fighting | | | |
| | Underground tank capacity | NA | NA | NA |
| | Draw-off connection | NA | NA | NA |
| | Fire service inlet | NA | NA | NA |
| | Access to tank | NA | NA | NA |
| | Overhead Tank capacity | NA | NA | NA |
| 15. | Exit Signage. | NA | NA | NA |
| 16. | Provision of Lifts. | | | |
| | Pressurization of Lift Shaft | NA | NA | NA |
| | Pressurization of Lift lobby | NA | NA | NA NA |
| | Communication In lift Car | NA | NA | NA NA |
| | Fireman's Grounding Switch | NA | NA | NA |
| | Lift Signage | NA | NA | NA NA |
| 17. | Standby power supply | NA | NA NA | NA NA |
| 18. | Refuge Area. | | | 1311 |
| | | | | |
| | Total Area | NA NA | NA | NA |
| 19. | Location Fire Control Room | NA | NA | NA |
| | Detector System Panel | <u> </u> | | |
| | Detector System Faffe | NA A | NA | NA |

| n Panel NA NA | | | |
|---------------|----------------|----------------|--|
| NA | NA | NA | |
| NA | NA | NA NA | |
| | NA NA NA | NA NA NA NA NA | |

The fire protection systems provided in the building were tested, checked and found functional at the time of inspection.

Note: Electric meter and electrical panel are installed at safer location.

Keeping in view of deemed compliance of the minimum standards of fire prevention and fire safety measures as required under DOE circular no. 3298-3398 dated 01/03/2011, it is recommended to renew the Fire Safety Certificate issued vide letter number F6/DFS/MS/School/2018/1330 dated 06/06/2018.

Signature of Inspecting Officer Name: Rajeev Kumar Sinha

Designation : ADO/B.W.

De (folloy

put up Corrected Inspection report

Aso (sawana)