

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: NEW DELHI- 110001

आज़ादी_क अमृत महोत्सव

Vo. F6/DFS/MS/Ind./WZ/2024/ 423

Dated: 01/67/2024

FIRE SAFETY CERTIFICATE

Certified that the M/s. K. R. Industries, Located at H-31, Udyog Nagar, Industrial Area, Rohtak Road, New Delhi-110041, comprised of Basement + Ground + Mezzanine Floor + 01 Upper Floor only owned / occupied by M/s. K. R. Industries, was issued Fire Safety Certificate by this department vide letter No. F6/DFS/MS/2019/WZ/1535 dated 26/07/2019. The said premises was re inspected by the officer concerned of this department on 27/06/2024 in the presence of Sh. Ashwani Kapoor (Owner/Partner) and found that the premises have deemed complied with the fire prevention and fire safety requirements in accordance with Rule 33 of the Delhi Fire Service Rule, 2010 and that the building/premises is fit for occupancy class "Industrial" Group G with effect from Olot/2024 for a period of three years in accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under Rule 38 of the Delhi Fire Service Rules, 2010, printed below.

Tel No. 011-23414000

Copy to: -

- The Deputy Commissioner, MCD office, P-496-276, Rohini institutional area, Sector-5, Rohini, Delhi.
- 2. The Authorized Signatory, M/s. K. R. Industries, H-31, Udyog Nagar, Rohtak Road, New Delhi-110041.

Following Fire Safety Directive must be adhered to :-

- 1. The Basement shall be used as per BBL.
- 2. All the means of escape shall be kept free of all type of obstruction all the time.
- 3. All the employees shall be acquainted with the use and maintenance of all fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.
- 4. All the fire fighting equipments shall be maintained in perfect working condition all the time and any lapse rendering non-functional if fire safety measures, management shall be responsible.
- 5. Any deviation, with regards to construction, ventilation, occupation, electric installation etc. may be got verified from the concerned authorities. In case of deviation the NOC be treated as Null & Void.
- 6. The Fire Safety Certificate may not be treated in any case for regularizations of unauthorized construction / unauthorized use of land if any.
- 7. All comments / directions of licensing Department shall always be permitted and followed.
- 8. The owner /occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on www.dfs.delhigovt.nic.in
- 9. The owner / occupier shall apply for renewal of this Fire Safety Certificate to the Director in 'Form J' (sub Rule (1) of Rule 37) along with copy of the certificate, six months prior to its expiry.

INSPECTION REPORT

1. Name & address of the building

: M/s. K. R. Industries Located at H-31, Udyog Nagar, Industrial Area, Rohtak Road, New R

17

W

T

, 1

. 1

et:

r

? !

I

10

Delhi-110041.

2. Type of Occupancy

: Industrial, Group-G

3. Type of Case

: Renewal (B + G + Mezz. + 1^{st} floor)

4. Details of previous NOC

: F6/DFS/MS/2019/WZ/1535 dated 26/07/2019

5. Fire Safety directives Letter No.

: F6/DFS/MS/BP/86/1816 dated 19/12/1986

6. Date of inspection

: 27/06/2024

7. Name of the Inspecting Officer

: Aman Kumar Lathar, ADO (JWP)

 Name and designation of Officer from the building side

: Sh. Ashwani Kapoor (Owner/Partner)

9. Year of Construction

: Old

10. Applicant's letter no.

: nil dated 06/06/2024

	10. Applicant's letter no.					
S No	Minimum standards on fire prevention and fire safety U/R 33	BBL Requirements/ as per FSC dated 26/07/2019	Provided at site	Remarks MR/NMR		
1.	Access of building					
	 Road width 	06 m	Provided	MR		
	 Gate width 	4.5 m	Provided	MR		
	 Width of internal road 	03 m	Provided	MR		
2.	Number, width, Type & Arrangements of exits					
	 a. Number of staircases 					
	 Upper floors 	02	Provided	MR		
	 Basements 	02	Provided	MR		
	 b. Width of staircases 		:			
	 Upper floors 	1.2 m	Provided	MR		
	 Basements 	1.2 m	Provided	MR		
	 c. Protection of exits 		1			
	 Fire check door 	Required	Provided	MR		
	 Pressurization 	NA NA	NA	NA		
	d. No of continuous	As per	01	MR		
	staircase to terrace	Sanctioned plan		2200000		
	e. Width Of Corridor	NA NA	NA	NA		
	f. Door Size	1.0 m	Provided	MR		
3.	Compartmentation					
1	 Fire check door 	Required	Provided	MR		
	 Sealing of electrical shafts 	NA	NA	NA		
	 Fire Rating of shaft door 	NA	NA	NA		
	Water Curtain	NA	NA	NA		
	 Fire Dampers 	NA	NA	NA		
4.	Smoke managements System					
	 Basements 	Required	Provided	MR		
	Upper floors	NA	NA	NA		
5.	Fire Extinguishers			INTO C. INT.		
	 Total numbers 	08 nos.	15 nos.	MR		
	 Types 	ABC & CO ₂	Provided	MR		
	IS marking	ISI marked	Provided	MR		
	First – Aid Hose Reels		TTOVICE	IVIIC		
	 Total numbers on each floor 	01	Provided	MR		
	 Length of hose reel hose 	30 m	Provided	MR		
	Nozzle diameter	0 5 mm	Provided	MR		

	N-27					
	Automatic fire detection and alarming	system				
7.		NA	NA	NA		
	Type of detectors	NA	NA	NA		
1 1	Location of Main Panel	NA	NA	NA		
1 1	Location of Repeater Panel	NA	NA	NA		
1 1	 Alternate source of power 	NA	NA	NA		
	 Hooters' Location 		NA	NA		
8.	MOEFA	NA	NA NA	NA NA		
9.	Public Address System	NA	1471			
10.	Automatic Sprinkler System	n !	Provided	d MR		
70.	Basements	Required	NA	NA		
	Upper Floor	NA NA	NA	NA		
	 Sprinkler above false ceiling 	NA	111.1			
11.	Internal Hydrants:	374	NA	NA		
	Size of riser/down- comer	NA NA	NA NA	NA		
	 Number of hydrants per 	NA	1172	2000		
	floor	NA	NA	NA		
	Hose Box	NA				
12.		NIA	NA	NA		
	 Total number of hydrants 	NA NA	NA	NA		
1	Hose Box	NA	11.2			
13.	Pumping Arrangements:					
	Ground Level	900 Lit/min.	Provided	MR		
	Discharge of main pump	30 m	Provided	MR		
	Head of main pumpNumber of main pumps	NA	NA	NA		
	> Jockey pump out put	NA	NA	NA		
	> Jockey pump head	NA	NA	NA		
	Standby Pump out put	NA	NA	NA NA		
-	Standby Pump Head	NA	NA Provided	MR		
V	Auto Staring/Manual	Required	Provided	IVIIC		
	stopping	Required	Provided	MR		
	 Pump House Access Terrace level 	Required		Y		
ľ	► Discharge of pump	NA	NA	NA		
	> Head of the pump	NA	NA	NA		
	> Power supply	NA	NA	NA NA		
	> Auto starting of pump	NA	NA	NA		
1	4. Captive water Storage for firefighting	50,000 ltrs.	Provided	MR		
	 Underground tank capacity 	Required	Provided	MR		
V	Draw off connectionFire service inlet	Required	Provided	MR		
	> Access to tank	Required	Provided	MR MR		
	Overhead Tank capacity	10,000 ltrs.	Provided Provided	MR		
T	5 Exit Signage	Required	Provided	WIK		
	6 Provision of Lifts	NA	NA	NA		
	Pressurization of Lift Shaft	NA NA	NA -	NA		
- 1	Pressurization of lift lobbyCommunication in lift Car	NA	NA	NA		
V	> Fireman's Grounding	NA	NA	NA NA		
Ü	Switch	NA	NA			
	> Lift Signage	Required	Provided	MR		
_	Standby power supplyRefuge Area			NA		
-	18. Refuge Area ➤ Total area	NA	NA NA	NA NA		
	> Location	NA	INA			
	19. Fire control room	NA	NA	NA		
	 Detector system panel Flow Switch Panel 	NA NA	NA	NA		
	> PA System Panel	NA	NA	NA NA		
	▶ Battery backup	NA NA	NA NA	NA NA		
	▶ Building Floor Plans	NA NA	NA NA	NA		
	20. Special Fire Protection Systems for Protection of special Risks, if any;	1 0 W	\$1975.52			
	Protection of special Risks, if any,	(Ma				

The fire protection systems provided in the building were checked and found functional at the time of inspection. Shortcomings issued vide letter no. F6/DFS/MS/WZ/2022/1874 dated 26/07/2022 are rectified.

In view of the deemed compliance of minimum standards of fire prevention and fire safety requirements under the rules, renewal of Fire Safety Certificate issued vide letter no. F6/DFS/MS/2019/WZ/1535 dated 26/07/2019 is recommended under rule 37 of the Delhi Fire Service Rule, 2010 under DFS Act 2007.

Accordingly DFA is prepared & put up for approval please.

perolur

ADO (JWP)

Director

F.T. Jetter is added for your mignature 1st.

Director