

GOVERNMENT OF NATIONAL CAPITAL TERRITOTY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: NEW DELHI- 110001

F.6/DFS/MS/Cinema/2024/SZ/435

Dated:08 /01 / 2024

FIRE SAFETY CERTIFICATE

Certified that the **M/s PVR Anupam** located at Community Centre, Saket, New Delhi 110017 (Audi 1 to 4) at 2nd 3rd 4th Floor in the building comprised of Basement, Ground + Mezzanine + 04 upper floor owner/occupied by PVR INOX LIMITED was issued FSC by this department vide letter No. F.6/DFS/MS/Cinema/2021/SZ/393 Dated 16/08/2021. The premises was re-inspected by the officers concerned of this department on 01/07/2024 in the presence of Ms. Neha (Manager) and found that the premise have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class "Assembly Building, Group-D" with effect from 08/04/2024 for a period of Three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

Issued on 08 07 /2024 at New Delhi by

DIRECTOR DELHI FIRE SERVICE


Copy to: -

1. Authorized Signatory, PVR Anupam at Community Centre, Saket, Wew Delhi 110017.

2. SDM/ Hauz Khas, at M.B. Road, Saket, New Delhi 110068.

Conditions for the validity of Fire Safety Certificate:-

- All the fire safety and means of escape facilities shall be maintained in good working condition at all time. Any lapse rendering the fire safety or means of evacuation facilities non-functional shall be the responsibility of the management.
- Building Sanctioning authority may verify any deviation with regard to construction/occupancy in the building. In case of any deviation, the fire safety certificate stands null & void.
- The staff shall be trained for operating fire fighting system and mock evacuation drill be conducted at regular interval and record be maintained.
- 4. The basement shall be used strictly as per the provisions of Building Bye Laws.
- 5. The Owner/Occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules, 2010. The form is available on www.dfs.delhigovt.nic.in.
- 6. The Owner/Occupier shall apply for renewal of this Fire Safety Certificate to the Director in the form 'J' [sub rule (1) of rule 37] along with copy of this certificate, six months prior to its expiry. The form is available on www.dfs.delhigovt.nic.in.





	INSPECT	TON DI	POD	r	(M)	ृत म	हात्स		
1	Name & Address of the Building	PVR	Anupa -11001	m a	t Community Centre,	Sake	t, Nev		
2	Type of Occupancy	- CUII	TIOO	. /			Canal Co		
3	Building Comprised of	Rosen	ioly Bu	ildin	g "Group-D" (Cinema)				
4	Type of Case	Renev	ent, G	round	I, Mezzanine + 4 upper	floors	Ě		
5	Details of Previous NOC			/O:					
6	Fire Safety Directives Letter No	Nil	-3/M3/	Cine	ma/2021/SZ/393 Dated	16/08	3/202		
7	Date of Inspection	01.07	2024			1			
8	Name of the Inspecting Officers				O (D CD)	6 E			
9	Name & Designation of Officers from the building side	DO (South) & ADO (BCP) Ms. Neha (Manager)							
10	Year of construction	Basement (Elect. Panel, DG set, pump house & store; GF & Mezzanine floor (Food counter, booking, office, coffices), 2 nd floor (03 Audi's), 3 rd floor (01 Audi)							
11	Applicant letter No.	Email dated 27/06/2024							
S. No	Minimum standards on Fire Prevention and Fire Safety U/R 33	Old NOC Dt 29/07/2009 Requirement		09	Provided at Site	Remarks MR/NMR			
1	Access to Building.	neg	in eine	ut					
	1. Road width		mtr	_	9 mtr	1	MR		
	2. Gate width		NA	-	4.5 mtr	-	NA		
	Width of internal road		NA	Tu Di	NA NA	_	NA		
2	Number, width, type and arrangements of	exits.	xits.						
	a. Number of Staircase								
	1. Upper floors		4 No's		2 No - GF to 4th floor 2 No- GF to 2nd floor				
	2. Basement floor	2 No's + 01 ramp		mp	2 No's + 01 ramp				
	b. Width of Staircase				Religious Philadel	Ý			
	1. Upper floors	Requ	Required GF. to 4th floor- 1.84 & 1.5 (S/C is 1.0 m fm 4th floor to te GF to 2nd floor- 1.73 & 1.7.		race)	MR			
	2. Basement floor	Requ	ired	1.5	0, 1.64 & 01 ramp of 1.40) mtr	MR		
	c. Protection of exits				Minute 21 May 1				
20.75	Fire check door		NA		NA	1	NA		
SHAM	2. Pressurization		NA		NA	1	NA		
-	d. No. of continuous staircase to terrace	1	One		One	1	MR		
215	e. Width of corridor		NA		NA	NA			
MAG	f. Door Size /Exits	1	1,5 m		1.5 m	MR			
3	Compartmentation.								
	Fire check door.		NA		NA	1	NA		
	Sealing of electrical shafts.	Required			Provided	MR			
100	Fire rating of shaft door.	NA			NA	NA			
	4. Water curtain	NA NA			NA NA	NA NA			
	5. Fire dampers.		NA		NA	1	NA.		
4.	Smoke Management system.	-			Day 11.1		€D.		
	Basement Upper floors		quired quired		Provided Provided		AR AR		
5.	Fire Extinguishers.	Re	lunca		Flovided				
J.		62 No's ABC/Co2/W.Co2 ISI marked			72 No's	MR			
	Total numbers Types			02	Co2- 44, W.Co2-28	MR			
	3. ISI Marking			-	Provided	MR			
6.	First Aid Hose Reels.								
	Total numbers on each floor.	Hose Reel			Two in each Audi	M	IR		
	Length of hose-reel hose.			- 1			R		
	Z. Lengin of nose-thei nose	1		- 1	30 mtr	M	LIC.		





Automatic Fire Detection and Alarming system. MR Smoke & Heat Required 1. Type of detectors NA NA NA 2. Location of Main Panel NA NA NA 3. Location of Repeater Panel MR Provided Required 4. Alternate source of power NA NA 5. Hooter's location NA MR Provided Required MOEFA/MCP 8. NA NA NA 9. **Public Address System Automatic Sprinkler System** 10. MR Provided Required 1. Basement NA NA 2. Upper floors NA NA NA 3. Sprinkler above false ceiling NA 11. Internal Hydrants. MR 100 mm Required 1. Size of Riser/Down-comer MR One 2. Number of Hydrant per floor Required MR One 3. Hose box. Required 12. Yard Hydrants. MR 4 No's 1. Total number of hydrants. Required MR 2. Hose box. 4 No's Required 13. Pumping arrangements. a) Ground Level MR Discharge of main pump. 1620 LPM Required Required Head of main pump. MR 40 mtr Number of main pumps. One One MR Jockey Pump output. Required 180 LPM MR Jockey Pump head. Required MR 40 mtr Standby Pump output. Required 1620 LPM MR Standby Pump head. Required 40 mtr MR Auto Starting/Manual Stopping. Required Provided MR Terrace Level Discharge of pump. 900 LPM 900 LPM MR Head of pump. 40 mtr 40 mtr MR Power supply. Required Provided MR Auto starting of pump. Required Provided MR 14. Captive water storage for Fire Fighting. 1. Underground tank capacity. 50,000 Ltr 50,000 Ltr MR 2. Draw-off connection. Required Provided MR 3. Fire Service Inlet. Required Provided MR Access to tank. Required Provided MR Overhead tank capacity. 30,000 Ltr 30,000 Ltr MR 15. Exit Signage. Required Provided MR 16. Provision of Lifts. 1. Pressurization of lift shaft. NA NA NA 2. Pressurization of lift lobby. NA NA NA 3. Communication in lift car. NA NA NA 4. Fireman's switch. NA NA NA Lift signage. NA NA NA **Standby Power Supply** 17 Required Provided MR 18. Refuge Area

NA

NA

NA

NA

NA

NA

PVR Anupam located at Anupam Complex, Saket, New Delhi

1. Total area

2. Location



110



	Fire Control Room.		भी आज़ादी व अमृत म	Cite
19.	1. Detector System Panel.	NA		
	2. Flow Switch Panel.		NA NA	NA
	3. PA system Panel.	NA NA	NA	NA
	4. Battery backup	NA	NA	NA
	Building floor plan	NA NA	NA	NA
20.	Special Fire Protection System for the	NA	NA	NA
	Protection of special Risk if any	Required	04 No's Co2 type FE cap. 22	MR
	Details of Seating Capacity & Exits are as l	helow.	Kg provided near elect panel	
	The Fire protection systems provided in the	e Cinema huil	dia	1 2
afety F.6/DFS	The Fire protection systems provided in the all at the time of inspection. Keeping in view of the deemed compliance measures as required under the S/MS/Cinema/2021/SZ/393 Dated 16/08/2021 recommended.	e Cinema buil	um standards on fire prevention	and fir
safety F.6/DFS 2010 is	Keeping in view of the deemed compliance measures as required under the S/MS/Cinema/2021/SZ/393 Dated 16/08/2021 recommended. Accordingly, DFA is put up for approval and	e of the minim rules, the l, renewal under	um standards on fire prevention FSC issued vide letter rule 37 of the Delhi Fire Servi	and firer No
safety F.6/DFS 2010 is Signate	Keeping in view of the deemed compliance measures as required under the S/MS/Cinema/2021/SZ/393 Dated 16/08/2021 recommended. Accordingly, DFA is put up for approval and under the system of the Inspection Officer	e of the minim rules, the l, renewal under	um standards on fire prevention FSC issued vide letter rule 37 of the Delhi Fire Servinse. Signature of the Inspecting Of	and firer No ce rules
safety F.6/DFS 2010 is Signate Name:	Keeping in view of the deemed compliance measures as required under the S/MS/Cinema/2021/SZ/393 Dated 16/08/2021 recommended. Accordingly, DFA is put up for approval and	e of the minim rules, the l, renewal under	um standards on fire prevention FSC issued vide letter rule 37 of the Delhi Fire Servi	and fire No ce rules

F.1. Letter et pr signature PI 1/4