## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE, NEW DELHI-110001

No. F6/DFS/MS/2024/School/WZ/ 623

Dated: 04/07/2024

## **FIRE SAFETY CERTIFICATE**

Certified that the Kendriya Vidyalaya Sector 3, Rohini, Delhi-110085, (School ID-1413272) comprised of Ground + 02 upper floors has already been issued FSC by this department vide letter No. F.6/DFS/MS/School/2021/WZ/309 dated 05.04.2021. The premises was reinspected by the officer concerned of this department on 21.06.2024 in the presence of Mr. Anita Singh (Principal) and found that the said building have deemed complied with the fire prevention and fire safety requirements in accordance with Rule 33 of the Delhi Fire Service Rules, 2010 and that the premises fit for occupancy class Group B Educational with effect from O4 07 2024 for a period of 03 years in accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subjected to compliance of the conditions under Rule 38 of the Delhi Fire Service Rules, 2010.

Issued on 04/07/2024 at New Delhi by

Atul Garg)
DIRECTOR
Ph; 011-23414000

## Copy to: -

- 1. The Director, Education, Government of N.C.T of Delhi. Old Sect. Delhi 54. (School ID-1413272)
- 2. The Principal, Kendriya Vidyalaya Sector 3, Rohini, Delhi-110085. Conditions for the validity of Fire Safety Certificate:
- 1. All the fire safety arrangement provided there-in shall be maintained in good working conditions at all times.
- 2. Loss of life or property due to non functional fire safety measure shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation with regard to the construction etc shall be verified by the concerned building sanctioning agency.
- 5. This certificate cannot be treated in any case for regularizations of unauthorized construction.
- 6. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director of Form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six months prior to its expiry".
- 7. The owner / occupier shall submit a declaration every year in form "K" provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on
- 8. All the means of escape shall be kept free of any obstruction all the time to evacuate the occupant, in a safe manner, in the event of emergency.

http://www.delhi.gov.in/wps/wcm/connect/doit\_fire/FIRE/Home/Fire+Safety+Acts+and+Rules/ http://www.delhi.gov.in/wps/wcm/connect/doit\_fire/FIRE/Home/Forms

		. <u>I</u>	INSPECTION REPORT					
_	Name & add	lress of the building	Kendriy	ya Vidyalaya Sector	r 3, Rohini, Delhi-1100s	85		
2.	Type of Occ		Kendriya Vidyalaya Sector 3, Rohini, Delhi-110085.  Educational					
3.	Type of Cas	e	Renewa	al (01 Block, Grou	nd + 02 upper floors)			
4.	Committee of the Commit	revious NOC	F.6/DFS	S/MS/School/2021/	/WZ/309 dated 05.04.20	05.04.2021.		
5.		ire Safety directives letter No		NBC Part-IV. 21.06.2024.				
6.	Date of inspection							
New York				h. Ajay Kumar Sharma (ADO Rohini)				
8.	Name and de From the bu	esignation of officers ilding side	Mrs. An	ita Singh (Principal)				
9.	Year of Con	struction	2006	006				
10.	Applicant's			.2500 dated 05.06.2	2024.			
S. No	. Minimum Standards on fire preven		ention	NBC Requirement	Provided at site	Remarks MR/NMR		
1.	Access to b			Requirement		MACHINIA		
		oad width		Accessible	Accessible	MD		
						MR		
	2000	e width		Accessible	6.2m	MR		
_	10.000	th of internal road		-NA-	-NA-	-NA-		
2.		idth, Type & Arrangem	ent of Exit	ts				
		of staircases		04===	04	1.00		
		pper Floors		04nos.	04nos.	MR		
		asements		-NA-	-NA-	-NA-		
	Action of the second second	f staircases						
	• U	pper Floor		1.5m	1.5m	MR		
	• B	asements		-NA-	-NA-	-NA-		
	c. Protect	on of exits						
	• F	re check door		-NA-	-NA-	-NA-		
	•	Pressurization		-NA-	-NA-	-NA-		
	d. No. of cor	tinuous staircases to terrace		02nos.	03nos.	MR		
	e. Width of	Corridor		-NA-	2.46m	-NA-		
	f. Door Size	The Charles of Section 7		-NA-	-NA-	-NA-		
3.	Compartme							
	a) Fire	check door		-NA-	-NA-	-NA-		
		ling of electrical shafts		-NA-	-NA-	-NA-		
	(60)	Rating of shaft door		-NA-	-NA-	-NA-		
		ter Curtain		-NA-	-NA-	-NA-		
	263	Dampers		-NA-	-NA-	-NA-		
4.		agement System						
P. 5500	a) Base			-NA-	-NA-	-NA-		
-		per floors		12 a/c per hour	Natural ventilated	MR		
E	Fire Exting					-100-100000		
5.		tal numbers		22nos.	25nos.	MR		
	60.			ABC/CO2	ABC-22/CO2-03	MR		
	b) Typ	arking		ISI marked	Yes	MR		
•	c) IS n First-Aid H							
6.	rirst-Ald H	al numbers on each floo	or	03nos.	Provided	MR		
	a) Tota	ngth of hose reel hose		30mm	Provided	MR		
		zzle diameter		5m	Provided	MR		
	_ N N							

	N-2	9 5 7 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1					
_	a) Type of detectors	-NA-	-NA-	-NA-			
	b) Location of Main Panel	-NA-	-NA-	-NA-			
	c) Location of Repeater Panel	-NA-	-NA-	-NA-			
	d) Alternate source of power	-NA-	-NA-	-NA-			
	e) Hooters' Location	-NA-	-NA-	-NA-			
8.	MOEFA	-NA-	-NA-	-NA-			
9.	Public Address System	-NA-	-NA-	-10.			
10.			- /	-NA-			
	a) Basement	-NA-	-NA-	-NA-			
	b) Ground & Upper Floors	-NA-	-NA-	-NA-			
	c) Sprinkler above false ceiling	-NA-	-NA-	-IVA			
11.				-NA-			
	a) Size of riser/down-comer	-NA-	-NA-	-NA-			
	b) Number of hydrants per floor	-NA-	-NA-				
	c) Hose Box	-NA-	-NA-	-NA-			
12.			_	I NIA			
	a) Total number of hydrants	-NA-	-NA-	-NA-			
	b) Hose Box	-NA-	-NA-	-NA-			
13.			2000	-NA-			
	Ground Level	-NA-	-NA-	7.25.00			
	Discharge of main Pump	-NA-	-NA-	-NA-			
	➤ Head of Main pump	-NA-	-NA-	-NA-			
	Number of main pumps	-NA-	-NA-	-NA-			
	> Jockey Pump out put	-NA-	-NA-	-NA-			
	> Jockey pump head	-NA-	-NA-	-NA-			
	> Standby Pump out put	-NA-	-NA-	-NA-			
	> Standby Pump Head	-NA-	-NA-	-NA-			
	<ul><li>➤ Auto Starting/Manual Stopping</li><li>➤ Pump House Access</li></ul>	-NA-	-NA-	-NA-			
		-NA-	-NA-	-NA-			
	Terrace level	II					
	Discharge of pump	450lpm	450lpm	MR			
	➤ Head of the pump	40m	40m	MR			
	> Power Supply	Required	Provided	MR			
	> Auto Starting of pump	Required	Provided	MR			
4.	Captive Water Storage for fire fighting						
	Underground tank capacity	-NA-	-NA-	-NA-			
	> Draw-off connection	-NA-	-NA-				
	➤ Fire service inlet	-NA-		-NA-			
	> Access to tank		-NA-	-NA			
		-NA-	-NA-	-NA-			
	Overhead Tank capacity	10,000ltr	10,000ltr.	MR			
5.	Exit Signage.	Required	Provided	MR			
5.	Provision of Lifts.						
	a) Pressurization of Lift Shaft	-NA-	-NA-	-NA-			
	b) Pressurization of Lift lobby	-NA-	-NA-	-NA-			
	c) Communication In lift Car	-NA-	-NA-	-NA-			
	d) Fireman's Grounding Switch	-NA-	-NA-	-NA-			
	e) Lift Signage	-NA-	-NA-	-NA-			
+	Standby power supply	-NA-	-NA-				
100	Standby power suppry		Cont. 14 (4)	-NA-			

Z Z 3) Total Area	-NA-	-NA-	-NA-
a) Total Area b) Location	-NA-	-NA-	-NA-
Fire Control Room		-NA-	-NA-
a) Detector System Panel	-NA- -NA-	-NA-	-NA-
b) Flow Switch Panel	-NA-	-NA-	-NA-
c) PA System Panel d) Battery backup	-NA-	-NA-	-NA-
e) Building Floor Plans	-NA-	-NA-	-NA-
O. Special Fire Protection System for	-NA-	-NA-	Notae No

The fire protection systems provided in the building were test checked and found functional at the time

of inspection.

In view of the deemed compliance of the minimum standards of the fire prevention and fire vide letter issued NOC under the rules the required F.6/DFS/MS/\$chool/2021/WZ/309 dated 05.04.2021 is recommended for renewal under rule 37 of the Delhi Fire Service rules 2010.

> Signature of the Inspecting Officer Ajay Kumar Sharma Name Designation ADO(Rohini)

Director 1 1 de proposition 20 per letter la fruit de for kind pencedano Signature Pleane.