#### GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE, CONNAUGHT PLACE NEW DELHI

No. F6/DFS/MS/2024/GH 277

Dated: 08/ 07/2024

## FIRE SAFETY CERTIFICATE

Certified that the building of M/s Hotel Rahul Palace, Located at 5/3, WEA Tank road, Ajmal khan road, Karol Bagh, New Delhi-110005, in a building comprised of basement, ground plus three upper floors using basement as (shops, office & store), ground floor (reception & 01 guest room), first & second floor (9 rooms each floor), & third floor (08 rooms) (Total=26 guest rooms) and a pantry for staff on terrace (now sealed/closed) was issued FSC vide Letter No F6/DFS/MS/GH/SZ/2021/392, dated 16/09/21. The premises was re inspected by the officer concerned of this department on 03/07/2024 in the presence of Sh. Gaurav Singh (Manager) and observed that all the fire prevention and fire safety arrangements provided in the premises found in good working condition. The premises have therefore deemed complied with the fire prevention and fire safety requirements in accordance with Rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class "Residential" (guest house) at ground floor (reception & 01 guest room), first & second floor (9 rooms each floor), & third floor (08 rooms) (Total=26 guest rooms) with effect from 08/07/2024 for a period of three years in accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under Rule 38 of the Delhi Fire Service Rules, 2010.

Issued on .. 0.8 . 0.7.1.2.2.4. at New Delhi by.

Director Delhi Fire Service

### Copy to:

- The Joint. Commissioner of Police (Lic), 1<sup>st</sup> Floor, Licensing Unit, Police Station, Defence Colony, New Delhi.
- 2. The Manager, M/s Hotel Rahul Palace, Located at 5/3, WEA Tank road, Ajmal khan road, Karol Bagh, New Delhi-110005.

# Following fire safety directives must be adhered to:-

- 1. 4th floor shall not be used for any purpose as undertaking given by owner.
- 2. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- 3. Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.
- 4. The trained staff should be available round the clock.
- 5. Any deviations w.r.t. construction shall be verified by the concerned building sanctioning agency.
- 6. The certificate may not be treated in any case for the regularization of the unauthorized construction, if any.
- 7. Basement strictly shall be kept vacant as seen during inspection.
- 8. The owner/ occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its expiry.
- 9. The owner/occupier shall submit a declaration every year in the form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on <a href="https://www.dfs.delhigovt.nic.in">www.dfs.delhigovt.nic.in</a>

1/38

#### **INSPECTION REPORT**

 Name & address of the building: M/s Hotel Rahul Palace, Located at 5/3, WEA Tank road, Ajmal khan road, Karol Bagh, New Delhi-110005.

2. Type of Occupancy

:Lodging or rooming "A-1"

3. Type of Case : Renewal (Running at Ground, 1<sup>st</sup>, 2<sup>nd</sup>, & 3<sup>rd</sup> floor in a building comprised of Basement, Ground + 3 Upper Floor)

4. Details of previous NOC: F6/DFS/MS/GH/SZ/2021/392, dated 16/09/21

5. Fire Safety directives Letter No.: Nil

6. Date of inspection

:03/07/2024

7. Name of the Inspecting Officer: ADO (DWK)

8. Name and designation of Officer

from the building side

: Sh. Gaurav Singh (Manager)

9. Year of Construction

: Before 2001

10. Applicant's letter No.

: 2024062209787, dated 22/06/2024

S No	Minimum standards on fire prevention and fire safety U/R		As per N/27, N/28 & N/29			Provided at site		Remarks MR/NMR	
1.	Access of building					W 21 1 2			1 x m
	Road width	6 mtr			Provided				MR
	Gate width	4.5	70700	NA Direct access			ible from road		MR
	<ul> <li>Width of internal road</li> </ul>	NA							NA .
2.	Number, width, Type & Arrang	eme	nts o	f exits					
	a. Number of staircases.	-			Λ1		MD (	Doing of	d cose)
	<ul> <li>Upper floors</li> </ul>	01			01		_	Being ol	i case)
	<ul> <li>Basements</li> </ul>	02			02	Nos.	·MR		
	<ul> <li>b. Width of staircases</li> </ul>					1 11	1 10	m :	-14>
	Upper floors	1000000	25m	- Annescato		1-1.44m			old case)
	Basements	1.2	25m	1.28	3 &	21.29m	MR	(Being	old case)
	c. Protection of exits								
	Fire check door	NA NA					NA		
	Pressurization	NA			_ N	IA 💮		NA	
	d. No of continuous	01				0	1		MR
	staircase to terrace								
	e. Width Of Corridor	1.2	25m	D (*)	1.	5m, 1.32	2m		MR
	f. Door Size	Old case		se	0.87 m		MR (Being old case		old case)
3.	Compartmentation					John, T.			
	Fire check door			NA			NA		NA
	Sealing of electrical sh			NA	1A		Sealed NA		1
	<ul> <li>Fire Rating of shaft do</li> </ul>	or		NA					NA
	Water Curtain			NA			NA	- 1	NA
	Fire Dampers			NA			NA	-	NA NA
4.	Smoke managements System								11/1
	Basements	30	0 a/c	per hou	r	Provide	d		MR
	Upper floors	12 a/c per hour						MR	
	100								



1/39

5.	Fire Extinguishers				200 1-0	
	Total numbers	Nos.		Provided	MR	
	<ul> <li>Types</li> </ul>	AB	C & CC	2	CO <sub>2</sub> & ABC	MR MR
	<ul> <li>IS marking</li> </ul>	Req	uired		Provided	
5.	First - Aid Hose Reels				· · · · · · · · · · · · · · · · · · ·	
	Total numbers on ea floor	01		Provided	MR	
	<ul> <li>Length of hose reel l</li> </ul>	hose	30 mtr 5 MM		Provided	MR
	Nozzle diameter				Provided	MR
7	Automatic fire detection and	d alarmi	ng syste	m		
	<ul> <li>Type of detectors</li> </ul>		) detect		Provided	MR
	<ul> <li>Location of Main Panel</li> </ul>	Rec	quired		Provided	MR
	<ul> <li>Location of Repeate Panel</li> </ul>	r NA		NA		NA
	<ul> <li>Alternate source of power</li> </ul>	Rec	quired	DG se	t 62.5 KVA	MR
	<ul> <li>Hooters' Location</li> </ul>	NA	ko		NA	NA
8.	MOEFA		quired	Provid		MR
9.	Public Address System		quired Provided			MR
10.	Automatic Sprinkler System					
	Basements		quired		Provided	MR
	<ul> <li>Upper Floor</li> </ul>	NA			NA	NA
9	<ul> <li>Sprinkler above fals ceiling</li> </ul>	e · NA		NA		NA
11.	Internal Hydrants:					
_	<ul> <li>Size of riser/down-</li> </ul>	comer	N/	A	NA	NA
	<ul> <li>Number of hydrants</li> </ul>	per floo	or NA	<u> </u>	NA	NA
	<ul> <li>Hose Box</li> </ul>		N/	COS	NA NA	NA NA
12.	Yard Hydrants			i, Ta		1321
	Total number of hyd	Irants	N/	A 🔹	NA	NA
	Hose Box		N/	4	NA	NA
13.	Pumping Arrangements:					0.00
	Ground Level			II.		
	<ul> <li>Discharge of main p</li> </ul>	ump	NA -		NA	NA
	Head of main pump		NA		NA	NA
	Number of main pur		NA		NA	NA
	Jockey pump out pu	t	NA		NA	NA
	> Jockey pump head		NA		NA	NA
	Standby Pump out p	and the same of th	NA		NA	NA
	<ul><li>Standby Pump Head</li><li>Auto Staring/Manua</li></ul>		NA		NA	NA
	stopping		NA		NA	NA
	<ul> <li>Pump House Access</li> <li>Terrace level</li> </ul>	5	NA		NA	NA
	Discharge of pump		450		I n	1/2/2
	Head of the pump		450 lp		Provided	MR
	Power supply		30 mt		Provided	MR
	Auto starting of pun	ap	Requi		Provided	MR
	saming or pun	-Р	Requi	red	Provided	MR
		X	2	6		

4.	Under ground tank     capacity	NA			NA	NA
١	> Draw off connection	NA			NA	NA
	➤ Fire service inlet	NA			NA	NA
	Access to tank	NA			NA	NA
	<ul> <li>Overhead Tank capacity</li> </ul>	Old c			MR (Being old case)	
15	Exit Signage	Required			Provided	MR
16.	Provision of Lifts	•				•
	Pressurization of Lift S	haft '	NA		NA	NA
	<ul> <li>Pressurization of lift lo</li> </ul>	bby	NA		NA	NA
	> Communication in lift	Required		Provided	. MR	
	<ul> <li>Fireman's Grounding Switch</li> </ul>		Required		Provided	MR
	➤ Lift Signage		Reg	uired	Provided	MR
17. Standby power supply		Required			Provided	MR
18						
> Total area		NA		NA	NA	
	> Location		NA		NA	NA
1	9. Fire control room		8			
	Detector system panel	NA			NA	NA
	Flow Switch Panel	NA			NA	NA
1	➤ Battery backup R		NA		NA	NA
			quired		Provided	MR
	Building Floor Plans	s NA			NA /	NA
	<ol> <li>Special Fire Protection Syste Protection of special Risks,</li> </ol>			NA	УA	NA

The fire protection systems provided in the building were test checked and found

functional at the time of inspection.

In view of the deemed compliance of minimum standards on fire prevention and fire safety as required under the rules the FSC issued vide letter No. F6/DFS/MS/GH/SZ/2021/392, dated 16/09/21 renewal under Rule 37 of the Delhi Fire Service Rules 2010 is recommended. If approved the FSC may be issued.

Signature of the Inspecting Officer

Name: Sh. Udaivir Singh Designation: ADO (DWK)