

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTER: DELIH FIRE SERVICE: NEW DELHI- 110001



No. F6/DFS/MS/School/WZ/2024/ 653

Dated: 10 07 2024

FIRE SAFETY CERTIFICATE

Certified that the Govt. Sarvodaya Kanya Vidyalaya, ID-1617005 (Morning) & 1617227 (Evening), Located at Ranhaula, New Delhi-110041, comprised of 04 blocks of Ground + 01 Upper Floors only owned/occupied by the Govt. Sarvodaya Kanya Vidyalaya, was issued Fire Safety Certificate by this department Vide Letter No. F6/DFS/MS/School/2021/WZ/278 dated 31/03/2021. The said premises was re-inspected by the officer concerned of this department on 03/07/2024 in the presence of Sh. Janardan (Estate Manager) and found that the premises/building have deemed complied with the fire prevention and fire safety requirements in accordance D.O.E. Cr. No. 3298-3398 dated 01/03/2011 and that the premises/building is fit for occupancy class "Educational Building" Group B with effect from 10/07/2024 for a period of three years, subject to compliance of the conditions, printed below.

Issued on 10 07 2024 at New Delhi by.

Tel No. 011-23414000

Copy to: -

1. The Director, Directorate of Education, GNCT of Delhi, Old Secretariat Delhi - 110054.

2. The Principal, Govt. Sarvodaya Kanya Vidyalaya, ID-1617005 (Morning) & 1617227 (Evening), Ranhaula, New Delhi-110041.

Following fire safety directives must be adhered to:-

1. All the means of escape shall be kept free of all type of obstruction all the time.

2. All the employees shall be acquainted with the use and maintenance of all fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.

3. All the fire fighting equipments shall be maintained in perfect working condition all the time and any lapse rendering non-functional if fire safety measures, management shall be responsible.

4. Any deviation, with regards to construction, ventilation, occupation, electric installation etc. may be got verified from the concerned authorities.

5. The Fire Safety Certificate may not be treated in any case for regularizations of unauthorized construction / unauthorized use of land if any.

6. All comments / directions of licensing Department shall always be permitted and followed.

7. The owner /occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on www.dfs.delhigovt.nic.in

8. The owner / occupier shall apply for renewal of this Fire Safety Certificate to the Director in 'Form J' (sub Rule (1) of Rule 37) along with copy of the certificate, six months prior to its

9. The school principal has submitted an undertaking that remaining electrical instrument held under staircases will be shifted as early as possible & principal will be held responsible for any mishappening due to fire till the shifting of electric meter/panel

INSPECTION REPORT

1. Name and address of the building: Govt. Sarvodaya Kanya Vidylaya (ID-1617005,

Morning) & (ID-1617227, Evening) Located at

Ranhaula, New Delhi-110041.

2. Type of Occupancy

: Educational, (04 Blocks - G + 01 Upper Floors)

3. Type of Case

: Renewal

4. Details of previous NOC

: F6/DFS/MS/School/2021/WZ/278 Dated 31/03/2021

5. Fire Safety directives Letter No.

: D.O.E Circular no.3298-3398 dated 01-03-2011

Date of inspection

: 03/07/2024

Name of the Inspecting Officer

: Aman Kumar Lathar, ADO (JWP)

8. Name and designation of Officer

from the building side

: Sh. Janardan (Estate Manger)

9. Year of Construction

: 2009

| S | Minimum standards on fire | D.O.E. Cir | cular No. | Provided at | Ren | narke | |
|----|--|---|-----------|-----------------------------------|-------------------|-------|--|
| No | prevention and fire safety U/R 33 | 3298-3398 | | site | Remarks MR/NMR | | |
| | | 01/03/2011/ as per FSC | | Site. | MINIMI | | |
| | <u>→</u> | dated 31/0 | 3/2021 | | | | |
| 1. | Access of building | | | | | | |
| | Road width | 06 m | | Provided | MR | | |
| | Gate width | 4.5 m | | Provided | | MR | |
| | Width of internal road | NA | | NA | | NA. | |
| 2. | Number, width, Type & Arrangem | ents of exit | S | | | | |
| | a. Number of staircases | | | | | | |
| | Upper floors | 01 each blocks BL | | -1=02, BL-2=02, 3=02 & BL-4=02 | | MR | |
| | Basements | NA | | NA | | NA | |
| | b. Width of staircases | | | | | 1/1 | |
| | Upper floors | 1.5 m BL-1=1.45 m x 2 BL-2=1.45 m x 1 & 1.5 n BL-3=1.45 m x 2 | | -1=1.45 m x 2 | | MF | |
| | | | | im x 1 & 1.5 m x 1 | | | |
| | | | | | | | |
| | 455 | BL-4=1.50 m x 2 | | | | | |
| | Basements | NA | | NA | | NA | |
| | c. Protection of exits | | | | | | |
| | Fire check door | NA | | NA | NA | | |
| | Pressurization | NA | | NA | NA | | |
| | d. No of continuous staircase to terrace | NA | | NA | MR | | |
| | e. Width Of Corridor f. Door Size | 1.5 m | | Provided | MR | | |
| | i. Door Size | 1 m (Class Room) | | 1 m (Class Ro | | MR | |
| 3. | Comment | 1.5 n | n (Hall) | 1.9 m x 2 (Ha | all) | 11388 | |
| 2. | Compartmentation | | | NA | <u> </u> | | |
| | Fire check door | N. | A | NA | | NA | |
| | Sealing of electrical shafts | NA | | 2011 | | NA | |
| | Fire Rating of shaft door | NA | | NA N | | NA | |
| | Water Curtain | NA | | SOURCE CO. | | NA | |
| | Fire Dampers | NA | | NA N | | - | |

| 4. | Smoke managements System | | | ¥ 1. | | |
|-----|---|-----------------------|----------|----------------|--|--|
| | Basements | NA | NA | NA | | |
| | Upper floors | NA | NA | NA | | |
| 5. | Fire Extinguishers | | | 3 99.50 | | |
| ٥. | Total numbers | · 20 nos. | 35 nos. | MR | | |
| | • Types | ABC & CO ₂ | Provided | MR | | |
| | ISI marking | ISI marked | Provided | MR | | |
| 6. | First - Aid Hose Reels | | | N/ | | |
| 0. | Total numbers on each floor | NA | NA | N/ | | |
| | Length of hose reel hose | NA | NA | N/ | | |
| | Nozzle diameter | NA | NA | INZ | | |
| 7. | Automatic fire detection and alarming system | | | | | |
| | Type of detectors | NA | NA | N/ | | |
| | Location of Main Panel | NA | NA | N/ | | |
| | Location of Repeater Panel | NA | NA | N/ | | |
| | Alternate source of power | NΛ | NA | N. | | |
| | Hooters' Location | NA | NΛ | | | |
| 8. | MOEFA | NA | NA | N. | | |
| 9. | Public Address System | NA | NA | N/ | | |
| 10. | Automatic Sprinkler System | | | - | | |
| 10. | Basements | NA | NA | N _z | | |
| | Upper Floor | NA | NA | N/ | | |
| | Sprinkler above false ceiling | NA | NA | N/ | | |
| 11. | Internal Hydrants: | | 27.4 | N. | | |
| | Size of riser/down- comer | NA | NA | N. | | |
| | Number of hydrants per floor | NA | NA | N. | | |
| | Hose Box | NA | NA | IN | | |
| 12. | Yard Hydrants | NA | NA | l N | | |
| | Total number of hydrants | NA | NA NA | N. | | |
| | Hose Box | INA | | 3://5.8 | | |
| 13. | Pumping Arrangements: Ground Level | | | | | |
| | Discharge of main pump | NA | NA | N:A | | |
| | > Head of main pump | NA | NA | NA | | |
| | > Number of main pumps | NA | NA | NA | | |
| | > Jockey pump out put | NA | NA | NA | | |
| - | > Jockey pump head | NA | NA | NA | | |
| - 1 | Standby Pump out put | NA | NA | N/ | | |
| | > Standby Pump Head | NA | NA | NA | | |
| - 1 | Auto Staring/Manual | NA | NA | NA | | |
| | stopping > Pump House Access | NA | NA | N/ | | |
| | Terrace level | 11/7 | 4 | 7053 | | |
| | > Discharge of pump | NA | NA | N/ | | |
| | > Head of the pump | NA | NA | N/ | | |
| | Power supply | NΛ | NA | N/ | | |
| | ➤ Auto starting of pump | NΛ | NA | N/ | | |
| 14. | | | | | | |
| | Under ground tank capacity | NA | NA NA | NA NA | | |
| | Draw off connection | NA | NA NA | N/ | | |
| | Fire service inlet | NA | NA | | | |
| | Access to tank | NA | NA | N/ | | |
| | Overhead Tank capacity | NA | NA | N/ | | |
| 15 | Exit Signage | NA | NA | N/ | | |
| 16. | W. W. W. | | | | | |
| | > Pressurization of Lift Shaft | NA | NA NA | N/ N/ | | |
| - 1 | Pressurization of lift lobby Communication in lift Car | NA NA | NA NA | N/ | | |
| | | NA | INA | | | |
| | Fireman's Grounding Switch | | NA | N/ | | |

| | ➤ Lift Signage | NA | NA | NA |
|------------|---|----|----|----|
| 17. 18. | Standby power supply Refuge Area | NA | NA | NA |
| | > Total area > Location | NA | NA | NA |
| 19. | Fire control room | NA | NA | NA |
| | Detector system panel Flow Switch Panel PA System Panel Battery backup Building Floor Plans | NA | NA | NA |
| -1 | | NA | NA | NA |
| | | NA | NA | NA |
| 20 | | NA | NA | NA |
| | | NA | NA | NA |
| 20. | Special Fire Protection Systems for Protection of special Risks, if any; | NA | NA | NA |

Note:- In the reply of the earlier shortcoming issued to vide letter no. F6/DFS/MS/WZ/2024/School/55 dated 14/02/2024, the school principal has submitted an undertaking that remaining electrical instrument held under staircases of Block 'B' 'C' and 'D' will be shifted as earlier as possible.

Fire protection systems provided in the building were checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety requirements as per D.O.E. Circular no. 3298-3398 dated 01.03.2011, letter of issued vide renewal Fire Safety -Certificate F6/DFS/MS/School/2021/WZ/278 Dated 31/03/2021 is recommended.

Accordingly DFA is prepared for approval & signature please.

Aman Kumar Latha ADO (JWP)

Dero(w2)

Sir, F.T. letter is added for your rigniture 1st.

[411th 116]

- 10/07/24

ADD (2007)

Dreetox