

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE, CONNAUGHT PLACE NEW DELHI

No. F6/DFS/MS/2024/CH 286

Dated: 12 /07/2024

FIRE SAFETY CERTIFICATE

Certified that the building of M/s Hotel Sun Star Heritage, Located at Ground, 1st, 2nd & 3rd floor 8A/43, WEA, Karol Bagh, New Delhi-110005, in a building comprised of basement, ground plus three upper floors using basement as (storage), ground floor (reception & 03 guest room), first, second & third floor (5 rooms each floor) (Total=18 guest rooms) and 01 staff room with pantry on terrace (now sealed/closed) was issued FSC vide Letter No F6/DFS/MS/GH/SZ/2021/156, dated 25/03/2021. The premises was re inspected by the officer concerned of this department on 08/07/2024 in the presence of Sh. Abhinav Sharma and observed that all the fire prevention and fire safety arrangements provided in the premises found in good working condition. The premises have therefore deemed complied with the fire prevention and fire safety requirements in accordance with Rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class "Residential" (guest house) at ground floor (reception & 03 guest room), first, second & third floor (5 rooms each floor) (Total=18 guest rooms) with effect from 12 of 2024 for a period of three years in accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under Rule 38 of the Delhi Fire Service Rules, 2010.

Issued on ...12. 0.7-1.202.4. at New Delhi by.

Copy to:

 The Joint. Commissioner of Police (Lic), 1st Floor, Licensing Unit, Police Station, Defence Colony, New Delhi.

2. The Manager, M/s Hotel Sun Star Heritage, Located at Ground, 1st, 2nd & 3rd floor 8A/43, WEA, Karol Bagh, New Delhi-110005.

Following fire safety directives must be adhered to:-

1. 4th floor shall not be used for any purpose as undertaking given by owner.

- 2. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- 3. Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.
- 4. The trained staff should be available round the clock.
- 5. Any deviations w.r.t. construction shall be verified by the concerned building sanctioning agency.
- 6. The certificate may not be treated in any case for the regularization of the unauthorized construction, if any.
- 7. Basement strictly shall be kept vacant as seen during inspection.

8. The owner/ occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its expiry.

9. The owner/occupier shall submit a declaration every year in the form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on www.dfs.delhigovt.nic.in

1)36

INSPECTION REPORT

 Name & address of the building: M/s Hotel Sun Star Heritage, Located at Ground, 1st, 2nd & 3rd floor 8A/43, WEA, Karol Bagh, New Delhi-110005.

2. Type of Occupancy

:Lodging or rooming "A-1"

3. Type of Case : Renewal (Running at Ground, 1st, 2nd & 3rd floor in a building comprised of Basement + Ground + 03 Upper Floors and 01 staff room with pantry on terrace (now sealed/closed)

4. Details of previous NOC: F6/DFS/MS/GH/SZ/2021/156, dated 25/03/2021

5. Fire Safety directives Letter No.: Nil

6. Date of inspection

:08/07/2024

7. Name of the Inspecting Officer: ADO (DWK)

8. Name and designation of Officer

from the building side

: Sh. Abhinav Sharma

9. Year of Construction

: Before 2001

10. Applicant's letter No.

: 2024042005636, dated 19/06/2024

S No	Minimum standards on fire prevention and fire safety U/R	33	As per 1 N/31 &		Pro site	vided a	t Rema	
1.	Access of building				_			1.00
	Road width	06	mtr		Provid		155	MR
	Gate width			Direc	ct acces	sible fro	m road	MR
	Width of internal road	NA	4	NA	17		P 7	NA
2.	Number, width, Type & Arrar	ngeme	ents of e	xits				
	a. Number of staircases				0.1) (D	(Daina al	q.ooco)
	Upper floors	2.500000	No.		01	_	(Being of	u case)
	 Basements 	01	No.		01 Nos.	MR		
	b. Width of staircases		1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 -					
	 Upper floors 	3.35000	d case	1.22			MR (Being	
	Basements	Ol	Old case		1.15m		MR (Being old case	
	c. Protection of exits							
	Fire check door	Re	quired	Prov	ided			MR NA
	Pressurization		NA			NA		
	d. No of continuous	01	CHECK CO.			01		MR
	staircase to terrace	1						
	e. Width Of Corridor	1 1	m	1.20	m		MR (Being old ca	
	f. Door Size	Ol	d case ·	0.75	m	ı	MR (Being	g old case)
3.	Compartmentation		Dogu	ired	Prov	rided		MR
	Fire check door		Require NA		NA NA		1	
	Sealing of electrical sl		120,000,000	NA NA				NA
	Fire Rating of shaft do	oor	r NA		NA NA		NA	
	Water Curtain		NA		NA NA			NA
	Fire Dampers		NA	_	INA			1111
4.	Smoke managements System		SON BUILDING	Tn	vided			MR
	Basements 30	a/c p	er hour	7 7 7 7 7				MR
-	• Upper floors 12	a/c p	er hour	Prov	vided	led		IVIIC



M 37

		15	N 1.	01		Provided		M	R
	Contract Con				<u>د</u>		3C	M	R
	5 5	2319,41.79			2			MI	R
	WHILE DESCRIPTION OF THE STATE	Ke	quii	cu		Provided		1	
First -		-				Drovided		M	R
•		01				Plovided			
	• • • • • • • • • • • • • • • • • • • •	20	mtr	_		Provided		MI	R
•		30	ши			110,140			
12		5 N	ИΜ			Provided		MI	2
Autom		. ATT-2 100 s		svste	m				
Autom						Provided		_	_
•		NA	\			NA		NA	1
	Panel							NT A	_
•	Location of Repeater	N/	1	d	NA			NA	1
	Panel							MI	-
•	Alternate source of	Re	quir	ed	DG se	t 82 KVA		IVII	•
		NI	6			NIA		I N	Ā
MODE		200000	100	-	P	DESERTE .	3.40		
Service and a se	-7.12				The state of the s				-
		Ke	quir	ea	Provid	ieu	IVII		_
Auton		N/		2.	Provide	d Area le	ss than 200	sa.m	ıtr
•	TOTAL							1	1625
•				_					
	ceiling	346	Fi.	- 1		1.100			
Intern	The state of the s								
ı				NA	ì	NA		NA	
•		r flo	or	.NA		NA		NA	1
•	100 M		NA			NA	NA		1
Yard I		Tee							Ť
•		NA	A.			NA		NA	
48		N/	ν			774		2020 10	1
Pump		147	A		NA		NA	L	
•	Ground Level				•/				╀
•	Discharge of main pun	np	NA	4		NA		NIA	┞
>	Head of main pump	•		_					-
	Number of main pump	S	NA NA			NA			-
	Jockey pump out put				NA				
	Standby Pump out put	tandby Pump out put					NA		
	Standby Pump Head			1000		NA			
>	Auto Staring/Manual			_					
	stopping		1 17	•		NA		NA	
1100			N	4		NA		NIA	
			1921		IM		NA		
À	Head of the nump			450 lpm		Provided		MR	_
	Power supply					Provided		_	
A									-
	,		100	quir	υα	Provided			
					94				
	Autom MOEF Public Autom Yard I	 Type of detectors Location of Main Panel Location of Repeater Panel Alternate source of power Hooters' Location MOEFA Public Address System Automatic Sprinkler System Basements Upper Floor Sprinkler above false ceiling Internal Hydrants: Size of riser/down-core Number of hydrants peeds to hydrants Hose Box Yard Hydrants Total number of hydrants Hose Box Pumping Arrangements: Ground Level Discharge of main pump Number of main pump Number of main pump Jockey pump out put Jockey pump out put Jockey pump Head Standby Pump Out put Standby Pump Head Auto Staring/Manual stopping Pump House Access Terrace level Discharge of pump Head of the pump Power supply 	• Total numbers • Types • IS marking First – Aid Hose Reels • Total numbers on each floor • Length of hose reel hose • Nozzle diameter Automatic fire detection and alarmi • Type of detectors • Location of Main Panel • Location of Repeater Panel • Alternate source of power • Hooters' Location MOEFA Republic Address System Automatic Sprinkler System • Basements • Upper Floor • Sprinkler above false ceiling Internal Hydrants: • Size of riser/down-comer • Number of hydrants per floor • Hose Box Yard Hydrants • Total number of hydrants per floor • Hose Box Yard Hydrants • Total number of hydrants • Total number of main pump • Head of main pump • Number of main pump • Number of main pump • Number of main pump • Standby Pump out put • Jockey pump head • Standby Pump Out put • Standby Pump Head • Auto Staring/Manual stopping • Pump House Access • Terrace level • Discharge of pump • Head of the pump • Power supply	• Total numbers • Types • Types • IS marking First – Aid Hose Reels • Total numbers on each floor • Length of hose reel hose • Nozzle diameter • Nozzle diameter • Location of Main Panel • Location of Repeater Panel • Alternate source of power • Hooters' Location MOEFA Public Address System • Basements • Upper Floor • Sprinkler System • Basements • Upper Floor • Sprinkler above false ceiling Internal Hydrants: • Size of riser/down-comer • Number of hydrants per floor • Hose Box Yard Hydrants • Total number of hydrants • Hose Box Pumping Arrangements: • Ground Level • Discharge of main pump > Head of main pump > Number of main pump > Head of main pump > Number of main pump > Standby Pump out put > Standby Pump out put > Standby Pump Head > Auto Staring/Manual stopping > Pump House Access • Terrace level > Discharge of pump > Head of the pump > Power supply > Auto starting of pump > Auto starting of pump > Head of the pump > Power supply > Auto starting of pump	• Total numbers • Types • IS marking First – Aid Hose Reels • Total numbers on each floor • Length of hose reel hose • Nozzle diameter Automatic fire detection and alarming syste • Type of detectors • Location of Main Panel • Location of Repeater Panel • Alternate source of power • Hooters' Location MOEFA Automatic Sprinkler System • Basements • Upper Floor • Basements • Upper Floor • Sprinkler above false ceiling Internal Hydrants: • Size of riser/down-comer • Number of hydrants per floor • Hose Box Yard Hydrants • Total number of hydrants per floor • Hose Box Yard Hydrants • Total number of main pump > Head of main pump > Head of main pump > Head of main pump > Jockey pump out put > Jockey pump out put > Jockey pump out put > Jockey pump head > Standby Pump Head > Auto Staring/Manual stopping > Pump House Access • Terrace level > Discharge of pump > Head of the pump > Power supply > Auto starting of pump	Total numbers Types Types IS marking First – Aid Hose Reels Total numbers on each floor Length of hose reel hose Nozzle diameter Type of detectors Location of Main Panel Alternate source of power Hooters' Location Basements Basements Upper Floor Sprinkler above false ceiling Internal Hydrants: Size of riser/down-comer Number of hydrants per floor Hose Box Yard Hydrants Ground Level Discharge of pump Head of main pump Standby Pump Head Auto Staring/Manual stopping Power supply Head of the pump Power supply Power supply Power supply Iotal number of pump Head of the pump Power supply Iotal number of pump Head of the pump Power supply Iotal number of pump Head of the pump Power supply Iotal number of pump Head of the pump Power supply Iotal number of pump Head of the pump Power supply Iotal number of pump Head of the pump Power supply Iotal number of pump Head of the pump Power supply Iotal number of pump Head of the pump Power supply Iotal number of pump Head of the pump Power supply Iotal number of pump Head of the pump Power supply Iotal number of pump Head of the pump Power supply	Total numbers Types Types Types Total numbers on Each floor Length of hose reel hose Nozzle diameter Type of detectors Location of Main Panel Location of Repeater Panel Alternate source of power Hooters' Location Basements Upper Floor Basements Sprinkler above false ceiling Internal Hydrants Size of riser/down-comer Number of hydrants per floor Namber of hydrants Total number of hydrants Hose Box Pumping Arrangements: Ground Level Discharge of pump Head of the pump Power supply Power supply Power supply Provided Required Provided NA NA Provided Provided NA	Total numbers Types Types Sarck & CCO2 Types Sarck & CCO2 Sarck & CCO2 CCO2 & ABC CCO2 & ACCAC CCO2 & ABC CCO2 & ACCAC NA N	Total numbers Types ABC & CO₂ CO₂ & ABC MM ABC & CO₂ CO₂ & ABC MM Frovided MI First — Aid Hose Reels Total numbers on each floor Length of hose reel hose Nozzle diameter MI Automatic fire detection and alarming system Type of detectors Location of Main Panel Location of Repeater Panel Alternate source of power Hooters' Location MOEFA Required MR Automatic Sprinkler System Basements Sprinkler System Basements Sprinkler above false ceiling Internal Hydrants: Size of riser/down-comer Number of hydrants per floor Hose Box Pumping Arrangements: Ground Level Discharge of main pump Head of main pump Head of main pump Head of the pump Head of the pump Power supply Auto starting of pump Provided MI Provided MI MA NA

					36.1
4.	Captive water Storage for fire fi	ghting	g:		
4.	Under ground tank capacity	NA		NA	NA
	> Draw off connection	NA		NA	. NA
	> Fire service inlet	NA		Provid	ed
	> Access to tank	NA		NA	NA
	Overhead Tank capacity	Old	case	5,000	ltr MR
15	Exit Signage	Regi	aired	Provid	led MR
16.	Provision of Lifts				
10.	> Pressurization of Lift Sl	naft	NA	NA	NA
	> Pressurization of lift lob		NA	NA	NA
	> Communication in lift (Required	Provid	led MR	
	> Fireman's Grounding Switch		Required	Provid	led MR
	➤ Lift Signage	1		Provid	led MR
17			Required Required	AND TO SERVICE AND THE PARTY OF	
17			Atoquaso		
18	. Refuge Area > Total area		NA	NA	NA
1	> Location		NA	NA	NA NA
1	P. Fire control room				
1	> Detector system panel			NA	NA
				NA	. NA
	> PA System Panel	NA NA		NA	NA
	 Battery backup Building Floor Plans 			NA	NA
				NA	NA
1	O. Special Fire Protection System Protection of special Risks, in	ns for	NA	NA	A NA

The fire protection systems provided in the building were test checked and found

functional at the time of inspection.

In view of the deemed compliance of minimum standards on fire prevention and fire safety as required under the rules the FSC issued vide letter No. F6/DFS/MS/GH/SZ/2021/156, dated 25/03/2021 renewal under Rule 37 of the Delhi Fire Service Rules 2010 is recommended. If approved the FSC may be issued.

Signature of the Inspecting Officer

Name: Sh. Udaivir Singh Designation: ADO (DWK)