

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE, CONNAUGHT PLACE NEW DELHI

No. F6/DFS/MS/CGHS/SZ/2024/ 4 65

Dated: 23 p7/2024

FIRE SAFETY CERTIFICATE

Certified that the building of Pacific CGHS Ltd. Located at Plot No-39, Sector-10, Dwarka, New Delhi-110075, having 02 blocks comprised of stilt + 05/06 Upper floors was issued FSC by this department vide letter No. F6/DFS/MS/CGHS/2002/1120, dated 10/07/2002. The premise was re inspected by the officer concerned of this department on 09/07/2024 in the presence of. Sh. Dishant Kumar (Manager) and found that the said building have deemed complied with the fire prevention and fire safety requirements in accordance with Rule 33 of the Delhi Fire Service Rule, 2010 and that the premises is fit for occupancy class "Residential Building" Group A-4 with effect from 23 of 2021 for a period of five years in accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under Rule 38 of the Delhi Fire Service Rules, 2010.

Issued on 23 07 2024 at New Delhi by.

Delhi Fire Service

Copy to:

 The President, Pacific CGHS Ltd. Located at Plot No-39, Sector-10, Dwarka, New Delhi-110075.

2. The Joint Director (Building) DDA, Vikas Sadan, INA, Delhi-110023.

Following fire safety directives must be adhered to:-

- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- 2. Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.

3. The trained staff should be available round the clock.

- 4. Any deviations w.r.t. construction shall be verified by the concerned building sanctioning agency.
- 5. The certificate may not be treated in any case for the regularization of the unauthorized construction, if any.

6. Basement shall be used as per building bye laws.

7. The owner/ occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its expiry. www.dfs.delhigovt.nic.in.

8. The owner/occupier shall submit a declaration every year in the form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on www.dfs.delhigovt.nic.in

V/19

INSPECTION REPORT

 Name & address of the building: Pacific CGHS Ltd. Located at Plot No-39, Sector-10, Dwarka, New Delhi-110075.

2. Type of Occupancy : Residential Building "A" (Apartment)

3. Type of Cas : Renewal 02 block= stilt + 6 UF & Stilt+5UF

4. Details of previous NOC : F6/DFS/MS/CGHS/2002/1120, dated 10/07/2002

5. Fire Safety directives Letter No.: F6/DFS/MS/CGHS/95/1189, dated 04/08/95

6. Date of inspection : 09/07/2024

7. Name of the Inspecting Officer: Sh. Udai vir Singh ADO (DWK)

8. Name and designation of Officer

from the building side : Sh. Dishant Kumar (Manager)

9. Year of Construction : 1996

10. Applicant's letter No. : Email dated-01/07/2024

lo	Minimum standards on fire prevention and fire safety U/R 33	2500	As Per NBC			Provided at site		_	emarks IR/NMF	
	Access of building									
	Road width .		09 mtrs				M			
	Gate width	4.5 mtr	.5 mtrs		Provided		M		R	
	 Width of internal road 	6 mtrs 390cm		m to 61	to 6m M		R(Being old ca		ase)	
2.	Number, width, Type & Arranger	nents of	exits							
	 a. Number of staircases 								_	
	Upper floors Basements	3 no.	ck	Provi		ided		MR		
		NA	NA N			JA I			NA	
	b. Width of staircases				-					
	Upper floorsBasements				BL-A=112cm,2x88cn BL-B=107cm,2x88cn			2000	R (Being case)	
				NA	and the same		NA			
	c. Protection of exits					1 - 1.		-		
	 Fire check door Pressurization d. No of continuous staircase to terrace e. Width Of Corridor f. Door Size 	N/A	N/A			N/A		N/A		
		N/A	N/A			N/A		N/A		
		01 each block			7 1	Provided		MR		
		N/A				N/A		N/A		
		N/A		1	N/A		N/A			
3.	Compartmentation	+	-				10.550% 833	-		
	Fire check door	N/A				N/A		N/A		
	 Sealing of electrical shafts Fire Rating of shaft door Water Curtain Fire Dampers 	N/A				N/A		N/A		
			N/A			N/A		N/A		
		N/A						N/A		
4.		N/A						N/A		
4.	Smoke managements System					- " - " - " - " - " - " - " - " - " - "				
	Basements	NA	NA			NA		NA -		
	 Upper floors 	12 a/c	12 a/c per hour Pr			rovided		MF	{	

N/20

i.	Fire Extinguishers				, D	wided		MR	-
	• Types CC		nos. caer me		rovided			+	
						O ₂ , ABC, Water Co2		MR MR	-
			ISI			Provided		MR	-
5.	First -	Aid Hose Reels					100	0	H
8745	Total numbers on each floor		02 Nos. Each floor		The transmission and the same	Provided M		H	
	•	Length of hose reel hose		30 m			Provided M		L
	Nozzle diameter			5 mm		Provided	Provided MF		L
7.	Autom	atic fire detection and aları	ning s	system			121		L
55	Type of detectors			N/A	N/A	7 1)	N/A Provided MI		-
	Location of Main Panel Location of Repeater Panel			Ground floo	or	Provided	TOVIGOR		
				N/A	N/A		N/A MR		
	•	Alternate source of power		Required	Provi	Provided		Colo.	
	•	Hooters' Location		Near stairca	ise .	Provided	MF		
0	MOEE	. A		Required	Provi	ded	MI		
8.	MOEFA Public Address System			Required	Provi	ded	MR		
9.				There were a second		E E W			
10.	N. 7. A				NA		NA		
	• Dascinches		N/A	N/A			15	I/A	
	•	 Upper Floor Sprinkler above false N/A 		0.000000			1	I/A	
		ceiling	147		22				
11.								ИR	
1 1.	Size of riser/down- comer			100 mm		rovided	Ovided		
	Number of hydrants per floor			1 each bloc	1970	Provided	1	M	R
	Hose Box			01 No.	Provide	d			-
12.	Vard	Hydrants					12	МR	-
12.	Total number of hydrants Hose Box			Required		rided	icu		1
				Required	Prov	ided	ed		
12	Dump	ing Arrangements							-
13	. Pump	Ground Level				1571	NA		
		Discharge of main pun	np	INA		NA	NA NA	-	-
	 Discharge of main pump Head of main pump Number of main pumps Jockey pump out put Jockey pump head 			NA .		NA	374		-
				INA		NA		_	
				INA		NA	274		(4)
				NA		NA	NIA		-
	D	Standby Pump out put			NA ·		NA NA		-
	Standby Pump Head			NA		NA	3.7.4		
	Auto Staring/Manual				NA	NA			
	stopping > Pump House Access Terrace level			NA NA			NA		
				1000 m					
				450 lpm		Provided MF			_
	>	Discharge of pump		40m		Provided			-
	>	> Head of the pump			Required		Provided MF		
	>	Power supply		Required		Provided MR			
	> Auto starting of pump		Required						
							×	_ [
-								- 1	
		TV.		M.			170	-	





N|2|

4.	aptive water Storage for fire fight. Under ground tank capacity	2,00,000 ltrs P		Provided		MR		
	 Fire service inlet Access to tank Overhead Tank capacity 		D		Provided		MR	
					ovided	MR MR		
			ired	Provided				
	4	10,00	00 ltr each b	each block Provided			MR	
	xit Signage	Requ		ovide		=	MR	
6. F	rovision of Lifts		5		1	IVIK		
	> Pressurization of Lift Sha	aft	N/A	N/A N/A		N/A		
1	 Pressurization of lift lobb Communication in lift C 	by	N/A			N/A		
1	Fireman's Grounding Swit		ar Required		Provided			
-	► Lift Signage	viien	Required	P	rovided	MR MR		
			Required		rovided	MR		
17.	\$tandby power supply		Required	DG Set 60 KVA		MR		
18.	Refuge Area			-		1.000		
	Total area		N/A	1	N/A			
	> Location		N/A		N/A		N/A N/A	
19.	Fire control room		DEL KARRESON					
	Detector system panel	N/A	N/A N/A N/A N/A N/A Provided			N/A		
01	Flow Switch Panel	N/			N/A	N/A		
	PA System PanelBattery backup	· N/			Provided .	N/A		
	Building Floor Plans		N/A		Provided		N/A	
			Required		Provided		MR	
20	 Special Fire Protection Systems for Protection of special Risks, if any; 		Required		CO2 fire extinguisher provide near electric panel		rided M	

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

In view of the deemed compliance of minimum standards on fire prevention and fire safety as required under the rules the FSC issued vide letter No. F6/DFS/MS/CGHS/2002/1120, dated 10/07/2002 renewal under Rule 37 of the Delhi Fire Service Rules 2010 is recommended. If approved, the FSC may be issued.

Signature of the hispecting Officer Name

Designation

MADIOWIA

olso dialay

In the son

Am I pm