FORM 'H' FORM FOR ISSUING FIRE SAFETY CERTIFICATE

[Refer sub - rule (1) of rule 35] GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE, CONNAUGHT PLACE **NEW DELHI**

No. F6/DFS/MS/SZ/2024/School 709

Dated: 23 /07/2024

FIRE SAFETY CERTIFICATE

Certified that the Govt. Co- Ed. Senior Secondary School, Located at Sector -06, Site-II, Dwarka New Delhi - 110075. comprised of Ground + 03 Upper Floors owned / occupied by Delhi Government was issued FSC vide Letter No. /DFS/MS/SZ /2021/441, dated 06/07/2021 The premises was re inspected by the officers concerned of this department on 12/07/2024 in the presence of Dr. Seema Bhardwaj (Principal) and found that the said building have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rule, 2010 and that the premises is fit for occupancy class-B "Educational" with effect from 23 07 2024 for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

Issued on . 23 .07. 2024.. at New Delhi by.

Director

Copy to:

- 1. Govt. Co- Ed. Senior Secondary School, Sector -06, Site-II, Dwarka, New Delhi 110075.
- 2. Directorate of Education Old Secretariat Delhi 110054

Following fire safety directives must be adhered to:-

- 1 All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- 2 Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.
- 3 The trained staff should be available round the clock.
- 4 Any deviations w.r.t. construction shall be verified by the concerned building sanctioning agency.
- 5 The certificate may not be treated in any case for the regularization of the unauthorized
- 6 The owner/ occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its
- 7 Basement shall be used strictly as per building bye laws.
- 8 The owner/occupier shall submit a declaration every year in the form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on www.dfs.delhigovt.nic.in.

INSPECTION REPORT

 Name & address of the building: Govt. Co- Ed. Senior Secondary School, Located at Sector -06, Site-II New Delhi – 110075.

2. Type of Occupancy: Educational Old building (3 BL=G+3UF attached with each floors)

3. Type of Case

: Renewal

4. Details of previous NOC: F6/DFS/MS/SZ/2021/441, dated 06/07/2021

5. Fire Safety directives Letter No.: DOE 3298-3398 dated 01-03-2011

6. Date of inspection

: 12/07/2024

7. Name of the Inspecting Officer: Udai vir singh, ADO (DWK)

8. Name and designation of Officer

from the building side

:Dr. Seema Bhardwaj (Principal)

9. Year of Construction

: 2010

10. Applicant's letter No. ·

:GCOED/SSS/DWK/S-VI/81, dated 25/06/2024

No.	Minimum standards on fire prevention and fire safety U/R	2 33	Requireme N/11, N/12			Provided at site		emark R/NN		
۱.	Access of building Road width	Accessible(06mtrs)		rs)	Provided			MR		
	Gate width	4.5mtrs			provided			1000	MR	
	Width of internal road	NA			NA			·	IA	
2.	Number, width, Type & Arra	ngem	ents of exits			7" 11 1				
	a. Number of staircases					T				
	Upper floors	(1000)			4 Provided		MR			
	Basements	NA		N	NA		NA .			
	b. Width of staircases									
-	Upper floors	1.5m if less than 1.5m additional staire case of 75cm in required		m	Old building (3 BL- attached with each floors) 2X150cm,1x143cm,1x145cm			m	MR	
	Basements	NA			NA				NA	
	c. Protection of exits		18					-		
	 Fire check door Pressurization d. No of continuous staircase to terrace e. Width Of Corridor 	N/		10000				NA		
1		N/	D#-0	IA			NA			
		Re	equired P	Provided MR						
4		15	150cm 152cm to 100m(512 table)				M	IR.		
	f. Door Size		100cm 90cm &109cm(Double door) MR(

No. W

4/19

3.	Compartmentation				4		
<i>.</i>	Fire check door		NA	N	JA		NA
	Sealing of electric	al chafte	NA		IA .	- 1	VA
	Fire Rating of share		NA NA		IA		NA
	Water Curtain	ii door	ACCULATO				NA NA
	Fire Dampers		NA		IA.		
1.			NA	IN	A	- I	NA
+ .	Smoke managements System						
	 Basements 	NA		N	Α .	N	IA
	 Upper floors 	Requi	ired 1	Vatural v	ventilation pr	ovide	i MR
5.	Fire Extinguishers	_		-			
	 Total numbers 	20 no	s.	37	Provided Provided	M	íR ·
	 Types 	ABC	$\& CO_2$	Pr	ovided		IR
	 IS marking 	ISI ma	arked	Pr	ovided	-	R
5	First - Aid Hose Reels				,		
	 Total numbers on e 	ach floor	2	Pr	ovided	M	R
	 Length of hose reel 	hose	30m		ovided	M	1500
	 Nozzle diameter 		5mm		ovided	M	
,	Automatic fire detection ar	nd alarmin	g system	, , , ,	vided	IVI	
	 Type of detectors 	NA	8 -) - 1 - 1	NA			INTA
	 Location of Main 	NA	V	NA			NA
	Panel	NA		NA			NA
	 Location of 			1121			NA
	Repeater Panel	NA		NA			NTA
	 Alternate source of 						NA
	power	NA		NA		-	774
	Hooters' Location						NA
	MOEFA	NA		NA			
0.	Public Address System	NA		NA			NA
·	Automatic Sprinkler System			2 12 1	840		NA
	Basements	NA		NA			
	• Upper Floor	NA		NA			NA ·
	Sprinkler above folco a : !!	NA		15110-200-2		l	NA
١.	false ceiling Internal Hydrants:	10 VOID		NA			NA ·
	Size of a contract to						
	 Size of riser/down- c 	omer	NA		100		
	Number of hydrants Hose Box	per floor	NA		100mm		NA
2.	Yard Hydrants		NA	200	Two		NA
1	• Total				Provided		NA
1	 Total number of hydrants 	NA		T			
1	• Hose Box			Two			NA
1	11026 P0X	NA		Des			
				Provi	ded		NA
	_					- 1	
				1			

٨١	120
N	90

T			V: I		
Pi	imping Arrangements:	T		γ,	
	 Ground Level 				NA
	Discharge of main pump NA			NA ·	NA NA
	Head of main pump	NA		NA	NA NA
	Number of main pum	os NA		NA	
\mathbb{H}	Jockey pump out put	NA		NA	NA
	Jockey pump head	NA		NA	NA
	 Standby Pump out put Standby Pump Head Auto Staring/Manual stopping Pump House Access Terrace level 			NA	NA
				NA	NA
				NA	NA
- [NA	NA
					LVO
	Discharge of pump	450	lpm	Provided	MR
	> Head of the pump	40N	/Itr	Provided	MR
^	> Power supply	Rec	uired	Provided	MR
	Auto starting of pum	1100	quired	Provided	MR
4.	Captive water Storage for fir	re fighting:	a least		
	 Underground tank capacity 	NA	-2	NA	NA
	> Draw off connection	NA		NA .	NA
-	> Fire service inlet NA > Access to tank			NA	NA
- 1				NA	NA
			trs	Provided	MR
	capacity	10,000L		Tiovided	IVIK
15	Exit Signage	Require	d	Provided	MR ·
16.	Provision of Lifts			Kare All Colors	IVIK
	Pressurization of Li	ft Shaft	NA	NA	NA.
	Pressurization of life	t lobby	NA	NA	NA
	 Communication in lift Ca Fireman's Grounding Sw 		NA	NA NA	NA
			NA	NA NA	NA
	➤ Lift Signage		NA	NA NA	NA
17.	Standby power supply	•		INA	NA
18.	Refuge Area		NA	NA	NIA
	> Total area				NA
	> Location		NA	NA	
19.	Fire control room		NA	NA	NA
	THOUIT TOURS			TWI-	NA NA
	 Detector system pa Flow Switch Panel 	nel	NA·	NA	
	> PA System Panel		NA	NA	NA
	> Battery backup	NA		NA	
	Building Floor Pla	NA	NA	NA	
	Floor Pla	ns	NA	NA	NA NA
			1111	NA	
					NA
	X.	TD .			. 4

Special Fire Protection Systems for Protection of special Risks, if any;	NA	NA	NA
10 M			

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

In view of the deemed compliance of minimum standards on fire prevention and fire safety as required under the rules the FSC issued vide letter No. F6/DFS/MS/SZ /2021/441, dated 06/07/2021 renewal under Rule 37 of the Delhi Fire Service Rules 2010 is recommended. If approved, the FSC may be issued.

Signature of the Inspecting Officer

Name Udou Designation

10 see of 18/2/11

Dinector () ()