

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: NEW DELHI - 110001



No F 6 / DFS / MS / 2024 /School/WZ/ 701

Dated 23/07/2024

FIRE SAFETY CERTIFICATE

Certified that the Sarvodaya Kanya Vidyalaya located at Tulsi Nagar, Delhi- 110035 comprised of 02 Blocks interconnected (A Block- Ground plus first floor) & (B- Block-Ground plus three upper floors) owned/ occupied by Sarvodaya Kanya Vidyalaya have complied with the fire prevention and fire safety requirements in accordance with DOE circular no. 3298-3398 dated 01.03.2011 and verified by the officers concerned of Fire Service on 11.07.2024 in the presence of Sh. Rakesh Kumar Jaiswal (Principal) and found that the building/ premises is fit for occupancy Group B Educational with effect from 23 07 24 for a period of 03 (Three) years subject to compliance of the conditions mentioned below:

Issued on ...23 07 2024 at New Delhi by

Ale A

Copy to:-

1. The Director of Education, Govt. of NCT of Delhi, Old Secretariat, Delhi.

2. The Principal, Sarvodaya Kanya Vidyalaya located at Tulsi Nagar, Delhi- 110035.

Conditions for the validity of Fire Safety Certificate:

1. All the fire safety arrangement provided there-in shall be maintained in good working conditions at all times.

2. Loss of life or property due to non functional fire safety measure shall be at the responsibility of the management.

3. The trained fire fighting staff should be available round the clock.

4. Any deviation with regard to the construction etc shall be verified by the concerned building sanctioning agency.

5. This certificate cannot be treated in any case for regularizations of unauthorized

construction.

6. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director of Form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six months prior to its expiry".

7. The owner / occupier shall submit a declaration every year in form "K" provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on

WWW.dfs.Delhigovt.nic.in

8. All the means of escape shall be kept free of any obstruction all the time to evacuate the occupant, in a safe manner, in the event of emergency.

INSPECTION REPORT Name & address of the building:

Sarvodaya Kanya Vidyalaya, Tulsi Nagar , Delhi- 110035.

2. Type of Occupancy
3. Building Comprised of
4. Type of Case
5. Details of Previous NOC
6. Fire Safety directives letter No
7. Date of inspection
8. Name of Inspecting Officer
9. Name and designation of officers

From the building side : 02 Blocks (01 Blocks, G+1) & 01 Block (G+3) Interconnected in H Shape New Case

Nil

DOE circular No. 3298-3398 dated 01/03/2011

11/07/2024

R.K.Sinha, ADO (BW)

From the building side Dr. R.K. Jaiswal (Principal)

Minimum Standards on fire prevention and fire safety U/R 3	DOE Requirement	Provided at site	Remarks MR/NMF			
Access to building						
Road width	6 m	Provided	MR			
Gate width	4.5 m	Directly Accessible	MR			
Width of internal road	NA	NA	NA			
Number, Width, Type & Arrangement of Exits						
Number of staircases						
Upper Floors	02	03	MR			
Basements	NA	NA	NA			
Width of staircases	aircases					
Upper Floor	1.50 m each	2 m, 1.40 m & 1.35 m	MR			
	NA	NA	NA			
Dascinents						
E E E E E E E E E E E E E E E E E E E	NA	NA	NA			
	11/1/20/1/20	- CANALE	NA			
	• • • • • • • • • • • • • • • • • • • •					
No. of continuous staircases to terrace	Required	Provided	MR			
Width of Corridor	NA	NA	NA			
Door Size	1 m	1 m, Double Door with	MR			
	NA	NA I	NA			
		2000,000				
The second secon		=1 ×	NA			
		83000	NA			
			NA			
	7.77.7					
Smoke Management System						
Basements	NA	NA	NA			
Upper floors	Required	Naturally Ventilated	MR			
Fire Extinguishers						
Total numbers	1 @ 300 sqm	Provided	MR			
Types	ABC Type		MR			
IS marking						
Total numbers on each floor	01 in each block	Provided	100			
Length of hose reel hose	30 m		MR			
		5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5	MR			
Type of detectors NA						
		- 22 22	NA			
	ALCO INC		NA			
		NA	NA			
	NA NA	NA	NA			
Hooters' Location	NA	NA				
MOEFA	NA	110	NA			
	Access to building Road width Gate width Width of internal road Number, Width, Type & Arrange Number of staircases Upper Floors Basements Width of staircases Upper Floor Basements Protection of exits Fire check door Pressurization No. of continuous staircases to terrace Width of Corridor Door Size Compartmentation Fire check door Sealing of electrical shafts Fire Rating of shaft door Water Curtain Fire Dampers Smoke Mana gement System Basements Upper floors Fire Extinguishers Total numbers Types IS marking First-Aid Hose Reels Total numbers on each floor Length of hose reel hose Nozzle diameter Automatic fire detection and alarm Type of detectors Location of Repeater Panel Alternate source of power	Road width 6 m Width of internal road NA Number, Width of internal road NA Number, Width, Type & Arrangement of Exits Number of staircases Upper Floors 02 Basements NA Width of staircases Upper Floor 1.50 m each Basements NA Protection of exits Fire check door NA Pressurization NA NA No. of continuous staircases to terrace Width of Corridor NA Door Size Compartmentation Fire check door NA Sealing of electrical shafts NA Fire Rating of shaft door NA Water Curtain NA Fire Dampers NA Smoke Management System Basements NA Upper floors Required Fire Extinguishers Total numbers NA Required First-Aid Hose Reels Total numbers on each floor 01 in each block Length of hose reel hose NA	Prevention and fire safety U/R 33 Requirement			

	- 9	1
A 1	1	ч
10		,

				100		
		N-14		WY.		
•	Public Address System	NA	NA	- VA		
10.	Automatic Sprinkler System			147		
	Basement	NA	374			
	Ground Floor	NA NA	NA NA	NA		
	Sprinkler above false ceiling	NA	NA NA	NA		
11.	Internal Hydrants		IVA	NA		
	Size of riser/down-comer	NA	100 D 11 1			
	Number of hydrants per floor	NA	100 mm, Provided 01 in each block	NA NA		
2550	Hose Box	NA	01 in each block	NA NA		
12.	Yard Hydrants			1377		
	Total number of hydrants	NA	NA	NA		
13	Hose Box	NA	NA	NA		
13.	Pumping Arrangements Ground Level		The state of the s			
	Discharge of main Pump	374				
	200 A 100 A 201	NA NA	NA NA	NA		
	Head of Main pump	IVA	NA	NA		
	Number of main pumps	NA	NA	NA		
	Jockey Pump out put	NA	NA	NA		
	Jockey pump head	NA -	NA	NA		
	Standby Pump Out put	NA	NA	NA		
	Standby Pump Head	NA	NA	NA		
	Auto Starting/Manual Stopping	NA	NA	NA NA		
	Pump House Access	NA	NA	NA		
	Terrace level					
	Discharge of pump	450 lpm	Provided	MR		
	Head of the pump	40 m	Provided	MR		
	Power Supply	Required	Provided	MR		
	Auto Starting of pump	Required	Provided	MR		
14.	Captive water Storage for fire fighting					
	Underground tank capacity	NA	NA	NA		
	Draw-off connection	NA	NA	NA		
	Fire service inlet	NA	NA	NA		
	Access to tank	NA	NA	NA		
15.	Overhead Tank capacity Exit Signage.	10,000 ltrs	Provided	MR		
٠٠.		Required	Provided	MR		
16.	Provision of Lifts.					
	Pressurization of Lift Shaft	NA	NA	NA		
	Pressurization of Lift lobby	NA	NA	Owner market		
	Communication In lift Car	NA	NA NA	NA NA		
	Fireman's Grounding Switch	NA	NA	NA NA		
	Lift Signage	NA	NA NA			
17.	Standby power supply	NA NA	250000	NA		
18.	Refuge Area.	.,,,	NA	NA		
	Total Area Location	NA	NA	NA		
19.	Fire Control Room	NA	NA	NA NA		
	Detector System Panel	377				
	Flow Switch Panel	NA NA	NA	NA		
	PA System Panel	NA NA	NA	NA		
	Battery backup	NA	NA	NA		
		NA	NA	NA		
	Building Floor Plans	NA NA	NA	NA		

Ŋ

Ī

2

e

è

: