

#### GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE, CONNAUGHT PLACE

No. F6/DFS/MS/2024/ GH/SWZ/298 NEW DELHI

Dated: 22 / 07/2024

#### **FIRE SAFETY CERTIFICATE**

Certified that the building of M/s Guest House Arihant Inn, Located at Ground, 1<sup>st</sup>, 2<sup>nd</sup>, & 3<sup>rd</sup> floor 7A/69, WEA Channa market, Karol Bagh, New Delhi-110005, in a building comprised of basement, ground plus three upper floors using basement as (storage), ground floor (reception & 02 guest rooms), first, second & third floor (06 guest rooms each floor) (Total=20 guest rooms) was issued FSC vide Letter No F6/DFS/MS/GH/SZ/2021/195, dated 01/07/21. The premises was re inspected by the officer concerned of this department on 15/07/2024 in the presence of Sh. Muri Chaudhary (Manager) and observed that all the fire prevention and fire safety arrangements provided in the premises found in good working condition. The premises have therefore deemed complied with the fire prevention and fire safety requirements in accordance with Rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class "Residential" (guest house) at ground floor (reception & 02 guest rooms), first, second & third floor (06 guest rooms each floor) (Total=20 guest rooms) with effect from 2207 1024 for a period of three years in accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under Rule 38 of the Delhi Fire Service Rules, 2010.

Issued on ... 29 07 2024. at New Delhi by.

### Copy to:

- The Joint. Commissioner of Police (Lic), 1<sup>st</sup> Floor, Licensing Unit, Police Station, Defence Colony, New Delhi.
- 2. The Manager, M/s Guest House Arihant Inn, Located at Ground, 1<sup>st</sup>, 2<sup>nd</sup>, & 3<sup>rd</sup> floor 7A/69, WEA Channa market, Karol Bagh, New Delhi-110005.

## Following fire safety directives must be adhered to:-

- All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- 2. Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.
- 3. The trained staff should be available round the clock.
- 4. Any deviations w.r.t. construction shall be verified by the concerned building sanctioning agency.

  The certificate may not be tracted in the concerned building sanctioning agency.
- 5. The certificate may not be treated in any case for the regularization of the unauthorized construction, if any.
- 6. Basement strictly shall be kept vacant as seen during inspection.
- 7. The owner/ occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its expiry.
- 8. The owner/occupier shall submit a declaration every year in the form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on <a href="https://www.dfs.delhigovt.nic.in">www.dfs.delhigovt.nic.in</a>

# N/5) INSPECTION REPORT

 Name & address of the building: M/s Guest House Arihant Inn, Located at Ground, 1<sup>st</sup>, 2<sup>nd</sup>, & 3<sup>rd</sup> floor 7A/69, WEA Channa market, Karol Bagh, New Delhi-110005.

2. Type of Occupancy : Lodging or rooming "A-1"

3. Type of Case: Renewal (Running at Ground, 1<sup>st</sup>, 2<sup>nd</sup>, & 3<sup>rd</sup> floor in a building comprised of Basement, Ground + 3 Upper Floor)

4. Details of previous NOC: F6/DFS/MS/GH/SZ/2021/195, dated 01/07/21

5. Fire Safety directives Letter No.: Nil

6. Date of inspection : 15/07/2024

7. Name of the Inspecting Officer: ADO (DWK)

8. Name and designation of Officer

from the building side : Sh. Muri Chaudhary (Manager)

9. Year of Construction : Before 2001

10. Applicant's letter No. : 2024062409876, dated 24/06/2024

S No	Minimum standards on fire prevention and fire safety U/R	33	As per N/42, N/43 & N/44					Rema MR/N		
1.	Access of building				10.7					
	<ul> <li>Road width</li> </ul>	6				ovided occessible from road			MR MR	
	<ul> <li>Gate width</li> </ul>									
	<ul> <li>Width of internal road</li> </ul>	NA		NA					NA	
2.	Number, width, Type & Arrangements of exits									
	a. Number of staircases		8.4%			T				
	<ul> <li>Upper floors</li> </ul>	0	ld case		01	. 1	MR (Being old MR (Being old			
	<ul> <li>Basements</li> </ul>	0	ld case		01 No.					
	<ul> <li>b. Width of staircases</li> </ul>			,				B 01	_ 5000)	
	<ul> <li>Upper floors</li> </ul>	1	.25m	1.06	1.06m MR (Being			(Being	old case	
	<ul> <li>Basements</li> </ul>	1	.25m	1.30	1.30m MR (Being			old case)		
	c. Protection of exits		1			H		(=	ora vaso)	
	<ul> <li>Fire check door</li> </ul>	R	equired	Provided			MR			
	<ul> <li>Pressurization</li> </ul>	. 1	IA .			NA		NA		
	d. No of continuous staircase to terrace	0	01 ·			01			MR	
	e. Width Of Corridor f. Door Size		old case		3.30m			MR		
			Old case		0.86 m		MR (Being old case			
3.	Compartmentation									
	<ul> <li>Fire check door</li> </ul>		Required	Pro	vided				MR	
	<ul> <li>Sealing of electrical shafts</li> </ul>	1	NA.			Sealed		NA		
	Fire Rating of shaft door	NA				NA		NA		
	Water Curtain		NA			NA			NA	
	Fire Dampers		NA			NA		-	NA	

Xo h

MSZ

_							-	
4.	- mone managements by stem				T = -		- Is	
	Basements		a/c pe		-	vided		IR .
_	Upper floors	12	a/c per	r hour	Na	tural ventila	ition	
5.	Fire Extinguishers							
	<ul> <li>Total numbers</li> </ul>		Nos.	NTMP.		Provided		M
	• Types		3C & C	$O_2$		CO <sub>2</sub> & AB	C	M
	<ul> <li>IS marking</li> </ul>	Re	quired		Ī	Provided		M
6.	First - Aid Hose Reels							
	<ul> <li>Total numbers on each</li> </ul>	1	01			Provided		M
	floor							
	<ul> <li>Length of hose reel ho</li> </ul>	se	30 m	tr		Provided		MI
,	Nozzle diameter		5 MN	N '	]	Provided		M
7.	Automatic fire detection and a	larmi	ng syste	em				
	<ul> <li>Type of detectors</li> </ul>	CC	detect	ors	I	Provided		MR
	<ul> <li>Location of Main Panel</li> </ul>	Req	uired		F	Provided		MR
	<ul> <li>Location of Repeater Panel</li> </ul>	NA		NA				NA
	Alternate source of	-						
	power		uired	DG s	set 62	.5 KVA	9	MR
-	Hooters' Location	NA			N/	1		NA
	MOEFA	Requ		Provi	ded			MR
).	Public Address System	Requ	iired	Provid	ded			MR
<u>'.</u>	Automatic Sprinkler System							
	Basements	Requ	iired			Provided		MR
-1	• Upper Floor	NA			-	NA		NA
-	Sprinkler above false  sailing	NA		÷	, (s	NA		NA
	ceiling Internal Hydrants:							
+	Size of riser/down-come		1	,				
	Number of hydronic man	er	NA			NA		NA
1	<ul><li>Number of hydrants per :</li><li>Hose Box</li></ul>	HOOT	NA		1	NA		NA
+	1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 -	,	NA		1	NA		NA
+	Yard Hydrants			,				
I	<ul> <li>Total number of hydrants</li> </ul>	3	NA		_	NA		NA
+,	Hose Box		NA		1	NA		NA
ť	Pumping Arrangements:		*				((4))	
	Ground Level				1	14		
	Discharge of main pump     Head of main	N.			_	NA .		NA
	<ul><li>Head of main pump</li><li>Number of main pumps</li></ul>	N <sub>2</sub>				IA		NA
	> Jockey pump out put	N/		-	_	IA		NA
	> Jockey pump head	NA NA	7363		_	IA .		NA
	<ul> <li>Standby Pump out put</li> </ul>	NA NA				A		NA YA
	Standby Pump Head	NA NA			_	A A		NA IA
	Auto Staring/Manual	NA			_	A A		JA
	stopping	1.12	•		14	А	L	IA
	Pump House Access	NA			N.	Α	<b>X</b>	IA
	Terrace level	- 1.		,	1 14	•		A
	Discharge of pump	450	lpm		Pro	vided	·   N	IR I
	> Head of the pump		ntrs	_		vided		IR IR
	> Power supply		uired		_	vided		IR I
	W Allto starting of many				_			
	Auto starting of pump	Req	uired		Pro	vided	N/	R

Jo W

4.	Captive water Storage for fire fi	ahtina	•	_					
			•	1					
	0 ,	NA		NA		NA			
- 1	capacity  > Draw off connection								
		NA		NA		NA			
- 1	Fire service inlet	NA			NA				
	Access to tank	NA		NA		NA MR			
	<ul> <li>Overhead Tank capacity</li> </ul>	5000	ltr	500	0 ltr				
15	Exit Signage	Required		Provided		MR			
16.	Provision of Lifts								
	Pressurization of Lift Sh	NA	NA		NA				
	Pressurization of lift lobby .		NA	NA Provided		NA MR			
	Communication in lift C	Required							
	➤ Fireman's Grounding Switch		Required		Provided .				
	➤ Lift Signage		Required		Provided				
17.	Standby power supply		Required	Provided		MR			
18.	Refuge Area								
	> Total area	NA		NA		NA			
	> Location	NA	NA		NA				
19.	Fire control room								
	Detector system panel	NA		NA		NA			
	> Flow Switch Panel	NA		NA		NA NA			
	> PA System Panel	NA		0.9000000000000000000000000000000000000	NA				
I	> Battery backup Requ		uired	Pro	Provided				
	Building Floor Plans	NA		NA		NA			
20		s for any;	NA		NA	NA			

The fire protection systems provided in the building were test checked and found

functional at the time of inspection.

In view of the deemed compliance of minimum standards on fire prevention and fire safety as required under the rules the FSC issued vide letter No. F6/DFS/MS/GH/SZ/2021/195, dated 01/07/21 renewal under Rule 37 of the Delhi Fire Service Rules 2010 is recommended. If approved the FSC may be issued.

Signature of the Inspecting Officer

Name: Sh. Udaivir Singh pesignation : ADO (DWK)