GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE, NEW DELHI – 110001

No.F6/DFS/MS/GH/NDZ/2024/ 291

Dated: 18 /07 /2024

FIRE SAFETY CERTIFICATE

Director Delhi Fire Service

Tel: 011-23414000

Copy to:-

- 1. The Commissioner, MCD:- to kindly ensure the occupancy as detailed above & deviation, if any.
- 2. The Joint Commissioner of Police (Licensing), 1st Floor, Police Station Defence Colony, New Delhi. w.r.to ID No. 2024062009680 dated 21.06.2024.
- 3. The Licensee, M/s O K Guest House at 129, Gali Jatwara, Pul Mithai, Delhi -110006.

Conditions for the validity of Fire Safety Certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in.
- 7. The means of escape shall be kept unobstructed / unlocked for unhindered evacuation in case of an emergency.
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub Rule (I) of Rule 37] along with a copy of this Certificate, six month prior to its expiry. Any change in the occupancy shall be intimated to this Deptt. and approval shall be obtained thereto before occupancy of the same.
- 9. The occupancy of above 3rd floor shall not be allowed as per clause 7.31 in UBBL-2016.

- 10/27-

| | | | TION REPORT | | | |
|-----|--------------------------|--|--|---------------------|--------------|--|
| * | Name | & address of the building | M/s O K Guest I | 2 | wara, Pul | |
| | | | Mithai, Delhi - 06. | | | |
| 8 | Buildi | ng is comprised of | (Ground + 04 upp | er floors) | 20 1912 | |
| | | | Ground floor - (0) | 2 shops + reception | n + 01 guest | |
| | | | room) | | | |
| | | | 1 st floor – (03 gues | | | |
| | | | 2 nd floor - (03 gues | | | |
| | | | 3 rd floor - (03 gues | st rooms) | 1 2 22 2 | |
| | | | 4th floor - (not in | use as per affi | davit dated | |
| | 100 | | 05.07.2024) | | | |
| 3 | Type | of occupancy | Residential Group | A-1 | | |
| 4 | | of case | Renewal (old case) | | | |
| 5 | | ls of previous FSC | F6/DFS/MS/GH/N | | d | |
| 5 | Details of previous 1.90 | | 26.03.2021 | | W | |
| 6 | Dia. | safety direction letter no. | Nil | | | |
| 6 | | ANTENNA CALLERY | 05.07.2024 | | | |
| 7 | Date of inspection | | Sumit Kumar, ADO (SPM) | | | |
| 8 | | | | | | |
| 9 | | e of the designation of officer | Managor | | h de l' | |
| | | the building side | 1997 | | | |
| 10 | | of construction | Online application | on I.D. No. 202 | 4062009680 | |
| 11 | App | licant's letter no. | dated on 21.06.20 | 24 | | |
| | | | Requirement/ | Provided at | Remarks | |
| S.N | Min | imum Standards on fire vention and fire safety | Existing fire | Site | MIR/ | |
| 0 | Pre | uirements U/R 33 | safety | | NMR | |
| | req | in ements of R 55 | arrangements | | | |
| 1 | Acc | ess To Building: | | | DIA | |
| | | d width | NA | 1.25 mtr. | NA NA | |
| | Gate width | | NA | NA NA | NA NA | |
| | Wie | Ith of internal road | NA SET VIEW | NA NA | INA | |
| 2 | Nu | mber, Width, Type and Arrai | igement of Exits: | | | |
| | A | Number of staircases | 01 no. | 01 no. | MR / | |
| | | a Upper floor | NA | NA | NA | |
| | | b Basement | IVA | | / | |
| | В | Width of staircases | 80 cms. | 87 - 97 cms. | MR | |
| | | a Upper floor b Basement | NA | NA | NA | |
| | C | Protection of exits | The state of the s | (C. 0.0.2000) | | |
| | C | a Fire check door | NA | NA | NA | |
| | | b Pressurization | NA | NA | NA | |
| | D | No. of continuous staircases | | 01 no. | MR | |
| | | to terrace | | | 1 | |
| | E | Width of corridor | NA | NA | NA | |
| | F | Door size | 1.0 mtr. | 1.0 mtr. | MR / | |
| 3 | Co | mpartmentation: | 10 1 27 | 1 | 1374 | |
| | A | Fire check door | NA | NA | NA | |
| | В | Sealing of electrical shafts | NA | NA | NA | |
| | C | Fire rating of shaft door | NA | NA | NA | |
| | D | Water curtain | NA | NA | NA | |
| | E | Fire dampers | NA | NA | NA | |
| 4 | | | | 137 | 1 574 | |
| | A | Basement | NA CPV | NA Natural | NA NGD | |
| - 1 | В | Upper floor | 12 ACPH | Natural | MR | |

| 5. | E: | re Fytinguish | | | - | - | |
|----|----------------|--|-------------------|----------|-------------------|--------------|----------|
| ٥. | A | re Extinguisher: Total numbers | 7 | | | | 1.00 |
| | | A CHARLES THE PROPERTY OF THE PARTY OF THE P | 08 nos | L | 09 nos | 3. | MR |
| | В | Types | CO ₂ & | ABC | CO ₂ & | ABC | MR |
| | C | ISI marking | Requir | ed | Provide | ed | MR |
| 6 | Fi | rst-Aid-Hose Reels: | | | | | |
| | A | Total numbers of each floor | 1 no. | | 01 no. | | MR |
| | В | Length of hose reel hose | 30 mtrs | | 30 mtrs. | Ď. | MR |
| | C | Nozzle diameter | 05 mm | | 05 mm | | MR |
| 7 | Au | tomatic Fire Detection An | d Alarming | System: | | | |
| | A | Type of detectors (CO type) | Require | | Provided | ı | MR / |
| | В | Location of main panel | Required | 1 | Provided | | MR / |
| | C | Location of repeater pan | el NA | | NA | | NA |
| | D | Alternate source of power | | | Provided | | MR |
| _ | E | Hooters | Required | | Provided | | MR / |
| 8 | | DEFA: | NA | | Siren Provided | | NA TA |
| 9 | - | blic Address System: | NA | | NA | 1 | VA |
| 10 | - | tomatic Sprinkler System: | | | | - 1 | F.A. |
| | A | Basement | NA | | NA | | IA . |
| | В | Upper floor | NA | | NA . | | 'A |
| | С | Sprinkler above false ceiling | NA | ì | NA | N | A |
| 1 | - | ernal Hydrants: | _ | | | 155 | |
| | A | size of riser/down-comer | | | Α | N/ | |
| | В | Number of hydrants per floor | NA | <u> </u> | A | N/ | |
| | С | Hose box | NA | N | A | NA | <u> </u> |
| 2 | _ | d Hydrants: | 1574 | 157 | | LATA | |
| | A | Total number of hydrants | NA - | N. | | NA | |
| | В | Hose box | NA | N/ | 4 | NA | |
| 3 | _ | ping Arrangements: | | | | | |
| | A | Ground level Discharge of main pump | NA | NA. | | NA | - 2 |
| | a) b) | Head of main pump | NA NA | NA NA | | NA | |
| 1 | | Number of main pumps | NA NA | NA | | NA NA | |
| | c) d) | Jockey pump out put | NA NA | NA NA | | NA NA | |
| | e) | Jockey pump head | NA NA | NA NA | | NA NA | × × |
| | f) | Standby pump out put | NA | NA NA | | NA NA | Fi. |
| ŀ | g) | Standby pump head | NA | - NA | | NA | |
| | h) | Auto starting /manual | NA | NA | | NA | |
| - | | stopping | NIA | | 4 | a toronto la | |
| - | i) B | Pump house access Terrace level | NA | NA | | NA | |
| 1 | a) | Discharge of pump | 225 LPM | 225 1 | DM | | |
| - | b) | Head of the pump | 40 mtrs. | 40 m | | MR | |
| ŀ | c) | Power supply | Required | Provi | 1-12-1-1-2 | MR | |
| - | d) | Auto starting of pump | Required | Provi | | MR MR | |

| 4 | A | tive Water Storage For Fire F Underground tank capacity | NA NA | NA | INT | | |
|-----|---------------------|--|-------------|-------------|----------|--|--|
| ŀ | B | Draw-off connection | NA NA | NA NA | NA NA | | |
| 1 | c | Fire service inlet | NA NA | | NA | | |
| H | D | Access to tank | | NA | NA | | |
| 1 | - | Overhead tank capacity | NA 2.500 I | Provided | NA | | |
| 15 | | | 2,500 ltrs. | 3,000 ltrs. | MR | | |
| 200 | Exit Signage: | | Required | Provided | MR | | |
| 16 | Provision of Lifts: | | Provided | | | | |
| | A | Pressurization of lift shaft | NA | NA | NA | | |
| | B | Pressurization of lift lobby | NA | NA | NA | | |
| | C | Communication in lift car | NA | NA | NA | | |
| | D | Firemen's grounding switch | NA | NA | NA | | |
| | E | Lift signage | NA | NA | NA | | |
| 17 | Sta | andby Power Supply: | Required | Provided | MR | | |
| 18 | | | | | | | |
| | A | Total area | NA | NA | NA | | |
| | B | Location | NA | NA | NA | | |
| 19 | Fire Control Room: | | | | | | |
| | A | Detector system panel | NA | NA | NA | | |
| | В | Flow switch panel | NA | NA | NA | | |
| | C | | NA | NA | NA | | |
| | D | And the property of the second | NA | NA | NA | | |
| | E | | NA | NA | ŇA | | |
| 20 | | pecial Fire Protection Systems F pecial Risks, If Any: | NA | NA | | | |

The fire protection systems provided in the building were tested, checked at random and found functional at the time of inspection.

Shortcomings communicated vide letter No.F6/DFS/MS/GH/NDZ/2024/251 dated 21/05/2024 has been rectified.

The owner has submitted an affidavit dated 05.07.2024 stating that not to use any floor above third floor for any purpose in accordance with Gazette Notification dated 27.05.2019.

In view of the deemed compliance of minimum standards of fire prevention and fire safety measures as required under the Rules, the FSC issued vide letter no. F6/DFS/MS/GH/NDZ/2021/166 dated 26.03.2021 is recommended to be renewed upto 3rd floor only, under Rule 35 of the Delhi Fire Service Rules, 2010.

> Signature of the Inspecting Name Sumit Kumar

Designation

ADO (SPM)