FORM 'H'

FORM FOR ISSUING FIRE SAFETY CERTIFICATE

[Refer sub - rule (1) of rule 35]

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE, CONNAUGHT PLACE

No.F6/DFS/MS/SZ/2024/3chool 720 NEW DELHI

Dated: 25/07/2024

FIRE SAFETY CERTIFICATE

Certified that building of Rana Pratap Govt. (Sindhi) Sarvodaya Vidyalaya Located at New Rajender Nager, New Delhi-110060. comprised of Ground + 02 Upper Floors was issued FSC vide Letter No. F.6/DFS/MS/School/2015/SZ/209 dated 11/02/2015 (Issued to G+1UF) owned / occupied by Rana Pratap Govt. (Sindhi) Sarvodaya Vidyalaya have complied with the fire prevention and fire safety requirements in accordance with Rule 33 of the Delhi Fire Service Rule, 2010 and verified by the officers concerned of this department on 16/07/2024 in the presence of Dr. Hans Raj Modi (Principal) and found that the said building is fit for occupancy class "Educational" Group B Sub Division B – 1 with effect from 25/07/2024 for a period of three years in accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under Rule 38 of the Delhi Fire Service Rules, 2010.

Issued on ... 25 0.7 2.24 at New Delhi.

Director,

Copy to:

- The Principal, Rana Pratap Govt. (Sindhi) Sarvodaya Vidyalaya Located at New Rajender Nager, New Delhi-110060, School ID-2128032
- 2. Directorate of Education Old Secretariat Delhi 110054.

Following fire safety directives must be adhered to:-

- All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- 2. Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.
- 3. The trained staff should be available round the clock.
- 4. Any deviations w.r.t. construction shall be verified by the concerned building sanctioning agency.
- 5. The certificate may not be treated in any case for the regularization of the unauthorized construction, if any.
- 6. Basement shall be used strictly as per building bye laws.
- 7. The owner/occupier shall submit a declaration every year in the form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on www.dfs.delhigovt.nic.in.
- 8. The owner/ occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its expiry.

INSPECTION REPORT

 Name & address of the building: Rana Pratap Govt. (Sindhi) Sarvodaya Vidyalaya Located at New Rajender Nager, New Delhi-110060.

2. Type of Occupancy : Educational (Ground + 02 Upper Floor)

3. Type of Case : Addition/Alteration (New Case)

 Details of previous NOC: F.6/DFS/MS/School/2015/SZ/209 dated 11/02/2015 (Issued to G+1 UFs)

5. Fire Safety directives Letter No.:. NBC

6. Date of inspection : 16/07/2024

7. Name of the Inspecting Officer: ADO (DWK)

Name and designation of Officer

from the building side : Dr. Hans Raj Modi (Principal)

9. Year of Construction : 1960& 2017-18

10. Applicant's letter No. : Email date 24/06/2024

	Minimum standards on fire prevention and fire safety U/R 33	As per NBC	Provided at site	Remarks MR/NMR
	Access of building			
	Road width	06 mtrs 06 mtrs		MR
ı	Gate width	4.5mtrs Dir	ectly accessible from i	road MR
	 Width of internal road 	NA	NA	NA
2.	Number, width, Type & Arrangement	s of exits		
	a. Number of staircases		19	
	Upper floors	02 No's	03 No's	MR
	Basements	NA	NA -	NA
T T	b. Width of staircases			
	 Upper floors 	1.5 mtr	1x1.30m &2x 1.5m	MR
	Basements	NA	NA	NA
	c. Protection of exits			
	 Fire check door 	NA	NA	NA
	 Pressurization 	NA '	NA	NA
•	d. No of continuous staircase to terrace	NA	NA	NA
	e. Width Of Corridor	150 cms	Provided	MR
	f. Door Size	100cm	1m Provided	MR
3.	Compartmentation			
	Fire check door	NA	NA	NA
	Sealing of electrical shafts	NA	NA	NA
	Fire Rating of shaft door	NA	NA	NA
	Water Curtain	NA	NA	NA
4.	• Fire Dampers	NA	NA	NA
-	Smoke managements System			
	Basements	NA	NA	NA
	Upper floors	12 a/c per h	our Natural ventila provided	ation MR

	Fire Extinguishers		25 Provided		MR
	Total numbers	01 for every 300	35 Provided		MR
	Types	sqm ABC & CC	Co2 &ABC		MR
	IS marking	ISI marked	Provided		
	First – Aid Hose Reels		.1.1		MR
)	The state of another floor	03 each floor	Provided		MR
	• Total numbers on each noor	30 m	Provided		MR
2	 Length of hose reel hose 	05mm	Provided		
	Nozzle diameter			NA	
1.	Nozzie diameter Automatic fire detection and alarmin	NA NA	NA	NA NA	
	 Type of detectors 	NA	NA	NA NA	
	Location of Main Panel	NA	NA	NA NA	
	Location of Repeater Panel	NA	NA	NA NA	
	 Alternate source of power 	NA	NA		
	Hooters' Location	Name 2	NA	NA	
	MOEFA	NA NA	NA	NA	
3	Public Address System	NA			
).	Automatic Sprinkler System	TNA	NA	NA	
0.	D anto	NA NA	NA	NA	
	Basements Upper Floor	NA	NA	NA .	
	Sprinkler above false ceiling	NA.			
	Sprinkler above raise It departs:		NA	NA	
1.	Internal Hydrants: • Size of riser/down- comer	NA	NA NA	NA	
	Number of hydrants per floor	NA	NA NA	NA	
	Number of flydrants per	NA	11/2		
	Hose Box		NA	NA	
2.	Yard Hydrants	NA	NA NA	NA	100
	Total number of hydrants	NA	INA		
	Hose Box				
3.	Pumping Arrangements:		INIA	NA	
	Cround Level	NA	NA NA	NA	
	Discharge of main pump	NA	·NA	NA	
	> Head of main pump	NA	NA	NA	
	> Number of main pumps	NA	NA NA	NA	
_/	> Jockey pump out put	NA	NA NA	NA.	
	 Jockey pump head Standby Pump out put 	NA ·	NA NA	NA	
	a Jha Dumn Head	NA	NA NA	NA	
	Ctaring/Manifal Stupping	NA	NA NA	NA	
	- ITauce Access	NA	NA	II C	
	 Pump House Access Terrace level 		Provided	MR	
	Discharge of pump	450 lpm	Provided	MR	
	> Head of the pump	40 m	Provided	MR	
	> Power supply	Required	Provided	MR	
	Auto starting of pump	Required	Piovided		
_	Captive water Storage for fire fighting:		NA	NA	
1.	Under ground tank capacity	NA	NA NA	NA	
	> Draw off connection	INA	NA NA	NA	
	> Fire service inlet	INA .	NA NA	NA	
	4	IVA	NA Provided	MR	
	Quarhand Tank capacity 10,000 III			MR	
_		ed Provided			
1	Exit Signage Require	1.6	8		
		73-5-33 V			- 0
		180			9

. P	rovision of Lifts				
-	> Pressurization of Lift Shaft	NA	NA	NA NA	
	Pressurization of lift lobby	NA	NA	NA	
	> Communication in lift Car	NA	NA	NA	
	Fireman's Grounding Switch	NA	NA	NA	
1	➤ Lift Signage	NA	NA	NA	175
7.	Standby power supply	NA	NA	NA	
	Refuge Area			1000	
	> Total area	NA	NA	NA	
	> Location	NA	NA	NA	
19.	Fire control room				_
	> Detector system panel	NA	NA	NA	_
	> Flow Switch Panel	NA	NA	NA	_
0	> PA System Panel	NA	NA	NA	
\	> Battery backup	NA	NA	NA	
١.	> Building Floor Plans	NA	NA	NA	\Box
20		NA	NA	NA	

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under Rule 35 of the Delhi Fire Service Rules 2010

Signature of the Inspecting Officer Name Name

Designation