GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE, NEW DELHI-110001

No. F6/DFS/MS/2024/WZ/ 499

FIRE SAFETY CERTIFICATE

Dated: 02 08 2024

Certified that the M/s A-41, Mangol Puri Block-A, Industrial Area, Phase-II, Mangol Puri, Delhi-83, comprised of Ground + Mezzanine + First Floor only owned/occupied by Mr. Anil Wadhawan was issued FSC by this department vide letter No. F.6/DFS/MS/2021/WZ/372 dated 03.08.2021. The premises was re-inspected by the officer concerned of this department on 23.07.2024 in the presence of Sh. Harpreet (Head Currency Chest) and found that the said building have deemed complied with the fire prevention and fire safety requirements in accordance with Rule 33 of the Delhi Fire Service Rules, 2010 and that the premises fit for occupancy class "Business Occupancy" (Bank Chest) in Industrial Building with effect from D2 08 2024 for a period of three years in accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subjected to compliance of the conditions under Rule 38 of the Delhi Fire Service Rules, 2010.

Issued on 0708 2024 at New Delhi by

DIRECTOR
Ph: 011-23414000

Copy to :-

1. Sh. Anil Wadhawan (Owner), A-41, Mangol Puri Block-A, Industrial Area, Phase-II, Mangol Puri, Delhi-83.

Conditions for validity of Fire Safety Certificate;

- 1. All the fire safety arrangement provided there-in shall be maintained in good working conditions at all times.
- 2. Loss of life or property due to non functional fire safety measure shall be at the responsibility of the management.

2. The trained fire fighting staff should be available round the clock.

3. Any deviation with regard to the construction etc shall be verified by the concerned building sanctioning agency.

4. This certificate cannot be treated in any case for regularizations of unauthorized construction.

5. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director along with a copy of this Certificate, six months prior to its expiry".

6. The owner / occupier shall submit a declaration every year in form "K" provided in the first schedule of Delhi Fire Service Rules 2010. The form "K" is available on http://www.delhi.gov.in/wps/wcm/connect/doit_fire/FIRE/Home/Fire+Safety+Acts+and+Rules/ http://www.delhi.gov.in/wps/wcm/connect/doit_fire/FIRE/Home/Forms

_			INSPE	CTION REPORT			
1.	Name & ad	dress of the building	A-41, Mangol Puri Block-A, Industrial Area, Phase-II, Mang Puri Delhi-83				
2.	Type of Case Re Details of Previous NOC F.6 Fire Safety directives letter No Date of inspection 23. Name of Inspecting Officer Sh		(Grou	Business Occupancy in Industrial Building (Bank Ches			
3.			Renewal (Ground, Mezzanine & 1st floor)				
4.			F.6/DF	F.6/DFS/MS/2021/WZ/372 dated 03.08.2021. F.6/DFS/MS/BP/2012/711 dated 29.02.2012			
5.							
6.			23.07.2024				
7.			Sh. Aj	Sh. Ajay Kumar Sharma (ADO Rohini)			
	From the b	designation of officers uilding side	-	Sh. Harpreet (Head Currency Chest)			
9.	Year of Construction 1992 O. Applicant's letter No. Onlin			Online e-mail dated 22.07.2024. NRC Part-IV Provided at site Remarks			
10			117711111111111111111111111111111111111				
S.	Minimum	Standards on fire prev	ention	NBC Part-IV	Provided at site	MR/NMR	
No	and fire sa	fety U/R 33		Requirements		1	
1.	Access to	building		1.1.	Accessible	MR	
	• Ro	ad width		Accessible	4.5m	MR	
	• Ga	te width		Accessible		-NA-	
	Width of internal road			-NA-	-NA-	-INA-	
2.	Number.	Width, Type & Arrang	ement of	Exits			
S		er of staircases	ē.			1 m	
	AND BANGERY	Jpper Floors	1	02nos.	02nos.	MR	
		Basements		-NA-	-NA-	-NA-	
100	1						
	b. Width of staircases		1.25 & 1.5m	1.25 & 1.5m	MR		
		Upper Floor		-NA-	-NA-	-NA-	
		Basements		177			
	c. Protection of exits		· ·	Required	Provided	MR	
	• I	Fire check door		-NA-	-NA-	-NA-	
	•	Pressurization		#6%E	-NA-	-NA-	
	d. No. of c	ontinuous staircases to	terrace	-NA-	1.5m	MR	
	e. Width o	f Corridor		1.5m	1.25m	MR	
	f. Door Size			1.0m	1.2311	+	
3.	Compartn	nentation	. 1		7 .1.1	MR	
	Fire check door			Required	Provided	-NA-	
	Sealing of electrical shafts		-NA-	-NA-	-NA-		
		Rating of shaft door		-NA-	-NA-		
		ter Curtain		-NA-	-NA-	-NA-	
	101 13		- 4	-NA-	-NA-	-NA-	
		Dampers		/ 8	ng i g		
•	Smoke Management System			-NA-	-NA-	-NA-	
	a) Basements			Required	Provided	MR	
	b) Upper floors		/				
	Fire Extinguishers			06nos.	06nos.	MR	
	Total numbers			ABC/CO2/Wco2	ABC/CO2/Wco2	MR	
	• Types		11	ISI marked	Yes	MR	
	IS marking		1	181 marked			

cut #

M	26
3.5	

		1.10-					
-	Length of hose reel hose	30mm	Provided	MR			
	Length of hose reel hose Nozzle diameter	5m	Provided	MR			
7.	Nozzle diameter Automatic fire detection and alarming system						
7.	a) Type of detectors	-NA-	Provided	-NA-			
	b) Location of Main Panel	-NA-	Provided	-NA-			
	c) Location of Repeater Panel	-NA-	-NA-	-NA-			
	d) Alternate source of power	-NA-	Provided	-NA-			
	e) Hooters' Location	-NA-	Provided	-NA-			
8.	MOEFA	-NA-	-NA-	-NA-			
9.	Public Address System	-NA-	-NA-	-NA-			
10.	Automatic Sprinkler System						
	Basement	-NA-	-NA-	-NA-			
	Ground & Upper Floors	Required	Provided	MR			
	Sprinkler above false ceiling	-NA-	-NA-	-NA-			
11.	Internal Hydrants						
n III	Size of riser/down-comer	100mm	Provided	MR			
	Number of hydrants per floor	01nos.	Provided	MR			
	Hose Box	01nos.	Provided	MR			
12.	Yard Hydrants						
	Total number of hydrants	-NA-	-NA-	-NA-			
	Hose Box	-NA-	-NA-	-NA-			
13.	Pumping Arrangements		7-10 Table 1	141			
	Ground Level	-NA-	-NA-	-NA-			
	Discharge of main Pump	-NA-	-NA-	-NA-			
	Head of Main pump	-NA-	-NA-	1			
	Number of main pumps	-NA-	-NA-	-NA-			
	Jockey Pump out put	-NA-	-NA-	-NA-			
	Jockey pump head	-NA-	-NA-	-NA-			
	Standby Pump out put	-NA-	-NA-	-NA-			
	Standby Pump Head	-NA-		-NA-			
- 1	Auto Starting/Manual Stopping	-NA-	-NA-	-NA-			
	➤ Pump House Access	-NA-	-NA-	-NA-			
	Terrace level	-1VA-	-NA-	-NA-			
İ	 Discharge of pump 	0001		owner U			
1	> Head of the pump	900lpm	900lpm	MR			
İ	➤ Power Supply	40m	40m	MR			
	> Auto Starting of pump	Required	Provided	MR			
14.	Captive Water Storage for fire fighting	Required	Provided	MR			
	Underground 4. 1						
ł	onderground tank capacity	-NA-	-NA-				
	> Draw-off connection	-NA-		-NA-			
	➤ Fire service inlet		-NA-	-NA-			
	Access to tank	-NA-	-NA-	-NA-			
		-NA-	-NA-				
15.	Overhead Tank capacity Exit Signage.	10,000ltr	10,000ltr	-NA-			
_	Provision of Lifts.	Required		MR			
10.50	or Entra.			MR			
}	Pressurization of Lift Shaft						
	Pressurization of Lift lobby	-NA-	-NA-	-NA-			
	Communication In lift Car	-NA-	-NA-	-NA-			
_				A A A			

到	Fireman's Grounding Switch	Required	Provided	MR	
121	Fireman s Glounding Switch	Required	Provided	MR	
17	• Lift Signage	Required	Provided	MR	
17.	Standby power supply				
18.	Refuge Area.	-NA-	-NA-	-NA-	
-	> Total Area	-NA-	-NA-	-NA-	
ŀ	> Location	144.			
9.	Fire Control Room	-NA-	-NA-	-NA-	
	Detector System Panel	-NA-	-NA-	-NA-	
ŀ	Flow Switch Panel	-NA-	-NA-	-NA-	
}	PA System Panel		-NA-	-NA-	
	Battery backup	-NA-	-NA-	-NA-	
	Building Floor Plans	-NA-	-NA-	-NA-	
20.	Special Fire Protection System for Protection of special Risks, if any:	-NA-			

Accordingly, the fire protection systems provided in the building were tested/ check

Keeping in view the satisfactory compliance of the minimum standards on fire prevention and found in working condition at the time of inspection. fire safety required as stipulated in NBC Part-4, and removal of shortcomings issued vide letter no. 265 dated 16.05.2024, the FSC issued vide letter no. F.6/DFS/MS/2021/WZ/372 dated 03.08.2021, renewal under rule 37 of the Delhi Fire Service Rules, 2010 is recommended.

> Signature of the Inspecting Officer Ajay Kumar Sharma Name

Designation ADO(Rohini)

perusal and