

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI **HEADQUARTER: DELHI FIRE SERVICE: NEW DELHI- 110001**



No. F6/DFS/MS/School/WZ/2024/ 73/

Dated: 30 07 2024

FIRE SAFETY CERTIFICATE

Certified that the Divyansh Public School, Located at C-20, Street No. 6, Amar Colony, Nangloi, Delhi-110041, comprised of Ground + 02 Upper Floors & earlier the school building comprised of Ground + 01 Upper Floor only, was issued Fire Safety Certificate by this department Vide Letter No. F6/DFS/MS/School/2021/WZ/388 dated 14/06/2021, owned/occupied by the Divyansh Public School have complied with the fire prevention and fire safety requirements in accordance with D.O.E. Circular no. 3298-3398 dated 01/03/2011 and Verified by the officer concerned of Fire Service on 04/07/2024 in the presence of Sh. Vinod Bhati (Manager) and that the premises/building is fit for occupancy class "Educational Building" Group B with effect from 30 67 2024 for a period of three years in accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under Rule 38 of the Delhi Fire Service Rules, 2010, printed below.

Issued on 30107/2024 at New Delhi by.

Director

Tel No. 011-234140

Copy to: -

The Director, Directorate of Education, GNCT of Delhi, Old Secretariat Delhi – 110054.

2. The Principal, Divyansh Public School, C-20, Street No. 6, Amar Colony, Nangloi, Delhi-110041.

Following fire safety directives must be adhered to:-

1. All the means of escape shall be kept free of all type of obstruction all the time.

2. All the employees shall be acquainted with the use and maintenance of all fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.

3. All the fire fighting equipments shall be maintained in perfect working condition all the time and any lapse rendering non-functional if fire safety measures, management shall be responsible.

4. Any deviation, with regards to construction, ventilation, occupation, electric installation etc.

may be got verified from the concerned authorities.

5. The Fire Safety Certificate may not be treated in any case for regularizations of unauthorized construction / unauthorized use of land if any.

6. All comments / directions of licensing Department shall always be permitted and followed.

7. The owner /occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on www.dfs.delhigovt.nic.in

8. The owner / occupier shall apply for renewal of this Fire Safety Certificate to the Director in 'Form J' (sub Rule (1) of Rule 37) along with copy of the certificate, six months prior to its expiry.

INSPECTION REPORT

Name and address of the building: Divyansh Public School, located at C-20, Street

No. 6, Amar Colony, Nangloi, Delhi-110041

)]

:1

Type of Occupancy : Educational, (G + 02 Upper Floors)

3. Type of Case : New Case/Addition of 2nd floor

4. Details of previous NOC : F6/DFS/MS/School/2021/WZ/388 Dated 14/06/2021

(for Ground + 01 Upper Floor only)

5. Fire Safety directives Letter No. : D.O.E. Circular dated 01/03/2011

6. Date of inspection : 16/07/2024

7. Name of the Inspecting Officer : Aman Kumar Lathar, ADO (JWP)

8. Name and designation of Officer

from the building side : Sh. Vinod Bhati (Manager)

9. Year of Construction : G.F - 2006, 1st floor - 2013 & 2nd floor-2015-16

10. Applicant's letter No. : email dated 24/06/2024

S No	Minimum standards on fire prevention and fire safety U/R 33	D.O.E. Circ. Dt 01/03/2011/NBC (Part- IV) Requirements		Provided at site		Remarks MR/NMR		
1.	Access of building 06 m 05 m MR being o					eing old case		
	 Road width 	06 m	Provided			MR		
	Gate width	4.5 m NA	De villa	NA		NA		
П	 Width of internal road 		4	DIV N				
2.	Number, width, Type & Arrangements of exits							
۷.	a. Number of staircases			02		MR		
	 Upper floors Basements Width of staircases Upper floors 	01	100	NA		NA		
		NA	IVA					
		1.5 m or less &	1.2 m x 1			MR		
				0.80 m x 1				
	and the state of the second of	0.75 m	Ť	NA		NA		
	Basements	NA	17.					
	c. Protection of exits	may priling	942/13	NA		NA		
	Fire check door	NA				NA		
+	Pressurization	NA		NA	3	MR		
ŀ	d. No of continuous	01	100	Provideo	1			
t	staircase to terrace	NA	-	NA		NA		
ı	e. Width Of Corridor	NA	-	Provide	d	MR		
	f. Door Size	1.0 m	-	NA				
3.	Compartmentation		-	NA		NA		
	 Fire check door 	NA						
	Sealing of electrical	NA	e day	NA		NA		
	shafts	NA		NA		NA		
	 Fire Rating of shaft door 	NA	- 1	NA		NA		
	Water Curtain	NA	1.0	NA		NA		
-	Fire Dampers	7 T	Mr. u	1.1 0				
4.	Smoke managements System							
	Basements	NA		NA		NA		
	Upper floors	NA		NA		NA		
5.	Fire Extinguishers							
	Total numbers	07 nos.	AL V	18 nos.		MR		
	Types	ABC & CO ₂	Provided			MR		
	ISI marking	ISI marked	Provided			MR		

6.	First – Aid Hose Reels	MA A	Drovided	
0,	Total numbers on each floor	01	Provided	
	Length of hose reel hose	30 m	Provided	M
	Nozzle diameter	05 mm	Provided	MR
7.	Automatic fire detection and alarming s	ystem	T NA	NIA
	Type of detectors	IVA	NA NA	NA NA
	Location of Main Panel	NA		NA NA
	Location of Repeater Panel	NA	NA	NA NA
	Alternate source of power	NA	NA	NA
	Hooters' Location	NA	NA	NA
3.	MOEFA	NA	NA	NA
).	Public Address System	NA	NA	NA
10.	Automatic Sprinkler System			
	Basements	NA	NA	NA NA
	Upper Floor	NA	NA	NA
		NA NA	NA	NA
11.	Sprinkler above false ceiling Internal Hydrants:	INA	1471	III IVA
	Size of riser/down-comer	NIA	T NA	NIA
	Number of budget	NA	NA NA	NA NA
155	Number of hydrants per floor Hose Box	NA NA	NA NA	NA NA
12.	Yard Hydrants	NA	NA	NA
	Total number of hydrants Hose Box	NA	NA	NA
13.	Pumping Arrangements:	NA	NA	NA
ļ.	Ground Level		the standard of	Maje -
	• Discharge of main pump		A SYLDING TO	1
	Head of main pump	NA	NA	NA
	Number of main pumps	NA	NA	NA
	Jockey pump out put	NA	NA	NA
	Jockey pump head	NA	NA	NA
	Standby Pump out put	NA	NA	NA
	Standby Pump Hand	NA NA	NA	NA
	Auto Staring/Manual	NA	NA	NA
	stopping	NA	NA	NA
	Pump House Access	NA	NA	NA
	• Terrace level	450 lpm	April 10 January 1.	
	 Discharge of pump Head of the pump 	40 m	Provided	MR
	Power supply	Required	Provided	MR
	Auto starting of numer	Required	Provided	MR
4.	Captive water Storage for fire fighting:	- toquired	Provided	MR
	• Under ground tank capacity			
	Draw off connection	NA	NA	
	Fire service inlet	NA	NA	NA
	Access to tank	NA	NA	NA
<u></u>	Overhead Tank capacity	NA 10 000 to	NA	NA
5	Exit Signage	10,000 ltrs	Provided	NA MD
6.	Provision of Lifts	Required	Provided	MR
	> Pressurization of Lift Shaft	. NA		MR
	Pressurization of lift lobby	NA NA	NA	NA
	Communication in lift Cor	NA NA	NA	NA NA
	 ➢ Fireman's Grounding Switch ➢ Lift Signage 	NA	NA	NA NA
	Zitt Signage	NA	NA	NA
7.	Standby power supply		NA	NA
8.	Refuge Area	NA	NA	Les IV
Oli I	> Total area	NIA		NA
	> Location	NA NA	NA	NIA
		11/4	NA	NA NA
				NA
9.	Fire control room	1.5		
	➤ Detector system panel	NA	T N	
	Flow Switch Panel	c NA	NA NA	NA
			NA	NA

> PA System Panel	NA	NA	NA
➤ Battery backup	NA	NA	NA
➤ Building Floor Plans	NA	NA	NA
Special Fire Protection Systems for Protection of special Risks, if any; Fire protection systems provide	NA	NA	NA

functional at the time of inspection. Shortcoming issued vide letter no. F6/DFS/MS/2017/1690 dated 05/07/2017 found rectified.

Keeping in view of substantial compliance of the minimum standards of fire prevention and fire safety requirements as per D.O.E. Circular no. 3298-3398 dated 01.03.2011, grant of Fire safety Certificate is recommended under rule 35 of the Delhi Fire service Rules 2010 under the DFS Act 2007.

Accordingly, DFA is put up for approval & signature please.

Aman Kumar L ADO (JWP)