

OF NATIONAL CAPITAL TERRITORY OF DELHI **HEAD QUARTERS: DELHI FIRE SERVICE: NEW DELHI - 110001**

No F 6 / DFS / MS / 2024/ School/WZ/

Certified that the Govt. Girls Sr. Sec. School located at D- Block, Ashok Vihar, Phase-1, Delhi-110052 comprised of 03 Blocks (02 Blocks- Ground plus first floor & 01 Block Ground upper floors) was issued FSC by this department vide letter No F6/DFS/MS/WZ/2021/377 dated 12.05.2021. The premises was re-inspected by the officer concerned of this department on 20.07.2024 in the presence of Smt. Jyoti Bhatia (Principal), and observed that all the fire prevention and fire safety arrangements as provided in the premises found in good working condition. The premises have deemed complied with fire prevention & fire safety requirements in accordance with circular issued by Director of Education letter no 3298-3398 dated 01.03.2011 and the building/ premise is fit for occupancy Group B Educational with effect from .30.07.20.24. for a period of three years, in accordance with the Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40, subject to compliance of the conditions under Rule 38 of the Delhi Fire Service Rules, 2010 printed below.

Issued on 30/07/2024 at New Delhi, by

Ph. 011-23414000

Copy to: -

- 1. The Principal, Govt. Girls Sr. Sec. School located at D- Block, Ashok Vihar, Phase-1, Delhi-110052.
- 2. The Director, Education, Government of NCT of Delhi. Old Sect. Delhi-110054.

Conditions for the validity of Fire Safety Certificate:

- 1. All the fire safety arrangement provided there-in shall be maintained in good working conditions at all times.
- 2. Loss of life or property due to non functional fire safety measure shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation with regard to the construction etc shall be verified by the concerned building sanctioning agency.
- 5. This certificate cannot be treated in any case for regularizations of unauthorized
- 6. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director of Form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six months prior to its expiry".
- 7. The owner / occupier shall submit a declaration every year in form "K" provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 8. The electrical panels inside the corridor must be removed within a time period of 3 months from the date of issuance of the Fire Safety Certificate. Failing to do so the Fire Safety Certificate will be null and void.

INSPECTION REPORT

1. Name & address of the building: Govt. Girls Sr. Sec. School located at D- Block, Ashok Vihar, Phase-1,

Delhi- 110052.

2. Type of Occupancy : Educational

3. Building Comprised of : 03 Blocks (Old Block = G+2 & New Block = 02 Blocks of G+1)

4. Type of Case Renewal

5. Details of Previous NOC F6/DFS/MS/WZ/2021/377 Dated- 12/05/2021

6. Fire Safety directives letter No: DOE Circular Dated 01/03/2011

7. Date of inspection 20 /07/2024

8. Name of Inspecting Officer : R.K.Sinha, ADO (BW)

9. Name and designation of officers

From the building side : Smt. Jyoti Bhatia (Principal)

10. Year of Construction 1980 & 2015

| 0. | Minimum Standards on fire prevention and fire safety U/R 33 | DOE/ Inspection rep dated 09/04/2021 | | Provided at site | Remarks MR/NMR | | | |
|----------|--|--|---|--|-------------------|--|--|--|
| | Access to building | | | | | | | |
| | Road width | 6 m | | Provided | MR | | | |
| | Gate width | 5 m | | Provided | MR | | | |
| | Width of internal road | NA | | NA | NA | | | |
| • | Number, Width, Type & Arrangeme | ent of Exits | - | | | | | |
| | a. Number of staircases | | | | | | | |
| | Upper Floors | Old Block – 2 New blocks- 1 in ea block | ach | Old Block- 3 New Blocks- 1 in each block | MR | | | |
| | Basements | NA NA | | NA | NA | | | |
| | b. Width of staircases | | | | | | | |
| | Upper Floor | 1.50 m each | Old Block- 1.6 m, 2× 1.25 m New Blocks- 1.5 m each | | MR(old case) | | | |
| | Basements | NA | | NA NA | NA | | | |
| | c. Protection of exits | | | | -14.5 | | | |
| | Fire check door | NA | | NA I | NA | | | |
| | Pressurization | NA | | NA NA | NA NA | | | |
| | | 7 | | AAA | INA | | | |
| | d. No. of continuous staircases to terrace | 01 in each block | | Provided | MR | | | |
| | e. Width of Corridor | 1.5 m | | Provided | MR | | | |
| | f. Door Size | 1 m | | Provided | MR | | | |
| 3. | Compartmentation | DAIL TOWN | | | | | | |
| | Fire check door | NA | T | 111 | | | | |
| | I VAN HUMMER OMMER | | - | NA | NA | | | |
| | or ciccuitat silaits | NA | | NA | NA | | | |
| | Fire Rating of shaft door Water Curtain | NA | | NA | NA | | | |
| | Fire Dampers | NA | | NA | NA | | | |
| 4. | Smoke Management System | NA | | NA | . NA | | | |
| | and the second s | od and the | | | | | | |
| + | Basements | NA | | NA | NA | | | |
| | Upper floors | Required | 1-1 | Naturally Ventilated | MR | | | |
| 5. | Fire Extinguishers | | | | | | | |
| | Total numbers | 27 Nos. | | 27. | | | | |
| | • Types | ABC/ Co2 Type | | 37 Nos. | MR | | | |
| | IS marking | | <u> </u> | Provided | MR | | | |
| 6. | First-Aid Hose Reels | Required | | Provided | MR | | | |
| | Total numbers on each floor | 02 | | Three I | | | | |
| | Length of hose reel hose | 30 m | 44 | Provided | MR | | | |
| | Nozzle diameter | 5 mm | | Provided | MR | | | |
| 7. | | | | Provided | MR | | | |
| | Type of detectors | | | | | | | |
| | | NA | | NA | | | | |
| | Docarroll of Main Panel | NA | | NA | NA | | | |
| The same | Location of Repeater Panel | NA | 100 | | NA | | | |
| | | a de la companya della companya della companya de la companya della companya dell | - | NA | NA | | | |

| _ | | • • • | | |
|-----|---|-----------------|-------------------------|----------|
| | Alternate source of power | NA | NA | N |
| | a. Dansey V seeder | NA | 2.00 | NX |
| 8. | Hooters' Location MOEFA | | NA NA | NA |
| 9. | Public Address System | NA NA | NA NA | NA |
| 10. | | I NA | NA NA | NA |
| 11. | Basement | NA | NA I | |
| | Ground Floor | NA | NA NA | NA |
| | Sprinkler above false ceiling | NA | NA NA | NA |
| | | 100/2004 | NA . | NA |
| | Size of riser/down-comer | NA | NA T | |
| | Number of hydrants per floor | NA | NA NA | NA |
| | Hose Box | NA | NA | NA NA |
| 12. | Yard Hydrants | | | INA |
| | Total number of hydrants | NA | NA | NA |
| | Hose Box | NA | NA | NA NA |
| 13. | Pumping Arrangements | | | IVA. |
| | Ground Level | _ 2_ 1 | | _ |
| | Discharge of main Pump | NA | NA | NA |
| | > Head of Main pump | NA . | NA NA | NA NA |
| | 1 | | * | |
| | > Number of main pumps | NA | NA | NA |
| | > Jockey Pump out put | NA | NA | NA |
| | > Jockey pump head | NA | NA | NA |
| | > Standby Pump out put | NA | NA | NA |
| | > Standby Pump Head | NA | NA NA | NA |
| | ➤ Auto Starting/Manual Stopping | NA | NA | NA |
| | > Pump House Access | NA | NA | ŊA |
| | Terrace level | | | |
| | ➤ Discharge of pump | 450 lpm | 2 × 450 1 | 1 10 |
| | | 450 lpm 40 m | 2 × 450 lpm Provided | MR MR |
| | > Head of the pump | | Hovided | MIK |
| | > Power Supply | Required | Provided | MR |
| | > Auto Starting of pump | Required | Provided | MR |
| 4. | Captive Water Storage for fire fighting | | | |
| | Underground tank capacity | NA | NA | NA |
| | > Draw-off connection | NA | NA NA | NA NA |
| | > Fire service inlet | NA NA | NA NA | NA NA |
| | > Access to tank | NA NA | NA NA | NA NA |
| | Overhead Tank capacity | 10,000 ltrs | Provided | |
| 5. | Exit Signage. | Required | Provided | MR MR |
| П | | Mana | Tiovided | IVIK |
| 6. | Provision of Lifts. | 3 | | |
| | Pressurization of Lift Shaft | NA | NA | NA |
| | Pressurization of Lift lobby | NA | NA | NA |
| | Communication In lift Car | NA | NA | NA |
| | Fireman's Grounding Switch | NA · | NA | NA |
| | Lift Signage | NA | NA NA | NA |
| | - Lan applaye | 14/1 | INV | 45500 |
| 1 | | N/A | 374 | 274 |
| | Standby power supply | NA | NA | NA |
| | Standby power supply Refuge Area. | NA . | NA | NA |
| | Standby power supply Refuge Area. > Total Area | NA NA | NA | NA NA |
| l. | Standby power supply Refuge Area. > Total Area > Location | | | |
| | Standby power supply Refuge Area. > Total Area | NA NA | NA | NA |
| l. | Standby power supply Refuge Area. > Total Area > Location | NA NA | NA | NA |

| 16.50 | | | | |
|------------|---|----------|---|----|
| PA | System Panel | . NA | NA | NA |
| • Bat | ery backup | NA NA | NA | NA |
| • Bui | ding Floor Plans | NA | NA | NA |
| pecial Fir | Protection System for of special Risks, if any: | Required | Co2 extinguisher provided near electrical panel | MR |

The fire protection systems provided in the building were tested, checked and found functional at the time of inspection.

Note:- Electrical panels installed inside the corridor have to be removed to a safer place.

Keeping in view of deemed compliance of the minimum standards of fire prevention and fire safety measures as required under DOE Circular No. 3298-3398 dated 01/03/2011, it is renew the Fire Safety Certificate issued vide recommended to

F6/DFS/MS/WZ/2021/377 dated 12/05/2021.

Signature of Inspecting Officer Name: Rajeev Kumar Sinha

Designation: ADO/B.W.