

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE, CONNAUGHT PLACE NEW DELHI

No. F6/DFS/MS/CGHS/SZ/2024/ 500

Dated: 02 /08/2024

Direct

Delhi Fire Ser

FIRE SAFETY CERTIFICATE

Certified that the building of Indian Bank staff CGHS Ltd. Located at Plot No 32, Sector – 6, Dwarka, Phase-1, New Delhi 110075, having 01 block comprised of Stilt + 7 Upper floors was issued No Objection Certificate by this department vide letter No. F6/DFS/MS/CGHS/99/2787, dated 01/03/1999. The premise was re inspected by the officer concerned of this department on 24/07/2024 in the presence of. Sh. Rakesh Kundu (President) and found that the said building have deemed complied with the fire prevention and fire safety requirements in accordance with Rule 33 of the Delhi Fire Service Rule, 2010 and that the premises is fit for occupancy class "Residential Building" Group A-4 with effect from 02 08 2024 for a period of five years in accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under Rule 38 of the Delhi Fire Service Rules, 2010.

Issued on 02 08 7024 at New Delhi by.

Copy to:

- 1. The President, Indian Bank staff CGHS Ltd. Located at Plot No 32, Sector 6, Dwarka, Phase-1, New Delhi 110075.
- 2. The Joint Director (Building) DDA, Vikas Sadan, INA, Delhi-110023.

Following fire safety directives must be adhered to:-

- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- 2. Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.
- 3. The trained staff should be available round the clock.
- 4. Any deviations w.r.t. construction shall be verified by the concerned building sanctioning agency.
- 5. The certificate may not be treated in any case for the regularization of the unauthorized construction, if any.
- 6. Basement shall be used as per building bye laws.
- 7. The owner/ occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its expiry. www.dfs.delhigovt.nic.in.
- 8. The owner/occupier shall submit a declaration every year in the form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on www.dfs.delhigovt.nic.in

N/k
INSPECTION REPORT

 Name & address of the building: Indian Bank staff CGHS Ltd. Located at Plot No 32, Sector – 6, Dwarka, Phase-1, New Delhi 110075.

2. Type of Occupancy

: Residential Building "A"

3. Type of Case: Renewal (01 high rise block Stilt+7 UFs + 4 two blochs CIS+4-0 に しんか かんと

4. Details of previous NOC: F6/DFS/MS/CGHS/99/2787, dated 01/03/1999

5. Fire Safety directives L. No.: F6/MS/DFS/CGHS/94/1448, dated 11/10/1994

6. Date of inspection

: 24/07/2024

7. Name of the Inspecting Officer: ADO (DWK)

8. Name and designation of Officer

from the building side: Sh. Rakesh Kundu (President)

9. Year of Construction

: Before 1996

10. Applicant's letter No.

: Nil dated 27/06/2024

No	Minimum standards on fire prevention and fire safety U/R 33	As per l	As per NBC Pro		ded at	Remarks MR/N		/NMR		
	Access of building					****				
•			9 mtr			Provided MF		3		
,	Gate width	1.5 mtr			Provided N		ИR .			
	Width of internal road	6 m	520	cm to6m	m			MR(skia		
2	Number, width, Type & Arrangeme	ents of ex	its					70		
			Ma sias			9		40		
	a. Number of staircases	02 N	02 Nos. bloc			ded	MR	MR '		
	Upper floors			1	N/A 1			N/A		
	Basements Width of staircases		7.	- 1						
	Upper floors Basements		m	125 & 9	90 cm MR old			d case		
			N/A N/A				N/A			
li .	c. Protection of exits									
	Fire check door	N/A			N/A	7	N	/A		
-	Pressurization		N/A				N	N/A		
i	d. No of continuous staircase to		Required			d	M	MR ·		
Į.	terrace	N/A			N/A		N	/A		
	e. Width Of Corridor f. Door Size	Requ	uired		1 mtr			MR		
3.	Compartmentation						·			
	Fire check door	N/A			N/A		N	/A		
ľ	 Sealing of electrical shafts 	N/A	3		N/A		N	/A		
	 Fire Rating of shaft door 	N/A	N. Committee		N/A		N	/A		
	Water Curtain	N/A	}		N/A		N.	/A		
	Fire Dampers	N/A			N/A		N	/A		
4.	Smoke managements System									
1	Basements	N/A			N/A		N	/A		
	Upper floors		Required			ventilatio	n M	MR		

Xo, h

NIT

- 1	Di Datia suighore											
5.	Fire Extinguishers	02 r	02 nos each floor			Provided			MR			
	Total numbers		CO ₂ & WCO ₂ ISI marked			Provided Provided			MR			
	Types Secreting				Ì				MR			
	IS marking	+ 151			\top							
5.	First - Aid Hose Reels	010	each	floor			Provid	led		MR		
	Total numbers on each floor	30					Provid	ded		MR		
	Length of hose reel hose		nm			-	Provid	ded		MF		
	Nozzle diameter				-	_		Mark Co.				
7.	Automatic fire detection and alarmin	ig syst	A	_	IN	/A			N/	A		
	Type of detectors		14/23			Ground floor			MR			
	Location of Main Panel		Ground moor			N/A			N/			
	 Location of Repeater Panel Alternate source of power Hooters' Location 		DG Set			DG Set 125 KVA			MR MR			
			Appropriate place			Provided		mease	se MR MR			
8.	MOEFA	7.251-31	equir	ed		er er on te	ded		_			1
9.	Public Address System	N	/A		N	I/A] N	/A		1
10.	Automatic Sprinkler System											1
	Basements		N/	A N	N/A			N/A				4
	Upper Floor		N/	A 1	N/A			N/A				1
	Sprinkler above false ceilin	g	N/	1000	N/A			N/A				
			1.30		San Child				2 3			
11.	Internal Hydrants	1	00 m	nm		Pr	ovideo	i			MR	
	Size of riser/down-comer Size of riser/down-comer		rovi				ovide			1	MR	
	Number of hydrants per flo	ASS. 1				-	rovide				MR	
	Hose Box	R	Requi	irea		PI	Ovide	4)				
12.	Yard Hydrants		-			-	access to the Cal			1	МR	-
	 Total number of hydrants 			rovided		5656	ovided				(636-21) 73 V	-
	Hose Box		R	equired		Pre	ovided	1			MR	_
13.	Pumping Arrangements		E.							-		_
	Ground Level	N/	N/A N/A			1			N	N/A		
3	 Discharge of main pump 		/A	N/A		Y		1	N/A			
	> Head of main pump		/A	N/A						N/A		
	Number of main pumps		/A		N/A					N/A		
	Jockey pump out put	55000	Water Street		N/A N/A					N/A		-
	Jockey pump head		/A		(0)17050-							
	Standby Pump out put	-	/A		N/A				N/A			_
	> Standby Pump Head	N	I/A N/A			N/A						
	➤ Auto Staring/Manual	N	I/A		N/	A				N/A		
	stopping	N	I/A		N/A				N/A			
	> Pump House Access	-	MAGE		[D]							
	Terrace level	1	50.1-	om ocak	bla	ole	Dec	vided		1	MR	_
	> Discharge of pump			om each	0100							
	> Head of the pump	1.00	40m			Provided		2000000	MR			
	> Power supply	R	Required		Provided		led	MR		1		
	Auto starting of pump	R	Requ	ired		1	Provi	ded		MI	3	
14.	Captive water Storage for fire fig		•							1		
17.				200000	1 1+-	9	2000)00 1t			MD	
	Under ground tank capac	ity	L	200000 ltr					00 ltrs.		MR	
	> Draw of connection			Required		I		Provided			MR	1
	> Fire service inlet			Requir	ed		Pr	ovided			MR	-
			H	Required			Provided				L. Carles and	
	> Access to tank			Keamr	ea		Pr	aviaea			IVIK	
	Access to tankOverhead Tank capacity		-	10,000		D	rovide			_	MR MR	-

e.	Exit Signage Requi		Provi	ded	· MR			
5.	Provision of Lifts							
-	> Pressurization of Lift Shaft		Ά	N/A		N/A		
 Pressurization of lift lobby Communication in lift Car 			Ά	N/A	N/A	N/A		
		Car Re	equired	Provided	MR	MR		
•	Fireman's Grounding	Re	equired	Provided		M		
	Switch Lift Signage Standby power supply		equired	Provided		MR		
9			quired	DG Set Pro	MR			
•	Refuge Area							
	> Total area	N/	Ά	N/A	N/A			
	> Location	. N	Ά	N/A	N/A	N/A		
	Fire control room		N/A	N/A	N/A	4		
1	Detector system panelFlow Switch Panel			N/A	N/A	N/A N/A N/A N/A N/A her near MR		
2			N/A	N/A	N/A			
 PA System Panel Battery backup Building Floor Plans 			N/A	Provide				
			N/A		T			
	> Building Floor Flans		N/A	N/A				
	Special Fire Protection Systems Protection of special Risks, if a		Required ABC fire electric pa		extinguisher near nel			

The fire protection systems provided in the building were test checked and found functional

In view of the deemed compliance of minimum standards on fire prevention and fire safety at the time of inspection. as required under the rules the NOC issued vide letter No. F6/DFS/MS/CGHS/99/2787, dated as required under the rules the INOC issued vide letter No. ro/Drs/MS/COHS/99/2/8/, dated 01/03/1999 renewal under Rule 37 of the Delhi Fire Service Rules 2010 is recommended.

This renewal of FS is only for C-Block is High Rix Block. Rest Two Hooks are not averal under DFS Ret 2017, Ruley 2010.

Signature of the Inspecting Officer Name Was Vis Singh Designation ADO DEUT

(etter