## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE, NEW DELHI – 110001

No.F6/DFS/MS/Metro/WZ/2024/ 495

Dated: 31 /07 /2024

## FIRE SAFETY CERTIFICATE

Certified that the Madipur Metro Station (Elevated) (Line No.-05) located at Madipur New Delhi comprised of (Ground + First Floor is used as a Concourse + Second floor letter (As Platform) issued **FSC** vide was F6/MS/DFS/MS/Metro/2021/MN/363 dated 29/07/2021. The premises was re-inspected by the officer concerned of this department on 22/07/2024 in the presence of Sh. Sanyam Jain (Assistant Manager/Fire) and found that the said metro station have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rule, 2010 and that the building / premises is fit for the occupancy class "Assembly" Group D Sub Division D -7 (Except PD Area) with effect from 31,07,2024. for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

Issued on 31 07 2024... at New Delhi by.

(Atal Garg

Director

Copy to:

1. Sh. V.P. Singh (Dy. CEE/E&M/RC-1), DMRC, Metro Bhawan, Fire Brigade, Lane, Barakhamba Road, New Delhi – 110001.

## Following fire safety directives must be adhered to:-

- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- 2. Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.
- 3. The trained staff should be available round the clock.
- 4. Any deviations w.r.t. construction shall be verified by the concerned building sanctioning agency.
- 5. The basement shall be used as per building bye laws 1983.
- 6. The certificate may not be treated in any case for the regularization of the unauthorized construction, if any.
- 7. The owner/ occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its expiry.
- 8. The owner/occupier shall submit a declaration every year in the form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on <a href="https://www.dfs.delhigovt.nic.in">www.dfs.delhigovt.nic.in</a>.

1		<u>IN</u>	SPEC	TION REPORT					
1.	Name &	address of the building	Madipur Metro Station (Elevated) (Line No05), Located at Madipur New Delhi.						
2.	Type of	f Occupancy	Assembly (Metro Station) (Ground, 1 <sup>st</sup> floor (concourse) & 2 <sup>nd</sup> floor (Platform Level)						
3.	Type o	f Case	Renev	val	1)				
4.	Details	of previous NOC	F6/DF	S/MS/Metro/2021	/MN/363 dated 29/07/2	2000			
5.	Fire Sa	fety directives letter No				021			
		f inspection	F6/DFS/MS/BP/2010/509 dated 23/08/2010 22/07/2024						
		of the Inspecting Officers							
8.	Name	and designation of	Sh. Sa	Sarabjeet Singh ADO (MN) Sh. Sanyam Jain (Assistant Manager/Fire)					
9 1	officer Vear of	s from the building side Construction			*				
					ious insp. report dtd- 14				
		ant's letter No.	DMR	C/O&M/Fire/NOC	C/L-05/2024/01 dated 24	/06/2024			
lo.	preve	nimum Standards on fire ntion and fire safety U/R	R 33 35	equired as per Rule (6) of DFS Rule 201	Provided at site	Remarks MR/NMR			
	Access	to building	Later -			Di .			
	•	Road width		On Main Road	Provided	MR			
	-	Gate width		5 m	Provided	MR			
2	N.	Width of internal road	10.0	NA	NA	NA			
HY.	a Nur	Number, Width, Type & Arrangement of Exits a. Number of staircases							
200	•	Upper Floors		2+4	0.40	) (D			
	-	Basements	أعريت		2+4 Provided	MR			
	b. Wi	dth of staircases		NA	NA	NA			
	•	Upper Floors		Required 1) 2m x 2, (G to 1 <sup>st</sup> ) 2) 4m x 2 & 2m x (1 <sup>st</sup> to 2 <sup>nd</sup> )	1) G to C (1 <sup>st</sup> fl) 2.20 m x 2) Lower concourse to up concourse (1 <sup>st</sup> to 2 <sup>nd</sup> fl) 4.20m x 2	per			
		Basements		NA NA	NA NA	NA			
	c. Pro	tection of exits		4.	a Transita	1			
	•	Fire check door		NA	NA	NA			
	•	Pressurization		NA	NA	NA			
		of continuous staircases to t	errace	NA	NA .	NA			
		dth of Corridor oor Size		Required 1.5m	Hall Provided	MR			
3	-	partmentation.		III	Provided	MR			
3	Com		0.7	Required	Provided	MR			
		Sealing of electrical shaft	ts	Required	Provided	MR			
		Fire Rating of shaft door		Required	Provided	MR			
20.5		Water Curtain		NA	NA	NA			
		Fire Dampers		NA	NA	NA			
4	Smo	ke Management System.		7					
		Basements		NA	NA	NA			
		• Upper floors	1 12	NA	NA	NA			
-	Fire	Extinguishers		1					
5	Total numbers			20 Nos.	Provided	MR			
3		10tal numbers		Control Control					
3		Types IS marking		CO <sub>2</sub> , DCP type ISI marked	Provided	MR			

N	13
1	1>

6	First-Aid Hose Reels.		1				
	Total numbers on each floor	2+4	Provided	MR			
	<ul> <li>Length of hose reel hose</li> </ul>	45m	Provided	MR			
	Nozzle diameter	6.5mm	Provided	MR			
7	Automatic fire detection and alarming system.						
	Type of detectors	Smoke	Provided	MR			
	Location of Main Panel	Required	Provided	MR			
	<ul> <li>Location of Repeater Panel</li> </ul>	Required	Provided	MR			
	Alternate source of power	Required	Provided	MR			
	Hooters' Location	Required	Provided	MR			
8	MOEFA	Required	Provided	MR			
9	Public Address System.	Required	Provided	MR			
10		Required in comme	ercial Area)				
	Basement	NA	NA	NA			
	Upper Floor	Required in PD area	Provided	MR			
	Sprinkler above false ceiling	NA NA	NA	NA			
11	Internal Hydrants						
	Size of riser/down-comer	150 mm	Provided	MR			
	Number of hydrants per floor	02 at each P.F.	Provided	MR			
	Hose Box	Required	Provided	MR			
12	Yard Hydrants.	Required		1411			
	Total number of hydrants	02	Provided	MR			
	Hose Box		Provided	MR			
13	Pumping Arrangements.	Required	- LOYAGO	IVIK			
	Ground Level						
	Discharge of main Pump	10001					
	> Head of Main pump	1800 lpm	Provided	MR			
	> Number of main pumps	70m	Provided	MR			
	> Jockey Pump out put	180 lpm	Provided	MR			
	> Jockey pump head	70m	Provided Provided	MR			
	Standby Pump out put	1800 lpm	Provided	MR			
	Standby Pump Head	70m	Provided	MR MR			
	➤ Auto Starting/ Manual stopping	Required	Provided	MR			
	➤ Pump House Access	Required	Provided	MR			
	Terrace level	roquired	1 TO VIGEU	IVIK			
	➢ Discharge of pump	NA	NA	NA			
	> Head of the pump	NA NA	NA	NA			
	> Power Supply	NA	NA	NA			
	> Auto Starting of pump	NA	NA	NA			
4	Captive Water Storage for fire fighting		2.8999				
•		50,000 ltrs	Provided	MR			
	Underground tank capacity		Provided				
	> Draw-off connection	Required Required	Provided	MR			
	> Fire service inlet		* 55.00000000000000000000000000000000000	MR			
	Access to tank	Required	Provided	MR			
	Overhead Tank capacity	10,000 ltrs	Provided	MR			
5	Exit Signage.	Required	Provided	MR			

2 ADO MN 507 2024 The fire protection systems provided in the building were checked and found functional at the time of inspection.

panel/stations etc.

Keeping in view of deemed compliance of the minimum standards on fire prevention and fire safety required under the rules, renewal of Fire Safety Certificate issued by this deptt. letter no.- F6/DFS/MS/Metro/2021/MN/363 dated 29/07/2021 is recommended.

DYCHI/WIZ

Protection of special Risks, if any:

Signature of the Inspecting Officer

Name: - Sarabjeet Singh

Designation: - ADO (MN)

24. 32 A. A. P. M.

1 26/7

29 Hy 2014

Deneeter

May M

Sir, F. T i's put up for your kind persual & signature please.