GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CANNAUGHT PLACE NEW DELHI- 110001

No. F6/DFS/MS/School/2024/SZ/ 729

Dated: 29/07/2024

FIRE SAFETY CERTIFICATE

Certified that the New Delhi Public School, A-Block, Vikaspuri, New Delhi-110018, comprised of ground floor plus three upper floors, owned/occupied by New Delhi Public School was issued FSC by this department vide letter no. F.6/DFS/MS/school/2021/SZ/410 dated 28.06.2021. The School building was re-inspected by the officer concerned of this department on 16.07.2024 in the presence of Sh. Naresh Sharma (Manager) and found that the school building have deemed complied with the fire prevention and fire safety requirements in accordance with Rule 33 of the Delhi Fire Service Rules, 2010 and that the building is fit for occupancy class "Educational" w.e.f. 2907/2024 for a period of three years in accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under Rule-38 of the Delhi Fire Service Rules, 2010 printed as below.

Issued on 29 07 2024 at New Delhi.

Director i Fire Service

Delhi Fire Service

Copy to: -

- 1. The Principal, New Delhi Public School, A-Block, Vikaspuri, New Delhi-110018.
- 2. Director of Education, GNCT of NCT of Delhi, Old Secretariat, New Delhi-110054.

Following fire safety directives must be adhered to: -

- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- 2. The means of escape shall be kept unlocked and unobstructed for unhindered evacuation of occupants in case of emergency.
- 3. Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.
- 4. The trained staff should be available round the clock.
- 5. Any deviations w.r.t. construction shall be verified by the concerned building sanctioning agency.
- 6. The certificate may not be treated in any case for the regularization of the unauthorized construction, if any.
- 7. Basement shall be used as per the building bye laws.
- 8. The owner/occupier shall submit a declaration every year in the form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on www.dfs.delhigovt.nic.in.
- 9. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in the Form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six months prior to its expiry.

MLY

INSPECTION REPORT

1. Name & address of the building

: New Delhi Public School, A-Block, Vikaspuri, New Delhi-18.

2. Building is comprised of

: Ground plus three upper Floors

3. Type of Occupancy

: Educational

J. 17P- -- 1

a mar

4. Type of Case5. Details of Previous NOC

: Renewal : F.6/DFS/MS/school/2021/SZ/410 dated 28.06.2021

6. Fire Safety direction letter No

: Nil

7. Date of Inspection

: 16,07,2024

8. Name of the Inspecting Officers:

: ADO R.K. YADAV

9. Name of the designation of Officer

from the building side

: Sh. Naresh Sharma (Manager)

10. Year of Construction

: 2003-2004

11. Applicant's letter No

: Online email Id abcfiresystems@hotmail.com dated 24.06.2024

S. No.	Minimum Standards on fire prevention and fire safety requirements U/R 33	Requirement	Provided at Site	Remarks MR/NMR		
1	Access to building					
	Road width	06 m	06 m	MR		
	Gate width	4.5 mtrs.	4.5 mtrs.	MR		
	Width of internal road	N.A.	N.A.	N.A.		
2	Number, Width, Type and Arrangement	of Exits				
	a. Number of Staircases	03 no.	03 no.	MR		
	Upper Floor	N.A.	N.A.	N.A.		
	Basement	N.A.	N.A.	N.A.		
	B. Width of Staircases	1.50 m	1.60,1.60 &1.70 m	MR		
	Upper Floor	N.A.	N.A.	N.A.		
	Basement		N.A.	N.A.		
	c. Protection of exits	N.A.		N.A.		
	Fire check door	N.A.	N.A.	MR		
	Pressurization	01 no.	01 no.			
	e. No. of continuous staircases to terrace	1.50 m	2.15 & 2.10 m	MR		
	g. Width of Corridor h. Door Size	1.0 m	1.12 m	MR		
3	Compartmentation.					
	Fire check door	N.A.	N.A.	N.A.		
	Sealing of electrical shafts	N.A.	N.A.	N.A.		
	Fire rating of shaft door	N.A.	N.A.	N.A.		
	Water curtain	N.A.	N.A.	N.A.		
1.5	Fire Dampers	N.A.	N.A.	N.A.		
4	Smoke Management System.					
	Basement	N.A.	N.A.	N.A.		
	Upper floor	Required	Natural Ventilation	MR		

15

h

5.	Fire Extinguisher						
	Total numbers types IS marking	16 Nos.	16 Nos.				
		CO ₂ & ABC	CO ₂ & ABC	MR			
		ISI marked	ISI marked	MR			
6	First-aid-Hose Reels.						
	Total numbers of each floor	01 Nos.	D	January 1			
	Length of hose reel hose Nozzle diameter	30 m	Provided	MR			
		05 mm	30 m	MR			
7	Automatic fire detection and alarming sy	200	05 mm	MR			
	The state of the s						
	Type of detectors Location of main panel Location of repeater panel Alternate source of power Hooters	N.A,	N.A.	N.A.			
		N.A.	N.A.	N.A.			
		N.A.	N.A.	N.A.			
		N.A.	N.A.	N.A.			
		N.A.	N.A.	N.A.			
8	MOEFA	N.A.	N.A.	N.A.			
9	Public address System.	N.A.	N.A.	N.A.			
10	Automatic Sprinkler System.		100	N.A.			
	basement	N.A.	N.A.	Faty)			
	upper floor sprinkler above false ceiling	N.A.	N.A.	N.A.			
		N.A.	N.A.	N.A.			
11	Internal Hydrants		INA.	N.A.			
	size of riser/down-comer	Einlin III KAN	White by Yorks	4.16			
	Number of hydrants per floor Hose Box	100 mm	Provided	MR			
		01Nos.	Provided	MR			
12	Yard Hydrants.	01Nos.	Provided	MR			
	Tard Hydrants.						
	Total number of hydrants Hose Box	N.A.	N.A.	NI A			
		N.A.	N.A.	N.A.			
13	Pumping Arrangements.						
	Ground Level	N.A.	N.A.				
	Discharge of main Pump	N.A.	N.A.	N.A.			
	➤ Head of Main Pump ➤ Number of main pumps	N.A.	N.A.	N.A.			
	 Jockey pump out put Jockey pump head Standby pump out put Standby pump Head Auto Starting /Manual stopping Pump House Access Terrace Level 	N.A.	N.A.	N.A.			
		N.A.	N.A.	N.A.			
		N.A.	N.A.	N.A.			
		N.A.	N.A.	N.A.			
		N.A.	N.A.	N.A.			
		N.A.	N.A.	N.A.			
		N.A.	N.A.	N.A.			
	Discharge of pump Head of the Pump	450 & 180 LPM					
	Head of the PumpPower supply	430 & 180 LPM	450 & 180 LPM	MR			
	Auto Starting of pump	Required	40 m	MR			
	otating of pump	Required	Provided	MR			
14			Provided	MR			
14	Captive Water Storage for Fire Fighting	45. 1					
	Underground tank capacity	N.A.	50.00				
	Draw-off connection Fire service inlet	N.A.	50,000 ltrs	MR			
		. 1.4 1.	N.A.				

Fire service inlet N.A. N.A. N.A. N.A. Access to tank Two way Overhead Tank capacity N.A. N.A. N.A. N.A. 10,000 ltrs 30 000 ltm

15	Exit Signage.	Required	Provided	MR		
16	Provision of Lifts.					
	Pressur zation of Lift Shaft	N.A.	N.A.	N.A.		
	Pressurization of Lift lobby	N.A.	N.A.	N.A.		
	Communication in lift car Firemen's grounding switch	N.A.	N.A.	N.A.		
		N.A.	N.A.	N.A.		
	Lift Signage	N.A.	N.A.	N.A.		
17	Standby power supply	N.A.	N.A.	N.A.		
18	Refuge Area.					
	Total area	N.A.	N.A.	N.A.		
	Location	N.A.	N.A.	N.A.		
19	Fire Control Room					
	Detector system panel	N.A.	N.A.	N.A.		
	Flow switch panel	N.A.	N.A.	N.A.		
	PA system panel	N.A.	N.A.	N.A.		
	Batter backup	N.A.	N.A.	N.A.		
	Building Floor Plans	N.A.	N.A.	N.A.		
20	Special Fire Protection systems for protection of special Risks, if any:	N.A.	N.A.	N.A.		

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards on fire prevention and fire prevention and Fire safety measures as required under the rules the FSC issued vide letter no. F.6/DFS/MS/school/2021/SZ/410 dated 28.06.2021, renewal under rule 37 of the Delhi Fire Service Rules 2010 is recommended.

Signature of the Inspecting Officer

Name- R.K. Yadav Designation- ADO (JKP)

DO (South West)

Sinetar My

MOJOKI