

### FORM 'II'

# FORM FOR ISSUING FIRE SAFETY CERTIFICATE

[Refer sub - rule (1) of rule 35]

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE, CONNAUGHT PLACE

**NEW DELHI** 

No.F6/DFS/MS/2024/School 733

Dated:30 /07/2024

### FIRE SAFETY CERTIFICATE

Certified that the building New Era Public School Located at Pochanpur Sector – 24, Phase-II Dwarka, New Delhi – 110077 having two blocks, A block comprised of Ground + One Upper Floor, & B- block comprised of Basement + ground + 01 Upper floor was issued Fire Safety Certificate vide this department letter No. F.6/DFS/MS/2021/638 dated 24/08/2021. The premises was re inspected by the officer concerned of this department on 19/07/2024 in the presence of Sh. Arvind Sharma (Maintenance In charge) and found that premises have deemed complied with the fire prevention and fire safety requirements in accordance DOE Circular 3298-3398 Dated 01/03/2011 and that the building is fit for occupancy class B "Educational building" with effect from 30/07/2024 for a period of three years, subject to compliance of the condition printed as under.

Issued on .30/67/2024 at New Delhi by.

tul Garg)
Director
Delhi Fire Service.

### Copy to:

- 1. The Principal, New Era Public School, Pochanpur Sector 24, Phase-II Dwarka, New Delhi 110077
- 2. The, Directorate of Education Old Secretariat Delhi 110054

#### Following fire safety directives must be adhered to:-

- 1 All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- 2 Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.
- 3 The trained staff should be available round the clock.
- 4 Any deviations w.r.t. construction shall be verified by the concerned building sanctioning agency.
- 5 The certificate may not be treated in any case for the regularization of the unauthorized construction, if any.
- 6 The owner/ occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its expiry. <a href="www.dfs.delhigovt.nic.in">www.dfs.delhigovt.nic.in</a>.
- 7 Basement shall be used strictly as per building bye laws.
- 8 The owner/occupier shall submit a declaration every year in the form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on <a href="www.dfs.delhigovt.nic.in">www.dfs.delhigovt.nic.in</a>.

## **INSPECTION REPORT**

 Name & address of the building: New Era Public School Located at Pochanpur Sector – 24, Phase-II Dwarka, New Delhi – 110077

2. Type of Occupancy : Educational Two Blocks, A- blocks= Ground + One Upper Floor, & B- block= Basement + ground + 01 Upper floor

3. Type of Case : Renewal

4. Details of previous NOC: F.6/DFS/MS/2021/638 dated 24/08/2021

5. Fire Safety directives Letter No. : . Circular. No 3298-3398 Dated 01/03/2011

6. Date of inspection : 19/07/2024

7. Name of the Inspecting Officer: ADO (DWK)

No. of class rooms=26 Plot area=20234m<sup>2</sup> Covered area=6280m<sup>2</sup>

No. of Students=550

8. Name and designation of Officer

from the building side : Sh. Arvind Sharma (Maintenance Incharge)


9. Year of Construction

: 2011

10. Applicant's letter No.

: Email Dated - 29/06/2024

	Minimum standards on fire prevention					Remarks MR/NMR	
_	and fire safety U/R 33	N/13 & N/14		site	site MR		
.	Access of building			The same of the sa	T		
	Road width	06 mtrs				/IR	
	Gate width	Accessible		Provided M		1R	
	Width of internal road	NA		NA N		NA	
	Number, width, Type & Arrangements	s of exits					
	a. Number of staircases		9	8	<u> </u>	l a m	
	<ul> <li>Upper floors</li> </ul>	04 Nos.		04 Nos.	1	MR	
	Basements	02 Nos.		02 Nos. MR		ι	
	b. Width of staircases				1.5	m m :	
	Upper floors	(including railing) (1.5 mtr 2x142cm(including railing) 1			MR (Being Old case) MR (Being Old case)		
	Basements			-			
	c. Protection of exits						
	Fire check door	NA		NA	NA		
	Pressurization	NA	NA NA		NA		
	d. No of continuous staircase	NA		NA		NA	
	to terrace	1.5 mtr		Provided		MR	
	e. Width Of Corridor f. Door Size	01 mtr	100 cm(including door frame)		MR, ole Case		
3.	Compartmentation			D III			
	Fire check door	NA		NA	NA		
	<ul> <li>Sealing of electrical shafts</li> </ul>	NA		NA	1 3 2 2 3 4 4 4 4 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5		
	<ul> <li>Fire Rating of shaft door</li> </ul>	NA		NA		NA	
	Water Curtain	NA		NA		NA	
	Fire Dampers	NA .		NA		NA	
4.	Smoke managements System						
	Basements	Require			d	MR	
	Upper floors	NA Natu		atural ventilation		NA	



		nguishers	01 20	s.ABC & CO <sub>2</sub> for	08 no	s each floor	M	R	
		otal numbers		300 sq. mtrs	Provi			MR MR	
		ypes	ISI ma		- AMM 6-2000 2	narked	M		
		S marking	101 111						
•	Total humbers on each moor		03 Nos.	03 N	os.	М	R		
			30 mtr		30 mtr		MR		
	Length of hose reel hose			05 mm		5 mm		MR	
	1 NOZZIC GIAITICICI				O ALMAN				
7.	Automatic fire detection and alarming			NA NA	N	NA N		NA .	
	Type of detectors     Location of Main Panel			NA NA		NA		NA	
				NA NA		- Action		NA	
		Location of Repeater Panel		NA				IA	
	Alternate source of power		NA .	. N.		NA			
		looters' Location					11.000.000.000		
3.	MOEFA			NA	N.	2002	NA NA		
)		ddress System		NA NA	NA NA				
0.		ic Sprinkler System			m		1.00		
		asements		Required	40000	Provided MR			
0		Ipper Floor		NA	N.		NA NA		
		prinkler above false	ceiling	NA	. N	NA			
1.		Hydrants:							
		ize of riser/down- co		NA		100 mm NA			
		lumber of hydrants p	er floor			03 Nos. NA			
		lose Box		NA	A Provided		NA		
2.	Yard Hy	drants							
	<ul> <li>Total number of hydrants</li> </ul>			NA	02	2 Nos.	Nos. NA		
	• F	Iose Box		NA		rovided	NA		
13.	Pumping	Arrangements:				1 11 11	1 - 1 - 2		
		Fround Level			N 1940				
	Discharge of main pump		NA	N	NA NA		-		
		lead of main pump		NA		A	NA	-	
				NA	NA		NA NA		
	▶ J			NA		A			
	Jockey pump head		NA		20,22		NA		
	> S	tandby Pump out pu	t	NA		NA NA		NA	
	> 5	tandby Pump Head		NIA				NA	
	> A	uto Staring/Manual	stoppin	g NA		NA		NA	
	Pump House Access		NA NA		NA		NA		
	• ]	errace level		INM	_ N	NA		NA	
	× I	Discharge of pump		450 lm 0 11	001				
	> F	lead of the pump		450 lpm & 13	80 lpm			n M	
	> F	ower supply		30 mtr	_	30 mtr	MR		
	> Auto starting of pump		Required	equired Provided		MR			
14.	Captive	water Storage for fa-	e fiel i	Required	197	Provided	MR		
	• Under ground						41440		
	<ul> <li>Draw off connection</li> <li>Fire service inlet</li> <li>Access to tank</li> </ul>		NA	N	A	NA NA			
			NA		A				
			NA		IA	NA			
	• (	verhead Tank		NA		A	NA		
15	Overhead Tank capacity     Exit Signage		5,000 ltr		A CONTRACTOR OF THE PARTY OF TH	NA			
			NA			MR (Old case			
				, . I	(A	NA			
							100		

6.	rovision of Lifts  > Pressurization of Lift Shaft			$\top$					
		NA	NA	NA					
	<ul> <li>Pressurization of lift lobby</li> <li>Communication in lift Car</li> </ul>	NA	NA	NA					
		NA	NA	NA					
	<ul> <li>Fireman's Grounding Switch</li> <li>Lift Signage</li> </ul>	NA	NA	NA					
-		NA	NA	NA					
7.	Standby power supply	NA	NA	NA					
18.	Refuge Area								
- 1	> Total area	NA	NA	NA					
10	> Location	NA	NA	NA					
19.	rire control room								
	> Detector system panel	NA	NA	NA					
	Flow Switch Panel	ΝA	NA	NA					
	<ul> <li>▶ PA System Panel</li> <li>▶ Battery backup</li> <li>▶ Building Floor Plans</li> </ul>	NA	NA	NA					
		NA	NA	NA					
		NA	NA	NA					
20.	Special Fire Protection Systems for Protection of special Risks, if any;	Required	ABC fire extinguisher provided near electric panel		MR				

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

In view of the deemed compliance of minimum standards on fire prevention and fire safety as required under the rules the NOC issued vide letter No. F.6/DFS/MS/2021/638 dated 24/08/2021 renewal under Rule 37 of the Delhi Fire Service Rules 2010 is recommended.

Note: - Two pumps of 450 lpm connected with a underground water tank are also found provided.

Signature of the Inspecting Officer Name Vac Vir Simple

Designation

W 2/2/2/19

CFO (S2) Ing

Dinector M

And my