

## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: NEW DELHI - 110001



No F 6 / DFS / MS / 2024 /School/WZ/ 811

19/08/2024 Dated

FIRE SAFETY CERTIFICATE

Certified that the Govt. Boys Sr. Sec. School located at Bakhtawarpur, Delhi- 110036 comprised of 02 Blocks (Ground and first floor) owned/ occupied by Govt. Boys Sr. Sec. School have complied with the fire prevention and fire safety requirements in accordance with DOE circular no. 3298-3398 dated 01.03.2011 and verified by the officers concerned of Fire Service on 06.08.2024 in the presence of Sh. Dinesh Kumar (Vice Principal) and found that the building/ premises is fit for occupancy Group B Educational with effect from for a period of 03 (Three) years subject to compliance of the conditions mentioned below:

Issued on ...19.08 .2.24... at New Delhi by

Ph. 011-23414000

## Copy to:-

1. The Director of Education, Govt. of NCT of Delhi, Old Secretariat, Delhi.

2. The Principal, Govt. Boys Sr. Sec. School located at Bakhtawarpur, Delhi- 110036.

## Conditions for the validity of Fire Safety Certificate:

1. All the fire safety arrangement provided there-in shall be maintained in good working conditions at all times.

2. Loss of life or property due to non functional fire safety measure shall be at the responsibility of the management.

3. The trained fire fighting staff should be available round the clock.

4. Any deviation with regard to the construction etc shall be verified by the concerned building sanctioning agency.

5. This certificate cannot be treated in any case for regularizations of unauthorized construction.

6. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director of Form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six months prior to its expiry".

7. The owner / occupier shall submit a declaration every year in form "K" provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on WWW.dfs.Delhigovt.nic.in

8. All the means of escape shall be kept free of any obstruction all the time to evacuate the occupant, in a safe manner, in the event of emergency.

9. Electrical Panel under the staircase must be removed or been segregated by fire check door within a period of three months from the date of issuance of the Fire Safety Certificate. Failing to do so the Fire Safety Certificate will be null and void.

INSPECTION REPORT

Name & address of the building : Govt. Boys Sr. Sec. School located at Bakhtawarpur, Delhi- 110036. Type of Occupancy

Building Comprised of 02 Blocks (Ground plus First floor) 3. 4. Type of Case
5. Details of Previous NOC New Case

F6/DFS/MS/2021/School/WZ/398 dated 23/06/2021

(Previous FSC was for Single Block Ground and First floor) 6. Fire Safety directives letter No :

DOE circular No. 3298-3398 dated 01/03/2011 7. Date of inspection 06/08/2024

8. Name of Inspecting Officer R.K.Sinha, ADO (BW)

9. Name and designation of officers

From the building side
10. Year of Construction
11. Applicant's letter No. Sh. Dinesh Kumar (Vice Principal)

0.	prevention and fire safety II/R 33	Mail id Dated 29/07  DOE  Requirement	Provided at site	Remarks	
•	Access to building	1 cancin		MR/NMR	
	Road width	. 6 m	Provided	MR	
	Gate width	4.5 m	Provided	MR	
	Width of internal road	NA	NA	NA	
•	Number, Width, Type & Arrangemen	nt of Exits		NA.	
	a. Number of staircases				
	Upper Floors	A Block- 01 B Block- 01	A Block- 02 B Block- 01	MR	
	Basements	NA	NA	NA	
	b. Width of staircases	and a second			
	Upper Floor	1.50 m each	A Block- 1.37 m × 2 B Block- 1.50 m	MR	
	Basements	NA	NA	NA	
	c. Protection of exits				
	Fire check door	NA	NA	NA	
į	<ul> <li>Pressurization</li> </ul>	NA	NA	NA NA	
	d. No. of continuous staircases to terrace	NA	NA	NA NA	
	e. Width of Corridor	NA	NA	NA	
	f. Door Size	1 m	Provided with double door	MR	
١.	Compartmentation				
	Fire check door	NA	NA	MA	
	Sealing of electrical shafts	NA	10 m (c)	NA	
	Fire Rating of shaft door	NA NA	NA	NA	
	Water Curtain	NA NA	NA	NA	
	Fire Dampers	NA NA	NA	NA	
	Smoke Management System	NA NA	NA ·	NA	
	Basements	NA	NA	NA	
	Upper floors	Required	Naturally Ventilated	MR	
	Fire Extinguishers				
	Total numbers	10	22	100	
	Types	ABC Type	Provided	MR	
	IS marking	Required	Provided	MR	
ś.	First-Aid Hose Reels	required	Flovided	MR	
200	Total numbers on each floor	NA	NA	NTA.	
	<ul> <li>Length of hose reel hose</li> </ul>	NA	NA NA	NA NA	
	Nozzle diameter	NA	NA NA	NA	
,			IM	NA	
7.	Automatic fire detection and alarming system				
	Type of detectors	NA	NA	NA	
	Location of Main Panel	NA	NA	NA	
	<ul> <li>Location of Repeater Panel</li> </ul>	NA	NA NA	NA	
	<ul> <li>Alternate source of power</li> </ul>		0.75670.20	INM	

N	1	1	3
V-			

	X	W-13	· · · · · · · · · · · · · · · · · · ·	NA NA	
	nedopost timent	NA	NA	\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	
	Hooters' Location	NA	NA NA	NA / 2	
8. 9.	MOEFA Public Address System	NA NA	NA NA	NA •	
17.20	Automatic Sprinkler System			-	
10.		NA	NA	· NA	
	Basement	NA NA	NA NA	NA NA	
	Ground Floor	NA NA	NA NA	NA NA	
	Sprinkler above false ceiling	INA	MO.	INA .	
11.	Internal Hydrants				
	Size of riser/down-comer	NA	NA	NA	
-	Number of hydrants per floor	NA	NA	NA	
	Hose Box	NA	NA	NA	
12.	Yard Hydrants				
	Total number of hydrants	NA	NA	NA	
H	Hose Box	NA	NA	. NA	
13.	Pumping Arrangements			1	
	Ground Level				
-	Ground Level     Discharge of main Pump	NA	NA	NA	
F	➤ Head of Main pump	NA	NA	,NA	
		NA	NA	NA	
	> Number of main pumps	NA	NA	NA NA	
-	> Jockey Pump out put	NA NA	NA NA	NA NA	
-	<ul> <li>Jockey pump head</li> <li>Standby Pump out put</li> </ul>	NA NA	NA ·	NA NA	
H	Standby Pump Head	NA	NA	NA -	
- 1	> Auto Starting/Manual	NA	NA	NA	
	Stopping		<u> </u>		
	> Pump House Access	· NA	NA	NA	
	Terrace level				
-	➤ Discharge of pump	NA	NA	NA NA	
-		NA	NA	NA	
L	➤ Head of the pump		***		
	> Power Supply	NA NA	NA	NA	
14	➤ Auto Starting of pump  Captive Water Storage for fire fighting	NA	NA	NA	
14.			A STATE OF THE STA	1 1	
-	Underground tank capacity	NA	NA	NA NA	
_	> Draw-off connection	NA .	NA NA	NA NA	
	> Fire service inlet	NA	NA	NA NA	
	> Access to tank	NA	NA NA	NA	
15.	Overhead Tank capacity  Frit Signage	NA Paguired	NA Provided	NA MP	
2-CON   5-K	Exit Signage.	Required	Provided	MR	
16.	Provision of Lifts.	8		ti.	
	Pressurization of Lift Shaft	NA	NA	NA	
(4)	Pressurization of Lift lobby	NA	NA	NA	
	Communication In lift Car	NA	NA	NA	
	Fireman's Grounding Switch	NA	NA	NA	
	Lift Signage	NA	NA	NA	
7. S	Standby power supply	NA	NA	NA NA	
8. R	Refuge Area.				
_	D. Total Acces				
-	➤ Total Area  ➤ Location	NA	NA	NA	
1	Location	) NA	NA	NA	

ti	Detector System Panel	NA	-	
	Flow Switch Panel	NA	NA NA	NA
	PA System Panel	NA	NA NA	NA
	Battery backup	NA	NA	NA
	Building Floor Plans	NA	NA	NA
0.	Special Fire Protection System for Protection of special Risks, if any:	NA	NA	NA NA

The fire protection systems provided in the building were tested, checked and found functional at the time of inspection.

Note: Electrical panel under the staircase has to be removed to a safer place or been segregated by fire check door.

Keeping in view of substantial compliance of the minimum standards of fire prevention and fire safety measures as required under DOE circular no. 3298-3398 dated 01/03/2011, it is recommended to grant Fire Safety Certificate.

Apo

Signature of Inspecting Officer Name: Rajeev Kumar Sinha Designation: ADO/B.W.

by Cho /w2)

Do (pp)

CFof Mus

13 81 20m

2 St Onthe Put

rsai f

15/8/4

Dreets lowy of

100 A A & ...