

## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI – 110001

No.F6/DFS/MS/GH/NDZ/2024/315

Dated: .01./082024

## FIRE SAFETY CERTIFICATE

Certified that the Peace Point Guest House located at 8681, D.B.G. Road, Pahar Ganj, New Delhi, comprised of Ground + 04 Upper floors, Ground floor (07 guest rooms + reception), 1st floor to 3rd floor (09 guest rooms at each floor), fourth floor not in use as per undertaking dated 13.11.19, total 34 guest rooms up to third floor only owned/occupied by Peace Point Guest House was earlier granted FSC by this department vide letter No.F6/DFS/MS/GH/2018/NDZ/2021/391 dated 16/09/21. Now, the premise was re-inspected by the officer concerned of this department on 23/07/24 in the presence of Sh. Neeraj Jain and found that the said guest house has deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Residential, Sub Division-A-1 Ground floor (07 guest rooms + reception), 1st floor to 3rd floor (09 guest rooms at each floor) total -34 guest rooms up to third floor only and valid up to the period of three year from the date of issue in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued 01/08/2024 at New Delhi by

DIRECTOR Delhi Fire Service

Copy to:-

1. The Commissioner, North MCD, New Delhi: to ensure the occupancy in the building as per above details.

2. The Addl. Commissioner of Police (Lic), First Floor, P.S. Defence Colony New Delhi.

ID NO. 2024070910666 dated 09/07/24.

3. The Manager, Peace Point Guest House at 8681, D.B.G. Road, Pahar Ganj, New Delhi.

Condition for the validity of fire safety certificate

 All the fire safety arrangements provided therein shall be maintained in good working conditions at all times. This FSC is valid for guest house up to third floor only.

2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the

management.

3. The trained fire fighting staff should be available round the clock.

 The compliance with regards to electrical installation, structural stability, set back area, occupancy and any deviation in construction etc. shall be verified from authority concerned.

5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if

any.

 The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on <a href="https://www.dfs.delhigovt.nic.in">www.dfs.delhigovt.nic.in</a>

The means of escape shall be kept unobstructed / unlocked for unhindered evacuation in case of an emergency.

8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".

9. Any flammable material for interior decoration is prohibited.

INSPECTION REPORT 1. Name & address of the building Peace Point Guest House located at 8681, D.B.G. Road, Pahar Ganj, New Delhi 2. Type of occupancy: -Residential, Sub Division-A-1 Gr. + 04 Upper floors (total 34 Guest rooms) Ground floor (07 guest rooms + reception), 1st floor to 3rd floor (09 guest rooms at each floor), 4th floor (01 staff room) not in use as per affidavit dated 13.11.21 3. Type of case: -Renewal 4. Details of previous FSC: -No. F6/DFS/MS/GH/2018/NDZ/2021/391 dated 16/09/21 5. Fire safety directives No.-N/A 6. Date of inspection: -23/07/24 7. Name of the inspecting officer: -Sh. Ravinder Singh (ADO/CC) 8. Name & designation of officer From the building side: -Sh. Neeraj Jain 9. Year of construction:-1990 10. Applicant's letter No:-ID NO. 2024070910666 dated 09/07/24... Old Case S.No. Minimum Standards on fire Requirement/ Provided at site Remarks Existing fire safety Prevention and fire safety MR/NMR arrangements U/R 33 1. Access to Building N/A 1) Road width N/A N/A 2) Gate width N/A N/A N/A N/A N/A 3) Width of internal road N/A 2. Number, Width Type & Arrangement of Exits A. Number of staircases MR 01 Nos. 01 Nos. 1. Upper floors N/A N/A N/A 2. Basements B. Width of staircase 1.25 mtr. MR 0.80 mtr. 1. Upper floors N/A N/A N/A 2. Basements C. Protection of exits MR Provided Required 1. Fire check door N/A N/A N/A 2. Pressurization N/A N/A D. No. of continuous N/A staircase to terrace N/A N/A N/A E. Width of corridor MR 1.0 mtr. 1.0 mtr. F. Door size Compartmentation 3. N/A N/A N/A 1) Fire check door N/A 2) Sealing of electrical shafts N/A N/A N/A N/A 3) Fire rating of shaft door N/A N/A N/A N/A 4) Water curtain N/A N/A N/A 5) Fire Dampers Smoke Management System 4. N/A N/A N/A 1) Basements Natural/exhaust MR 12 a/c per 2) Upper floors hour Fire Extinguishers

11/29

10 Nos.

ABC & CO2

MR

MR

10 Nos.

ABC & CO2

5.

1) Total numbers

2) Types

N130

	3) ISI marking	Required	Provided	1 Am		
5.	First-Aid Hose Reel	required	Tiovided	MR		
	1) Total number of eachfloor	01	-			
	2) Length of hose reel hose	01		MR		
	3) Nozzle diameter	30 mtr.	30 mtr. /	MR		
7.		05 mm	05 mm	MR		
/•	Automatic Fire Detection & Alarming System					
	1) Type of detectors CO type	Required	Provided /	MR		
	2) Location of main panel	Required	Provided	MR		
	3) Location of repeater panel	N/A	N/A	N/A		
	4) Alternate source of power	Required	Provided	MR		
	5) Hooter's Location	Ground floor	Provided	MR		
8.	MOEFA	Required	Provided			
9.	Public Address System	Required	Provided	MR		
10.	Automatic Sprinkler System	required	Tiovided	MR		
	1) Basement	N/A	N/A	27/1		
	2) Upper floors	N/A		N/A		
	3) Sprinkler above false	N/A	N/A	N/A		
	ceiling	11//1	N/A	N/A		
11.	Internal Hydrants	N. 14				
	1) Size of riser/down-comer	N/A	NT/A			
	2) Number of hydrants per	N/A	N/A	N/A		
	floor	IV/A	N/A	N/A		
	3) Hose box	N/A	NI/A			
12.	Yard Hydrants	IVA	N/A	N/A		
	1) Total number of hydrants N/A					
	2) Hose box	N/A	N/A	N/A		
13.	Pumping Arrangement	IV/A	N/A	N/A		
	1) Ground level	NI/A				
	a) Discharge of main	N/A	N/A	N/A		
	pump	N/A	N/A	N/A		
	b) Head of main pump	N/A	27/4	2		
	c) Number of main pump	N/A N/A	N/A	N/A		
	d) Jockey pump out put	N/A	N/A	N/A		
	e) Jockey pump head	N/A	N/A	N/A		
	f) Stand by pump output	N/A	N/A	N/A		
	) Ci 11		N/A	N/A		
		N/A	N/A	N/A		
	h) Auto starting/Manual stopping	N/A	N/A	N/A		
	2) Terrace level					
		450 I DM	450 7 7 2			
	a) Discharge of pump	450 LPM	450 LPM	MR		
	a) Discharge of pump     b) Head of pump	30 mtr.	30 mtr.	MR		
	a) Discharge of pump     b) Head of pump     c) Power supply	30 mtr. Required	30 mtr.  Provided	MR MR		
	a) Discharge of pump     b) Head of pump     c) Power supply	30 mtr.	30 mtr.	MR		
14	a) Discharge of pump b) Head of pump c) Power supply d) Auto starting of pump	30 mtr. Required Required	30 mtr.  Provided	MR MR		
14.	a) Discharge of pump b) Head of pump c) Power supply d) Auto starting of pump  Captive Water Storage for Fir	30 mtr. Required Required	30 mtr.  Provided	MR MR		
14.	a) Discharge of pump b) Head of pump c) Power supply d) Auto starting of pump  Captive Water Storage for Fir 1) Under ground tank	30 mtr. Required Required	30 mtr.  Provided	MR MR MR		
14.	a) Discharge of pump b) Head of pump c) Power supply d) Auto starting of pump  Captive Water Storage for Fir 1) Under ground tank capacity	30 mtr. Required Required  e Fighting N/A	30 mtr. Provided Provided N/A	MR MR		
14.	a) Discharge of pump b) Head of pump c) Power supply d) Auto starting of pump  Captive Water Storage for Fir 1) Under ground tank capacity a) Draw-off connection	30 mtr. Required Required  e Fighting N/A  N/A	30 mtr. Provided Provided  N/A  N/A	MR MR MR		
14.	a) Discharge of pump b) Head of pump c) Power supply d) Auto starting of pump  Captive Water Storage for Fir 1) Under ground tank capacity	30 mtr. Required Required  e Fighting N/A	30 mtr. Provided Provided N/A	MR MR MR		

5000	capacity				
15.	Exit Signage.	Required	Provided	-	
16.	Provision of Lifts.		Flovided	MR	
	a) Pressurization of lift shaft	N/A	N/A	N/A	
	<ul><li>b) Pressurization of lift lobby</li></ul>	N/A	N/A	N/A	
	c) Communication in lift car	N/A	N/A	N/A	
	d) Fireman's switch	N/A	N/A	N/A	
-	e) Lift signage	N/A	N/A	20.076.00	
17.	Stand by Power Supply	Required	Provided	N/A	
18.	Refuge Area	N/A	N/A	MR N/A	
	Total area location	N/A	N/A	N/A	
19.	Fire Control Room	N/A	N/A	N/A	
	a) Detector system panel	N/A	N/A	N/A	
	b) Flow switch panel	N/A	N/A	N/A	
	c) PA system panel	N/A	N/A	N/A	
	d) Battery backup	N/A	N/A	N/A	
	e) Building floor plan	N/A	N/A	N/A	
20.	Special Fire Protection System for Protection of special Risk, if any:				

The fire protection systems provided in the building were randomly tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the FSC issued vide letter no. F6/DFS/MS/GH/2018/NDZ/2021/391 dated 16/09/21, renewal under rule 35 of the Delhi Fire Service rules 2010, is recommended up to third floor.

Signature of the Inspecting Officer

Name: Ravinder Singh Designation: ADO (CC)

297124

Dycho (moz)

2407/24

29 TH Jaon

Dinecter

89/07/N

Agyl