GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: NEW DELHI - 110001

No F 6/DFS/MS/2024/School/WZ/ 8 60

Dated:/6 /08/2024

FIRE SAFETY CERTIFICATE

Certified that the De Indian Public School located at Pocket-II, Sector-24, Rohini, Delhi-110085 comprised of building Basement + Ground + 03 upper floor owned/ occupied by the DE Indian Public School was granted FSC by this department vide letter No F.6/DFS/MS/2021/School/WZ/864 dated 21.10.2021 for Ground + 02 upper floors. The premises was re-inspected by the officer concerned of this department on 24.07.2024 in the presence of Mrs. Padmini Dubey Ojha (Officiating Principal) and observed that the building all the fire prevention and fire safety arrangements as provided in the premises found in good working condition. The premises have deemed complied with requirements of circular issued by Director of Education letter no 262-362 dated 17.01.2005 and the building/ premise is fit for occupancy "Group B Educational" with effect from 16 08 2024 for a period of three years, in accordance with rule 36 unless under rule 37 or sooner cancelled under rule 40 and subject to compliance of the conditions under rule 38 of Delhi Fire Service Rules, 2010:

DIRECTOR Ph; 011-23414000

Copy to: -

1. The Director, Education, Government of N.C.T of Delhi. Old Sectt. Delhi - 54.

2. The Principal, De-Indian Public School, Pocket-II, Sec-24, Rohini, Delhi-85.

Conditions for the validity of Fire Safety Certificate:

- 1. All the fire safety arrangement provided there-in shall be maintained in good working conditions at all times.
- 2. Loss of life or property due to non functional fire safety measure shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- Any deviation with regard to the construction etc shall be verified by the concerned building sanctioning agency.
- 5. This certificate cannot be treated in any case for regularizations of unauthorized construction.
- 6. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director of Form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six months prior to its expiry".
- 7. The owner / occupier shall submit a declaration every year in form "K" provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on <u>WWW.dfs.Delhigovt.nic.in</u>
- 8. The occupancy of the school activity is restricted up to 2nd floor level only. The occupancy for 3rd floor & basement will only be considered after obtaining approval of building authority only. Failing which FSC shall stand null and void.

INSPECTION REPORT

Name & address of the building: De Indian Public School located at Pocket-II, Sector-24, Rohini,

Delhi-110085.

2. Type of Occupancy : Educational

3. Type of Case : Renewal (Ground + 2 upper floors)

4. Details of Previous NOC : F.6/DFS/MS/2016/School/WZ/860 dated 25.05.2016

5. Fire Safety directives letter No : Director of Education Circular letter no.262-362 dated 17.01.2005

6. Date of inspection : 07.09.2021

7. Name of Inspecting Officer : A.K.Sharma ADO(Rohini)

8. Name and designation of officers

From the building side : Smt. Seema Awasthi (Principal)

9 Year of Construction : 2009 & 2015

S. No.	Applicant's letter No. : Online e-mai Minimum Standards on fire prevention and fire safety U/R 33	DOE Cir.	Provided at site	Remarks MR/NMR
		17.01.2005		
•	Access to building		11	
	Road width	Accessible	Accessible	MR
	Gate width	Accessible	4.5m	MR
	Width of internal road	NA	NA	NA
	Number, Width, Type & Arrangement of	Exits		
	a. Number of staircases			100
	Upper Floors	02	02	MR
	Basements	NA	NA	NA
	b. Width of staircases			
560	Upper Floor	1.5m	1.65m & 1.35m	MR(old case
	Basements	NA	NA	NA
	c. Protection of exits			
	Fire check door	NA	NA	NA
	Pressurization	NA	NA	NA
	d. No. of continuous staircases to terrace	01	02	MR
	e. Width of Corridor	NA	NA	NA
	f. Door Size	NA	NA	NA
3.	Compartmentation		E '51	1 - 3
	Fire check door	NA	NA	NA
	Sealing of electrical shafts	NA	NA	NA
	Fire Rating of shaft door	NA	NA	NA
	Water Curtain Fire Departure	NA	NA	NA
	Fire Dampers	NA	NA	NA
1.	Smoke Management System	· · · · · · · · · · · · · · · · · · ·		
	Basements	30 a/c per hour	NA	NA
	Upper floors	12 a/c per hour	Natural ventilated	MR
5.	Fire Extinguishers		- the	
	Total numbers	15nos.	15nos.	MR
	Types	ABC/CO2	ABC-15	MR
	I\$ marking	ISI marked	Yes	MR
6.	First-Aid Hose Reels			
	 Total numbers on each floor 	Required	Provided	MR
	Length of hose reel hose	30mm	Provided	MR
20	Nozzle diameter	5m	Provided	MR
7.	Automatic fire detection and alarming sys	tem	111	1
	Type of detectors	NA	NA	NA

	Location of Main Panel	NA	NA	N/
	Location of Main Panel Location of Repeater Panel	NA NA	NA NA	N/
	Alternate source of power	NA NA	NA NA	NA.
	Hooters' Location	NA NA	NA NA	NA.
8.	MOEFA	Required	Provided	MR
9.		Required	Provided	MR
10.	Public Address System Automatic Sprinkler System	Required	Tiovided	
10.		NA NA	NA NA	NA
	BasementGround & Upper Floors	NA NA	NA NA	NA NA
	Sprinkler above false ceiling	NA NA	NA NA	NA NA
11.	Internal Hydrants	INA	INA	III
11.	Size of riser/down-comer	100mm	Provided	MR
A	Number of hydrants per floor	02	Provided	MR
	Hose Box	02	Provided	MR
12.	Yard Hydrants	02	Provided	MIK
12.	Total number of hydrants	NA	NIA	NTA.
	Hose Box	NA NA	NA NA	NA NA
13.	Pumping Arrangements	NA	NA	NA
201	Ground Level	NA	NA	374
	Discharge of main Pump		NA	NA
	 Head of Main pump 	NA NA	NA NA	NA
	Number of main pumps	NA	NA	- NA
	Jockey Pump out put	NA 1801	NA	NA
	> Jockey pump head	180lpm	Provided	MR
- 100	Standby Pump out put	40m	Provided	MR
200	➤ Standby Pump Head	NA NA	NA	- NA
	> Auto Starting/Manual Stopping	NA NA	NA	NÀ
	> Pump House Access	NA	NA	NA
		NA	NA	NA
	Terrace level	1='= 1' -1	T11 1	
	Discharge of pumpHead of the pump	900lpm	900lpm	MR
	> Power Supply	40m	40m	_
	Auto Starting of pump	Required	Provided	MR
4. (272 271 1	Required	Provided	MR
	Captive Water Storage for fire fighting		- 4	
	 Underground tank capacity Draw-off connection 	NA	NA	NA
	Fire service inlet	NA	NA	NA
	Access to tank	NA	NA	NA
8	 Overhead Tank capacity 	NA	NA	NA
. E	xit Signage.	5,000ltr	5,000ltr	MR
U. P. Carrie	rovision of Lifts.	Required	Provided	MR
			- 1	ATEC CONTACT
	Pressurization of Lift Shaft Pressurization of Lift Shaft	NA	NA	NA
	 Pressurization of Lift lobby Communication In lift Car 	NA	NA	NA
	Fireman's Grounding Switch	NA	NA	NA NA
	Lift Signage	NA	NA	
		NA	NA NA	NA
	andby power supply	NA	NA NA	NA
Re	fuge Area.		IVA	NA
	> Total Area	NA	N	
	> Location	NA	NA	NA
		11/1	NA	NA

Fire Control Room			N#)
Detector System Panel Flow Switch Panel	NA		, X
Flow Switch Panel PA System Panel	NA	NA	NA
PA System Panel Battery backup	NA	NA	NA
Building Floor Plans	NA	NA	NA
Special Fire D	NA	NA	NA
Special Fire Protection System for Protection of special Risks, if any:		NA NA	NIA
The fire protection	INA	NA	NA
The fire protection systems provided in the base time of inspection. Keeping in view the satisfactory compand fire safety required as stipulated in direct NOC issued vide letter of even no F.6/DFS/M under rule 37 of the Delhi Fire Service Rules,	liance of the	necked and found funct	ional at

Atto (w2) Prosent of claring of two floors.

Apploisant submitted the declaration

Refronce on forms.

Deto(w2)

Deto(w2)

ARSO Rohimi

For letter is put up for visit poursol and Organitus places

Differ (m2) 21/10/2021 Chyc