## TIONAL CAPITAL TERRITORY OF DELHI DOUARTERS: DELHI FIRE SERVICE, NEW DELHI – 110001

No. F6/DFS/MS/GH/NDZ/2024/ 349

Dated: 27/08/2024

Certified that the M/s Naaz Guest House situated at 734, Kabari Bazar, Jama Masjid, Delhi - 06, comprised of Ground + 4 upper floors: Ground floor - (commercial), 1st floor - (12 guest rooms + 01 staff room + reception), 2<sup>nd</sup> floor - (10 guest rooms + 02 store rooms), 3<sup>rd</sup> floor -(05 guest rooms + 04 staff rooms) & 4th floor- (not in use), total 27 guest rooms was granted FSC by this department vide letter no. F6/DFS/MS/GH/NDZ/2021/74 dated 05.02.2021. The building/premises was re-inspected by officer concerned of this department on 12.08.2024 in presence of Mohd. Danish (Owner) and found that the building has deemed complied with the fire prevention and fire safety requirements in accordance with Rule 33 of Delhi Fire Service Rules, 2010. The owner has submitted an affidavit on 12.11.2019 stating not to use any floor above third floor for any purpose. Accordingly, the premises is fit for occupancy of (Group-A-1) "Residential", 1st floor - (12 guest rooms), 2nd floor - (10 guest rooms) & 3rd floor - (05 guest rooms) for total 27 guest rooms upto 3rd floor only with effect from ... 27. 0.8. 2024.. for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under rule 40 and subject to conditions under rule 38 of Delhi Fire service Rules, 2010 subject to condition printed below.

Issued on .....27/08/2024 ......at New Delhi by

Tel: 011-23414000

## Copy to:-

- 1. The Commissioner, MCD:- to kindly ensure the occupancy as detailed above & deviation, if any.
- 2. The Joint Commissioner of Police (Licensing), 1st Floor, Police Station Defence Colony, New Delhi. w.r.to ID No. 2024072411496 dated 24.07.2024.
- 3. The Licensee, M/s Naaz Guest House at 734, Kabari Bazar, Jama Masjid, Delhi 06.

## Conditions for the validity of fire safety certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".
- 8. Any change in the occupancy shall be intimated to this Deptt. and approval shall be obtained thereto before occupancy of the same.
- 9. The occupancy of above 3<sup>rd</sup> floor not allowed as per clause 7.31 in UBBL-2016.

|      |                                  | INSPEC  | CTION REPORT  |                      |                |  |
|------|----------------------------------|---|---|----------------------|----------------|--|
|      | Nome                             | & address of the building                         | M/a Nooz Cuest  | House at 734, Ka     | bari Bazar     |  |
|      | Ivaille o                        | x address of the building                         |   |                      |                |  |
|      | 20.11                            |   | Jama Masjid, Delhi - 06.  |                      |                |  |
|      | Buildir                          | ng is comprised of                                | Ground + 04 upper floors  |                      |                |  |
| 1    |                                  |   | Ground floor – (commercial use)  1 <sup>st</sup> floor – (12 guest rooms + 01 staff room -                                      |                      |                |  |
| 1    |                                  |   | 1 <sup>st</sup> floor - (12 g   | guest rooms + 01 si  | all loom       |  |
|      |                                  |   | reception)  |                      |                |  |
| -    |                                  |   | 2 <sup>nd</sup> floor - (10 gu  | est rooms + 02 store | rooms)         |  |
| . 1  |                                  |   | 3 <sup>rd</sup> floor – (05 guest rooms + 04 staff rooms) 4 <sup>th</sup> floor- (not in use as per affidavit dated 12.11.2019) |                      |                |  |
|      |                                  |   |   |                      |                |  |
|      |                                  |   |   |                      |                |  |
| 2    | Type of occupancy                |   | Residential Group A-1   |                      |                |  |
| 3    |                                  |   | n 1/ald age   | 2)                   | 7 00 0001      |  |
| 2    | Type of case                     |   | F6/DFS/MS/GH/   | NDZ/2021/74 dated (  | )5.02.2021     |  |
| 5    | Details of previous FSC          |   | Nil   |                      |                |  |
| 6    | Fire safety direction letter no. |   | 12.08.2024  |                      |                |  |
| 7    | Date                             | of inspection of the inspecting officers          | Sumit Kumar, AI   | OO (SPM)             |                |  |
| 8    | Name                             | of the designation of                             | 11/0  | wner)                |                |  |
| 9    | Name                             | of the designation of                             | ATTENDED STORY  |                      |                |  |
|      | office                           | er from the building side                         | Old   |                      | . 106 lete     |  |
| 10   |                                  | of construction                                   | Old Online application no. 2024072411496 date   |                      |                |  |
| 11   | Appl                             | icant's letter no.                                | 24.07.2024  |                      |                |  |
|      | 1000                             | a. lands on fire                                  | Requirement/  | Provided at Site     | Remarks<br>MR/ |  |
| S.No | Mini                             | mum Standards on fire ention and fire safety      | Existing fire   |                      | NMR            |  |
|      | Prev                             | irements U/R 33                                   | safety -  |                      | 141/22         |  |
|      | requ                             | III cincin di 722 03                              | arrangements  |                      |                |  |
| 1    | Acc                              | ess To Building:                                  | Tara  | 08 m                 | NA             |  |
|      |                                  | d width   | NA  | NA NA                | NA             |  |
|      | Gate                             | width   | NA<br>NA  | NA NA                | NA             |  |
|      | Wid                              | th of internal road                               | angement of Exits:  |                      |                |  |
| 2    | Nun                              | th of internal road<br>nber, Width, Type and Arra | angement of   |                      |                |  |
|      | A                                | Number of staircases                              | 01 no.  | 01 no.               | MR             |  |
|      |                                  | a Upper floor                                     | NA  | NA                   | NA             |  |
|      |                                  | b Basement Width of staircases                    |   |                      |                |  |
|      | В                                | a Upper floor                                     | 80 cms.   | 96 to 140 cms.       | MR             |  |
|      |                                  | b Basement  | NA  | NA                   | NA             |  |
|      | C                                | Protection of exits                               |   | D de d               | MR             |  |
|      |                                  | a Fire check door                                 | Required  | Provided<br>NA       | NA             |  |
|      |                                  | b Pressurization                                  | NA NA   | NA<br>NA             | NA             |  |
|      | D                                | No. of continuous staircase                       | s NA  | IM                   | Danies III     |  |
|      |                                  | to terrace Width of corridor                      | NA  | NA                   | NA             |  |
|      | E                                | Door size   | 1.0 mtr.  | 1.0 mtr.             | MR             |  |
| 1    | F                                | mpartmentation:                                   |   |                      |                |  |
| 3    | A Fire check door                |   | NA  | NA                   | NA             |  |
|      | B                                | Sealing of electrical shafts                      | NA  | NA                   | NA             |  |
|      | C                                | Fire rating of shaft door                         | NA  | NA                   | NA             |  |
|      | D                                | Water curtain                                     | NA  | NA                   | NA<br>NA       |  |
|      | E                                | Fire dampers                                      | NA  | NA                   | NA             |  |
| 4    | Sm                               | oke Management System:                            | 10 A CIPIT  | Provided             | MR             |  |
|      | A                                | Upper floors                                      | 12 ACPH<br>NA   | NA NA                | NA             |  |
|      |                                  | Basements   |   |                      |                |  |

| 5        | Fire E         | xtinguisher:   | 06 nos.  | 06 nos.           | M                  |  |  |  |  |
|----------|----------------|--|--|-------------------|--------------------|--|--|--|--|
| Ÿ        | A              | Total numbers  |  |                   | M                  |  |  |  |  |
|          | В              | Types  | CO <sub>2</sub> & ABC  |                   | ,50,0.00           |  |  |  |  |
|          | C              | ISI marking  | Required   | Provided          | M                  |  |  |  |  |
| <u> </u> | 0.23           | Aid-Hose Reels:  |  |                   |                    |  |  |  |  |
| _        | A              | Total numbers of each  | 01 no.   | 01 no.            | M                  |  |  |  |  |
|          | A              | floor  |  |                   |                    |  |  |  |  |
|          | В              | Length of hose reel hose   | 30 m   | 30 m              | M                  |  |  |  |  |
|          | C              | Nozzle diameter  | 05 mm  | 05 mm             | MI                 |  |  |  |  |
|          |                | natic Fire Detection And Alar  | ming System:   |                   |                    |  |  |  |  |
| 7        |                | Type of detectors (CO  | Required   | Provided          | MF                 |  |  |  |  |
|          | A              | type)  | 1  |                   |                    |  |  |  |  |
|          | В              | Location of main panel   | Required   | Provided at floor | 1 <sup>st</sup> MR |  |  |  |  |
|          | С              | Location of repeater   | NA   | NA                | NA                 |  |  |  |  |
|          | D              | Alternate source of power  | Required   | Provided          | MR                 |  |  |  |  |
|          | E              | Hooters  | Required   | Provided          | MR                 |  |  |  |  |
| 8        | MOEI           | AT IN CONTRACTOR OF THE PROPERTY OF THE PROPER | NA   | NA                | NA                 |  |  |  |  |
| 9        | AWAY RESERVED  | Address System:  | Required   | Provided          | MR                 |  |  |  |  |
| 10       |                | natic Sprinkler System:  |  |                   |                    |  |  |  |  |
| 10       | A              | Basement   | NA   | NA                | NA                 |  |  |  |  |
|          | В              | Upper floor  | NA   | NA                | NA                 |  |  |  |  |
|          | C              | Sprinkler above false  | NA   | NA                | NA                 |  |  |  |  |
| 11       | Intern         | ceiling  | *  | 81                |                    |  |  |  |  |
| **       | A              | size of riser/down-comer   | NA   | NA                | NA                 |  |  |  |  |
|          | В              | Number of hydrants per floor   | NA   | NA                | NA                 |  |  |  |  |
|          | C              | Hose box   | NA   | NA                | NA                 |  |  |  |  |
| 12       | Yard 1         | Yard Hydrants:   |  |                   |                    |  |  |  |  |
|          | A              | Total number of hydrants   | NA   | NA                | NA                 |  |  |  |  |
|          | В              | Hose box   | NA   | NA                | NA                 |  |  |  |  |
| 13       | Pumpi          | ing Arrangements:  |  | . T. A. C. C.     | 5.15.0             |  |  |  |  |
|          | A Ground level |  |  |                   |                    |  |  |  |  |
|          | a)             | Discharge of main pump   | NA   | NA                | NA                 |  |  |  |  |
|          | b)             | Head of main pump  | NA   | NA                | NA                 |  |  |  |  |
|          | c)             | Number of main pumps   | NA   | NA                | NA                 |  |  |  |  |
|          | d)             | Jockey pump out put  | NA   | NA                | NA                 |  |  |  |  |
|          | e)             | Jockey pump head   | NA   | NA -              | NA                 |  |  |  |  |
|          | f)             | Standby pump out put   | NA   | NA                | NA                 |  |  |  |  |
|          | g)<br>h)       | Standby pump head  | NA   | NA                | NA                 |  |  |  |  |
|          | 11)            | Auto starting /manual stopping   | NA -   | NA                | NA                 |  |  |  |  |
|          | i)             |  | NA   | NA                | NA                 |  |  |  |  |
|          | В              | Terrace level  |  | IVA               | NA                 |  |  |  |  |
|          | a)             | Discharge of pump  | 225 LPM  | 225 LPM           | MR                 |  |  |  |  |
|          | b)             | Head of the pump   | 1,1774   | 40 m              | MR                 |  |  |  |  |
|          | c)             | Power supply   | Control of the Contro | Provided          | MR                 |  |  |  |  |
|          | d)             | Auto starting of pump  |  | Provided          | MR                 |  |  |  |  |

| 14 | Captive Water Storage For Fire Fighting:  A Underground tank capacity NA NA NA |   |                   |             |          |  |  |
|----|--|---|-------------------|-------------|----------|--|--|
|    | B  | Draw-off connection                                       | NA                | NA          | NA       |  |  |
|    | c  | Fire service is a   | NA                | NA          | NA       |  |  |
| ŀ  | D  | Fire service inlet  | NA                | NA          | NA       |  |  |
|    | _  | Access to tank  | NA                | NA          | NA       |  |  |
| -  | E  | Overhead tank capacity                                    | 2,500 ltrs.       | 2,500 ltrs. | MR       |  |  |
| 15 |  | t Signage:  | Required          | Provided    | MR       |  |  |
| 16 | Provision of Lifts:  |   |                   |             |          |  |  |
|    | A  | Pressurization of lift shaft                              | NA                | NA          | NA       |  |  |
|    | B  | Pressurization of lift lobby                              | NA NA             | NA NA       | NA<br>NA |  |  |
|    | C  | Communication in lift car                                 | NA                | NA NA       | NA<br>NA |  |  |
| N  | D  | Firemen's grounding switch                                | NA NA             | NA NA       | NA<br>NA |  |  |
|    | E  | Lift signage  | NA NA             | NA NA       | NA NA    |  |  |
| 17 | Sta  | andby Power Supply:                                       | Required          | Provided    | MR       |  |  |
| 18 | Re   | Refuge Area:  |                   |             |          |  |  |
|    | A  | Total area  | NA                | NA          | NA       |  |  |
|    | B  | Location  | NA                | NA NA       | NA       |  |  |
| 19 | Fire Control Room:   |   |                   |             |          |  |  |
|    | A  | Detector system panel                                     | NA                | NA          | NA       |  |  |
|    | В  | Flow switch panel   | NA                | NA          | NA       |  |  |
|    | C  | Pa system panel   | NA                | NA NA       | NA       |  |  |
|    | D  | Battery backup  | NA                | NA          | NA       |  |  |
|    | E  | Building floor plans                                      | NA                | NA          | NA       |  |  |
| 20 | SI   | pecial Fire Protection Systems I<br>pecial Risks, If Any: | For Protection of | NA          | NA       |  |  |

The fire protection systems provided in the building were tested, checked at randomly and found functional at the time of inspection.

Shortcomings communicated vide letter No.F6/DFS/MS/GH/NDZ/2024/234 dated 16/05/2024 has been rectified.

Keeping in view of the deemed compliance of minimum standards of fire prevention and fire safety measures as required under the Rules, the FSC issued vide letter No F6/DFS/MS/GH/NDZ/2021/1/4 dated 05.02.2021 is recommended to be renewed upto 3<sup>rd</sup> floor only, under Rule 35 of the Delhi Fire Service Rules 2010.

Signature of the Inspecting Officer

Name

Sumit Kumar

Designation ADO (SPM)

1/16/14

Dych kroz

LIVE 24

Sirrectar My

1704302