



## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE, NEW DELHI-110001

No. F.6/DFS/MS/School/2024/SZ/ 836

Dated: 27/08/2024

## FIRE SAFETY CERTIFICATE

Certified that the **Sri Ram Shiksha Vidyalaya** located at Plot No-357, Village Kapashera, New Delhi-110037 (School ID: 1821264), comprised of ground plus two upper floors, owned/occupied by Sri Ram Shiksha Samiti (Regd.), has already been issued Fire Safety Certificate by this department vide letter No. F.6/DFS/MS/School/2020/SZ/397 dated 05/10/2020. The school premise was re-inspected by the officer concerned of this department on 09/08/2024 in the presence of Ms. Anju Bala (Principal) and found that the said school building have deemed complied with the fire prevention and fire safety requirement in accordance with rule 33 of Delhi Fire Service Rules, 2010 and that the building is fit for occupancy class **Group-B** (Educational) with effect from 27/08/2024 for a period of **three years** in accordance with rule 36 unless renewal under rule 37 or sooner cancelled under rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

Issued on 27/08/2024 at New Delhi by

DIRECTOR
DELHI FIRE SERVICE

Copy to: -

 The Principal, Sri Ram Shiksha Vidyalaya located at Plot No-357, Village Kapashera, New Delhi-110037

2. The Director of Education, Govt. of NCT of Delhi, Old Secretariat, New Delhi-110054

## Conditions for the validity of Fire Safety Certificate:

- 1. All the means of escape / entry / exit shall be kept free from any obstruction.
- 2. All the fire safety arrangement provided therein shall be maintained in good working conditions at all times.
- 3. Any loss of life or property due to non-functional fire safety measure shall be at the responsibility of the management.
- 4. All the staff members must know the correct method of operation of firefighting system.
- 5. This fire safety certificate may not in any way be treated as regularization (Clause 2.8 of UBBL-2016) of unauthorized construction or Alteration (Clause 1.4.3. of UBBL-2016), if any.
- 6. The owner/occupier shall submit a declaration every year in form "K" provided in the first schedule of Delhi Fire Service Rules 2010. The foam is available on <a href="www.dfs.delhigovt.nic.in.">www.dfs.delhigovt.nic.in.</a>
- 7. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule37] along with a copy of this Certificate, six months prior to its expiry".

	INSPECTION	ON REPORT		No 357	
1.	Name & address of the building	Sri Ram Shiksha Vidyalaya at Plot No. 357, Village Kapashera, New Delhi–110037 (School ID: 1821264)			
2.	Type of Occupancy	Educational Group-B (School)			
3.	Building Comprised of	Ground plus two upper floors.			
4.	Type of Case				
5.		F6/DFS/MS/School/2020/SZ/397 Dt. 05/10/2020			
6.	Details of previous NOC No.	Nil		L. P.	
-	Fire Safety directives Letter No.	09/08/2024			
7.	Date of inspection	ADO (SJ)			
8.	Name of the Inspecting Officer	Ms. Anju Bala (Principal)			
9.	Name and designation of Officer from the building side				
10.	Year of Construction	1 1 25/0/1/11/4 IIII OUGH			
11.	Applicant's letter No	Outdoor Diary No. 4398 dated 251			
S. No.	Minimum standards on fire	Old FSC	Provided at site	MR/NMR	
o. 140.	prevention and fire safety U/R 33	Requirements	IVIIG		
1.	Access of building		Approachable	MR	
1.	Road width	Required	4.5m	NA	
	Gate width	NA	NA	NA	
	Width of internal road	NA	NA		
	Number, width, Type & Arrangements	of exits			
2.	· C t-i-conne			MR	
	500	02 Nos	02 Nos	NA	
	Upper floors	NA	NA	IVA	
	Basements	har eld	Jan 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	1 MD	
	b. Width of staircases	1.5m	1.5m (each)	MR	
	Upper floors	NA	NA NA	NA	
100	Basements	The second secon	II / estatu E		
	c. Protection of exits	NA	NA	NA	
	<ul> <li>Fire check door</li> </ul>	NA	NA	NA	
	<ul> <li>Pressurization</li> </ul>		Two	MR	
all and	d. No of continuous staircase to terrace	One	2m	NA	
	Width of Corridor	1.5m	Provided	MR	
187	f. Door Size (Classroom / MP Hall)	1m / 1.2m	Tiovided		
3.	Compartmentation		NA	NA	
J	Fire check door	NA	NA NA	NA	
11	Sealing of electrical shafts	NA		NA	
100	Fire Rating of shaft door	NA	NA NA	NA	
1	Water Curtain	NA	NA	NA NA	
13	• Fire Dampers	NA	NA	INA	
-	Smoke managements System			NA	
4.	Basements	NA	NA		
	Upper floors	NA	NA	NA	
5.	Fire Extinguishers	saledol To back	10 NI	MR	
J.	Total numbers	10 Nos	10 Nos	MR	
	• Types	ABC/ CO <sub>2</sub>	ABC & CO <sub>2</sub>		
	ISI marking	ISI marked	Provided	MR	
6	First-Aid Hose Reels				
6.	Total numbers on each floor	One	Provided	MR	
	Length of hose reel hose	30m	Provided	MR	
- 1	Nozzle diameter	5mm	Provided	MR	



7.	Automatic fire detection and alarming	system		
grafi	Type of detector	NA	NA	NA
	Location of Main Panel	NA	NA	NA
	Location of Repeater Panel	NA	NA	NA
	Alternate source of power	NA	NA	NA
	Hooters' Location	NA	NA	NA
0	0.000000	NA	NA	NA
8.	MOEFA  D. His Address System	NA	NA	NA
9.	Public Address System		-	
10.	Automatic Sprinkler System	NA	NA	NA
	Basements	NA	NA	NA
	Upper Floor     It is also sailing.	NA	NA	NA
W-74-	Sprinkler above false ceiling  Literal Hydronts			
11.	Internal Hydrants  • Size of riser/down- comer	- NA	NA	NA
		NA	NA	NA
	Number of hydrants per floor	NA	NA	NA
10	Hose Box  Yard Hydrants		<del> </del>	1111
12.	Total number of hydrants	NA	NA	NA
	Hose Box	NA	NA	NA
12	Pumping Arrangements			2.55
13.		Vient some	and the second	
	20 - 10 - 10 - 10 - 10 - 10 - 10 - 10 -	NA	NA	NA
	<ul><li>Discharge of main pump</li><li>Head of main pump</li></ul>	NA NA	NA	NA NA
	> Number of main pumps	NA NA	NA NA	NA NA
	> Jockey pump out put	NA NA	NA NA	
	> Jockey pump out put > Jockey pump head	NA NA		NA
	Standby Pump out put		NA	NA
	Standby Pump Head	NA NA	NA	NA
	> Auto Staring/Manual stopping	NA NA	NA	NA
	> Pump House Access	NA NA	NA	NA
		NA	NA	NA
	Terrace level     Discharge of pump	450 1 0) 4	450 7 75 7	
	> Head of the pump	450 LPM 40m	450 LPM	MR
	Power supply	Required	Provided Provided	MR MR
3 110	➤ Auto starting of pump	Required	Provided	MR
14.	Captive water Storage for fire fighting		TIOVIGO	IVIK
	<ul> <li>Underground tank capacity</li> </ul>	NA	NA	NA
	> Draw of connection	NA	NA	NA
	Fire service inlet	NA	NA	NA
	Access to tank	NA	NA	NA
15	Overhead Tank capacity  Evit St.	10,000 Ltrs	Provided	MR
16.	Exit Signage Provision of Life	Required	Provided	MR
	Provision of Lifts  Pressurization of Life Signature		21011000	IVIK
	> Pressurization of Lift Shaft > Pressurization of U.S. L. L.	NA	NA	NA
	<ul> <li>Pressurization of lift lobby</li> <li>Communication in lift Car</li> </ul>	NA	NA	NA
	Fireman's Grounding Switch	NA	NA	NA
	➤ Lift Signage	NA	NA	NA
7.	Standby power supply	NA	NA	
8.	Refuge Area	NA	NA NA	NA NA
	> Total area	H CHI.	INA	NA
	Location	NA	NIA	
	Soution	NA	NA	NA
	BA		NA	NA

19.	Fire control room		NA	NA
	> Detector system panel	NA	200.00	NA
	<ul> <li>➢ Flow Switch Panel</li> <li>➢ PA System Panel</li> <li>➢ Battery backup</li> <li>➢ Building Floor Plans</li> </ul> Special Fire Protection systems for	NA	NA NA NA	NA
		NA		NA
		NA		NA
		NA NA		NA NA
20.		NA	NA	

The fire protection systems provided in the building/premises were checked, tested at random and found functional at the time of inspection. The shortcomings communicated vide this department letter No. F.6/DFS/MS/School/2024/SZ/14 dated 17/01/2024 found complied,

Keeping in view of the deemed compliance of the minimum standards on fire prevention and fire safety measures as required under the rule, the fire safety certificate issued vide letter No. F.6/DFS/MS/School/2020/SZ/397 dated 05/10/2020, renewal under rule 37 of the Delhi Fire Service Rules, 2010 is recommended.

Accordingly, DFA is put up for approval and signature please.

Signature of the Inspecting Officer
Name: Santosh Kumar

Designation: ADO (SJ)

Sineter / 19/4- Apylos

Sir, F.T weer is purply for your sing pl

fruman

June 124

Drestor My 8/8/18