Dated: 02/09/2024



No. F6/DFS/MS/2024/GH 357

FIRE SAFETY CERTIFICATE

Issued on 92, 2024. at New Delhi by.

Copy to:

 The Joint. Commissioner of Police (Lic), 1st Floor, Licensing Unit, Police Station, Defence Colony, New Delhi.

2. The Executive Engineer (Building), MCD, Civic Centre, Minto Road, New Delhi for information w.r.t. the use of the basement.

3. The Manager, M/s Hotel Swisston Palace Located at Ground, 1st, 2nd & 3rd floor 17A/18, WEA Karol Bagh, New Delhi-110005.

Condition for the validity of fire safety certificate

1. 4th floor shall not be used for any purpose as undertaking given by owner.

2. The staircase at terrace level shall be kept open & free from lock and key & all the exit shall be clear from any obstruction otherwise the FSC shall be null & void

3. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.

4. Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.

5. The trained staff should be available round the clock.

- 6. Any deviations w.r.t. construction shall be verified by the concerned building sanctioning agency.
- 7. The certificate may not be treated in any case for the regularization of the unauthorized construction, if any.

8. Basement strictly shall be used as per BBL.

- 9. The owner/ occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its expiry.
- 10. The owner/occupier shall submit a declaration every year in the form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on www.dfs.delhigovt.nic.in

INSPECTION REPORT

1. Name & address of the building: M/s Hotel Swisston Palace Located at Ground, 1st, 2nd & 3rd floor 17A/18, WEA Karol Bagh, New Delhi-110005.

2. Type of Occupancy

:Lodging or rooming "A-1"

3. Type of Case: Renewal (Running at Ground, 1st, 2nd & 3rd floor in a building comprised of Basement(Have separate entry/ exit), Ground + 4 Upper Floors & 01 office with staff room at 4th floor/terrace(Now vacant)

4. Details of previous NOC: F6/DFS/MS/GH/SZ/2021/412, dated 23/09/21

5. Fire Safety directives Letter No.: Nil

6. Date of inspection

7. Name of the Inspecting Officer: ADO (DWK)

8. Name and designation of Officer

from the building side

: Sh. Rahul Mishra (Manager)

9. Year of Construction

: Before 2001

10. Applicant's letter No.

: 2024081012502, dated 10/08/2024

S No	Minimum standards on fire prevention and fire safety U/R 33		As per N/34, 3 N/35 & N/36			Provided at site		Remarks MR/NMR		
1.	Access of building	200	†							
	Road width	6 n	ntr Pro		Prov	ovided .			MR	
	Gate width	NA							NA	
	Width of internal road	NA	F	NA					NA	
2.	Number, width, Type & Arrangements of exits									
	a. Number of staircases			T						
	Upper floors	01	4		01		MR (Being old ca		case)	
	Basements	01			01					
	b. Width of staircases	A its amount of the control of the c							· case)	
	Upper floors	Old case		1.25	m	77	MR (Being o	old case)	
	Basements	Old	case	1.15m			MR (Being o			
	c. Protection of exits									
	 Fire check door 	NA NA				7.11.19			NA	
	 Pressurization 	. NA				NA			NA	
1 7	d. No of continuous	01			01				MR	
	staircase to terrace									
	e. Width Of Corridor f. Door Size		1.0m		1.18m		MR (Being old ca		case)	
			Old case		0.80 m		MR (Being old			
3.	Compartmentation		x I							
	 Fire check door 	NA				NA			NA	
	Sealing of electrical shafts	Required			Sealed		MR			
	Fire Rating of shaft door	NA NA				NA	<u> </u>	E.	NA	
	Water Curtain					NA			NA	
	Fire Dampers	NA				NA			NA	

N/42

.	Smoke	managements System	er i								7-28
	•	Basements	30	a/c	per h	our	Pro	vide	ed		MF
-		Upper floors		_	per h		Pro				M
	Eins E		12 0	ar C	per ii	oui	110	714			
•	rire E	xtinguishers	163	N.T.	_	-	-+	Dec	vided		MR
	•	Total numbers	161					-	040300000000000000000000000000000000000	C	MR
	•	Types			¿ CO	2		CC	2 & AB	<u> </u>	
	•	IS marking	Rec	luir	ed			Pro	vided		MR
j.	First -	- Aid Hose Reels			Y						
	•	Total numbers on each		0	1			Pro	vided		MR
		floor	DES	2/	0 mtr	¥)	-	Dro	vided		MR
	•	Length of hose reel hos	e	1115	MM				vided		MR
	•	Nozzle diameter					—Т,	110	Viucu	35	1,11
7.	Autor	natic fire detection and a	larmii	ng s	syster	n			Provide	ad .	MR
	•	Type of detectors					ectors	-	Provide		MR
. 8		Location of Main Pane			_	uire	1	-	NA	eu	NA
_	•	Location of Repeater P			NA		ı [T	00	set 82.5	KMA	MR
	•		ower			uirec			Set 62.3	KVA	NA NA
	•	Hooters' Location			NA		N	A	1-(14)		
8.	MOE		Reg	uir	-	DOLLAR BANK	vided				MR
9.	Publi	c Address System	Req	uire	ed	Prov	rided		- CAR		MR
10.	Auto	matic Sprinkler System							100		1
	•	Basements	Reg		ed			-	rovided		MR
	•	Upper Floor	NA					-	Α		NA
		Sprinkler above false	NA					N	Α		NA
		ceiling									
11.	Inter	nal Hydrants:					A. N		883		
	IEÿ ĕ	Size of riser/down-con	ner		NA			N	A		NA
	•	Number of hydrants pe	r floo	r	NA		¥	N	A		NA
	•	Hose Box		Ì	NA			N	211/02/5		NA
12.	Yard	Hydrants					17.7			79	
	•	Total number of hydrar	nts		NA	8		N.	A		NA
	•	Hose Box		Ī	NA		6	N.	A		NA
13.	Pum	ping Arrangements:								1	
	•	Ground Level								1 Se	
	•	Discharge of main pum	T =	NA				N.	A		NA
	>			NA				N.	A		NA
	>			NA				N.	1.73	1 6	NA
100		Jockey pump out put	-	NA			41 ,	N.			NA
	2			NA				N.	5.50.0	1	NA
	1 SE	Standby Pump out putStandby Pump Head		NA			4	N.			NA
		Auto Staring/Manual		NA		-	1	N.			NA
		stopping		NA				N.	A		NA
	7	Pump House Access	4	NA				NT.	A		
		Terrace level	-	TAN	-	_		N	A	W - 1	NA
		Discharge of pump	- 1	450	lpm		Provi	do 4			
	112	Head of the pump			mtrs		Provi			MR	
	100	Power supply	-		quired		Provi			MR	
	,	Auto starting of pump			uired		Provi			MR	6
						1	1041	ueu		MR	·
								4			
*										1 -	
1		V-o			~						1

N/W

	Under ground tank capacity	NA	X	NA	NA				
	> Draw off connection	NA		NA	NA				
	Fire service inlet	NA		NA	NA				
1	Access to tank	NA		NA	NA MR				
	Overhead Tank capacity	Old	case	5000 ltr					
15	Exit Signage	Regi	ired	Provided	MR				
16.	Provision of Lifts								
4	Pressurization of Lift St	naft	NA	NA	NA				
	Pressurization of lift lob	Tessurization of fill loopy		NA	NA				
	Communication in lift (Car	NA	NA	NA				
	Fireman's Grounding Switch		NA	NA	NA				
	➤ Lift Signage	▶ Lift Signage			MR				
17.	- J F - Wez Buppij		Required	Provided	MR				
18.	Refuge Area								
	> Total area		NA	NA	NA				
10	> Location		NA	NA .	NA				
19.	Fire control room								
	Detector system panel	NA		NA	NA				
	Flow Switch Panel	NA		NA	NA NA				
	> PA System Panel	NA	4	NA					
	 Battery backup Building Floor Plans N 		uired	Provided	MR				
	➤ Building Floor Plans		NA	NA					
20.	Special Fire Protection System Protection of special Risks, if	s for any;	NA	NA	NA				

The fire protection systems provided in the building were test checked and found actional at the time of inspection.

In view of the deemed compliance of minimum standards on fire prevention and fire ety as required under the rules the FSC issued vide letter No. F6/DFS/MS/GH/SZ/2021/412, ted 23/09/21 renewal under Rule 37 of the Delhi Fire Service Rules 2010 is recommended. If proved the FSC may be issued.

Hote: Photographs of Understahing aign placed at cl

Signature of the Inspecting Officer

Name: Sh. Udaivir Singh Designation : ADO (DWK)

Color Malely

Directory Din

Whooded .