-

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE, CONNAUGHT PLACE

NEW DELHI

No. F6/DFS/MS/SZ/2024/EH/29 2

Dated: 09 /09/2024

FIRE SAFETY CERTIFICATE

Certified that M/s Bikanervala Foods Pvt. Ltd, Located at Ground Floor & First Floor, Plot No. 10, Sector-12 A, Dwarka, New Delhi in a building comprised of Basement+ Ground +03 Upper Floors, but the restaurant is runni1ng at Ground and 1st floor was issued FSC vide Letter no. F6/DFS/MS/SZ/2021/218, dated-08/09/2021, The premises was re inspected by the officers concerned of this department on 03-09-2024 in the presence of Sh. Chunnilal (Manager) & Sh. Varun (Employee) and found that the said building have deemed complied with the fire prevention and fire safety requirements in accordance with Rule 33 of the Delhi Fire Service Rule, 2010 and that the premises is fit for occupancy class "Assembly Building" Group D(At Ground & 1st Floor Only) with effect from 6 9 / 2021 for a period of three years in accordance with rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under Rule 38 of the Delhi Fire Service Rules, 2010.

Issued on 19, 109, 2024 at New Delhi by.

(Atul Garg) Director

Delhi Fire Service

Copy to:

- M/s Bikanervala Foods Pvt. Ltd , Located at Ground Floor & First Floor, Plot No. 10, Sector-12 A, Dwarka, New Delhi
- 2. The Executive Engineer (Building), MCD, Civic Centre, Minto Road, New Delhi.
- 3. The Add. Commissioner of Police (Lic), 1st Floor, Licensing Unit, Police Station, Defence Colony, New Delhi.

Following fire safety directives must be adhered to:-

- The staircase at terrace level shall be kept open & free from lock and key & all the exit shall be clear from any obstruction otherwise the FSC shall be null & void
- All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.
- 4. The trained staff should be available round the clock.
- 5. Any deviations w.r.t. construction shall be verified by the concerned building sanctioning agency.
- 6. The certificate may not be treated in any case for the regularization of the unauthorized construction, if any.
- 7. Basement shall be used as per building bye laws.
- 8. The owner/occupier shall submit a declaration every year in the form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on www.dfs.delhigovt.nic.in.
- The owner/ occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its

入/// ð INSPECTION REPORT

1. Name & address of the building: M/s Bikanervala Foods Pvt. Ltd, Located at Ground Floor & First Floor, Plot No. 10, Sector-12 A, Dwarka, New Delhi.

2. Type of Occupancy: Group D (Assembly Building) (At Ground & 1st Floor only)

Type of Case

: Renewal

4. Details of previous NOC

: F6/DFS/MS/SZ/2021/218, dated-08/09/2021

5. Fire Safety directives Letter No.: N/A

6. Date of inspection

: 03/09/2024

7. Name of the Inspecting Officer: Sh. Udaivir Singh ADO (DWK)

8. Name and designation of Officer

from the building side

:Sh. Chunnilal (Manager) & Sh. Varun (Employee)

9. Year of Construction

: 2009

10. Applicant's letter No. : Application No. 2024082112935 Dated -21/08/2024

S No	prevention and fire safety U/R 33		per N/7, 8 & N/9	Provid site	Provided at site		Remarks MR/NMR		
1.	Access of building	9 m	Provided		MR				
	Road width	4.5 m	2 20 040 1 10 2						
	Gate width Width of internal mod		NA NA		accessione noi		NA		
+	Width of internal road	000000000000000000000000000000000000000	MI (元の元本元)			A 1			
2	Number, width, Type & Arrangem a. Number of staircases	ients o	1 CAILS		-				
	 a. Number of staircases Upper floors Basements b. Width of staircases Upper floors 		2 Nos. 03 1		Nos. MR				
			IA	NA NA		NA			
1			***	11111		1.11.2			
			.5 m 2	X 150	cm & 10	00 cm	MR(Old (Case)	
ı	Basements	-	NA NA		NA				
	c. Protection of exits								
ı	Fire check door	l N	JA.	NA		NA			
П	Pressurization	N	JA.	NA			NA		
	d. No of continuous staircase terrace		Required		ovided	MR			
1	e. Width Of Corridor f. Door Size		1.5 mtr Opening in h		nall MR				
			02 m & 01 mtr on GF & 150 & 100 cm on FF		200, 145 & 100 cm on		MR		
	Compartmentation		¥1		-11				
	 Fire check door 		NA	NA		NA			
	 Sealing of electrical shafts Fire Rating of shaft door Water Curtain 	1	VΑ	NA	NA		NA		
L		1	NA ·	NA	NA ·		NA		
		1	NA .	NA			NA		
1	Fire Dampers		AV	NA		NA			

you h

N/II

			1				9700	t
4.	Smoke managements System							ł
	 Basements 	NA			NA			ł
	Upper floors	Require	ed N	latural ventila	ation	MR		ļ
j	Fire Extinguishers			717				L
	 Total numbers 	09 nos.		Provided		MR ·		L
	Types	ABC &		Provided		MR		L
	IS marking	ISI mark	ted	ISI marked		MR		
5.	First – Aid Hose Reels							
	Total numbers on each floor	01	Pı	rovided 1	MR			
	 Length of hose reel hose 	30 mtrs	Pr	ovided 1	MR			
	Nozzle diameter	5mm	pr	ovided 1	MR			
7.	Automatic fire detection and alarmin	ng system						
	Type of detectors	NA	Prov	ided	NA	3		
	Location of Main Panel	NA	NA		NA			
	Location of Repeater Panel	NA	NA		NA			
	Alternate source of power	NA	Provi	ided	NA			
	Hooters' Location	NA	Provi	ided	NA			
3.	MOEFA	Required	Provi	ded	MR			
) <u>. </u>	Public Address System	NA	NA		NA			
0.	Automatic Sprinkler System	* 10.0	1121		. 14. 2		20	
21237	Basements	NA	NA		NA			
	Upper Floor	NA	diameter		NA			
	Sprinkler above false ceiling	NA	NA	1772-1763-1750-1750-1750-1750-1750-1750-1750-1750	NA			
1.	Internal Hydrants:							
	Size of riser/down- comer	100 mm	Pı	rovided	MR			
	Number of hydrants per floor				MR			
	Hose Box	01 No	1 725 101	- PAY TANK DESCRIPTION	MR			
12.	Yard Hydrants	-	_			-		
	Total number of hydrants	NA	NA		NA			
	Hose Box	NA	NA		NA			Ī
3.	Pumping Arrangements:							_
	Ground Level							_
	Discharge of main pump	NA		NA	N.	A		
	➤ Head of main pump	NA		NA	N/	4	-	
	Number of main pumps	NA		NA	N/	4		
	Jockey pump out put	NA		NA	N/	A		
	Jockey pump head	NA		NA	N/	A		Ī
	Standby Pump out put	NA		NA	N/	A		
	> Standby Pump Head	NA		NA	N/	٨ - ،		
	N 4 C4 1 D4 1 4 1 4 1 4 1 4 1 4 1 4 1 4 1 4 1	NTA.	5.4	NA	N/	1		_
	> Auto Staring/Manual stopping	NA						-
	Pump House Access	NA NA	111	NA	N/			
	Pump House AccessTerrace level	NA NA	ψ	NA	1 200	2		
	 Pump House Access Terrace level Discharge of pump 	NA 450 lpm	ų Lo	Provided	l Mi	R		7.7
	 Pump House Access Terrace level Discharge of pump Head of the pump 	NA NA 450 lpm 40 m		1994	l Mi	R		7.7
	 Pump House Access Terrace level Discharge of pump Head of the pump Power supply 	NA 450 lpm 40 m Required	l	Provided Provided	l Mi	R R		
	 Pump House Access Terrace level Discharge of pump Head of the pump Power supply Auto starting of pump 	NA 450 lpm 40 m Required	l	Provided Provided	l Mi	R R		
4.	 Pump House Access Terrace level Discharge of pump Head of the pump Power supply Auto starting of pump Captive water Storage for fire fighting	NA 450 lpm 40 m Required Required		Provided Provided Provided Provided	l Mi l Mi l Mi	R R R		
1.	 Pump House Access Terrace level Discharge of pump Head of the pump Power supply Auto starting of pump Captive water Storage for fire fighting Under ground tank capacity 	NA 450 lpm 40 m Required Required 3:	l l	Provided Provided Provided Provided	I MI I MI I MI	R R R		
4.	 Pump House Access Terrace level Discharge of pump Head of the pump Power supply Auto starting of pump Captive water Storage for fire fighting Under ground tank capacity Draw off connection 	NA NA 450 lpm 40 m Required Required INA NA	I I	Provided Provided Provided Provided A	l Mi l Mi l Mi	R R R R R		
4.	 Pump House Access Terrace level Discharge of pump Head of the pump Power supply Auto starting of pump Captive water Storage for fire fighting Under ground tank capacity Draw off connection Fire service inlet 	NA 450 lpm 40 m Required Required NA NA Required	I NA NA Pr	Provided Provided Provided Provided A A rovided	I MII MII MII MII MII MII MII MII MII M	R R R R R NA NA MR		
4.	 Pump House Access Terrace level Discharge of pump Head of the pump Power supply Auto starting of pump Captive water Storage for fire fighting Under ground tank capacity Draw off connection Fire service inlet Access to tank 	NA 450 lpm 40 m Required Required NA NA Required NA	NA NA PI	Provided Provided Provided Provided A A rovided	I MII MII MII MII MII MII MII MII MII M	R R R R NA NA MR NA		
4.	 Pump House Access Terrace level Discharge of pump Head of the pump Power supply Auto starting of pump Captive water Storage for fire fighting Under ground tank capacity Draw off connection Fire service inlet 	NA 450 lpm 40 m Required Required NA NA Required	NA NA Pr	Provided Provided Provided Provided A A rovided	I MII MII MII MII MII MII MII MII MII M	R R R R R NA NA MR		

Wex

		M	112	
6.	Provision of Lifts			NA
-	Pressurization of Lift Shaft	NA	NA ·	
	Pressurization of lift lobby	NA	NA	NA
	Communication in lift Car	NA	NA	NA
-	> Fireman's Grounding Switch	NA	NA	NA
- 1	➤ Lift Signage	NA	NA	NA
17.	Standby power supply	Required	Provided	MR
18.	Refuge Area	7	_	NA
10.	> Total area	NA	NA	AND
	> Location	NA	NA	NA
19.	Fire control room	NA	NA	NA
	> Detector system panel	NA NA	NA	NA ·
	> PA System Panel		NA	NA
		NA	NA	NA
	> Battery backup	NA	NA	NA
	> Building Floor Plans	NA	- 100.00	· NA
20	Special Fire Protection Systems for Protection of special Risks, if any;	NA	NA	, MA

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

In view of the deemed compliance of minimum standards on fire prevention and fire safety as required under the rules the FSC issued vide letter no. F6/DFS/MS/SZ/2021/218, dated-08/09/2021 renewal under Rule 37 of the Delhi Fire Service Rules 2010 is recommended.

Signature of the Inspecting Officer
Name Usan Vir Simple
Designation Apological

100/50 / B/9/29

Director 19 2004

v Houdel oglalon