



GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE, NEW DELHI-110001

No. F.6/DFS/MS/H/2024/SZ/ 554

Dated: 11 / 09 /2024

FIRE SAFETY CERTIFICATE

Certified that the Warehouse namely Air Cargo Logistic Centre (ACLC-II) situated at IGI Airport, New Delhi-110037 (for Shristi Cargo Warehouse Pvt. Ltd), comprised of ground floor (Shed) only was issued Fire Safety Certificate by this department vide letter No. F.6/DFS/MS/H/2021/SZ/566 dated 17/11/2021. The premise was re-inspected by the officers concerned of this department on 23/08/2024 in the presence of Mr. Amit Chhabra (Facility Manager) & Mr. Kailash Sharma (Warehouse In-charge) and found that said premise/building have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the said building/premises is fit for occupancy class Group 'H' (Storage) with effect from 11 / 09 /2024 for a period of three years in accordance with rule 36 unless renewal under rule 37 or sooner cancelled under rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

Issued on 11/09/2029 at New Delhi by

(ATUL GARG)
DIRECTOR
DELHI FIRE SERVICE

Copy to: -

 Sh. Ritesh Yarlagadda (CEO), M/s Shristi Cargo Warehouse Pvt. Ltd, Office Block, Air Cargo Logistics Centre-II, Opp. Gate 6, Cargo Terminal, IGI Airport, New Delhi-110037

2. The C.E.O., DIAL, New Udaan Bhawan, Opp. Terminal-3, IGI Airport, New Delhi-110037

Conditions for the validity of Fire Safety Certificate:

- 1. All the means of escape/entry/exit shall be kept free from any obstruction.
- All the fire safety arrangement provided therein shall be maintained in good working conditions at all time as seen during inspection. Any loss of life property due to non-functional fire safety measures shall be at the responsibility of the management.
- 3. All the staff members must know the correct method of operation of firefighting system.
- Any deviation with regard to construction, ventilation, occupancy, electric installation etc. may be got verified from concerned authorities.
- 5. The owner/occupier shall submit a declaration every year in form "K" provided in the first schedule of Delhi Fire Service Rules, 2010. The form is available on www.dfs.delhigovt.nic.in
- 6. This fire safety certificate may not in any way be treated as regularization (Clause 2.8 of UBBL-2016) of unauthorized construction or alteration (Clause 1.4.3 of UBBL-2016), if any.
- 7. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule37] along with a copy of this Certificate, six months prior to its expiry.

| | | ON REPORT | | | | | |
|--|---|---|--|----------|--|--|--|
| Name & address of the building Warehouse namely Air Cargo Logistic | | | | | | | |
| | | (ACLC-II) at IGI Airport, New Delhi-110037 | | | | | |
| | | (for Shristi Cargo Warehouse Pvt. Limited) | | | | | |
| 2. | Type of Occupancy | Group-H (Storage Building) | | | | | |
| 3. | Building Comprised of | Ground floor (Shed) only Renewal F.6/DFS/MS/H/2021/SZ/566 dated 17/11/2021 | | | | | |
| 4 | Type of Case | | | | | | |
| 5 | Details of previous NOC | | | | | | |
| 6. | Fire Safety Directives Letter No. | F6/DFS/MS/2018/3614 Dt. 23/08/2018 (C/27) | | | | | |
| 7. | Date of inspection | 23/08/2024 | | | | | |
| 8. | Name of Inspecting Officer | DO (SD) and ADO (SJ) | | | | | |
| 9. | Name and designation of Officer from building side | Mr. Amit Chhabra (Facility Manager) and Mr. Kailash Sharma (Warehouse In-charge) | | | | | |
| 10. | Year of Construction | 2018 | | | | | |
| 11. | Applicant letter No. Form 'J' received through outdoor diary No. 5361 Dt. 16/08/2 | | | | | | |
| S . | Minimum standards on fire prevention | Old NOC Provided at site Rem | | Remarks | | | |
| No. | and fire safety U/R 33 | Requirements | | MR/NMI | | | |
| | Access of building | | act of some | | | | |
| | Road width | 6m | Provided | MR | | | |
| | Gate width | 4.5m | Provided | MR | | | |
| | Width of internal road | As per plan | 6m | MR | | | |
| | | | Om | 1,110 | | | |
| 2. | Number, width, Type & Arrangements of exits | | | | | | |
| | a. Number of staircases | | 374 | I NA | | | |
| | Upper floors | -NA- | -NA- | -NA | | | |
| | Basements | -NA- | -NA- | -NA | | | |
| | b. Width of staircases | | | | | | |
| | Upper floors | -NA- | -NA- | -NA | | | |
| | Basements | -NA- | -NA- | -NA | | | |
| | c. Protection of exits | #40X0 | | | | | |
| 1 | | -NA- | -NA- | -NA | | | |
| - 3 | Fire check door | -NA- | -NA- | -NA | | | |
| | Pressurization | | | | | | |
| | d. No of continuous staircase to terrace | -NA- | -NA- | -NA | | | |
| | e. Width of Corridor | -NA- | -NA- | -NA | | | |
| | f. Door Size | 28 x 1.5m | Provided | MR | | | |
| 3. | Compartmentation | | | | | | |
| | Fire check door | -NA- | -NA- | -NA | | | |
| Ĩ | Sealing of electrical shafts | -NA- | -NA- | -NA | | | |
| | Fire Rating of shaft door | -NA- | -NA- | -NA- | | | |
| | Water Curtain/Roof Screen/Curtain Board | Required | Provided | MR | | | |
| | Fire Dampers | -NA- | -NA- | -NA- | | | |
| 4. | Smoke managements System | 1 | | | | | |
| | Basements | -NA- | -NA- | -NA- | | | |
| | Ground / Upper floors | Annex. M | Provided | MR | | | |
| 5. | Fire Extinguishers | | | 1 | | | |
| | Total numbers | IOI | 80 Nos ABC/CO ₂ /W CO ₂ /Foam | MR MR | | | |
| | • Types | ISI marked | Provided | MR | | | |
| | ISI marking First Aid Hage Books | | Tiovided | 1 | | | |
| 6. | First-Aid Hose Reels Total numbers on each floor | | 16 Nos | MR | | | |
| 1 | Total numbers on each floor Length of hose reel hose | Hose-reels | 30m | MR | | | |
| | Nozzle diameter | | 5mm | MR | | | |

| 7. | Automatic fire detection and alarming system MR | | | | | |
|-----|--|----------------------|-------------------------|----------|--|--|
| | Type of detector | Smoke & Heat | Provided | | | |
| | Location of Main Panel | Ground floor | Provided | M | | |
| | Location of Repeater Panel | -NA- | -NA- | -Na | | |
| | Alternate source of power | Required | Provided | M | | |
| | Hooters' Location | All Areas | Provided | M | | |
| 8. | MOEFA | | Provided | MI | | |
| 9 | Public Address System | Required | Provided | Ml | | |
| 10 | Automatic Sprinkler System | Required | Flovided | | | |
| | Basements | -NA- | -NA- | -NA | | |
| | Ground Floor | Required | Provided | MI | | |
| | Sprinkler above false ceiling | -NA- | -NA- | -NA | | |
| 11 | Internal Hydrants | -NA- | -112 | | | |
| | Size of riser/down-comer | Required | 100mm | MF | | |
| | The second secon | Required | 16 Nos | MF | | |
| | Number of hydrants per floor Hose Box | Required | 16 Nos | MF | | |
| 10 | 1400 3000 | Required | 10 1405 | 1,11 | | |
| 12 | Yard Hydrants | | 20.11 | ME | | |
| | Total number of hydrants | Required | 28 Nos | MR | | |
| | Hose Box | Required | 28 Nos | MR | | |
| 13 | Pumping Arrangements | | | | | |
| | Ground Level | 1 2 1 | | | | |
| | Discharge of main pump | 2850 LPM | Provided | MR | | |
| | > Head of main pump | 70m | Provided | MR | | |
| | Number of main pumpsJockey pump out put | One | Provided | MR | | |
| | > Jockey pump head | 180 LPM 70m | Provided | MR | | |
| | Standby Pump out put | 2850 LPM | Provided Provided | MR MR | | |
| | > Standby Pump Head | 70m | Provided | MR | | |
| | Auto Staring/Manual stopping | Required | Provided | MR | | |
| | Pump House Access | Required | Provided | MR | | |
| | Terrace level | | | | | |
| | Discharge of pump | 450 LPM | Provided | MR | | |
| | > Head of the pump | 40m | Provided | MR | | |
| 1 | > Power supply | Required | Provided | MR | | |
| 14 | ➤ Auto starting of pump Captive water Storage for fire fighting | Required | Provided | MR | | |
| 14 | | 2.00.000 1 . | 2 22 222 7 | | | |
| | Underground tank capacity Draw of connection | 2,00,000 Ltrs | 2,00,000 Ltrs | MR | | |
| | > Fire service inlet | Required | Provided | MR | | |
| | > Access to tank | Required Required | Provided | MR | | |
| | Overhead Tank capacity | 10,000 Ltrs | Provided 10,000 Ltrs | MR MR | | |
| 15. | Exit Signage | Required | Provided | | | |
| 16. | Provision of Lifts | required | riovided | MR | | |
| | > Pressurization of Lift Shaft | -NA- | NIA | N. 1 | | |
| | > Pressurization of lift lobby | -NA- | -NA- | -NA- | | |
| | Communication in lift Car | | -NA- | -NA- | | |
| | > Fireman's Grounding Switch | -NA- | -NA- | -NA- | | |
| | ➤ Lift Signage | -NA- | -NA- | -NA- | | |
| 17 | | -NA- | -NA- | -NA | | |
| 17. | Standby power supply | Required | Provided | MR | | |
| 18. | Refuge Area | | | | | |
| | Total area | -NA- | -NA- | -NA- | | |
| | Location | -NA- | -NA- | -NA | | |



| : LEira Protection | Special Fire Protection Systems for Protection of Special Risks, if any; | Manual gas flooding / linear heat sensing tubes with CO ₂ cylinder in HT & LT panel | | MR |
|-----------------------|---|--|------|------|
| Building Floor I | > Detector system p > Flow Switch Panel > PA System Panel > Battery backup > Building Floor Plans | -NA- | -NA- | -NA- |
| Pattery backup | | -NA- | -NA- | -NA- |
| PA System Pane | | -NA- | -NA- | -NA- |
| Detector system | | -NA- | -NA- | -NA- |
| 19. Fire control room | Fire control room Detector system panel | -NA- | -NA- | -NA- |

The fire protection system provided in the building were checked, tested at random and found functional at the time of inspection.

Keeping in view of the deemed compliance of the minimum standards on fire prevention and fire safety measures as required under the rules, the fire safety certificate issued vide letter No. F.6/DFS/MS/H/2021/SZ/566 dated 17/11/2021, renewal under rule 37 of the Delhi Fire Service Rules, 2010 is recommended.

Accordingly, DFA is put up for approval and signature please.

Signature of the Inspecting Officer

Name: Manoj Kumar Sharma

Designation: DO (SD)

Signature of the Inspecting Officer

Name: Santosh Kumar Designation: ADO (SJ)

CFO (HQ)

6 91 20m

Director for

ADV 55

Sir, ft letter is putup for your dry. PL

09/09/29

Director (M)