GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE, NEW DELHI - 110001

No. F6/DFS/MS/GH/NDZ/2024/362

Dated: 04/09/2024

FIRE SAFETY CERTIFICATE

Certified that the M/s Rizwan Guest House located at 953, Gali Shyam Lal, Bazar Matia Mahal, Jama Masjid, Delhi, comprised of Ground + 04 upper floors: Ground floor- (03 guest rooms + reception), 1st floor - (04 guest rooms), 2nd floor - (04 guest rooms), 3rd floor - (04 guest rooms) & 4th floor - (not in use), total 15 guest rooms upto 3rd floor was granted FSC by this department vide letter no. F6/DFS/MS/GH/NDZ/2021/462 dated 01.10.2021. The building/premises was re-inspected by the officer concerned from this department on 16.08.2024 in presence of Mohd. Rizwan (Owner) and found that the building has deemed complied with the fire prevention and fire safety requirements in accordance with Rule 33 of Delhi Fire Service Rules, 2010. The owner has submitted an affidavit on 22.08.2024 stating not to use any floor above third floor for any purpose. Accordingly, the premises is fit for occupancy of (Group A-1) "Residential", Ground floor - (03 guest rooms), 1st floor - (04 guest rooms), 2nd floor - (04 guest rooms) & 3rd floor - (04 guest rooms) for total 15 guest rooms upto 3rd floor only, renewed under Rule 37 or sooner cancelled under Rule 40 and subject to conditions under Rule 38 of Delhi Fire service Rules, 2010 printed below.

Delhi Fire Service

Tel: 011-23414000

Copy to:-

1. The Commissioner, MCD:- to kindly ensure the occupancy as detailed above & deviation, if

2. The Joint Commissioner of Police (Licensing), 1st Floor, Police Station Defence Colony, New Delhi. w.r.to ID No. 2024080912466 dated 09.08.2024.

3. The Licensee, M/s Rizwan Guest House at 953, Gali Shyam Lal, Bazar Matia Mahal, Jama Masjid, Delhi.

Conditions for the validity of fire safety certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction,
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".
- 8. Any change in the occupancy shall be intimated to this Deptt. and approval shall be obtained thereto before occupancy of the same.
- 9. The occupancy of above 3rd floor not allowed as per clause 7.31 in UBBL-2016.
- 10. Basement found sealed with brick wall at the time of inspection.

El I 9 in a de de son o e i

_	INSPECTION REPORT						
l	Nam	e & address of the building	M/s Rizwan Guest Shyam Lal, Bazar Delhi.	M/s Rizwan Guest House located at 953, Gali Shyam Lal, Bazar Matia Mahal, Jama Masjid, Delhi.			
2	Build	ling is comprised of	Ground + 04 upper floors Ground floor - (03 guest rooms + reception) 1st floor - (04 guest rooms) 2nd floor - (04 guest rooms) 3rd floor - (04 guest rooms) 4th floor- (not in use as per affidavit dated 22.08.2024)				
3	Туре	of Occupancy	Residential Group A-1				
4	Туре	of Case	Renewal (old case)				
5	Deta	ils of Previous FSC	F6/DFS/MS/GH/ND2	F6/DFS/MS/GH/NDZ/2021/462 dated 01.10.2021			
6	-	Safety direction letter No	Nil				
7		of Inspection	16.08.2024	16.08.2024			
8	Nom	e of the Inspecting Officers	Sumit Kumar, ADO (SPM)				
9	Nam	e of the designation of Officer the building side	Mohd. Rizwan (Own	Mohd. Rizwan (Owner's)			
10	V	of Construction	Old	D 2024090012466 de	ted		
10		icant's letter No	Online application I.l	D.2024080912466 da			
11	Appi	Ivant 5 lotts.	09.08.2024	Descrided at Site	Remarks		
S.N o	Gundards on fire Requirement/						
1	Acc	ess to building		02 mtrs.	NA		
ı	Acc	Road width	NA (Spl. Area)		NA		
	B	Gate width	NA	NA NA	NA		
		variable of internal road	NA	INA			
,	Nur	ber, Width, Type and Arrange	ement of Exits				
2	1	Number of Staircases		01 no.	MR		
			01 no.	NA	NA		
	1	a Upper Floor	1996.70				
	A.	a Upper Floor b Basement	NA	1421			
	R	b Basement			MR		
	В.	b Basement Width of Staircases	80 cms	1 to 118 cms	MR NA		
	В.	b Basement Width of Staircases a Upper Floor b Basement					
	В.	b Basement Width of Staircases a Upper Floor b Basement Protection of exits	80 cms NA	1 to 118 cms NA			
		b Basement Width of Staircases a Upper Floor b Basement Protection of exits Fire check door	80 cms NA	1 to 118 cms NA NA	NA		
		b Basement Width of Staircases a Upper Floor b Basement Protection of exits Fire check door Pressurization No. of continuous staircases to	80 cms NA	1 to 118 cms NA	NA NA NA NA		
	C. D. E.	b Basement Width of Staircases a Upper Floor b Basement Protection of exits Fire check door Pressurization No. of continuous staircases to terrace	80 cms NA NA NA NA	1 to 118 cms NA NA NA	NA NA NA		
	C. D. E.	b Basement Width of Staircases a Upper Floor b Basement Protection of exits Fire check door Pressurization No. of continuous staircases to terrace Width of Corridor	NA NA NA NA NA	1 to 118 cms NA NA NA NA NA NA	NA NA NA NA		
	C. D. E.	b Basement Width of Staircases a Upper Floor b Basement Protection of exits Fire check door Pressurization No. of continuous staircases to terrace Width of Corridor Door size	80 cms NA NA NA NA	1 to 118 cms NA NA NA NA NA	NA NA NA NA		
3	C. D. E. G.	b Basement Width of Staircases a Upper Floor b Basement Protection of exits Fire check door Pressurization No. of continuous staircases to terrace Width of Corridor Door size mpartmentation	NA NA NA NA NA 1.0 m	1 to 118 cms NA NA NA NA NA 1.0 m	NA NA NA NA		
3	C. D. E. G. Co	b Basement Width of Staircases a Upper Floor b Basement Protection of exits Fire check door Pressurization No. of continuous staircases to terrace Width of Corridor Door size mpartmentation Fire check door	NA	1 to 118 cms NA NA NA NA NA NA	NA NA NA NA MR		
3	C. D. E. F. G.	b Basement Width of Staircases a Upper Floor b Basement Protection of exits Fire check door Pressurization No. of continuous staircases to terrace Width of Corridor Door size mpartmentation Fire check door Sealing of electrical shafts	NA N	1 to 118 cms NA	NA NA NA NA NA NA NA NA NA		
3	C. D. E. G. Co	b Basement Width of Staircases a Upper Floor b Basement Protection of exits Fire check door Pressurization No. of continuous staircases to terrace Width of Corridor Door size mpartmentation Fire check door Sealing of electrical shafts Fire rating of shaft door	NA N	NA N	NA		
3	C. D. E. G. Co A B C D	b Basement Width of Staircases a Upper Floor b Basement Protection of exits Fire check door Pressurization No. of continuous staircases to terrace Width of Corridor Door size mpartmentation Fire check door Sealing of electrical shafts Fire rating of shaft door Water curtain	NA N	1 to 118 cms NA	NA		
3	C. D. E. G. Co A B C D E	b Basement Width of Staircases a Upper Floor b Basement Protection of exits Fire check door Pressurization No. of continuous staircases to terrace Width of Corridor Door size mpartmentation Fire check door Sealing of electrical shafts Fire rating of shaft door Water curtain Fire Dampers	NA N	NA N	NA		
	C. D. E. G. Co A B C D E	Width of Staircases a Upper Floor b Basement Protection of exits Fire check door Pressurization No. of continuous staircases to terrace Width of Corridor Door size mpartmentation Fire check door Sealing of electrical shafts Fire rating of shaft door Water curtain Fire Dampers moke Management System.	NA N	1 to 118 cms NA	NA		

1.

\dashv		Extinguisher Total numbers	08 nos.	08 nos.	MR	
			CO ₂ & ABC	CO ₂ & ABC	MR	
		types IS madring	Required	Provided	MR	
		IS marking	Required	12.2		
	A	st-aid-Hose Reels. Total numbers of each floor	01 no.	Provided at 1st &	MR	
	В	Length of hose reel hose	30 mtrs.	30 mtrs.	MR	
	C	Nozzle diameter	5 mm	5 mm	MR	
	Automatic fire detection and alarming system.					
	-		Required	Provided	MR	
	A B	Type of detectors Location of main panel	Required	Provided at ground floor	MR	
	С	Location of repeater panel	NA	NA NA	NA	
	D	Alternate source of power	Required	Provided	MR	
	E	Hooters	Required	Provided	MR	
8	_	OEFA	NA	NA ,	NA	
9	Pu	blic address System.	Required	Provided	MR	
10	_	itomatic Sprinkler System.				
	A	Basement	NA	NA	NA	
	В	Upper floor	NA	NA	NA	
	C	Sprinkler above false ceiling	NA	NA NA	NA	
11	Internal Hydrants					
**	A	Size of riser/down-comer	NA	NA	NA	
	В	Number of hydrants per floor	NA NA	NA NA	NA	
	C	Hose Box	NA	NA NA	NA	
12		ard Hydrants.	A 14 A	, .	MA	
	A		NA	NA	NA	
	В		NA NA	NA NA		
13			IVA	INA	NA	
10	Pumping Arrangements. A Ground Level					
	a		NA	NA	DT 4	
	b		NA NA		NA	
	c		NA NA	NA NA	NA	
	d		NA NA	NA NA	NA	
	e		NA NA	NA NA	NA	
	f	Standby pump out put	NA NA	NA NA	NA	
	g	376 39	NA NA	NA NA	NA	
	h	Auto Starting /Manual stopping	NA	NA NA	NA NA	
	i		NA	NA	NA	
	I				-1/1	
	a		225 LPM	225 LPM.	MR	
	b		30 mtrs.	40 mtrs.	MR	
1	C	The second and the second seco	Required	Provided	MR	
	0	Auto starting of pump	Required	Provided	MR	
					TATE	

14	Captive Water Storage for Fire Fighting.					
	A	Underground tank capacity	NA	l NA	I NA	
	В	Draw-off connection	NA	NA NA	NA	
	C	Fire service inlet	NA NA	NA	NA	
	D	Access to tank	NA NA	NA	NA	
	E	Overhead tank capacity	2,500 ltrs	2,500 ltrs	MR	
15	Exit Signage.		Required	Provided	MR	
16	Provision of Lifts.					
	Α	Pressurization of lift shaft	NA	NA	NA	
	В	Pressurization of lift lobby	NA	NA	NA	
	C	Communication in lift car	NA	NA	NA	
- 1	D	Firemen's grounding switch	NA	NA	NA	
	E	Lift signage	NA	NA	NA	
17		ndby power supply	Required	Provided	MR	
18	Defense Area					
10			N.A	N.A	N.A	
- 1	A	Total area Location	N.A	N.A	N.A	
10	B Location					
19			NA	NA	NA	
	A	Detector system panel Flow switch panel	NA	NA	NA	
	В		NA	NA NA	NA	
- 1	C	PA system panel	NA	NA	NA	
	D	Battery backup	NA	NA	NA	
20	E Building floor Plans NA Special Fire Protection systems for protection of special		NA	NA		

During inspection it was observed that the building is comprised of ground + 04 upper floors. The same is also on record in the inspection report dated 02.11.2017 placed on file at N/19. There is also mention of basement in the building in initial inspections which was found sealed by masonry construction during this inspection.

The owner has submitted an affidavit dated 22.08.2024 stating the floor wise occupancy of the building and also stating that they shall not use any floor above 3rd floor for any purpose whatsoever.

The fire protection systems provided in the building were tested, checked at random and

found functional at the time of inspection.

In view of the deemed compliance of minimum standards of fire prevention and fire safety issued Rules, the **FSC** under_ the required F6/DFS/MS/GH/NDZ/2021/462 dated 01.10.2021 is recommended to be renewed upto 3rd floor only, under Rule 35 of the Delhi Fire Service Rules 2010.

> Signature of the Inspecting Officer Sumit Kumar

Name Designation

ADO (SPM)