

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI - 110001

No.F6/DFS/MS/EH/2024/296

Dated:11../99./2024

FIRE SAFETY CERTIFICATE

Certified that The Embassy Restaurant located at D- 11, Inner Circle, Connaught Circus, New Delhi in a building comprises of Ground + Mezzanine + 02 Upper floor, and Restaurant is running at Ground + Mezzanine floor, was earlier granted FSC by this department vide letter No.F6/DFS/MS/EH/2021/224 dated 10/09/2021. Now, the premises was re-inspected by the officers concerned of this department on 02/09/24 in the presence of Mr. Govind Ballabh Lakhery, Manager and found that the said premises has deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the restaurant premises is fit for occupancy class Assembly Building Group D, restaurant at ground and mez. floor only and valid up to the period of three year from the date of issue in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

Attl Garg)
DIRECTOR
Delhi Fire Service

Copy to:-

- 1. The Chief Architect, NDMC, Palika Kendra, New Delhi.
- 2. The Joint Commissioner of Police (Lic), First Floor, P.S. Defence Colony New Delhi. ID ID No. 2024081212605 dated 12/08/24.
- 3. The Manager, The Embassy Restaurant at D-11, Inner Circle, Connaught Circus, New Delhi.

Conditions for the validity of fire safety certificate

- 1. This FSC is valid for restaurant at ground & mezzanine floor only.
- 2. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- Any loss of life or property due to nonfunctional fire safety measures shall be at the responsibility of the management.
- 4. The compliance with regards to electrical installation, structural stability, set back area, occupancy and any deviation in construction etc. shall be verified from authority concerned.
- 5. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 6. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- The means of escape such as exits, staircases, corridor, etc shall be kept unobstructed / unlocked for unhindered evacuation in case of an emergency.
- The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".

INSPECTION REPORT

1. Name & address of the building

The Embassy Restaurant at D-11, Inner Circle, Connaught Circus, New Delhi.

2. Type of occupancy:-

Assembly Building Group-D

Gr. + Mezz. + 02 upper floors, Restaurant is running

at Ground + Mezzanine floor.

3. Type of case:-

Renewal

4. Details of previous FSC:-

F6/DFS/MS/EH/2021/224 dated 10/09/2021

5. Fire safety directives No .-6. Date of inspection:-

N/A 02/09/24

7. Name of the inspecting officer:-

Sh. Ravinder Singh (ADO/CC) Sh. Rajinder Atwal (DO/CD)

8. Name & designation of officer from the building side:-

Mr. Govind Ballabh Lakhery

9. Year of construction:-

Old Heritage Bldg.

10. Applicant's letter No:-

online id no.2024081212605 dated 12/08/24.

S.No	Minimum Standards on fire Prevention and fire safety U/R 33	Requirement/ Existing fire safety arrangements	Provided at site	Remarks MR/NMR	
1.	Access to Building		- (MR	
	1) Road width	09 mtr.	09 mtr.	N/A	
	2) Gate width	N/A	N/A		
	3)Width of internal road	N/A	N/A	N/A	
2.	Number, Width Type & Arrangement of Exits				
	A. Number of staircases) (D	
	1. Upper floors	01 No.	02 No.	MR	
	2. Basements	N/A	N/A	N/A	
	B. Width of staircase		1	\ m	
×	1. Upper floors	1.0 & 1.25 mtr.	1.0 & 1.25 mtr.	MR	
	2. Basements	N/A	N/A	N/A	
	C. Protection of exits	N/A	N/A	N/A	
	1. Fire check door	N/A	N/A	N/A	
	2. Pressurization	N/A	N/A	N/A	
	D. No. of continuous	01	01	MR	
	staircase to terrace	Line i a			
	E. Width of corridor	N/A	N/A	N/A	
	F. Door size	1.20 mtr.	1.20 mtr.	MR	
3.	Compartmentation				
	1) Fire check door	N/A	N/A	N/A	
	2) Sealing of electrical shafts	N/A	N/A	N/A	
	3) Fire rating of shaft door	N/A	N/A	N/A	
	4) Water curtain	N/A	N/A	N/A	
	5) Fire Dampers	N/A	N/A	N/A	
4.	Smoke Management System				
	1) Basements	N/A	N/A	N/A	
	2) Upper floors	12 ACPH	Exhaust fan	MR	
5.	Fire Extinguishers				
	1) Total numbers	10 Nos.	10 Nos.	MR	
	2) Types	ABC & CO2	ABC & CO2	MR	
	3) ISI marking	Required	Provided	MR	

al 128

6.	First-Aid Hose Reel					
			101	1/0		
	1) Total number of each	01	01	MR		
	floor	30 mtr.	30 mtr.	MR		
26	2) Length of hose reel hose	05 mm	05 mm /	MR		
	3) Nozzle diameter			1000000		
7.	Automatic Fire Detection &	N/A	N/A	N/A		
_	1) Type of detectors	N/A	N/A	N/A		
	2) Location of main panel	N/A	N/A	N/A		
	3) Location of repeater panel	(T) (N) (A) (A)		,		
	4) Alternate source of power	N/A	N/A	N/A		
	5) Hooter's Location	N/A	N/A	N/A		
	MOEFA	Required	Provided	MR		
-		N/A	N/A	N/A		
9.	Public Address System N/A N/A N/A Automatic Sprinkler System					
10.	1) Basement	N/A	N/A	N/A		
200	2) Upper floors	Required	Provided	MR		
	Sprinkler above false	N/A	N/A	N/A		
	ceiling					
11.	Internal Hydrants 1) Size of riser/down-comer	N/A	N/A	N/A		
	2) Number of hydrants per	N/A	N/A	N/A		
	floor 3) Hose box	N/A	N/A	N/A		
12.	Vord Hydrents					
12.	1) Total number of hydrants	N/A	N/A	N/A		
	2) Hose box	N/A	N/A	N/A		
13.	Pumping Arrangement					
10.	1) Ground level			7X		
	a) Discharge of main pump	N/A	N/A	N/A		
	b) Head of main pump	N/A	N/A	N/A		
	c) Number of main	N/A	N/A	N/A		
	d) Jockey pump out put	N/A	N/A	N/A		
	e) Jockey pump head	N/A	N/A	N/A		
	f) Stand by pump	N/A	N/A	N/A		
	output g) Stand by pump head	N/A	N/A	N/A		
	h) Auto starting/Manual stopping	N/A	N/A	N/A		
	2) Terrace level			/ > 00		
	a) Discharge of pump	450 LPM	450 &180 LPM	MR		
	b) Head of pump	30 mtr.	30 mtr.	MR		
-	c) Power supply	Required	Provided	MR		
	d) Auto starting of pump	Required	Provided /	MR		
14.	Captive Water Storage for	Fire Fighting		1 2 2/2/2		
	Under ground tank	N/A	N/A	N/A		

	capacity			1
	a) Draw-off connection	N/A	N/A	N/A
	b) Fire service inlet	Required	Provided	MR
	c) Access to tank	N/A	N/A	N/A
	d) Over head tank capacity	5,000 ltr.	5,000 ltr.	MR
15.	Exit Signage.	Required	Provided	MR
16.	Provision of Lifts.	quiieu	Tioriaca	IVIK
	a) Pressurization of lift shaft	N/A	N/A	N/A
	 b) Pressurization of lift lobby 	N/A	N/A	N/A
	c) Communication in lift car	N/A	N/A	N/A
	d) Fireman's switch	N/A	N/A	N/A
	e) Lift signage	N/A	N/A	N/A
17.	Stand by Power Supply	Required	Provided	MR
18.	Refuge Area	N/A	N/A	N/A
	Total area location	N/A	N/A	N/A
19.	Fire Control Room	N/A	N/A	N/A
	a) Detector system panel	N/A	N/A	N/A
	b) Flow switch panel	N/A	N/A	N/A
	c) PA system panel	N/A	N/A	N/A
	d) Battery backup	N/A	N/A	N/A
	e) Building floor plan	N/A	N/A	N/A
20.	Special Fire Protection Syste Risk, if any: ABC & Co2	m for Prote	ction of special	MR

The fire protection systems provided in the restaurant were randomly tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules. If agreed, we may renew the FSC issued vide letter no. F6/DFS/MS/EH/2021/224 dated 10/09/2021, under rule 35(6) of the Delhi Fire Service Rules 2010. Accordingly, DFA is put up for kind perusal and signature please.

Signature of the Inspecting Officer

Signature of the Inspecting Officer

Name :- Rajinder Atwal Designation :- DO (CD)

Name:-Ravinder Singh Designation:-ADO (CC

phice pages

F.O. Mugh

Directed 4/ gla

Morke

for Jour posus