

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE, CONNAUGHT PLACE

NEW DELHI

Dated:30 /09/2024

No. F6/DFS/MS/2024/GH/385 FIRE SAFETY CERTIFICATE

Certified that the building of M/s Hotel Sri Nanak Continental Guest House Located at 1st, 2nd & 3rd floor 2218-2222 Hardhyan Singh Road, Karol Bagh, New Delhi, in a building comprised of basement, ground plus three upper floors using basement as (other property & have separate entry /exit), ground floor (shops & reception), first & second floor (07 guest rooms, each floor) & third floor (09 rooms) (Total=23 guest rooms) and a staff kitchen with temporary shed on terrace (now sealed/closed) was issued FSC vide Letter No F6/DFS/MS/GH/SZ/2020/76, dated 25/02/2020. The premises was re inspected by the officer concerned of this department on 25/09/2024 in the presence of Sh. Naveen Singh (Manager) and observed that all the fire prevention and fire safety arrangements provided in the premises found in good working condition. The premises have therefore deemed complied with the fire prevention and fire safety requirements in accordance with Rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class "Residential" (guest house) at ground floor (shops & reception), first'& second floor (07 guest rooms, each floor) & third floor (09 rooms) (Total=23 guest rooms) with effect from 30 09 2024 for a period of three years in accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under Rule

38 of the Delhi Fire Service Rules, 2010. 109 2029 at New Delhi by.

Copy to:

1. The Joint. Commissioner of Police (Lic), 1st Floor, Licensing Unit, Police Station, Defence Colony, New Delhi.

2. The Executive Engineer (Building), MCD, Civic Centre, Minto Road, New Delhi for

information w.r.t. the use of the basement

3. The Manager, M/s Hotel Sri Nanak Continental Guest House Located at 2218-2222 Hardhyan Singh Road, Karol Bagh, New Delhi.

Condition for the validity of fire safety certificate

1. Terrace floor shall not be used for any purpose as undertaking given by owner.

2. The staircase at terrace level shall be kept open & free from lock and key & all the exit shall be clear from any obstruction otherwise the FSC shall be null & void

3. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.

4. Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.

5. The trained staff should be available round the clock.

6. Any deviations w.r.t. construction shall be verified by the concerned building sanctioning

7. The certificate may not be treated in any case for the regularization of the unauthorized construction, if any.

8. Basement strictly shall be kept vacant as seen during inspection.

9. The owner/ occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its expiry.

10. The owner/occupier shall submit a declaration every year in the form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on www.dfs.delhigovt.nic.in

INSPECTION REPORT

 Name & address of the building: M/s Hotel Sri Nanak Continental Guest House Located at 1st, 2nd & 3rd floor 2218-2222 Hardhyan Singh Road, Karol Bagh, New Delhi.

2. Type of Occupancy :Lodging or rooming "A-1"

3. Type of Case : Renewal (Running at 1st, 2nd, & 3rd floor in a building comprised of Basement, Ground + 3 Upper Floor & a staff kitchen with temporary shed on terrace now sealed/closed)

4. Details of previous NOC: F6/DFS/MS/GH/SZ/2020/76, dated 25/02/2020

5. Fire Safety directives Letter No.: Nil

6. Date of inspection :25/09/2024

7. Name of the Inspecting Officer: ADO (DWK)

8. Name and designation of Officer

from the building side : Sh. Naveen Singh (Manager)

9. Year of Construction : Before 1994

10. Applicant's letter No. : 2024091114129, dated 12/09/2024

| S No | Minimum standards on fire prevention and fire safety U/R | | As per N/24, N/25 & N/26 | | | Provided at site | | Remarks MR/NMR | |
|---------|--|----------|--|---------|------|------------------|------------|-------------------|---------|
| 1. | Access of building | 33 | 11/23 0 | 2 1N/ Z | 0 | Site | | MR/N | MK |
| | Road width | 61 | ntr | W. | T | rovide | d | | MR |
| | Gate width | N/ | A | 180 cm | | | | | NA |
| - | Width of internal road | N. | A | NA | J | | | | NA |
| 2. | Number, width, Type & Arrang | gem | ents of | exits | | | | | |
| | a. Number of staircases | | fer | | | | | | |
| | Upper floors | 01 | | | 01 | | MR | | |
| | Basements | | - Otl | ner pi | rope | rty sep | arate ent | ry/exit | |
| | b. Width of staircases | | | | | | | | |
| | Upper floors | O | d case | 100 | cm | | MR(| Being of | d case) |
| | Basements | | - Otl | ner pi | rope | rty sep | arate ent | ry/exit | |
| | c. Protection of exits | | | | | | | | |
| | Fire check door | N. | A | | | NA | | | NA |
| | Pressurization | NA 01 | | | NA | | | | NA |
| | d. No of continuous | | | | 01 | | 1 | M | |
| | staircase to terrace | | | | | | | | |
| | e. Width Of Corridor | | 25 cm | | | to 125 | | | MR |
| 150 | f. Door Size | 0 | ld case | | 83 (| em | MR(Be | ing old | case) |
| 3. | Compartmentation | NT. | | Lar | | | | | 20.277 |
| | Fire check door | N. | THE PARTY NAMED IN COLUMN TWO IS NOT THE PARTY N | N/ | 4 | | T & | | NA |
| | Sealing of electrical shafts | IN. | А | | | ı | JA. | | NA |
| | Fire Rating of shaft | N. | A | 17 | | N | J A | | NA |
| | door • Water Curtain | N. | | | | | NA | | NA |
| 1 | Fire Dampers | N. | A | | | N | ΙA | | NA |

vo h

| 4. | Smoke | managements S | | | | 411 | 9 <u>8</u> | | |
|-----|--|--|-------------|--------------|------------------|----------|-----------------------|-----------|--------|
| | - IIIOK | Daniel Barrents S | ystem | | | | | 7 | |
| | *** | Basements | | Ot | her pro | perty s | eparate entry/ex | it | |
| - | F: - D | Upper floors | 12 a/c | per ho | ur P | rovided | | | MR |
| 5. | Fire E | xtinguishers | | | | | | | MR |
| | • | Total numbers | | | 12 Nos. Provided | | | | |
| | • | Types | | | & CO | 1 | CO ₂ & ABC | _ | MR |
| | IS marking | | | Required | | | Provided | MR | |
| 6. | First - | | | | Provided | | | | |
| | • | Total numbers on each | | | | | Provided | MR | |
| | Length of hose reel hose | | | | 01 30 n | ote | Provided | | MR |
| | Nozzle diameter | | | 5 MM | | | Provided | MR | |
| 7. | Auton | natic fire detection | | | | | Tiovided | | |
| • | 7 kuton | | | | | | Provided | | MR |
| | | Type of detector | | CO detectors | | | Provided | | MR |
| | • | Location of Ma | un | Required | | | Flovided | | |
| | 000 | Panel | | NA NA | | | | | NA |
| | • | Location of Re | peater | INA | | 1477 | | la . | |
| | .044 | Panel | c | NA | | NA | | | NA |
| | • | Alternate source | e or | INA | | 11/7 | | | |
| | 10000 | power | | NA | | | NA | | NA |
| • | 1/05 | Hooters' Locat | ion | 27.1422.220 | ا عدا | Provid | | MR | |
| 8. | MOE | | | Requ | | Provid | | MR | |
| 9. | | Address System | | Requ | nred | FIOVE | ucu | | _ |
| 10. | Automatic Sprinkler System | | | | 10 |)thar nr | operty separate | entry/exi | it |
| | Basements | | | | | | NA NA | | NA |
| | • | Upper Floor | 2002 | NA NA | | | NA | | NA |
| | Sprinkler above false | | | | (0) | | 1111 | - | |
| | | ceiling | | | | 2.) | | | |
| 11. | Internal Hydrants: • Size of riser/down- com | | | | I NT A | | NA | | NA |
| | • | | | NA NA | | NA | | | |
| | • | r floor | floor NA NA | | NA | | NA | | |
| | • | Hose Box | | | INP | Y | 102 | | |
| 12. | Yard | Hydrants | | Thursday at | | | NA | | NA |
| | • | Total number | NA | | | INA | | | |
| | | hydrants | | | | | NA | | NA |
| | | Hose Box | | | | - | 11,72 | | |
| 13. | Pump | ing Arrangemen | ts: | | | - | | | |
| | • | Ground Level | | | | | NA | | NA |
| | | p NA | | | NA NA | | NA | | |
| | > | Discharge of main pum Head of main pump | | | NA | | NA NA | | NA |
| | \ \nabla | Number of main pumps | | | NA | 1 | NA NA | | NA |
| | > | Jockey pump of | out put | L | NA | | | | NA |
| | | lockey pump h | nead | _ | NA | | NA NA | | NA |
| | (400 | Standby Pump out put | | | NA | | NA NA | | NA |
| | | Standby Pump Head | | | NA | | NA NA | | NA |
| | | > Auto Staring/Manual | | | NA | | INA | | AMPONT |
| | | stopping | | | | | NIA | | NA |
| | > Pump House Access | | | | NA | | · NA | | |
| | Terrace level | | | | | | n | | MR |
| | > | 450 lpm | | | Provided | | MR | | |
| | | Ī | 30 mt | rs | Provided | | MR | | |
| | Head of the pump | | | | Requi | red | Provided | | MR |
| | Power supplyAuto starting of pump | | | | | | Provided | | IVII |
| | > > | Auto starting (| of pump | | Requi | red | Provided | | 1,122 |

| + | Under ground tank | NA | | T | | | | |
|-----|--|----------|-------------------|----------|----|--|--|--|
| | capacity | | | NA | NA | | | |
| | the second that the second the second that the second the second that the second the sec | NA | | NA | NA | | | |
| 1 | | NA | | Provided | NA | | | |
| | Access to tank | NA | | NA | NA | | | |
| | Overhead Tank capacity | 5000 | ltr | Provided | MR | | | |
| 15 | Exit Signage | Requ | uired | Provided | MR | | | |
| 16. | Provision of Lifts | | | | | | | |
| | Pressurization of Lift Sh | aft | NA | NA | NA | | | |
| - 1 | Pressurization of lift lobby | | NA | NA | NA | | | |
| - 1 | Communication in lift C | | Required | Provided | MR | | | |
| | Fireman's Grounding Switch | | Required | Provided | MR | | | |
| | ➤ Lift Signage | Required | | Provided | MR | | | |
| 17. | 7. Standby power supply | | Required | Provided | MR | | | |
| 18. | Refuge Area | | | | | | | |
| | > Total area | NA | | NA | NA | | | |
| | . > Location | | NA | NA | NA | | | |
| 19. | | | | | | | | |
| | Detector system panel | NA | | NA | NA | | | |
| 1 | Flow Switch Panel | NA | 0 | NA | NA | | | |
| | PA System Panel | NA | | NA | NA | | | |
| 1 | Battery backup | NA | | NA | NA | | | |
| 1 | > Building Floor Plans | NA | | NA | NA | | | |
| 20 | The second secon | is for | The second second | NA | NA | | | |

The fire protection systems provided in the building were test checked and found

functional at the time of inspection.

In view of the deemed compliance of minimum standards on fire prevention and fire safety as required under the rules the FSC issued vide letter No. F6/DFS/MS/GH/SZ/2020/76, dated 25/02/2020 renewal under Rule 37 of the Delhi Fire Service Rules 2010 is recommended. If approved the FSC may be issued.

Note: Photogoophia & undertaking blaced at c/166

1028/9/24 Signature of the Inspecting Officer

Name: Sh. Udaivir Singh Designation: ADO (DWK)

uplandel A