GOVERNMENT OF NATIONAL CAPITAL TERRITOTY OF DELHI **HEADQUARTERS: DELHI FIRE SERVICE: CONNAUGHT PLACE NEW DELHI- 110001**

F.6/DFS/MS/Indl./2024/SZ/ 607 No.

FIRE SAFETY CERTIFICATE

Certified that the M/s Ashok Dhar, located at A-67, FIEE, Okhla Industrial Area, Phase- II, New Delhi 110020 comprised of Basement, Stilt, Ground + Two upper floors owner/occupied by Mr. Ashok Kumar Dhar was issued FSC by this department vide letter no F6/DFS/MS/Indl./2021/SZ/487 dated 07/10/2021. The Premise was reinspected by the officer concerned of this department on 26/09/2024 in the presence of Mr. Pardeep Kumar Saxena and found that the said Industrial building have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rule, 2010 and found that the said building / premises is fit for occupancy class Group G "Industrial Building" with effect from 03/10 /2024 for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

Issued 03 10 /2024 at New Delhi by

DELHI PIRE SERVICE

Copy to: -

1. M/s Ashok Dhar at A-67, FIEE, Okhla Industrial Area, Phase-II, New Delhi-20

2. The Ex. Engineer (Bldg.), MCD, 8th Floor, Civic Centre, Minto Road, Delhi-02

Conditions for the validity of Fire Safety Certificate: -

- 1. All the means of escape/entry/exit shall be kept unlocked and free from any obstruction.
- 2. All the fire safety arrangements provided therein shall be maintained in good working condition at all time as seen during inspection. Any loss of life or property due to nonfunctional fire safety measures shall be at the responsibility of the management.

3. All the staff members must know the correct method of operation of firefighting system.

4. The basement shall be used strictly in accordance with BBL-1983

5. The owner/occupier shall submit a declaration every year in Form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in.

6. This fire safety certificate may not in any way be treated as regularization (Clause 2.8 of UBBL-2016) of unauthorized construction or Alteration (Clause 1.4.3 of UBBL-

2016), if any.

7. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six months prior to its expiry.

1111	INSPECTION REPORT					
1	Name & Address of the Building	M/s ASHOK DHAR, Plot No. A-67, FIEE, Okhla Industrial Area, Phase-II, New Delhi-110020				
2	Type of Occupancy	Industrial Building (Group-G)				
3	Building Comprised of	Basement, Stilt, Ground + 2 upper floors				
4	Type of Case	Renewal				
5	Details of Previous NOC	F6/DFS/MS/Ind1./2021/SZ/487 dated 07/10/2021				
6	Fire Safety Directives Letter No	F.6/DFS/MS/BP/	2013/257 Dated 16-01-20	013		
17	Date of Inspection	26/09/2024				
8	Name of the Inspecting Officers	DO (South) & ADO (BCP)				
9	Name & Designation of Officers from the building side	Mr. Pradeep Kumar				
10	Year of construction	2013	18/4 lig to 2/19/2 1			
11	Applicant letter No.	Outdoor diary no 6816 dated 23/09/2024				
S. No.	Minimum standards on Fire Prevention and Fire Safety U/R 33	NBC / BBL requirement	Provided at Site	Remarks MR/NMR		
1	Access to Building.		and mall are			
	Road width	12 mtr	Provided	MR		
	Gate width	4.5 mtr	Provided	MR		
1157	Width of internal road	-NA-	-NA-	-NA-		
2	Number, width, type & arrangement of exits	1 2				
MR	a. Number of Staircase		allow the statement of			
	Upper floors	2 Nos	Provided	MR		
	Basement floor	2 Nos	Provided	MR		
	b. Width of Staircase	Indi	r Standby Paris, or			
	Upper floors	1.50 mtr	1.50 mtr each	MR		
JHZ	Basement floor	1.50 mtr	1.50 mtr each	MR		
5131/5	c. Protection of exits					
	Fire check door	Required	Provided	MR		
	Pressurization	-NA-	-NA-	-NA-		
- 14	d. No. of continuous staircase to terrace	Two	Provided	MR		
	e. Width of corridor	-NA-	-NA-	-NA-		
	f. Door size	-NA-	-NA-	-NA-		
3	Compartmentation.	Sureman and	IN AUDITOR OF THE SALINE	1		
SESS	Fire check door.	Required	Provided	MR		
	Sealing of electrical shafts.	Required	Provided	MR		
MR	Fire rating of shaft door.	Required	Provided	MR		
	Water curtain	-NA-	-NA-	-NA-		
	Fire dampers.	-NA-	-NA-	-NA-		
4.	Smoke Management system.	35.11.6	**************************************	11171		
J.	Basement	30 ACPH	Exhaust fan provided	MR		
	Upper floors	12 ACPH	Natural ventilation	MR		
5.	Fire Extinguishers.	75.71	The second secon	AVAL.		
allyl	Total numbers	12 Nos	15 Nos	MR		
	Types	ABC / Co2	- Control of the cont			
	ISI Marking	The second of the second	ABC type	MR		
6.		ISI Marked	Provided	MR		
- 0,	First Aid Hose Reels.		as acidina	100		
A_{0}	Total numbers on each floor.	One	Provided	MR		
	 Length of hose-reel hose. 	30 m	Provided	MR		
10 Pm	Nozzle Diameter	5 mm	Provided	MR		
7	Automatic fire detection & alarming system.	list mil	THEREOF HUS-SHEAR A			
-	Type of detectors	Required	Smoke/Heat	MR		

N/22

				100
	Location of Main Panel	Required	Stilt floor	MR
1.0	Location of Repeater Panel	-NA-	-NA-	-NA-
U-07,	Alternate source of power	Required	Provided	MR
	Hooter's location	All Area	Provided	MR
8.	MOEFA	-NA-	-NA-	-NA-
9.	Public Address System	-NA-	-NA-	-NA-
10.	Automatic Sprinkler System			8
	Basement	Required	Provided	MR
	Upper floors	Required	Provided	MR
	Sprinkler above false ceiling	-NA-	-NA-	-NA-
11.	Internal Hydrants.			
	Size of Riser / Down-comer	100 mm	Provided	MR
	Number of Hydrant per floor	1 No	Provided	MR
	Hose box.	1 No	Provided	MR
12.	Yard Hydrants.	- 1 to 1 - 1 - 1 1 to	reach in a world	Was a
11/10	Total number of hydrants.	2 Nos	Provided	MR
	Hose box.	2 Nos	Provided	MR
13.	Pumping arrangements.		31 14-71 3	
	Ground Level		may will a	
	➤ Discharge of main pump.	2280 LPM	2280 LPM	MR
	Head of main pump.	60 mtr	60 mtr	MR
	Number of main pumps.	One	One	MR
	> Jockey Pump output.	180 LPM	180 LPM	MR
	> Jockey Pump head.	60 mtr	60 mtr	MR
	Standby Pump output.	2280 LPM	2280 LPM	MR
	> Standby Pump head.	60 mtr	60 mtr	MR
	➤ Auto Starting/Manual Stopping.	Required	Provided	MR
	Pump House Access	Required	Provided	MR
	Terrace Level			
30.17	Discharge of pump.	450 LPM	Provided	MR
	➤ Head of pump.	40 mtr	Provided	MR
	Power supply.	Required	Provided	MR
	Auto starting of pump.	Required	Provided	MR
14.	Captive water storage for fire fighting.		407.14000	
	Underground tank capacity.	1,00,000 ltrs	Provided	MR
	> Draw-off connection.	Required	Provided	MR
	Fire Service Inlet.	Required	Provided	MR
	Access to tank.	Required	Provided	MR
11	Overhead tank capacity.	10,000 Ltr	Provided	MR
15.	Exit Signage.	Required	Provided	MR
16.	Provision of Lifts.	100	Migration against a mount	+
10.	2 010 1 0	-NA-	-NA-	-NA-
		-NA-	-NA-	-NA-
	Pressurization of lift lobby.	Required	Provided	MR
	Communication in lift car.	Required	Provided	MR
	Fireman's switch.		Provided	
	Lift signage.	Required	USES ESPERIMENTAL SERVICES	MR
17	Standby Power Supply	Required	Provided (DG Set)	MR
18.	Refuge Area			
	Total area	-NA-	-NA-	-NA-
	Location	-NA-	-NA-	-NA-
19.				
19.		-NA-	-NA-	-NA-
	Detection System Panel			
		-NA-	-NA-	-NA



	T S in 1 Beard	-NA-	-NA-	-NA-
	Flow Switch Panel PA System Panel	-NA-	-NA-	-NA-
	Battery backup. Building Floor plans	-NA-	-NA-	-NA-
20.	Special Fire Protection Systems for Protection of Special Risks, if any.	Required	Provided 02 Nos ABC type fire extinguishers for LT panel	MR

The fire protection system provided in the building were randomly checked and found functional at the time of inspection.

Keeping in view of the deemed compliance of the minimum standard on fire prevention and fire safety measures as required under the rules, the FSC issued vide letter no F6/DF\$/MS/Indl./2021/SZ/487 dated 07/10/2021, renewal under rule 37 of the Delhi Fire Service rules, 2010 is recommended.

Accordingly DFA is put up for perusal and signature please

Signature of the Inspection Officer Name: Sh. Manoj Kumar Sharma

Design: DO (South)

Signature of the Inspecting Officer Name: Sh. Rajesh Kumar

Design: ADO (BCP)

B approved, f-P. letter is putup for me synatur !!