

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE, NEW DELHI – 110001

No. F6/DFS/MS/GH/NDZ/2024/394

Dated: 03 / 10 /2024

FIRE SAFETY CERTIFICATE

Delhi Fire Service C

Copy to:-

- 1. The Commissioner, MCD:- to kindly ensure the occupancy as detailed above & deviation, if any.
- 2. The Joint Commissioner of Police (Licensing), 1st Floor, Police Station Defence Colony, New Delhi. w.r.to ID No. 2024090913969 dated 09.09.2024.
- 3. The Licensee, M/s Mustafa Guest House situated at 3933, Urdu Bazar, Jama Masjid, Delhi 06.

Conditions for the validity of fire safety certificate

- All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".
- 8. Any change in the occupancy shall be intimated to this Deptt. and approval shall be obtained thereto before occupancy of the same.
- 9. The occupancy of above 3rd floor not allowed as per clause 7.31 in UBBL-2016.

| 1 | Na | | TION REPORT | . **4 2011 | Cir Corod | |
|-----|----------------------------|---|--|---|----------------------|-----|
| | | me & address of the building | M/s Mustafa Gu Ahmed Road, Da | est House at 291. rya Ganj, Delhi. | i, Sir Seyed | |
| 2 | Bu | ilding is comprised of | (Ground + 04 uni | er floors) | 200 | |
| | | | Ground floor - (reception + office + 02 guest rooms) | | | |
| | | | | | | |
| | | | | 2 nd floor - (02 gue | est rooms + 02 store | es) |
| | | | 3 rd floor - (02 gue | st rooms + 02 store | es) | |
| | U | | 4th floor - (not i | n use as per aff | idavit dated | |
| | | | 25.09.2024) | | | |
| 3 | Ty | pe of occupancy | Residential Group | | | |
| 4 | Ту | pe of case | Renewal (old case |) | | |
| 5 | Details of previous FSC | | F6/DFS/MS/GH/N | DZ/2020/104 date | :d | |
| | | | 18.03.2020 | | | |
| 6 | Fir | e safety direction letter no. | Nil | | | |
| 7 | _ | te of inspection | 25.09.2024 | | | |
| 8 | | me of the inspecting officers | Sumit Kumar, AD | O (SPM) | | |
| 9 | | me of the designation of officer | Manager | | | |
| - | | m the building side | A SECTION ASSESSMENT OF THE SECTION | | | |
| 10 | | ar of construction | 1993 | | | |
| 11 | | plicant's letter no. | Online application | Online application I.D. No. 2024090913969 | | |
| | | r-magne a markedunich | dated on 09.09.202 | | | |
| S.N | Mi | nimum Standards on fire | Requirement/ | Provided at | Remarks | |
| 0 | Prevention and fire safety | | Existing fire | Site | MIR/ | |
| 12 | requirements U/R 33 | | safety | | NMR | |
| | | - 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 | arrangements | | | |
| 1 | | cess To Building: | 1 | | T | |
| | | ad width | NA | 02 mtr. | NA | |
| | | te width | NA | NA | NA | |
| 2 | | idth of internal road Imber, Width, Type and Arran | NA | NA | NA NA | |
| | - | Number of staircases | genient of Exits: | 7 | | |
| | A | a Upper floor | 01 no. | 01 no. | MR | |
| | | b Basement | NA | NA | NA | |
| | В | Width of staircases | NA | INA | INA | |
| | D | a Upper floor | 80 cms. | 98 cms. | MR | |
| | | b Basement | NA | NA NA | NA NA | |
| | C | Protection of exits | - 34 4 | 1111 | INA | |
| | | a Fire check door | NA | NA | NA | |
| | | b Pressurization | NA | NA | NA | |
| | D | No. of continuous staircases | NA | NA | NA | |
| | | to terrace | | | | |
| | E | Width of corridor | NA | NA | NA | |
| | F | Door size | 1.0 mtr. | 1.0 mtr. | MR | |
| | | mpartmentation: | | | | |
| 3 | | Fire check door | NA | NA | NA | |
| 3 | A | Sealing of electrical shafts | NA | NA | NA | |
| 3 | В | | NA | NA | NA | |
| 3 | B | Fire rating of shaft door | IVA | | (CE) | |
| 3 | B C D | Fire rating of shaft door Water curtain | NA NA | NA | NA. | |
| | B C D | Fire rating of shaft door Water curtain Fire dampers | Dire | NA NA | NA NA | |
| | B C D E Sm | Fire rating of shaft door Water curtain Fire dampers oke Management System: | NA | | NA NA | |
| 3 | B C D | Fire rating of shaft door Water curtain Fire dampers | NA | | | |

| 5. | 2000 | re Extinguisher: | 1 **2 | 10 | MR / | | | |
|----|-------|---|---|---------------------------------|------|--|--|--|
| | A | Total numbers | 10 nos. | 10 nos. | MR | | | |
| | В | Types | CO ₂ & ABC | CO ₂ & ABC | | | | |
| | C | ISI marking | Required | Provided | MR | | | |
| 6 | Fin | First-Aid-Hose Reels: | | | | | | |
| | A | Total numbers of each floor | NA | 01 no. at 1 st floor | NA | | | |
| | В | Length of hose reel hose | NA | 30 mtrs. | NA | | | |
| | C | Nozzle diameter | NA | 05 mm | NA | | | |
| 7 | Au | Automatic Fire Detection And Alarming System: | | | | | | |
| | A | Type of detectors (CO type) | Required | Provided | MR / | | | |
| | В | Location of main panel | Required | Provided at reception | MR | | | |
| | C | Location of repeater panel | NA | NA | NA | | | |
| | D | Alternate source of power | Required | Provided | MR | | | |
| 8 | E | Hooters DEFA: | Required | Provided | MR | | | |
| | 77.55 | | NA | NA | NA | | | |
| 9 | | blic Address System: | Required | Provided | MR | | | |
| 10 | _ | tomatic Sprinkler System: | | | | | | |
| | A | Basement | NA | NA | NA | | | |
| | В | Upper floor | NA | NA | NA | | | |
| | C | Sprinkler above false ceiling | NA | NA | NA | | | |
| 11 | Inte | Internal Hydrants: | | | | | | |
| | A | size of riser/down-comer | NA | NA | NA | | | |
| | В | Number of hydrants per floor | NA | NA | NA | | | |
| | C | Hose box | NA | NA | NA | | | |
| 2 | Yar | Yard Hydrants: | | | | | | |
| | A | Total number of hydrants | NA | NA | NA | | | |
| | В | Hose box | NA | NA | NA | | | |
| 3 | Pum | ping Arrangements: | 3000 | 11/1 | INA | | | |
| | A | Ground level | | | | | | |
| - | a) | Discharge of main pump | NA | NIA | Tsv. | | | |
| | b) | Head of main pump | NA | NA | NA | | | |
| ŀ | c) | Number of main pumps | | NA | NA | | | |
| | d) | Jockey pump out put | NA | NA | NA | | | |
| | e) | Jockey pump head | NA | NA | NA | | | |
| | f) | Standby pump out put | NA | NA | NA | | | |
| - | g) | Standby pump head | NA | NA | NA | | | |
| - | h) | Auto starting /manual | NA | NA | NA | | | |
| | 52620 | stopping | NA | NA | NA | | | |
| | i) | Pump house access | NA | NA | | | | |
| | В | Terrace level | 4.14.1 | NA | NA | | | |
| | a) | Discharge of pump | NA | 1000 | T | | | |
| | b) | Head of the pump | NA NA | 225 LPM | NA | | | |
| 0 | ;) | Power supply | NA | 30 mtrs. | NA | | | |
| | 1) | Auto starting of pump | 1 2 2 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 | Provided | NA | | | |
| | , | our thig of pump | NA | Provided | NA | | | |

| | | Captive Water Storage For Fire Fighting: | | | | |
|-----|---------------------|---|----------|------------|----------|--|
| | A | Underground tank capacity | NA | NA. | NA | |
| | B | Draw-off connection | NA | NA | NA NA | |
| | Ç | Fire service inlet | NA | NA | NA NA | |
| | D | Access to tank | NA | NA. | NA NA | |
| | E | Overhead tank capacity | NA | 2500 ltrs. | NA | |
| 15 | Exi | t Signage: | Required | Provided | MR | |
| 16 | Provision of Lifts: | | | | | |
| | A | Pressurization of lift shaft | NA | NA | NA | |
| | В | Pressurization of lift lobby | NA | NA | NA | |
| - 1 | C | Communication in lift car | NA | NA | NA | |
| | D | Firemen's grounding switch | NA | NA | NA | |
| | E | Lift signage | NA | NA | NA | |
| 17 | | andby Power Supply: | NA | Provided | NA | |
| 18 | Refuge Area: | | | | | |
| | A | Total area | NA | NA | NA | |
| | В | Location | NA | NA | NA | |
| 19 | | | | | | |
| | A | Detector system panel | NA | NA | NA | |
| | В | Flow switch panel | NA | NA | NA | |
| | C | Pa system panel | NA | NA | NA | |
| | D | Battery backup | NA | NA | NA NA | |
| | E | Building floor plans | NA | NA | NA NA | |
| 20 | SI | pecial Fire Protection Systems F pecial Risks, If Any: | NA | IVA | | |

The fire protection systems provided in the building were tested, checked at random and found functional at the time of inspection.

Keeping in view of the deemed compliance of minimum standards of fire prevention and fire safety measures as required under the Rules, the FSC issued vide letter No. F6/DFS/MS/GH/NDZ/2021/97 dated 18.02.2021 is recommended to be renewed upto 3rd floor only, under Rule 35 of the Delhi Fire Service Rules 2010.

Signature of the Inspecting Officer Name Sumit Kumar Designation ADO (SPM)

2

DO (CD)

26/9/24

yero (moz)

25 191 20mg

Dinesta My

Hork Joh

up for signature, Please.