GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI **HEAD QUARTERS: DELHI FIRE SERVICE: NEW DELHI - 110001**

No. F6/DFS/MS/NDZ/2024/ 596

FIRE SAFETY CERTIFICATE

Certified that the M/s Pragati Filling Station (Indian oil petro pump) Jawahar lal Nehru Marg, New Delhi in a building comprised of Ground + 01 upper floor, Ground floor - ATM room, Workshop Manager's Office, Spare Parts Room, Electrical Panel Room, Petrol Pump and First floor - Offices, Toilet, Spare Parts room, was earlier granted FSC by this department vide letter No.F6/DFS/MS/NDZ/2021/444 dated 14/09/2021. Now, the premises was re-inspected by the officers concerned of this department on 17/09/24 in the presence of Sh. Abhinav Jain and found that the said Petrol Pump have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Hazardous Group J for petrol pump only with effect from .. 30 09 2024.. for period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed beldw. Issued .30,09,2014..at New Delhi by.

Copy to:-

1. M/S Pragati Filling Station, Jawahar lal Nehru Marg, New Delhi.

Conditions for the validity of fire safety certificate

1. This FSC is only for Petrol Pump.

2. "No Smoking" and "Not to use Mobile Phone" sign board should be displayed in such a manner as to be easily readable by all persons.

3. No trade Susceptible to Cause Ignition Petroleum vapors by generating heat, mechanical/electric spark should be allowed within the premises and its vicinity.

4. 04 nos. of CO2 gas type ISI capacity of 4.5 kg, 02 nos. of ABC stored pressure powder type ISI capacity 05 kg and 01 number of AFFF type ISI capacity 50 ltrs provided should be maintained in proper working order all the time.

5. The working employees at the petrol pump must be taught the correct method of operation

and maintenance of record of the extinguishers of chall submit a declaration every year in Fo 7. The owner / occupier shall submit a declaration every year in Form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in.

8. "The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six months prior to its expiry"

1/10

| INSP | ECTION REPORT | <u>I</u> illing Station, Jaw | ahar lal | | |
|--|--|--|-------------------|--|--|
| 1. Name & address of the building | | | anai iai | | |
| 2. Type of occupancy:- | | Nehru Marg, New Delhi | | | |
| 2. Type of occupancy:- | Hazardous Gr | | | | |
| 3. Type of case:- | Ground + 01 i | ipper Hoor | | | |
| 4. Details of previous NOC:- | Renewal | 4CAID7/0001/444 | datad | | |
| The Details of previous NOC:- | | 1S/NDZ/2021/444 | dated | | |
| 5. Fire safety directives No | | 14/09/2021. N/A | | | |
| 6. Date of inspection:- | | | | | |
| 7. Name of the inspecting office | 17/09/24 | S: | | | |
| of the hispecting office | | Singh (ADO/CC) Atwal (DO/CD) |) | | |
| 8. Name & designation of office | on, Kajinder | Atwai (DO/CD) | | | |
| From the building side:- | | Jain (Partner) | | | |
| 9. Year of construction:- | 2010 | Jain (Partner) | | | |
| 10. Applicant's letter No:- | 2005-00-00 Text #60 | ted 13.08.24. | | | |
| io. Minimum Standards on fire | Requirement | Provided at site | Damada | | |
| Prevention and fire safety U/R 33 | Existing | i lovided at site | Remarks MR/NMR | | |
| Access to Building | | | MINIMIN | | |
| 1) Road width | 06 | 20 | 72/7-00/ | | |
| 2) Gate width | 06 mtr. | 30 mtr. | MR | | |
| | N/A | N/A | N/A | | |
| 3) Width of internal road | N/A | N/A | N/A | | |
| viuth Type & A | rrangement of Ex | its | | | |
| The redifficer of staircases | | | | | |
| 1. Upper floors 2. Basements | 01 | 01 | MR | | |
| | N/A | N/A | N/A | | |
| B. Width of staircase | | | 1071 | | |
| 1. Upper floors | 0.80 mtr. | 1 mtr. | MR | | |
| 2. Basements | N/A | N/A | N/A | | |
| C. Protection of exits | | | IN/A | | |
| 1. Fire check door | N/A | N/A | DT/A | | |
| 2. Pressurization | N/A | N/A | N/A | | |
| D. No. of continuous | N/A | N/A | N/A | | |
| staircase to terrace | | IVA | N/A | | |
| E. Width of corridor | N/A | N/A | - | | |
| F. Door size Compartments: | 1 mtr. | 1 mtr. | N/A | | |
| nontraine and a compart time interesting | 1 | i iiu. | MR | | |
| 1) Fire check door | N/A | 77/4 | | | |
| 2) Sealing of electrical share | Ac NI/A | N/A | N/A | | |
| 3) Fire rating of shaft door | N/A | N/A | N/A | | |
| 4) Water curtain | N/A | N/A | N/A | | |
| 5) Fire Dampers | NI/A | N/A | N/A | | |
| 4. Smoke Management Syst | tem | N/A | N/A | | |
| 1) Basements | N/A | | - 1071 | | |
| 2) Upper floors | N/A | N/A | N/A | | |
| 5. Fire Extinguishers | IVA | N/A | N/A | | |
| 1) Total numbers | 01 Nos. mechanica | | | | |
| - | 10am 50 Kg 01 | inos. inechanical for | m MR | | |
| 2) Types | Nos. ABC 25 kg, 15 Nos. ABC 4.5 Kg | 50 Kg, 01 Nos. ABC 2 kg,15 Nos. ABC 4.5 K | | | |
| 2) Types | ABC, CO. | | 5 | | |
| 2) 70 | mech.foam | ABC, CO ₂ , mech. foam trolley | MR | | |
| 3) ISI marking | Required | | / | | |
| 6. First-Aid Hose Reel | and the second s | Provided | MD | | |
| 1) Total number of eachfl | oor N/A | | MR | | |
| - Cubii | IVA | N/A | _ | | |
| 2) Length of hose reel hos | se NI/A | - 11/1 | | | |
| 2) Length of hose reel hos | se N/A | N/A | N/A | | |

| | 410 | <u> </u> | Ÿ. | |
|---------------|---|--|--------------|--|
| | 3) Nozzle diameter | N/A | N/A | N/A |
| 7 | ·Automatic Fire Detection & | Alarming Sy | stem | |
| 7. | 1) Type of detectors | N/A | N/A | N/A |
| | 2) Location of main panel | N/A | N/A | N/A |
| | 3) Location of repeater panel | N/A | N/A | N/A |
| | 4) Alternate source of power | N/A | N/A | N/A |
| | 5) Hooter's Location | N/A | -N/A | N/A |
| -20 | | N/A | N/A | N/A |
| 8. | MOEFA | N/A | N/A | N/A |
| 9. | Public Address System | (1.5 miles 20 miles 2 | 1 1/1 2 | The state of the s |
| 10. | Automatic Sprinkler System | N/A | N/A | N/A |
| | 1) Basement | N/A | N/A | N/A |
| | 2) Upper floors | N/A | N/A | N/A |
| | 3) Sprinkler above false | N/A | 1 11/2 | 2.55 |
| | ceiling | | | |
| 11. | Internal Hydrants | T 31/A | N/A | N/A |
| | 1) Size of riser/down-comer | N/A | N/A | N/A |
| | 2) Number of hydrants per | N/A | IN/A | 13,23 |
| | floor | 27// | NI/A | N/A |
| | 3) Hose box | N/A | N/A | 14/21 |
| 12. | Yard Hydrants | Taxes | I NI/A | N/A |
| To the second | 1) Total number of hydrants | N/A | N/A | N/A |
| | 2) Hose box | N/A | N/A | IN/A |
| 13. | Pumping Arrangement | | | NI/A |
| 10. | 1) Ground level | N/A | N/A | N/A |
| | a) Discharge of main | N/A | N/A | N/A |
| | pump | | | 37/4 |
| | b) Head of main pump | N/A | N/A | N/A |
| | c) Number of main pump | N/A | N/A | N/A |
| | d) Jockey pump out put | N/A | N/A | N/A |
| | e) Jockey pump head | N/A | N/A | N/A |
| | f) Stand by pump output | | N/A | N/A |
| | - 1 | N/A | N/A | N/A |
| | g) Stand by pump head h) Auto starting/Manual | N/A | N/A | N/A |
| | stopping | is extracted | | |
| | | | | |
| | | N/A | N/A | N/A |
| | | N/A | N/A | N/A |
| | b) Head of pump | N/A | N/A | N/A |
| | c) Power supply | N/A | N/A | N/A |
| | d) Auto starting of pump | | AMAA | |
| 14. | Captive Water Storage for F | N/A | N/A | N/A |
| | 1) Under ground tank | IN/A | 13/21 | 5 84 B |
| | capacity | N/A | N/A | N/A |
| | a) Draw-off connection | | N/A | N/A |
| | b) Fire service inlet | N/A | N/A | N/A |
| 3.1 | c) Access to tank | N/A | N/A | N/A |
| | d) Over head tank | N/A | IN/A | IV/A |
| | capacity | B | Danidad | MR |
| 15. | No Smoking Signage | Required | Provided | 3.50 |
| | English & Hindi | | English & Hi | nui. |
| 16. | Provision of Lifts. | | | |
| 7.57/6 | a) Pressurization of lift | N/A | N/A | N/A |
| | shaft | | | |
| | b) Pressurization of lift | N/A | N/A | N/A |
| | D) FICSSUITZATION OF THE | - FCM-FS-70 | or switches | |

| | c) Communication in lift car | N/A | N/A | N/A |
|-----|------------------------------|-----|-----|-----|
| | d) Fireman's switch | N/A | N/A | N/A |
| | e) Lift signage | N/A | N/A | N/A |
| 17. | Stand by Power Supply | N/A | N/A | N/A |
| 18. | Refuge Area | N/A | N/A | N/A |
| | Total area location | N/A | N/A | N/A |
| 19. | Fire Control Room | N/A | N/A | N/A |
| | a) Detector system panel | N/A | N/A | N/A |
| | b) Flow switch panel | N/A | N/A | N/A |
| | c) PA system panel | N/A | N/A | N/A |
| | d) Battery backup | N/A | N/A | N/A |
| | e) Building floor plan | N/A | N/A | N/A |
| 20. | MR | | | |

The fire protection systems provided in the building were randomly tested, checked and found functional at the time of inspection.

Further, The CNG pump is also operating in the same premises but no fire safety

certificate is issued for CNG pump by this department.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules, if agreed, we may renew the FSC issued vide letter no. F6/DFS/MS/NDZ/2021/444 dated 14/09/2021, under rule 35 of the Delhi Fire Service Rules 2010. Accordingly, DFA is prepared and put up for kind perusal/approval and signature please.

Signature of the Inspecting Officer

Signature of the Inspecting Officer

Name :- Sh. Rajinder Atwal Designation :- DO (CD)

Name :- Sh. Ravinder Singh Designation: ADO (CC)

CFO COME