

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: NEW DELHI - 110001



No F 6 / DFS / MS / 2024 /WZ/622

Dated 10 10 2024

FIRE SAFETY CERTIFICATE

Certified that 2 BHK, 3 BHK & EWS Flats located at Pocket 6, Sector A 1 to A 4, Narela, Delhi-110040 comprised of 07 Blocks A-Block- 3 BHK (S+13), B-Block 3 BHK (S+16), C-Block-2 BHK (S+13), D-Block 2 BHK (S+13), E-Block 2BHK (S+13), F-Block-2 BHK (S+17), G Block- EWS EN8 (S+16) & EWS EN8a (S+16) attached with each other, Two tier combined basement & Common Facility Block (G+1) owned/ occupied by DDA have complied with the fire prevention and fire safety requirements in accordance with Rule 33 of the Delhi Fire Service Rules, 2010 and verified by the officers concerned of this department on 26.09.2024 in the presence of Sh. S.K. Pujari (Senior G.M.) and found that the building/premises is fit for occupancy "Residential Building A-4" & "Assembly Building D-3" with effect from 10/10/2024 for a period of five years for Residential Building and three years for Assembly Building in accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under Rule 38 of the Delhi Fire Service Rules, 2010 printed below.

Issued on ... 19 19 2024. at New Delhi by

Ph-011-23414000

Copy to:-

1. The Executive Engineer (Electrical), Electrical Division-4, DDA, 6th Floor, Madhuban Chowk, Rohini, New Delhi- 110085.

Conditions for the validity of Fire Safety Certificate:

- 1. All the fire safety arrangement provided there-in shall be maintained in good working conditions at all times.
- 2. Loss of life or property due to non functional fire safety measure shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation with regard to the construction etc shall be verified by the concerned building sanctioning agency.
- 5. This certificate cannot be treated in any case for regularizations of unauthorized construction.
- 6. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director of Form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six months prior to its expiry".
- 7. The owner / occupier shall submit a declaration every year in form "K" provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 8. All the means of escape shall be kept free of any obstruction all the time to evacuate the occupant, in a safe manner, in the event of emergency.
- 9. The basement shall be used as per BBL.

1. Name & address of the building: 2 BHK,3 BHK & EWS Flats (Design & Built Model) located at INSPECTION REPORT

Pocket 6, Sector A 1 to A 4, Narela, Delhi-110040.

: Residential Building Group "A-4 & Assembly Building D-3" 2. Type of Occupancy

: 07 Blocks = A-Block-3 BHK (S+13), B-Block 3 BHK (S+16), C-Block-2 BHK (S+13), D-Block 2 BHK (S+13), E-Block 2BHK (S+13), F-Block-3. Building Comprised of

2 BHK (S+17), G Block- EWS EN8 (S+16) & EWS EN8a (S+16)

attached with each other, Two tier combined basement & Common Facility

Block (G+1).

New 4. Type of Case

F6/DFS/MS/BP/2016/268 Dated- 25/10/2016 5. Details of Previous NOC 6. Fire Safety directives letter No

D.B. Mukharjee, DO (NW) & R.K.Sinha, ADO (BW) 7. Date of inspection

10	Year of (building side Construction it's letter No.	Sh. S.K. Pujari (Senior G 2023 F.W(13)/ELD-4/DDA/20/	1 25/2	10 dated 20/09/2024 ovided at site	Remarks MR/NMR
110	Minimum	Standards on fire on and fire safety U/R 33	As per Directive issued dated 25/10/2016	0		
			23/10/2		Provided	MR
	Access to building		12 m		Provided	MR
	 Road width 		6 m	Provided		MR
1	Gate width		6 m, 9 m	6 m, 9 m		
	• V	Vidth of internal road	ent of Exits			
		Vidth of internal road Width, Type & Arrangem				
	a. Number of staircases		EWS (03 Nos.),2 BHK (02			
	•	Upper Floors	in each block), 3 BHK 02 in each block common Facility block Nos.).01 fire tower a	k) &	Provided	MR
			block	- 11.4		MR
			18 Nos. & 03 Ram	ps	Flovided	
		Basements		524.5	Provided	MR
	b. Width	of staircases	1.5 m & Facility Bloc	k(2m	Provided	V
	•	Upper Floor	& 1.35 m) 1.5 m &(Ramp 4.5		Provided	MR
	•	Basements				MR
	c. Protection of exits		Required		Provided	MR
	•	Fire check door	Required		Provided	IVIX
	•	Pressurization	All		Provided	MR
	d. No. of continuous staircases to terrace		1.5		Provided	MR
		th of Corridor	1.5 m		Provided	MR
			1.3 III			
	f. Door Size					MR
3.		rtmentation	Required		Provided	
	•	Fire check door	Required		Provided	MR
	•	Sealing of electrical shafts			Provided	MR
	•	Fire Rating of shaft door	Required		Provided	MR
	-	Water Curtain (Basement)	Required		NA	NA
		Fire Dampers	NA I			
4.	Smoke	Management System		Provided Provided		MR
950	•	Basements	Required		Natural Ventilation	MR
	•	Upper floors	Required	21	Vaturui	
5.	Fire Extinguishers		10300.00		Provided	MR
	•	Total numbers	1@300 sqm		Provided	MR
		Types	ABC/CO2 Type		Provided	MR
	•	IS marking	Required		Lionidea	
6.		Aid Hose Reels	W. The state of th		Provided	MR

N14

		7.4					
	 Length of hose reel hose 	30 m	Provided	MR			
	 Nozzle diameter 	5 mm	Provided	MR			
	Automatic fire detection and alarm						
	Type of detectors	Smoke/ Heat	Provided	MR			
				MR			
	Location of Main Panel	At GF in each towe	A Some Management	NA			
	Location of Repeater Panel	NA NA	NA NA	MR			
	Alternate source of power	Required	Provided	MR			
	Hooters' Location	Every Floor	Provided	MR			
3.	MOEFA	Required	Provided Provided	MR			
).	Public Address System	Required	Provided				
10.	Automatic Sprinkler System						
	Basement	Required	Provided	MR			
	Upper Floor	Required in more than 45 mts	Provided	MR			
	- Carinklar above false sailing	NA NA	NA	NA			
	Sprinkler above false ceiling Lateral Manager		OF PERSONS ASSESSED.				
11.	Internal Hydrants			MR			
	Size of riser/down-comer	100 mm	Provided	MR			
	Number of hydrants per floor	02	Provided Provided	MR			
	Hose Box	02	Provided				
12.	Yard Hydrants						
		48 Nos	Provided	MR			
	Total number of hydrants	48 Nos	Provided	MR			
40040	Hose Box	107.02					
13.	Pumping Arrangements						
	Ground Level		Provided	MR			
	 Discharge of main Pump 	2280 LPM 115 m	Provided	MR			
	➢ Head of Main pump	113 111		MD			
	➤ Number of main pumps	05 Nos. (Hydrant-2 No Sprinkler-2 Nos., Wate Curtain-1 No.)	s., Provided	MR			
		5 Nos. 180 LPM	Provided	MR			
	Jockey Pump out putJockey pump head	115 m	Provided	MR			
		3 Nos. 2280 LPM	Provided	MR			
	> Standby Pump out put	Diesel operative	Provided	MR			
	> Standby Pump Head	115 m	Provided	MR			
	> Auto Starting/Manual	Required					
	Stopping > Pump House Access	Required	Provided	MR			
	Terrace level Common Facili		k				
	➤ Discharge of pump	450 LPM	Provided	MR			
	➤ Head of the pump	40 m	Provided	MR			
	➤ Power Supply	Required	Provided	MR			
	Auto Starting of pump	Required	Provided	MR			
14.	Captive Water Storage for fire fightin		D				
	Underground tank capacity	4,00,000 ltrs	Provided Provided	MR			
	> Draw-off connection	Connection		MR			
	Fire service inlet	Required Provided Required Provided		MR			
	> Access to tank	10000 ltrs in each	Provided	MR			
	Overhead Tank capacity	block		MR			
15.	Exit Signage.	Required	Provided	MR			
16.	Provision of Lifts.						
	Pressurization of Lift Shaft	Required	Provided	MR			
	*						

0/

		10-15					
	Pressurization of Lift lobby	Required	Provided	MR			
-		Required	Provided	MR			
	 Communication In lift Car 		Provided	MR			
Γ	 Fireman's Grounding Switch 	Required	A CONTRACTOR OF THE CONTRACTOR	MR			
t	Lift Signage	Required	Provided	MR			
17.	Standby power supply	Required	Provided	IAII			
18.	Refuge Area.						
		NA	NA	NA NA			
	> Total Area	NA	NA	IVA			
19.	Fire Control Room Required in each tower						
		Required	Provided	MR MR			
	Detector System Panel	Required	Provided	MR			
	Flow Switch Panel	Required	Provided				
	PA System Panel		Provided	MR			
	Battery backup	Required	Provided	MR			
	Building Floor Plans	Required	CO2 extinguishers	MR			
20.	Special Fire Protection System for Protection of special Risks, if any:	Required	Provided				

The fire protection systems provided in the building were tested, checked and found functional at the time of inspection. The management had rectified the shortcomings issued vide

Keeping in view of satisfactory compliance of the minimum standards of fire prevention letter no. F6/DFS/MS/2024/WZ/38 dated 09/02/2024. and fire safety measures as required under rules, it is recommended to grant Fire Safety Certificate under rule 35 of Delhi Fire Service Rules, 2010.

Signature of Inspecting Officer Name: D.B. Mukherjee Designation : DO/NW

Signature of Inspecting Officer Name: Rajeev Kumar Sinha

Designation: ADO (BW)

Deneto