

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI : DELHI FIRE SERVICE, CONNAUGHT **NEW DELHI**

No. F6/DFS/MS/School/WZ/2024/972

Dated: 04 / 10 /2024

FIRE SAFETY CERTIFICATE

Certified that the Government Sarvodaya Bal Vidyalaya located at Ramesh Nagar, New Delhi-110015, in a building Comprised of Ground +03 upper floors & old building comprised of two blocks ground + one upper floor each, one block ground + Auditorium, owned/occupied by Government Sarvodaya Bal Vidyalaya, Ramesh Nagar, New Delhi letter vide department this **FSC** by 110015, was issued F6/DFS/MS/School/MN/2021/662 dated 12/08/2021. The premises was re - inspected by the officer concerned by this department on 22/09/2024 in the presence of Sh. Mohammad Saifi (Principal) and found that the fire safety arrangements/equipments provided in the building found in good working condition. That the building/premises have deemed complied with fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire service Rules 2010 and the building/ premises is fit for occupancy class "Educational" (Group -B) with effect from .04.10.2024 for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010. Condition mentioned below.

Issued on ... 04/10/2024 at New Delhi.

Wirector .

Copy to:

1. The Principal, Government Sarvodaya Bal Vidyalaya located at Ramesh nagar, New Delhi-110015,<u>Email Id-</u>

2. Director of Education, GNCT of NCT of Delhi, Old Secretariat.

Following fire safety directives must be adhered to:-

1. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.

2. Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.

3. The trained staff should be available round the clock.

4. Any deviations w.r.t. construction shall be verified by the concerned building sanctioning agency.

5. The certificate may not be treated in any case for the regularization of the unauthorized construction, if any.

6. The owner/ occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its expiry.

7. The owner/occupier shall submit a declaration every year in the form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on www.dfs.delhigovt.nic.in.

1	Name & address of the building		TION REPORT	=0.	dvolera D	L Manne
1.	Identica se managa at was animaning	Delhi-	nment Sarvoday 110015.	a Dai Vi	uyalaya Kames	n Nagar, Ne
2.	Type of Occupancy	Educational				
	Type of Case	Renewal				
	Details of previous NOC	E4/DE	F6/DFS/MS/School/MN/2021/662 dated 12/08/2021			
	Fire Safety directives letter No	The second second	3/M3/School/M	N/2021/	662 dated 12/08	3/2021
29		Nil				
M. T.	Date of inspection	22/09/				
	Name of the Inspecting Officers Name and designation of officers from the building side	Sarabj Sh. M	Sarabjeet Singh ADO (MN) Sh. Mohammad Saifi (Principal)			
9.	Year of Construction	2016-1	7 (As per prev.)	Insp. ren	ort dtd19/08/	2021)
10.	Applicant's letter No.	Outdo	or diary no.6052	dated 04	4/09/2024	
The s	aid school is running in total	03 Bloc	ks (BLK-1= c	ground	+03 upper flo	ors, BLK-(
Groun S.	nd+01 upper floor,& BLK-03= G Minimum Standards on fire	Fround &	& Auditorium)			
No.	prevention and fire safety U/R 33		ired as per Rule 3 Rule 2010/BBL Requirement		Provided at site	Remark MR/NM
1	Access to building			+	per patter	474 THE
40	Road width	A. P.	6 mts	100	rovided	MR
	• Gate width		4.5m	I I	rovided	MR
	• Width of internal road	A. T	NA	1	NA	NA
2	Number, Width, Type & Arran	gement	of Exits		i inta	H3 . H1
	a. Number of staircases			e s bro		
-	Upper Floors		02	P	rovided	MR
	Basements b. Width of staircases		NA		NA	NA
	• Upper Floors	<u>.</u>	16	0.1	12_27/16	
	Basements		1.5 mts each	G+	03=3X1.5m, 1=1X1.5m, -1=2X1.5m	MR
-	c. Protection of exits		NA		NA	NA
	Fire check door		NTA T			
	Pressurization		NA NA		NA	NA
	e. No. of continuous staircases to terrac		01	TO TO	NA Provided	NA ND
	f. Width of Corridor		1.5 Mtr.		rovided	MR
1	g. Door Size		1.0m		rovided	MR MR
3	Compartmentation.					IVIK
	Fire check door		NA		NA	NA
į	 Sealing of electrical shafts 		NA	1 1	NA	NA
	 Fire Rating of shaft door 		NA	1	NA	NA
	Water Curtain		NA		ÑΑ	ŇA
	Fire Dampers		NA	an of	NA	NA
4	Smoke Management System.		A 11 A	to I v	171 i ig8 - 22	
	Basements		NA		NA	NA
	• Upper floors		NA		NA	NA
	Fire Extinguishers				T and	
5			12 nos.			as expense
5	 Total numbers 		_		rovided	MR
5			12 nos. CO ₂ , ABC type SI marked		rovided	MR MR

MVX

	First-Aid Hose Reels.			
	Total numbers on each floor	00 1		
	Length of hose reel hose	02	Provided	MR
-	Nozzle diameter	30m	Provided	MR
	x 1	5mm	Provided	MR
	 Automatic fire detection and alarming s Type of detectors 	and the same of th	NA I	NA
	Location of Main Panel	NA	7.700	NA
		NA.	NA	
	Location of Repeater Panel Alternate source of reverse	ŅA	NA NA	NA
	Alternate source of power Hooters' Location	NA	NA	NA
0		NA	NA.	NA
8	MOEFA	NA	NA	NA
9	Public Address System.	NA	NA	NA
10	Automatic Sprinkler System.	on-dil la fiere a	Laborated III park	7 5 3
	Basement	NA	NA	NA
	Upper Floor	NA	NA	NA
	Sprinkler above false ceiling	NA	NA .	NA
11	Internal Hydrants		and the far for	
	Size of riser/down-comer	NA	NA	NA
	Number of hydrants per floor	NA	NA	NA
111	Hose Box	NA	NA	NA
12	Yard Hydrants.	A resummance of	Brook Alexander	
	Total number of hydrants	NA	NA	NA
	Hose Box	NA	NA	NA
13	Pumping Arrangements.			
	Ground Level			
	Discharge of main Pump	NA	NA	NA
	➤ Head of Main pump	NA NA	NA NA	NA NA
	> Number of main pumps	NA	NA NA	NA NA
	> Jockey Pump out put	NA	NA NA	NA
	Jockey pump head	NA	NA	NA NA
	> Standby Pump out put	ÑĀ	NA	NA.
	➤ Standby Pump Head	NA	NA	NA
	Auto Starting/ Manual stopping	NA	NA	NA
	> Pump House Access	NA	NA	NA
, T	Terrace level			
7.	Discharge of pump	450 lpm	Provided	MR
	> Head of the pump	40 m	Provided	MR
11	> Power Supply	Required	Provided	MŔ
72.0	➤ Auto Starting of pump	Required	Provided	MŔ
14	Captive Water Storage for fire fightin			<u> </u>
	Underground tank capacity	NA	NA	NA
	> Draw-off connection	NA	NA	NA
	> Fire service inlet	NA	NA	NA
ľ	> Access to tank	NA NA	NA.	NA.
	Overhead Tank capacity	10,000 ltrs	Provided	MR
15	Exit Signage.	Required	Provided	MR

	AN							
4	Provision of Lifts.							
16	Pressurization of Lift Shaft	NA	NA	NÀ				
13	Pressurization of Lift lobby	NA	NA	NA				
	Communication In lift Car	NA	NA	NA				
	Fireman's Grounding Switch	NA	NA	NA				
	Lift Signage	NA	NA	NA				
17	Standby power supply	NA	NA	NA				
18	Refuge Area.							
	> Total Area	NA	NA	NA				
	> Location	NA	NA	NA				
19	Fire Control Room							
	Detector System Panel	NA	NA	NA				
	Flow Switch Panel	NA	NA	NA				
	PA System Panel	NA	NA	NA				
	Batter backup	NA	NA	NÀ				
	Building Floor Plans	NA	ŇA	NA				
20	Special Fire Protection Systems for Protection of special Risks, if any:	NA	NA	NA				

functional at the time of inspection.

In view of the deemed compliance of minimum standards on fire prevention and fire safety as required under the rules the NOC issued vide letter no. F6/DFS/MS/School/MN/2021/662 dated 12/08/2021, renewal under rule 35 of the Delhi Fire Service Rules 2010 is recommended.

Signature of the Inspecting Officer

Name: - Sarabjeet Singh

Designation: - ADO (MN)