

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: NEW DELHI- 110001



No. F6/DFS/MS/School/WZ/2024/984

Dated:-

07/10/2024

FIRE SAFETY CERTIFICATE

Certified that the Sunshine Ideal Public School Located at K-II Block, 50 Feet Road, Nihal Vihar, New Delhi-110041, comprised of Ground + 03 Upper Floors & earlier the School building was comprised of Ground + 01 Upper Floor only and was issued Fire Safety Certificate by this department Vide Letter No. F6/MS/DFS/2008/2214 dated 01/08/2008, owned/occupied by Sunshine Ideal Public School, have complied with the fire prevention and fire safety requirements in accordance with Rule 33 of the Delhi Fire Service Rule, 2010 and Verified by the officer concerned of Fire Service on 18/092024 in the presence of Sh. Sunil Marwaha (Manager) and that the premises/building is fit for occupancy class "Educational Building" Group B with effect from 01/10/2024 for a period of three years in accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under Rule 38 of the Delhi Fire Service Rules, 2010, printed below.

Issued on .. 0.7/10/2024 at New Delhi by.

Director

Tel. No. 011-23414000

Copy to: -

1. The Director, Directorate of Education, GNCT of Delhi, Old Secretariat Delhi – 110054.

2. The Principal, Sunshine Ideal Public School, K-II Block, 50 Feet Road, Nihal Vihar, New Delhi-110041.

Following fire safety directives must be adhered to:-

- 1. All the means of escape shall be kept free of all type of obstruction all the time.
- 2. All the employees shall be acquainted with the use and maintenance of all fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.
- 3. All the fire fighting equipments shall be maintained in perfect working condition all the time and any lapse rendering non-functional if fire safety measures, management shall be responsible.
- Any deviation, with regards to construction, ventilation, occupation, electric installation etc. may be got verified from the concerned authorities.
- 5. The Fire Safety Certificate may not be treated in any case for regularizations of unauthorized construction / unauthorized use of land if any.
- 6. All comments / directions of licensing Department shall always be permitted and followed.
- 7. The owner /occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on www.dfs.delhigovt.nic.in
- 8. The owner / occupier shall apply for renewal of this Fire Safety Certificate to the Director in 'Form J' (sub Rule (1) of Rule 37) along with copy of the certificate, six months prior to its expiry.

INSPECTION REPORT

: Sunshine Ideal Public School Located at K-II Block, 50 1. Name & address of the building

Feet Road, Nihal Vihar, New Delhi-110041

: Educational 2. Type of Occupancy

: New Case/Addition of 2nd floor & 3rd floor 3. Type of Case

: F6/MS/DFS/2008/2214 dated 01/08/2008 (for Ground + 4. Details of previous NOC

01 Upper Floor only)

: As per NBC (Part-IV) 5. Fire Safety directives letter No

: 18/09/2024 6. Date of inspection

: Aman Kumar Lathar, ADO (JWP) 7. Name of the Inspecting Officers

8. Name and designation of officers

: Sh. Sunil Marwaha (Manager)

: 2004 (G+01), 2013 (2nd floor) & 2019 (3rd floor) from the building side 9. Year of Construction

: email dated 12/09/2024

The	school building is comprised of Grou Minimum Standards on fire revention and fire safety U/R 33	NBC (Part-IV) Requirements	Provided at site	Remarks MR/NMR
1 Acc	ess to building	100	Provided	MR
1 Acc	Road width Gate width	06 m 4.5 m N/A	Provided N/A	MR N/A
	width of internal road mber, Width, Type & Arrangement			
a. N b. W c. Pi	fumber of staircases Upper Floors Basements Vidth of staircases Upper Floors Basements rotection of exits Fire check door Pressurization o. of continuous staircases to terrace Vidth of Corridor	02 nos. N/A 1.5 m 0.70 1.5 n N/A N/A N/A 02 1.5 m	04 nos. N/A to 0.90 m x 2 (G to 0.m x 2 (G to Terrace) N/A N/A N/A Provided 1.50 to 2.40 m	MR N/A 3) MR N/A N/A N/A N/A MR MR
1	oor Size	1.0 m (G+01) of 1.2 m (2 nd & 3 rd)		MR
	Fire Rating of shaft door	N/A N/A N/A	N/A N/A N/A	N/A N/A N/A
	Water Curtain Fire Dampers	N/A N/A	N/A N/A	N/A N/A

	Smoke Management System.	7.112	N/A	N/A	
	Basements	N/A	Natural Ventila		
	Upper floors	Required	Natural Ventila	ation wix	
5	Fire Extinguishers			1.00	
	Total numbers	08 nos.	09 nos.	MR	
	Types	ABC, CO ₂ type	Provided	MR	
		ISI marked	Provided	MR	
	IS marking				
6	First-Aid Hose Reels.	01 in each floor	Provided	MR	
	Total numbers on each floor		Provided	MR	
	Length of hose reel hose	30 m	Provided	MR	
-	Nozzle diameter	5 mm	Provided	IVIK	
7	Automatic fire detection and alarmi		l'		
	Type of detectors	N/A	N/A	N/A	
	Location of Main Panel	N/A	N/A	N/A	
	Location of Repeater Panel	N/A	N/A	N/A	
	Alternate source of power	N/A	N/A	N/A	
	Hooters' Location	N/A	N/A	N/A	
8	MOEFA	N/A	N/A	N/A	
9	Public Address System.	N/A	N/A	N/A	
10	Automatic Sprinkler System				
	Basement	N/A	N/A	N/A	
	Upper floors	N/A	N/A	N/A	
	Sprinkler above false ceiling	N/A	N/A	N/A	
11	Internal Hydrants				
SE	Size of riser/down-comer	N/A	N/A	N/A	
	Number of hydrants per floor	N/A	N/A	N/A	
	Hose Box	N/A	N/A	N/A	
12	Yard Hydrants.	WA	18/74	IN/A	
12	Total number of hydrants	N/A	N/A	NIA	
	Hose Box	N/A	N/A	N/A N/A	
2		N/A	IVA	IN/A	
13	• Ground Level				
	 Discharge of main Pump 	N/A	N/A	N/A	
	➤ Head of Main pump	N/A	N/A	N/A	
	Number of main pumps	N/A	N/A	N/A	
	Jockey Pump out put	N/A	N/A	N/A	
	 Jockey pump head 	N/A	N/A	N/A	
	Standby Pump out put	N/A	N/A	N/A	
	Standby Pump HeadAuto Starting/ Manual	N/A	N/A	N/A	
	stopping	N/A	N/A	N/A	
	Pump House Access	N/A	N/A	N/A	
	 Terrace level 				
	Discharge of pump	450 LPM	Provided	MR	
	Head of the pump	40 m	Provided	MR	
	Power Supply	Required	Provided	MR	
	Auto Starting of pump	Required	Provided	MR	

14	Captive Water Storage for fire figh	ting				
	Underground tank capacity	N/A	N/A	N/A		
	> Draw-off connection	N/A	N/A	N/A		
	> Fire service inlet	N/A	N/A	N/A		
	> Access to tank	N/A	N/A	N/A		
	Overhead Tank capacity	10,000 lts	Provided	MR		
5	Exit Signage.	Required	Provided	MR		
15	Provision of Lifts					
16	CI :A Ch-A	N/A	N/A	N/A		
	Pressurization of Lift Shalt Pressurization of Lift lobby	N/A	N/A	N/A		
	Communication In lift Car	N/A	N/A	N/A		
	Fireman's Grounding Switch	N/A	N/A	N/A		
	Lift Signage	N/A	N/A	N/A		
		N/A	N/A	N/A		
17	Standby power supply					
18	Refuge Area.	N/A	N/A	N/A		
	Total AreaLocation	N/A	N/A	N/A		
19	Fire Control Room					
17	Detector System Panel	N/A	N/A			
	Flow Switch Panel	N/A	N/A	N/A		
	PA System Panel	N/A	N/A	N/A		
	Batter backup	N/A	N/A	N/A		
	Building Floor Plans	N/A	N/A	N/A		
0	Special Fire Protection Systems for Protection of special Risks, if any:	N/A	N/A	N/A		

Note: - In the reply of the earlier shortcomings issued to vide letter no. F6/DFS/MS/School/WZ/2023/369 dated 31/08/2023, the school management has submitted an affidavit that school falls under non-confirming area, so the school was not approved from MCD.

Fire protection systems provided in the building were checked and found functional at the time of inspection.

Keeping in view substantial compliance of the minimum standards on fire prevention and fire safety requirements under the rules, grant of Fire safety Certificate is recommended under rule 35 of the Delhi Fire service Rules 2010 under the DFS Act 2007.

Accordingly, DFA is put up for approval please.

Aman Kumar Lathar ADO (JWP)

PP)2/m/

ACT LEASTON POSTONE

Arrecter My 9 2