## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE, CONNAUGHT PLACE NEW DELHI

No.F6/DFS/MS/SZ/2024/EH 319

Dated: 09//0/2024

## FIRE SAFETY CERTIFICATE

Certified that the M/S Drool kitchen (A unit of 4RS Hospitality Pvt. Ltd.), is running at ground floor of Metro Commercial Space, Metro station, Sec – 10, Dwarka, New Delhi – 110075 was issued FSC by this department vide letter no. F6/DFS/MS/SZ/2021/193 dated 24/08/2021 (FSC issued to metro station F6/DFS/MS/SZ/2023/147 dated 17/03/2023) The premises was inspected by the officer concerned of this department on 03/10/2024 in the presence of Sh. Suresh (Manager) and found that the premises have deemed complied with fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules 2010, and that the building is fit for occupancy class "Assembly" Group D with effect from 09/10/2024 for a period of three years in accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under Rule 38 of the Delhi Fire Service Rules, 2010

Issued on ... 0.9.110.2.2.4. at New Delhi by.

Copy to:

- 1. The Joint. Commissioner of Police (Lic), 1<sup>st</sup> Floor, Licensing Unit, Police Station, Defence Colony, New Delhi.
- 2. The Executive Engineer (Building), MCD, Civic Centre, Minto Road, New Delhi
- 3. The Manager, M/S Drool kitchen (A unit of 4RS Hospitality Pvt. Ltd.) Metro Commercial Space, Metro station, Sec 10, Dwarka, New Delhi 110075.

## Condition for the validity of fire safety certificate:-

- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- 2. Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.
- 3. The trained staff should be available round the clock.
- 4. Any deviations w.r.t. construction shall be verified by the concerned building sanctioning agency.
- 5. The certificate may not be treated in any case for the regularization of the unauthorized construction, if any.
- 6. Basement shall be used as per building bye laws.
- 7. The owner/occupier shall submit a declaration every year in the form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on <a href="https://www.dfs.delhigovt.nic.in">www.dfs.delhigovt.nic.in</a>.
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its expiry.

## INSPECTION REPORT

1. Name & address of the building: M/S Drool kitchen (A unit of 4RS Hospitality Pvt. Ltd.) at Metro Commercial Space, Metro station, Sec – 10, Dwarka, New Delhi – 110075

2. Type of Occupancy : Class-D (Assembly)( Restaurant- Ground floor)

3. Type of Case : Renewal

 Details of previous NOC: F6/DFS/MS/SZ/2021/193 dated 24/08/2021 (F6/DFS/MS/SZ/2023/147 dated 17/03/2023 issued to Sector 10 Metro Station)

5. Fire Safety directives Letter No.: Nil

6. Date of inspection : 03/10/2024

7. Name of the Inspecting Officer; Sh. Udai vir Singh ADO (DWK)

8. Name and designation of Officer

from the building side : Sh. Suresh (Manager)

9. Year of Construction : 2010

10. Applicant's letter No. : 2024091614324 dated 16/09/2024

S No	Minimum standards on fire prevention and fire safety U/R 33	As per N/18, N/19 & N/20		Provided at site	Remarks MR/NMR	
1.	Access of building  Road width	12 mtrs		12 mtr	MR	
	Gate width     Width of internal road	4.5 mtr NA		tly accessible from NA	road MR NA	
2.	Number, width, Type & Arrangeme  a. Number of staircases  • Upper floors  • Basements  b. Width of staircases  • Upper floors  • Basements  c. Protection of exits  • Fire check door  • Pressurization  d. No of continuous staircase to terrace  e. Width Of Corridor	NA N		NA N	NA N	
	f. Door Size  Compartmentation	02 mu	- v		case)	
3.	<ul> <li>Fire check door</li> <li>Sealing of electrical shafts</li> <li>Fire Rating of shaft door</li> <li>Water Curtain</li> <li>Fire Dampers</li> </ul>	NA		NA	NA NA	
		NA		NA	NA	
		NA		NA	NA NA	
		NA		NA	NA NA	
		NA		NA	NA .	

4.	Smoke managements System				
	Basements	NA	NA		NA
	<ul> <li>Upper floors</li> </ul>	12 a/c per hour	Exhaust fans F	rovided	MR
5.	Fire Extinguishers				
	Total numbers	08 Nos.	08 Nos.		MR
	<ul> <li>Types</li> </ul>	ABC, CO2	ABC		MR
	IS marking	ISI marked	Provided		MR
6.	First – Aid Hose Reel				
	<ul> <li>Total numbers on each</li> </ul>	01 No	Provided		MR
	floor			-	
	<ul> <li>Length of hose reel hose</li> </ul>	30 mtr	Provided		MR
	<ul> <li>Nozzle diameter</li> </ul>	5 mm	Provided		MR
7.	Automatic fire detection and alarmin				
	<ul> <li>Type of detectors</li> </ul>	Smoke	Provided	M	
	<ul> <li>Location of Main Panel</li> </ul>	Reception	Reception	M	
	<ul> <li>Location of Repeater Panel</li> </ul>	NA	NA	N/	
	<ul> <li>Alternate source of power</li> </ul>	Required	Battery backu		
	<ul> <li>Hooters' Location</li> </ul>	Near entry	Provided	M	R
8.	MOEFA	Required	Provided	M	R
9.	Public Address System	Required Provided		M	R
10.	Automatic Sprinkler System				
	Basements	NA	NA	N.	
	Upper Floor	Ground floor	Provided		MR
	Sprinkler above false	NA	NA	N	A
	ceiling	· ·			
11.	Internal Hydrants:	*			
- 1	Size of riser/down-comer	100 mm	Provided	M	ſR
_	Number of hydrants per	Ground floor	02	M	ſR
j 8	floor				
	Hose Box	Required	Provided	N	ſR
12.	Yard Hydrants	1			
12.	Total number of hydrants	NA	NA	N	IA
	Hose Box	NA	NA	N	ΙA
13.	Pumping Arrangements: Common	THE P. P. LEWIS CO., LANSING MICH.			
13.	Ground Level	The state of the s	: 0		
		NA	1800 lpm	1	NA
	Discharge of main pump  Head of main nump	NA	70 mtr		NA
	Head of main pump	NA	01		NA
	Number of main pumps	NA	180 lpm		NA
	> Jockey pump out put		70 mtr		NA
	> Jockey pump head	NA	1800 lpn	1	NA
	Standby Pump Out put	NA	70 mtr		NA NA
1	Standby Pump Head	NA		ı	NA NA
	Auto Staring/Manual	NA	Provided		NA NA
	stopping > Pump House Access	NA	Provided	1	IVA
1	Terrace level			MD or numn	
		450 LPM	Not provided	MR as pump at G. level at higher side	
	Discharge of pump				
	<ul><li>Head of the pump</li><li>Power supply</li></ul>		Not provided		
		Required	Not provided		00
	Auto starting of pump	Required	Not provided	D	00

1/25 Captive water Storage for fire fighting: Common with Metro Station Under ground tank capacity Draw off connection NA 50000ltrs NA Fire service inlet NA Provided NA NA Access to tank Provided NA NA

Provided

NA

-	<ul> <li>Overhead Tank capacity</li> </ul>		Provided	l NA			
15	Exit Signage	10000 ltrs	Not Provided	MR as pump at G. level at higher side			
_	D	Required	Provided	MR			
16.	Provision of Lifts		Trovided	IVIIX			
	Pressurization of Lift Shaft	NA	NA	NA			
1	Pressurization of lift lobby	NA	NA	NA			
ı	Communication in lift Car	NA	NA	NA			
	<ul><li>Fireman's Grounding</li><li>Switch</li><li>Lift Signage</li></ul>	NA	NA	NA			
		NA	NA	NA			
17.	Standby power supply	Required	DG set 125	KVA MR			
18.	Refuge Area	1					
	> Total area	NA	NA	NA			
	Location	NA	NA	NA			
19.	Fire control room						
	> Detector system panel	NA	NA	NA			
	➤ Flow Switch Panel	NA	NA	NA			
	> PA System Panel	NA	NA	NA			
	> Battery backup	NA	NA	NA			
	➤ Building Floor Plans	NA	NA	NA			
20							

The fire protection systems provided in the building were test checked and found

functional at the time of inspection.

Overhead Tank capacity

In view of the deemed compliance of minimum standards on fire prevention and fire safety as required under the rules the FSC issued vide letter no. F6/DFS/MS/SZ/2021/193 dated 24/08/2021 renewal under Rule 37 of the Delhi Fire Service Rules 2010 is recommended.

Signature of the Inspecting Officer

Name: Sh. Udaivir Singh Designation: ADO (DWK)

velandes