GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI - 110001

No.F6/DFS/MS/GH/NDZ/2024/ 405

Dated: 10/19/2024

FIRE SAFETY CERTIFICATE

Certified that the Mid Town Guest House located at 3647, Gali Ram Nath Patwa, Pahar Ganj, New Delhi comprised of Ground floor (Reception + 02 guest rooms), 1st floor to 3rd floor (04 guest rooms at each floor) and 4th floor found sealed and submitted an affidavit dated 16.10.2019 regarding not to use any floor above third floor - total 14 guest rooms up to third floor, was earlier granted FSC by this department vide letter No.F6/DFS/MS/GH/NDZ/2021/443 dated 29/09/21. Now, the premise was re-inspected by the officer concerned of this department on 01/10/24 in the presence of Manager and found that the said guest house has deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Residential, Sub Division-A-1 Ground floor (Reception + 02 guest rooms), 1st floor to 3rd floor (04 guest rooms at each floor) Total -14 guest rooms at ground to 3rd floor only and valid up to the period of three year from the date of issue in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued10/10/2024at New Delhi by.

Copy to:-

1. The Commissioner, North MCD, Civic Centre, New Delhi. : to ensure the occupancy as detailed above

2. The Addl. Commissioner of Police (Lic), First Floor, P.S. Defence Colony New Delhi. ID No 2024091014060 dated 10.09.24.

3. The Manager, Mid Town Guest House 3647, Gali Ram Nath Patwa, Pahar Ganj, New Delhi.

Conditions for the validity of fire safety certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times. This FSC is valid for guest house up to third floor only.
- 2. Any loss of life or property due to nonfunctional fire safety measures shall be at the responsibility of the management.

3. The trained fire fighting staff should be available round the clock.

- 4. The compliance with regards to electrical installation, structural stability, set back area, occupancy and any deviation in construction etc. shall be verified from authority concerned.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. The means of escape such as staircase, exits, corridor, etc shall be kept unobstructed / unlocked for unhindered evacuation in case of an emergency.
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".

9. Any flammable material for interior decoration is prohibited.

NIZZ

INSPECTION REPORT

1. Name & address of the building

Mid Town Guest House at 3647, Gali Ram Nath Patwa, Pahar Ganj, New Delhi.

2. Type of occupancy:-

Residential, Sub Division-A-1

Gr. + 04 Upper floors (total 14 guest rooms) Ground floor (reception + 02 guest rooms), 1st floor to 3rd floor (04 guest rooms at each floor) and 4th floor found sealed and an affidavit dated 16.10.2019 given by owner regarding not to use

3. Type of case:-

any floor above third floor. Renewal

4. Details of previous FSC:-

F6/DFS/MS/GH/NDZ/2021/443 dated

29/09/21.

5. Fire safety directives No.-

N/A

6. Date of inspection:-

01/10/24

7. Name of the inspecting officer:-

Sh. Ravinder Singh (ADO/CC)

8. Name & designation of officer From the building side:-

Manager

9. Year of construction:-

old

10. Applicant's letter No:-

ID No 2024091014060 dated 10.09.24.

Old Case S.No. Minimum Standards on fire Requirement/ Provided at site Remarks Prevention and fire safety U/R 33 Existing fire safety MR/NMR arrangements 1. Access to Building 1) Road width N/A N/A N/A 2) Gate width N/A N/A N/A 3) Width of internal road N/A N/A N/A Number, Width Type & Arrangement of Exits 2. A. Number of staircases 1. Upper floors 01 No. 01 No. MR 2. Basements N/A N/A N/A B. Width of staircase 1. Upper floors 0.80 mtr. 1.08mtr. MR 2. Basements N/A N/A N/A C. Protection of exits 1. Fire check door N/A N/A N/A 2. Pressurization N/A N/A N/A D. No. of continuous staircase to terrace N/A N/A N/A E. Width of corridor N/A N/A N/A F. Door size 1 mtr. 1 mtr. MR 3. Compartmentation 1) Fire check door N/A N/A N/A 2) Sealing of electrical shafts N/A N/A N/A 3) Fire rating of shaft door N/A N/A N/A 4) Water curtain N/A N/A N/A 5) Fire Dampers N/A N/A N/A 4. Smoke Management System 1) Basements N/A NA N/A 2) Upper floors Required Provided MR 5. Fire Extinguishers 1) Total numbers 08 Nos. 08 Nos. MR 2) Types ABC & CO2 ABC & CO2 MR 3) ISI marking Required Provided MR First-Aid Hose Reel 6. 1) Total number of eachfloor 01 01 MR

1	24

	34			1,70
	2) Length of hose reel hose	30 mtr.	30 mtr.	MR
	3) Nozzle diameter	05 mm	05 mm	MR
7.	Automatic Fire Detection &			
	1) Type of detectors Co type	Required	Provided	MR
	2) Location of main panel	Gr. floor	Provided	MR
	3) Location of repeater panel	N/A	N/A	N/A
	4) Alternate source of power	Required	Provided	MR
	5) Hooter's Location	Gr. floor	Provided	MR
8.	MOEFA	N/A	N/A	N/A
9.	Public Address System	N/A	N/A	N/A
10.	Automatic Sprinkler System			
	1) Basement	N/A	N/A	N/A
	2) Upper floors	N/A	N/A	N/A
	3) Sprinkler above false	N/A	N/A	N/A
	ceiling	-		1
1.	Internal Hydrants			
-	1) Size of riser/down-comer	N/A	N/A	N/A
	2) Number of hydrants per	N/A	N/A	N/A
	floor		1.07	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
	3) Hose box	N/A	N/A	N/A
12.	Yard Hydrants			17072
	1) Total number of hydrants	N/A	N/A	N/A
	2) Hose box	N/A	N/A	N/A
3.	Pumping Arrangement	1		1
V	1) Ground level	N/A	N/A	N/A
	a) Discharge of main	N/A	N/A	N/A
	pump			1
1	b) Head of main pump	N/A	N/A	N/A
	c) Number of main pump		N/A	N/A
	d) Jockey pump out put	N/A	N/A	N/A
	e) Jockey pump head	N/A	N/A	N/A
	f) Stand by pump output	N/A	N/A	N/A
	g) Stand by pump head	N/A	N/A	N/A
	h) Auto starting/Manual	N/A	N/A	N/A
	stopping	1		
-	2) Terrace level			
	a) Discharge of pump	220 LPM	220 LPM	MR
	b) Head of pump	30 mtr.	30 mtr.	MR
	c) Power supply	Required	Provided	MR
	d) Auto starting of pump	Required	Provided	MR
14.	Captive Water Storage for Fire Fighting			LNIA
1	1) Under ground tank	N/A	N/A	N/A
	a) Draw-off connection	N/A	N/A	N/A
		N/A N/A	N/A N/A	N/A N/A
	· ·	N/A N/A	N/A N/A	N/A N/A
	d) Over head tank	2500 ltr.	2500 ltr.	MR
	apacity	2500 Itt.	2500 III.	TVIII.
15.	Exit Signage.	Required	Provided	MR
16.	Provision of Lifts.		era zlobalitaca	
		N/A	N/A	N/A

NI	25
----	----

	shaft	7012		
	b) Pressurization of lift lobby	N/A	N/A	N/A
	c) Communication in lift car	N/A	N/A	N/A
	d) Fireman's switch	N/A	N/A	N/A
17.	e) Lift signage	N/A	N/A	N/A
	Stand by Power Supply	Required	Provided	MR
18.	Refuge Area	N/A	N/A	N/A
Total are	Total area location	N/A	N/A	N/A
b) Flow switch p c) PA system par	Fire Control Room	N/A	N/A	N/A
	a) Detector system panel	N/A	N/A	N/A
	b) Flow switch panel	N/A	N/A	N/A
		N/A	N/A	N/A
		N/A	N/A	N/A
	e) Building floor plan	N/A	N/A	N/A
20.	Special Fire Protection System for Protection of special Risk, if any:			N/A

The fire protection systems provided in the building were randomly tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules, if agreed, we may renew the FSC issued vide letter no. F6/DFS/MS/GH/NDZ/2021/443 dated 29/09/21, under rule 35(6) of the Delhi Fire Service rules 2010. Accordingly, reply letter is prepared and put up for kind perusal and signature please.

Signature of the Inspecting Officer

Name: - Ravinder Singh Designation :- ADO (CC)

of perturbooken peruelacal