## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI - 110001

No.F6/DFS/MS/GH/NDZ/2024/ 404

Dated: 1.0/.10/2024

FIRE SAFETY CERTIFICATE

Certified that the Suvidha Tourist Lodge Guest House located at 3418-21, Hari Mandir Marg, Pahar Ganj, New Delhi comprised of Ground floor (reception + 01 guest rooms), 1<sup>st</sup> floor to 3<sup>rd</sup> floor (02 guest rooms at each floor), 4<sup>th</sup> floor & above floor not in use as per affidavit dated 28.02.2020 total 07 guest rooms owned/occupied by Suvidha Tourist Lodge Guest House. The FSC was earlier granted by this department vide letter No.F6/DFS/MS/GH/NDZ/2021/451 dated 30/09/2021 for total 08 guest room. Now, the premise was re-inspected by the officers concerned of this department on 01/10/24 in the presence of Sh. Ansari Ahamad and found that the said guest has deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Residential, Sub Division-A-1 Ground floor (reception + 01 guest rooms), 1st floor to 3rd floor (02 guest rooms at each floor) -total -07 guest rooms upto third floor and valid up to the period of three year from the date of issue in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued ... 10 10 2024 .... at New Delhi by.

Copy to:-

1. The Commissioner, North MCD, Civic Centre, New Delhi : to kindly ensure the occupancy in the building as detailed above and deviation if any .

2. The Addl. Commissioner of Police (Lic), First Floor, P.S. Defence Colony New Delhi.

ID NO 2024091114083 dated 11.09.24.

3. The Manager, Suvidha Tourist Lodge Guest House at 3418-21, Hari Mandir Marg, Pahar Gani, New Delhi.

Conditions for the validity of fire safety certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times. This FSC is valid for guest house up to third floor only.
- 2. Any loss of life or property due to nonfunctional fire safety measures shall be at the responsibility of the management.

3. The trained fire fighting staff should be available round the clock.

4. The compliance with regards to electrical installation, structural stability, set back area, occupancy and any deviation in construction etc. shall be verified from authority concerned.

5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.

- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. The means of escape such as staircase, exits, corridor, etc shall be kept unobstructed / unlocked for unhindered evacuation in case of an emergency.
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".

9. Any flammable material for interior decoration is prohibited.

1	<u>INSPE</u> Name & address of the building	CTION REPOR			
1.	ivalle & address of the building		rist Lodge Guest F	louse at	
			ri Mandir Marg, Pa	ihar Ganj,	
2	Type of occupancy:-	New Delhi			
L.	Type of occupancy:-	Residential, Sub Division-A-1			
	is in		floors (total-07 guest		
		Ground floor (reception + 01 guest rooms), 1st floor to 3rdh floor (02 guest rooms at each floor) and 4th floor not in use as per affidavit dated 28.02.2020 Renewal			
	9				
	Type of case:-				
<ol><li>Details of previous FSC:-</li></ol>		No.F6/DFS/MS/GH/NDZ/2021/451 dated			
-		30/09/21. N/A 01/10/24			
	Fire safety directives No				
	Date of inspection:-				
	Name of the inspecting officer:	- Sh. Ravinder	Singh, ADO/CC		
8.	Name & designation of officer				
^	From the building side:-	Sh. Ansari A	hamad	90	
	Year of construction:-	1995	505050505 (Mr. 8) 12 12741W		
10.	Applicant's letter No:-	ID NO 2024091	.114083 dated 11/		
	[xc: o : : 5	The Control of the Control of the P	THE DATE OF SHIP STATES	se( Renewal)	
S.No.	Minimum Standards on fire Prevention and fire safety U/R 33	Requirement/ Existing fire safety	Provided at site	Remarks	
	Flevention and the salety O/R 33	arrangements		MR/NMR	
l.	Access to Building				
	1) Road width	N/A	N/A	N/A	
	2) Gate width	N/A	N/A	N/A	
	3)Width of internal road	N/A	N/A	N/A	
2.	Number, Width Type & Arr.	The respondences	its		
7.24	A. Number of staircases				
	1. Upper floors	01 No.	01 No.	MR	
	2. Basements	N/A	N/A	N/A	
	B. Width of staircase				
	1. Upper floors	0.80 mtr.	0.85mtr.	MR	
	Upper floors     Basements	0.80 mtr. N/A	0.85mtr. N/A	MR N/A	
	2. Basements	ACCOUNTED MINORANA		MR N/A	
		ACCOUNTED MINORANA		N/A	
	2. Basements C. Protection of exits	N/A	N/A N/A	Development	
	Basements     C. Protection of exits     Fire check door	N/A N/A	N/A	N/A N/A N/A	
	Basements     C. Protection of exits     Fire check door     Pressurization     No. of continuous staircase to terrace	N/A N/A N/A N/A	N/A N/A N/A N/A	N/A N/A N/A N/A	
	Basements     C. Protection of exits     Fire check door     Pressurization     No. of continuous staircase to terrace     Width of corridor	N/A N/A N/A N/A	N/A N/A N/A N/A	N/A N/A N/A N/A	
2	Basements     C. Protection of exits     Fire check door     Pressurization     No. of continuous staircase to terrace     Width of corridor     F. Door size	N/A N/A N/A N/A	N/A N/A N/A N/A	N/A N/A N/A N/A	
3.	2. Basements C. Protection of exits 1. Fire check door 2. Pressurization D. No. of continuous staircase to terrace E. Width of corridor F. Door size Compartmentation	N/A N/A N/A N/A N/A 1 mtr.	N/A N/A N/A N/A N/A 1 mtr.	N/A N/A N/A N/A N/A MR	
3.	2. Basements C. Protection of exits 1. Fire check door 2. Pressurization D. No. of continuous staircase to terrace E. Width of corridor F. Door size Compartmentation 1) Fire check door	N/A N/A N/A N/A N/A N/A N/A N/A	N/A N/A N/A N/A N/A N/A N/A N/A N/A	N/A N/A N/A N/A N/A N/A N/A	
3.	2. Basements C. Protection of exits 1. Fire check door 2. Pressurization D. No. of continuous staircase to terrace E. Width of corridor F. Door size Compartmentation 1) Fire check door 2) Sealing of electrical shafts	N/A N/A N/A N/A N/A 1 mtr.	N/A N/A N/A N/A N/A 1 mtr. N/A N/A	N/A N/A N/A N/A N/A N/A N/A N/A N/A	
3.	2. Basements C. Protection of exits 1. Fire check door 2. Pressurization D. No of continuous staircase to terrace E. Width of corridor F. Door size Compartmentation 1) Fire check door 2) Sealing of electrical shafts 3) Fire rating of shaft door	N/A N/A N/A N/A 1 mtr.  N/A N/A N/A	N/A N/A N/A N/A N/A I mtr.  N/A N/A N/A N/A N/A	N/A	
3.	2. Basements C. Protection of exits 1. Fire check door 2. Pressurization D. No of continuous staircase to terrace E. Width of corridor F. Door size Compartmentation 1) Fire check door 2) Sealing of electrical shafts 3) Fire rating of shaft door 4) Water curtain	N/A N/A N/A N/A 1 mtr.  N/A N/A N/A N/A N/A N/A	N/A N/A N/A N/A N/A 1 mtr.  N/A N/A N/A N/A N/A N/A	N/A	
	2. Basements C. Protection of exits 1. Fire check door 2. Pressurization D. No of continuous staircase to terrace E. Width of corridor F. Door size Compartmentation 1) Fire check door 2) Sealing of electrical shafts 3) Fire rating of shaft door 4) Water curtain 5) Fire Dampers	N/A N/A N/A N/A 1 mtr.  N/A N/A N/A N/A N/A N/A N/A	N/A N/A N/A N/A N/A I mtr.  N/A N/A N/A N/A N/A	N/A	
<b>3. 4.</b>	2. Basements C. Protection of exits 1. Fire check door 2. Pressurization D. No of continuous staircase to terrace E. Width of corridor F. Door size Compartmentation 1) Fire check door 2) Sealing of electrical shafts 3) Fire rating of shaft door 4) Water curtain 5) Fire Dampers Smoke Management System	N/A N/A N/A N/A N/A 1 mtr.  N/A N/A N/A N/A N/A N/A N/A	N/A  N/A  N/A  N/A  N/A  1 mtr.  N/A  N/A  N/A  N/A  N/A  N/A  N/A  N/	N/A	
	2. Basements C. Protection of exits 1. Fire check door 2. Pressurization D. No of continuous staircase to terrace E. Width of corridor F. Door size Compartmentation 1) Fire check door 2) Sealing of electrical shafts 3) Fire rating of shaft door 4) Water curtain 5) Fire Dampers	N/A N/A N/A N/A 1 mtr.  N/A N/A N/A N/A N/A N/A N/A	N/A N/A N/A N/A N/A 1 mtr.  N/A N/A N/A N/A N/A N/A	N/A	

10 Nos.

10 Nos.

MR

1) Total numbers

NB

	2) Types	ABC & CO2	ABC & CO2	MR		
İ	3) ISI marking	Required	Provided	MR		
	First-Aid Hose Reel					
	1) Total number of eachfloor	N/A	N/A	N/A		
1	2) Length of hose reel hose	N/A	N/A	N/A		
	3) Nozzle diameter	N/A	N/A	N/A		
	Automatic Fire Detection & Alarming System					
	1) Type of detectors CO type	Required	provided	MR		
	2) Location of main panel	Required	provided	MR		
	3) Location of repeater panel	N/A	N/A	N/A		
14	4) Alternate source of power	Required	provided	MR		
	5) Hooter's Location	Required	provided	MR		
	MOEFA	N/A	N/A	N/A		
	Public Address System	N/A	N/A	N/A		
).	Automatic Sprinkler System			N. C.		
•	1) Basement	N/A	N/A	N/A		
	2) Upper floors	N/A	N/A	N/A		
	3) Sprinkler above false	N/A	N/A	N/A		
	ceiling					
l	Internal Hydrants					
	1) Size of riser/down-comer	N/A	N/A	N/A		
	2) Number of hydrants per	N/A	N/A	N/A		
	floor					
	3) Hose box	N/A	N/A	N/A		
2.	Yard Hydrants			1.		
	1) Total number of hydrants	N/A	N/A	N/A		
	2) Hose box	N/A	N/A	N/A		
13.	Pumping Arrangement					
10.	1) Ground level	N/A	N/A	N/A		
	a) Discharge of main	N/A	N/A	N/A		
	pump			1		
	b) Head of main	N/A	N/A	N/A		
	pump			1		
	c) Number of main	N/A	N/A	N/A		
	pump			NI/A		
	d) Jockey pump out	N/A	N/A	N/A		
	put	37/4	NIA	N/A		
	e) Jockey pump head	N/A	N/A	N/A N/A		
	f) Stand by pump	N/A	N/A	IN/A		
	output	NI/A	N/A	N/A		
	g) Stand by pump	N/A	14/74	1071		
	head	N/A	N/A	N/A		
1	h) Auto starting/Manual	IVA .	11121	3.000.00		
1	stopping					
	2) Terrace level		X.			
1	a) Discharge of pump	N/A	N/A	N/A		
	w/ Distinct of paint	N/A	N/A	N/A		
		111/71				
	b) Head of pump	N/A	N/A	N/A		
		I Cresses parent		N/A N/A		

	<ol> <li>Under ground tank capacity</li> </ol>	N/A	N/A	N/A
	a) Draw-off connection	N/A	N/A	N/A
	b) Fire service inlet	N/A	N/A	N/A N/A
	c) Access to tank	N/A	N/A	N/A N/A
	d) Over head tank capacity	N/A	N/A	N/A N/A
15.	Exit Signage.	Required	Provided	MR
16.	Provision of Lifts.	required	Flovided	MK
	a) Pressurization of lift shaft	N/A	N/A	N/A
	b) Pressurization of lift lobby	N/A	N/A	N/A
	c) Communication in lift car	N/A	N/A	N/A
	d) Fireman's switch	N/A	N/A	N/A
	e) Lift signage	N/A	N/A	N/A
17.	Stand by Power Supply	Required	Provided	MR
18.	Refuge Area	N/A	N/A	N/A
3	Total area location	N/A	N/A	N/A
19.	Fire Control Room	N/A	N/A	N/A
	a) Detector system panel	N/A	N/A	N/A
	b) Flow switch panel	N/A	N/A	N/A
-	c) PA system panel	N/A	N/A	N/A
	d) Battery backup	N/A	N/A	N/A
	e) Building floor plan	N/A	N/A	N/A
20.	Special Fire Protection System Risk, if any:	n for Protec	tion of special	N/A

The fire protection systems provided in the building were randomly tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules, if agreed, we may renew the FSC issued vide letter no. No.F6/DFS/MS/GH/NDZ/2021/451 dated 30/09/21, under rule 35(6) of the Delhi Fire Service rules 2010. Accordingly, reply letter is prepared and put up for kind perusal and signature please.

Signature of the Inspecting Officer

Name: - Ravinder Singh Designation :- ADO (CC)

4/x/24

Dych (MDZ)

1 mgr

Director Mild 2

Liv Stign

April 9

ON