

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE, NEW DELHI – 110001

No. F6/DFS/MS/GH/NDZ/2024/ 419

Dated: | 8 / | 0 /2024

FIRE SAFETY CERTIFICATE

Certified that the M/s Aslam Guest House located at 501, Gali Matia Mahal, Jama Masjid Delhi, comprised of Ground + 03 upper floors: Ground floor- (commercial), 1st floor - (08 guest rooms + reception), 2nd floor - (08 guest rooms) & 3rd floor - (09 guest rooms), total 25 guest rooms was granted FSC by this department vide letter no. F6/DFS/MS/GH/NDZ/2021/461 dated 30.09.2021. The building/premises was re-inspected by the officer concerned of this department on 09.10.2024 in presence of Mohd. Ajmal (Owner) and found that the building has deemed complied with the fire prevention and fire safety requirements in accordance with Rule 33 of Delhi Fire Service Rules, 2010. Accordingly, the premises is fit for occupancy of "Group A-1 (Residential)", 1st floor - (08 guest rooms), 2nd floor - (08 guest rooms) & 3rd floor- (09 guest rooms) for total 25 guest rooms upto 3rd floor only, with effect from18. 10. 2024... for a period of three years in accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to conditions under Rule 38 of Delhi Fire Service Rules, 2010 printed below.

Issued on 18 10 2024 at New Delhi by

hi Fire Service

Copy to:-

- 1. The Joint Commissioner of Police (Licensing), 1st Floor, Police Station Defence Colony, New Delhi. w.r.to ID No. 2024092414690 dated 24.09.2024.
- 2. The Licensee, M/s Aslam Guest House at 501, Gali Matia Mahal, Jama Masjid Delhi.

Conditions for the validity of fire safety certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".
- 8. Any change in the occupancy shall be intimated to this Deptt. and approval shall be obtained thereto before occupancy of the same.

1	Non		ECTION REPORT		Coli Mos	
		& address of the building		M/s Aslam Guest House at 501, Gali Mat Mahal, Jama Masjid, Delhi - 06.		
2	Build	ing is comprised of	Ground + 03 upper floors Ground floor – (commercial use) 1 st floor – (08 guest rooms + reception) 2 nd floor – (08 guest rooms) 3 rd floor – (09 guest rooms)			
3	Type	of occupancy	Residential Group A-1			
4		of case	Renewal			
5		ils of previous FSC	F6/DFS/MS/GH/	F6/DFS/MS/GH/NDZ/2021/461 dated 30.09.202		
6		safety direction letter no.	Nil			
7		of inspection	09.10.2024	25 VSST		
100			** ****	Sumit Kumar, ADO (SPM)		
8		e of the inspecting officers				
9	offic	e of the designation of er from the building side		Mohd. Ajmal (Owner)		
10	Year	of construction		Old		
11	App	licant's letter no.	Online application no. 2024092414690 date 24.09.2024			
S.No	Pre	imum Standards on fire vention and fire safety uirements U/R 33	Requirement/ Existing fire safety arrangements	Provided at Site	Remark MR/ NMR	
1	Acc	ess To Building:	, w			
•		d width	NA (special area)	2.43 m	NA	
	Gat	e width	NA	NA	NA	
		Ith of internal road	NA	NA	NA	
2	Nu	nber, Width, Type and Arı	rangement of Exits:			
	A	Number of staircases				
		a Upper floor	01 no.	01 no.	MR	
		b Basement	NA	NA	NA	
				 	1411	
-	В	Width of staircases	0.00	1.10		
	В	Width of staircases a Upper floor	0.80 m	1.10 m	MR	
		Width of staircases a Upper floor b Basement	0.80 m NA	1.10 m NA		
	С	Width of staircases a Upper floor b Basement Protection of exits	NA	NA	MR NA	
		Width of staircases a Upper floor b Basement Protection of exits a Fire check door			MR	
		Width of staircases a Upper floor b Basement Protection of exits a Fire check door b Pressurization No. of continuous staircase to terrace	NA NA NA	NA NA NA NA	MR NA	
	C	Width of staircases a Upper floor b Basement Protection of exits a Fire check door b Pressurization No. of continuous staircase	NA NA NA NA NA NA	NA NA NA NA	MR NA NA	
	C D E F	Width of staircases a Upper floor b Basement Protection of exits a Fire check door b Pressurization No. of continuous staircase to terrace Width of corridor Door size	NA NA NA NA	NA NA NA NA	MR NA NA NA NA	
3	C D E F Co	Width of staircases a Upper floor b Basement Protection of exits a Fire check door b Pressurization No. of continuous staircase to terrace Width of corridor Door size mpartmentation:	NA NA NA NA NA 1.25 m	NA NA NA NA 1.25 m	MR NA NA NA NA NA	
3	C D E F Co A	Width of staircases a Upper floor b Basement Protection of exits a Fire check door b Pressurization No. of continuous staircase to terrace Width of corridor Door size mpartmentation: Fire check door	NA NA NA NA NA 1.25 m	NA NA NA NA 1.25 m	MR NA NA NA NA NA NA	
3	C D E F Co A B	Width of staircases a Upper floor b Basement Protection of exits a Fire check door b Pressurization No. of continuous staircase to terrace Width of corridor Door size mpartmentation: Fire check door Sealing of electrical shafts	NA NA NA NA NA 1.25 m	NA NA NA NA 1.25 m NA	MR NA	
3	C D E F Co A B C	Width of staircases a Upper floor b Basement Protection of exits a Fire check door b Pressurization No. of continuous staircase to terrace Width of corridor Door size mpartmentation: Fire check door Sealing of electrical shafts Fire rating of shaft door	NA NA NA NA 1.25 m NA NA NA NA	NA NA NA NA 1.25 m NA NA NA	MR NA	
3	C D E F Co A B C D	Width of staircases a Upper floor b Basement Protection of exits a Fire check door b Pressurization No. of continuous staircase to terrace Width of corridor Door size mpartmentation: Fire check door Sealing of electrical shafts Fire rating of shaft door Water curtain	NA	NA NA NA NA 1.25 m NA NA NA NA NA NA	MR NA	
3	C D E F Co A B C D E	Width of staircases a Upper floor b Basement Protection of exits a Fire check door b Pressurization No. of continuous staircase to terrace Width of corridor Door size mpartmentation: Fire check door Sealing of electrical shafts Fire rating of shaft door Water curtain Fire dampers	NA NA NA NA 1.25 m NA NA NA NA	NA NA NA NA 1.25 m NA NA NA	MR NA	
	C D E F Co A B C D E	Width of staircases a Upper floor b Basement Protection of exits a Fire check door b Pressurization No. of continuous staircase to terrace Width of corridor Door size mpartmentation: Fire check door Sealing of electrical shafts Fire rating of shaft door Water curtain	NA	NA NA NA NA 1.25 m NA NA NA NA NA NA	MR NA	

5.	A	Extinguisher: Total numbers	06 nos.	08 nos.		
-	B	Types	CO ₂ & ABC	Provided		
1			Required	Provided		
	C	ISI marking	Required	Provided		
6						
	A	floor	or no.	01 no.		
1	В	Length of hose reel hose	30 m	30 m		
1	C	Nozzle diameter	05 mm	05 mm		
7		natic Fire Detection And Alar	2 2 277772	V3 IIIII		
1	A	Type of detectors (CO	Required	Provided		
1	A .	type)	Required	Flovided		
	В	Location of main panel	Required	Provided at 1st		
			1	floor		
	C	Location of repeater	NA	NA		
		panel				
	D	Alternate source of power		NA		
	E	Hooters	Required	Provided		
8	MOEF		NA	NA		
9		Address System:	Required	Provided		
10	Autom	atic Sprinkler System:		•		
	A	Basement	NA	NA		
	В	Upper floor	NA	NA		
	C	Sprinkler above false	NA	NA		
		ceiling	IVA.	INA		
11	Interna	l Hydrants:		1		
	A	size of riser/down-comer	NA	NA		
	В	Number of hydrants per	NA	NA NA		
4		floor	144			
	C	Hose box	NA	NA		
12	Yard H	ydrants:	4			
	A	Total number of hydrants	NA	NA		
	B·	Hose box	NA NA	NA NA		
12			INA	NA .		
13	Pumping Arrangements:					
-	A	Ground level	T	T		
	a)	Discharge of main pump	NA	NA		
	b)	Head of main pump	NA	NA		
	c)	Number of main pumps	NA	NA		
	d)	Jockey pump out put	NA	NA		
100	e)	Jockey pump head	NA	NA		
	f)	Standby pump out put	NA	NA		
	g) h)	Standby pump head	NA	NA		
	,	Auto starting /manual stopping	NA	NA		
	i)	Pump house access	NA	NA		
	В	Terrace level	-1313	1110		
			224 1 224	Lager Dr.		
	a)	Discharge of pump	225 LPM	225 LPM		
	a) b)	Head of the pump	225 LPM 40 m	225 LPM 40 m		
	a)	Discharge of pump Head of the pump Power supply Auto starting of pump		The second secon		

14	Captive Water Stores P								
	Captive Water Storage For Fire Fighting: A Underground tank capacity NA NA NA NA								
	В	Draw-off connection	NA	NA	NA				
	C	Fire service inlet	NA	NA	NA				
	D	Access to tank	NA	NA	NA				
	E	Overhead tank capacity	NA	NA	NA				
15		it Signage:	2,500 ltrs.	2,500 ltrs.	MR				
16	Exit Signage:		Required	Provided	MR				
	Provision of Lifts:								
	A	Pressurization of lift shaft	NA	NA	NA				
	B	Pressurization of lift lobby	NA	NA NA	NA				
	C	Communication in lift car	NA	NA NA	NA				
	D	Firemen's grounding switch	NA	NA	NA				
	E	Lift signage	NA NA	NA NA	NA				
17	Sta	andby Power Supply:	Required	Provided	MR				
18	Re	Refuge Area:							
	A	Total area	NA	NA	NA				
	В	Location	NA	NA NA	NA				
19	Fire Control Room:								
	A	Detector system panel	NA	NA	NA				
	В	Flow switch panel	NA	NA	NA				
	C	Pa system panel	NA	NA	NA				
	D	Battery backup	NA	NA	NA				
	E	Building floor plans	NA	NA	NA				
20		ecial Fire Protection Systems F ecial Risks, If Any:	NA	NA					

The fire protection systems provided in the building were tested, checked at random and found functional at the time of inspection.

In view of the deemed compliance of minimum standards of fire prevention and fire safety measures as required under the Rules, the FSC issued vide letter no. F6/DFS/MS/GH/NDZ/2021/461 dated 30.09.2021 is recommended to be renewed for 25 guest rooms upto 3rd floor, under Rule 35 of the Delhi Fire Service Rules 2010.

> Signature of the Inspecting Officer Name Sumit Kumar Designation ADO (SPM)

3