



## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI **HEADQUARTERS: DELHI FIRE SERVICE, NEW DELHI-110001**

F.6/DFS/MS/EH/2024/SZ/ 343 No.

Dated: 21//o /2024

## FIRE SAFETY CERTIFICATE

Certified that M/s KFC Restaurant (A unit of Sapphire Foods India Pvt. Ltd.) located at Shop No. BG-06, Ground Floor, Ansal Plaza, Khel Gaon, Andrews Ganj, New Delhi-110049, comprised of Two Basements, Ground, Mezzanine & 03 upper floors have been issued FSC vide letter No. 05 dated 03/01/2024 and the restaurant running at ground floor, was issued Fire Safety Certificate vide this department letter No. F6/DFS/MS/EH/2021/SZ/311 dated 27/10/2021. The restaurant was re-inspected by the officer concerned of this department on 14/10/2024 in the presence of Mr. Junid (Manager) of the restaurant and observed that said premises have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the said premise is fit for occupancy class "Assembly Group D" (Eating House) up to 31/03/2027 in accordance with rule 36 unless renewal under rule 37 or sooner cancelled under rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

Issued on 21/10/2024 at New Delhi by

DIRECTOR DELHLFIRE SERVICE

## Copy to: -

1. The Joint Commissioner of Police, Licensing Branch, First Floor, Police Station Defence Colony, New Delhi-110049 (w.r.t. MHA ID: 2024100715343 dated 07/10/2024)

2. M/s KFC Restaurant (A unit of Sapphire Foods India Pvt. Ltd.) located at Shop No. BG-06, Ground Floor, Ansal Plaza, Khel Gaon, Andrews Ganj, New Delhi-110049

## Conditions for the validity of Fire Safety Certificate:

- All the means of escape/entry/exit shall be kept free from any obstruction.
- 2. All the fire safety arrangement provided therein shall be maintained in good working conditions at all time as seen during inspection. Any loss of life property due to non-functional fire safety measures shall be at the responsibility of the management.
- 3. All the staff members must know the correct method of operation of fire-fighting system.
- 4. The owner/occupier shall submit a declaration every year in form "K" provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in 5. This fire safety certificate may not in any way be treated as regularization (Clause 2.8 of UBBL-
- 2016) of unauthorized construction or alteration (Clause 1.4.3 of UBBL-2016), if any.
- 6. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule37] along with a copy of this Certificate, six months prior to its expiry.

N-2

	The state of the s				
1	Name & Address of the Building	TION REPORT			
	ess of the Building	M/s KFC Restaurant (A unit of Sapphire			
1		Foods India P	Foods India Pvt. Ltd.) at Shop No. BG-06,		
_		Ground Floor, Ansal Plaza, Khel Gaon,			
2	Type of Occupancy	Andrews Ganj, New Delhi-110049 Group-D, "Assembly" (Restaurant)			
3	Building Comprised of				
-			its, Ground, Mezz	anine +	
4	Type of Case	upper floors Renewal			
5	Details of Previous NOC				
6	Fire Safety Directives Letter No	F6/DFS/MS/EH/2021/SZ/311 dt. 27/10/202			
7	Date of Inspection	14/10/2024	Nil		
8	Name of the Inspecting Officers				
9	Name & Designation of Officers	ADO (SJ)			
	from the building side	Mr. Junid (Mar	Mr. Junid (Manager)		
10	Year of construction	100= 100=			
11		1997–1999	Restt at Gd. Floo		
S.	Applicant letter / online MHA Portal		0715343 dated 07/10	0/2024	
No.	Minimum standards on Fire	Old NOC	Provided at Site	Remark	
1	Prevention and Fire Safety U/R 33	Requirements		MR/NM	
-	Road width		No. F.6/DFS/MS/Mixed/SZ/2024/05 dated 03/01/2024		
		6m	Provided	MR	
	• Gate width	4.5m	Provided	MR	
2	Width of internal road	6m	Provided	MR	
2	Number, width, type & arrangement of exits.				
	a) Number of Staircase		intained by Ansal Pl		
	> Upper floors.	-NA-	-NA-	-NA-	
	Basement floor.	-NA-	-NA-	-NA-	
	b) Width of Staircase	Provided & maintained by Ansal Plaza Mall			
	> Upper floors	-NA-	-NA-	-NA-	
	> Basement floor	-NA-	-NA-	-NA-	
	c) Protection of exits		Provided & maintained by Ansal Plaza Mall		
	> Fire check door	Required	Provided	MR	
	> Pressurization	-NA-	-NA-	-NA-	
	d) No. of continuous staircase to terrace	-NA-	-NA-	-NA-	
	e) Width of corridor	1.5m	Provided	MR	
	f) Door size	1.5m x 2	2m & 1.5m	MR	
3	Service Control of the Control of th				
+	Compartmentation.		ntained by Ansal Pla		
	Fire check door.	Required	Provided	za Mall MR	
	<ul><li>Fire check door.</li><li>Sealing of electrical shafts.</li></ul>	Required Required	Provided Provided	za Mali MR MR	
	<ul> <li>Fire check door.</li> <li>Sealing of electrical shafts.</li> <li>Fire rating of shaft door.</li> </ul>	Required Required Required	Provided Provided Provided	za Mall MR MR MR	
	<ul> <li>Fire check door.</li> <li>Sealing of electrical shafts.</li> <li>Fire rating of shaft door.</li> <li>Water curtain</li> </ul>	Required Required Required -NA-	Provided Provided Provided -NA-	MR MR MR MR -NA-	
4.	<ul> <li>Fire check door.</li> <li>Sealing of electrical shafts.</li> <li>Fire rating of shaft door.</li> <li>Water curtain</li> <li>Fire dampers.</li> </ul>	Required Required Required -NANA-	Provided Provided Provided -NANA-	MR MR MR MR -NA-	
4.	<ul> <li>Fire check door.</li> <li>Sealing of electrical shafts.</li> <li>Fire rating of shaft door.</li> <li>Water curtain</li> <li>Fire dampers.</li> </ul> Smoke Management system.	Required Required Required -NANA- Provided & mai	Provided Provided Provided -NANA- ntained by Ansal Pla	MR MR MR MR -NANA- za Mall	
4.	<ul> <li>Fire check door.</li> <li>Sealing of electrical shafts.</li> <li>Fire rating of shaft door.</li> <li>Water curtain</li> <li>Fire dampers.</li> </ul> Smoke Management system. <ul> <li>Basement</li> </ul>	Required Required Required -NANA-	Provided Provided Provided -NANA- ntained by Ansal Pla	MR MR MR MR -NANAZa Mall -NA-	
	<ul> <li>Fire check door.</li> <li>Sealing of electrical shafts.</li> <li>Fire rating of shaft door.</li> <li>Water curtain</li> <li>Fire dampers.</li> </ul> Smoke Management system. <ul> <li>Basement</li> <li>Upper floors</li> </ul>	Required Required Required -NANA- Provided & mai	Provided Provided Provided -NANA- ntained by Ansal Pla	MR MR MR MR -NANA- Za Mall	
4.	<ul> <li>Fire check door.</li> <li>Sealing of electrical shafts.</li> <li>Fire rating of shaft door.</li> <li>Water curtain</li> <li>Fire dampers.</li> </ul> Smoke Management system. <ul> <li>Basement</li> </ul>	Required Required Required -NANA- Provided & mai -NANA-	Provided Provided Provided -NANA- ntained by Ansal Plate -NANA-	MR MR MR MR -NANANANANANANANANANA	
	<ul> <li>Fire check door.</li> <li>Sealing of electrical shafts.</li> <li>Fire rating of shaft door.</li> <li>Water curtain</li> <li>Fire dampers.</li> </ul> Smoke Management system. <ul> <li>Basement</li> <li>Upper floors</li> </ul> Fire Extinguishers.	Required Required Required -NANA- Provided & mai	Provided Provided Provided -NANA- ntained by Ansal Pla -NANA- Provided	MR MR MR -NANANANANAMR	
	<ul> <li>Fire check door.</li> <li>Sealing of electrical shafts.</li> <li>Fire rating of shaft door.</li> <li>Water curtain</li> <li>Fire dampers.</li> </ul> Smoke Management system. <ul> <li>Basement</li> <li>Upper floors</li> </ul> Fire Extinguishers. <ul> <li>Total numbers</li> <li>Types</li> <li>ISI Marking</li> </ul>	Required Required Required -NANA- Provided & mai -NANA-  06 Nos ABC/CO <sub>2</sub> /WCO <sub>2</sub> Required	Provided Provided Provided -NANA- ntained by Ansal Plat -NANA- Provided ABC, CO <sub>2</sub> , W.CO <sub>2</sub> Provided	MR MR -NANANANAMR MR MR MR	
	<ul> <li>Fire check door.</li> <li>Sealing of electrical shafts.</li> <li>Fire rating of shaft door.</li> <li>Water curtain</li> <li>Fire dampers.</li> <li>Smoke Management system.</li> <li>Basement</li> <li>Upper floors</li> <li>Fire Extinguishers.</li> <li>Total numbers</li> <li>Types</li> <li>ISI Marking</li> <li>First Aid Hose Reels.</li> </ul>	Required Required Required -NANA- Provided & main -NANA- 06 Nos ABC/CO <sub>2</sub> /WCO <sub>2</sub> Required Provided & main	Provided Provided Provided -NANA- ntained by Ansal Plat -NANA- Provided ABC, CO <sub>2</sub> , W.CO <sub>2</sub> Provided	MR MR MR -NANANANAMR MR MR MR	
5.	<ul> <li>Fire check door.</li> <li>Sealing of electrical shafts.</li> <li>Fire rating of shaft door.</li> <li>Water curtain</li> <li>Fire dampers.</li> </ul> Smoke Management system. <ul> <li>Basement</li> <li>Upper floors</li> </ul> Fire Extinguishers. <ul> <li>Total numbers</li> <li>Types</li> <li>ISI Marking</li> </ul> First Aid Hose Reels. <ul> <li>Total numbers on each floor.</li> </ul>	Required Required Required -NANANANANANANANA	Provided Provided Provided -NANA- ntained by Ansal Plat -NANA- Provided ABC, CO <sub>2</sub> , W.CO <sub>2</sub>	MR MR MR -NANANANAMR MR MR MR	
5.	<ul> <li>Fire check door.</li> <li>Sealing of electrical shafts.</li> <li>Fire rating of shaft door.</li> <li>Water curtain</li> <li>Fire dampers.</li> <li>Smoke Management system.</li> <li>Basement</li> <li>Upper floors</li> <li>Fire Extinguishers.</li> <li>Total numbers</li> <li>Types</li> <li>ISI Marking</li> <li>First Aid Hose Reels.</li> </ul>	Required Required Required -NANA- Provided & main -NANA- 06 Nos ABC/CO <sub>2</sub> /WCO <sub>2</sub> Required Provided & main	Provided Provided Provided -NANA- ntained by Ansal Plac -NANA- Provided ABC, CO <sub>2</sub> , W.CO <sub>2</sub> Provided ntained by Ansal Place	MR MR MR -NANANANANANANANA	

pr

7	Automatic fire detection & alarmin	ng system.			
	Type of detectors	Smoke & Heat		MR	
	Location of Main Panel	-NA-	Provided	-NA-	
	Location of Repeater Panel	-NA-	Provided	-NA	
1	Alternate source of power	Required	Provided	MR	
1	Hooter's location	Required	Provided	MR	
		Required	Provided	MR	
8	MOEFA				
9	Public Address System	Required	Provided	MR	
10	Automatic Sprinkler System		aintained by Ansal P		
	Basement	-NA-	-NA-	-NA-	
	<ul> <li>Upper floors.</li> </ul>	-NA-	-NA-	-NA-	
	<ul> <li>Sprinkler above false ceiling</li> </ul>	-NA-	-NA-	-NA-	
11	Internal Hydrants.	Provided & ma	aintained by Ansal P	aza Mall	
	Size of Riser/Down-comer	150mm	150mm	MR	
	Number of Hydrant per floor	2nos near Restt.	2nos near Restt.	MR	
			2nos near Restt.	MR	
	Hose box.	2nos near Restt.			
12	Yard Hydrants.		intained by Ansal Pl		
	<ul> <li>Total number of hydrants.</li> </ul>	08 Nos	08 Nos	MR	
1	<ul> <li>Hose box.</li> </ul>	08 Nos	08 Nos	MR	
13	Pumping arrangements.	Common fire-fig	hting system for entire	complex	
	Ground Level	Provided & ma	Provided & maintained by Ansal Plaza Mall		
Ī	Discharge of main pump.	Required	4050 LPM	MR	
1	➤ Head of main pump.	Required	90m	MR	
	Number of main pumps.	Required	Two	MR	
	Jockey Pump output.	Required	450 LPM	MR	
	Jockey Pump head.	Required	90m	MR	
	Standby Pump output.	Required	8100 LPM	MR	
	Standby Pump head.	Required	90m	MR	
	Auto Starting/Manual Stopping.	Required	Provided	MR	
- 1	➤ Pump house access.	Required	Provided	MR	
	Terrace Level	27.4	NA I	-NA-	
	Discharge of pump.	-NA-	-NA-		
	➤ Head of pump.	-NA-	-NA-	-NA-	
	➤ Power supply.	-NA-	-NA-	-NA-	
	Auto starting of pump.	-NA-	-NA-	-NA-	
14					
	Captive water storage for firefighting.		ting system for entire		
	<ul> <li>Underground tank capacity.</li> </ul>	4,50,000 Ltrs	4,50,000 Ltrs	MR	
	<ul> <li>Underground tank capacity.</li> <li>Draw-off connection.</li> </ul>	4,50,000 Ltrs Required	4,50,000 Ltrs Provided	MR MR	
	<ul> <li>Underground tank capacity.</li> <li>Draw-off connection.</li> <li>Fire Service Inlet.</li> </ul>	4,50,000 Ltrs Required Required	4,50,000 Ltrs Provided Provided	MR MR MR	
	<ul> <li>Underground tank capacity.</li> <li>Draw-off connection.</li> <li>Fire Service Inlet.</li> <li>Access to tank.</li> </ul>	4,50,000 Ltrs Required Required Required	4,50,000 Ltrs Provided Provided Provided	MR MR MR MR	
	<ul> <li>Underground tank capacity.</li> <li>Draw-off connection.</li> <li>Fire Service Inlet.</li> </ul>	4,50,000 Ltrs Required Required	4,50,000 Ltrs Provided Provided	MR MR MR MR MR	
15	<ul> <li>Underground tank capacity.</li> <li>Draw-off connection.</li> <li>Fire Service Inlet.</li> <li>Access to tank.</li> <li>Overhead tank capacity.</li> </ul> Exit Signage.	4,50,000 Ltrs Required Required Required 20,000 Ltrs Required	4,50,000 Ltrs Provided Provided Provided 20,000 Ltrs (AB Blk) 30,000 Ltrs (C Blk) Provided	MR MR MR MR MR	
15 16	<ul> <li>Underground tank capacity.</li> <li>Draw-off connection.</li> <li>Fire Service Inlet.</li> <li>Access to tank.</li> <li>Overhead tank capacity.</li> </ul> Exit Signage. Provision of Lifts.	4,50,000 Ltrs Required Required 20,000 Ltrs Required Provided & main	4,50,000 Ltrs Provided Provided Provided 20,000 Ltrs (AB Blk) 30,000 Ltrs (C Blk) Provided ntained by Ansal Plaz	MR MR MR MR MR MR	
	<ul> <li>Underground tank capacity.</li> <li>Draw-off connection.</li> <li>Fire Service Inlet.</li> <li>Access to tank.</li> <li>Overhead tank capacity.</li> </ul> Exit Signage.	4,50,000 Ltrs Required Required 20,000 Ltrs Required Provided & main	4,50,000 Ltrs Provided Provided Provided 20,000 Ltrs (AB Blk) 30,000 Ltrs (C Blk) Provided ntained by Ansal Plaz	MR MR MR MR MR MR	
	<ul> <li>Underground tank capacity.</li> <li>Draw-off connection.</li> <li>Fire Service Inlet.</li> <li>Access to tank.</li> <li>Overhead tank capacity.</li> </ul> Exit Signage. Provision of Lifts.	4,50,000 Ltrs Required Required 20,000 Ltrs Required Provided & main -NANA-	4,50,000 Ltrs Provided Provided Provided 20,000 Ltrs (AB Blk) 30,000 Ltrs (C Blk) Provided tained by Ansal Plaz -NA-	MR MR MR MR MR MR -NA-	
	<ul> <li>Underground tank capacity.</li> <li>Draw-off connection.</li> <li>Fire Service Inlet.</li> <li>Access to tank.</li> <li>Overhead tank capacity.</li> </ul> Exit Signage. Provision of Lifts. <ul> <li>Pressurization of lift shaft.</li> </ul>	4,50,000 Ltrs Required Required 20,000 Ltrs Required Provided & main -NANA- Required	4,50,000 Ltrs Provided Provided Provided 20,000 Ltrs (AB Blk) 30,000 Ltrs (C Blk) Provided  tained by Ansal Plaz  -NANA- Provided	MR MR MR MR MR MR -NA- MR	
	<ul> <li>Underground tank capacity.</li> <li>Draw-off connection.</li> <li>Fire Service Inlet.</li> <li>Access to tank.</li> <li>Overhead tank capacity.</li> <li>Exit Signage.</li> <li>Provision of Lifts.</li> <li>Pressurization of lift shaft.</li> <li>Pressurization of lift lobby.</li> </ul>	4,50,000 Ltrs Required Required 20,000 Ltrs Required Provided & main -NANA-	4,50,000 Ltrs Provided Provided Provided 20,000 Ltrs (AB Blk) 30,000 Ltrs (C Blk) Provided  -NANA- Provided Provided Provided	MR MR MR MR MR MR -NANAMR MR	
	<ul> <li>Underground tank capacity.</li> <li>Draw-off connection.</li> <li>Fire Service Inlet.</li> <li>Access to tank.</li> <li>Overhead tank capacity.</li> <li>Exit Signage.</li> <li>Provision of Lifts.</li> <li>Pressurization of lift shaft.</li> <li>Pressurization of lift lobby.</li> <li>Communication in lift car.</li> <li>Fireman's switch.</li> </ul>	4,50,000 Ltrs Required Required 20,000 Ltrs Required Provided & main -NANA- Required	4,50,000 Ltrs Provided Provided Provided 20,000 Ltrs (AB Blk) 30,000 Ltrs (C Blk) Provided  tained by Ansal Plaz  -NANA- Provided	MR MR MR MR MR MR -NA- MR	
16	<ul> <li>Underground tank capacity.</li> <li>Draw-off connection.</li> <li>Fire Service Inlet.</li> <li>Access to tank.</li> <li>Overhead tank capacity.</li> <li>Exit Signage.</li> <li>Provision of Lifts.</li> <li>Pressurization of lift shaft.</li> <li>Pressurization of lift lobby.</li> <li>Communication in lift car.</li> <li>Fireman's switch.</li> <li>Lift signage.</li> </ul>	4,50,000 Ltrs Required Required 20,000 Ltrs Required Provided & main -NANA- Required Required Required	4,50,000 Ltrs Provided Provided Provided 20,000 Ltrs (AB Blk) 30,000 Ltrs (C Blk) Provided  -NANA- Provided Provided Provided	MR MR MR MR MR MR -NANAMR MR	
	<ul> <li>Underground tank capacity.</li> <li>Draw-off connection.</li> <li>Fire Service Inlet.</li> <li>Access to tank.</li> <li>Overhead tank capacity.</li> <li>Exit Signage.</li> <li>Provision of Lifts.</li> <li>Pressurization of lift shaft.</li> <li>Pressurization of lift lobby.</li> <li>Communication in lift car.</li> <li>Fireman's switch.</li> <li>Lift signage.</li> <li>Standby Power Supply</li> </ul>	4,50,000 Ltrs Required Required 20,000 Ltrs Required Provided & main -NANA- Required Required	4,50,000 Ltrs Provided Provided Provided 20,000 Ltrs (AB Blk) 30,000 Ltrs (C Blk) Provided -NANA- Provided Provided Provided Provided Provided Provided	MR MR MR MR MR MR  MR  A Mall  -NA- MR MR MR MR MR	
16	<ul> <li>Underground tank capacity.</li> <li>Draw-off connection.</li> <li>Fire Service Inlet.</li> <li>Access to tank.</li> <li>Overhead tank capacity.</li> <li>Exit Signage.</li> <li>Provision of Lifts.</li> <li>Pressurization of lift shaft.</li> <li>Pressurization of lift lobby.</li> <li>Communication in lift car.</li> <li>Fireman's switch.</li> <li>Lift signage.</li> </ul>	4,50,000 Ltrs Required Required 20,000 Ltrs Required Provided & main -NANA- Required Required Required	4,50,000 Ltrs Provided Provided Provided 20,000 Ltrs (AB Blk) 30,000 Ltrs (C Blk) Provided -NANA- Provided Provided Provided Provided Provided Provided	MR MR MR MR MR MR  MR  MR  MR  MR  MR	

19	Fire Control Room.	Provided & maintained by Ansal Mall		
	Detector system panel.	Required	Provided	MR
	Flow switch panel.	-NA-	-NA-	-NA-
	PA system panel.     Battery backup.	Required Required	Provided Provided	MR MR
	Building floor plan.	-NA-	-NA-	-NA-
20	Special Fire Protection System for the Protection of Special Risk, if any.	CO <sub>2</sub> and ABC type fire extinguisher		MR

The fire protection systems provided in the building/premises were checked, tested at random and found functional at the time of inspection.

Keeping in view of the deemed compliance of the minimum standards on fire prevention and fire safety measures as required under the rules, renewal of fire safety certificate issued vide letter No. F6/DFS/MS/EH/2021/SZ/311 dated 27/10/2021, under rule 37 of the Delhi Fire Service Rules, 2010 is recommended.

Accordingly, DFA is put up for approval and signature please.

Signature of the Inspecting Officer

Name: Santosh Kumar Designation: ADO (SJ)