GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE, NEW DELHI – 110001

No. F6/DFS/MS/GH/NDZ/2024/ 420

Dated: 18/10/2024

FIRE SAFETY CERTIFICATE

Certified that the M/s Tamanna Guest House situated at 2294, Gali Qasim Jan, Ballimaran, Delhi, comprised of Ground + 04 upper floors: Ground floor - (reception + office + 01 dormitory for 11 beds), 1st floor - (06 guest rooms), 2nd floor - (05 guest rooms), 3rd floor - (07 guest rooms) & 4th floor- (not in use), total 18 guest rooms and 01 dormitory for 11 beds was granted FSC by this department vide letter no. F6/DFS/MS/GH/NDZ/2021/413 dated 23.09.2021. The building/premises was re-inspected by officer concerned of this department on 09.10.2024 in presence of Mohd. Naimuddin Sheikh (Owner) and found that the building has deemed complied with the fire prevention and fire safety requirements in accordance with Rule 33 of Delhi Fire Service Rules, 2010. The owner has submitted an affidavit on 09.10.2024 stating not to use any floor above third floor for any purpose. Accordingly, the premises is fit for occupancy of (Group-A-1) "Residential", ground floor - (01 dormitory for 10 beds), 1st floor - (06 guest rooms), 2nd floor - (05 guest rooms) & 3rd floor - (07 guest rooms) for total 18 guest rooms and 01 dormitory for 10 beds upto 3rd floor only, with effect from18./10/2024. for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under rule 40 and subject to conditions under rule 38 of Delhi Fire service Rules, 2010 subject to condition printed below.

Director Della Fire Service

Tel: 011-23414000

Copy to:-

- 1. The Commissioner, MCD:- to kindly ensure the occupancy as detailed above & deviation, if any.
- The Joint Commissioner of Police (Licensing), 1st Floor, Police Station Defence Colony, New Delhi. w.r.to ID No. 2024092514746 dated 25.09.2024.
- 3. The Licensee, M/s Tamanna Guest House at 2294, Gali Qasim Jan, Ballimaran, Delhi.

Conditions for the validity of fire safety certificate

- All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".
- 8. Any change in the occupancy shall be intimated to this Deptt. and approval shall be obtained thereto before occupancy of the same.
- 9. The occupancy of above 3rd floor not allowed as per clause 7.31 in UBBL-2016.

| | | INSP | | ON REPORT | | | |
|------|--|--|--------|--|---|--|--|
| | Name & | & address of the building | M Q | M/s Tamanna Guest House at 2294, G. Qasim Jan, Ballimaran, Delhi - 06. | | | |
| | Building is comprised of | | G | Ground + 04 upper floors Ground floor - (reception + office + 0) | | | |
| | | | | dormitory for 10 beds) 1 st floor – (06 guest rooms) 2 nd floor – (05 guest rooms) | | | |
| | | | | | | | |
| | | | 1 | | | | |
| | | | 2 | | | | |
| | | | 3 | 3 rd floor - (07 guest rooms) 4 th floor- (not in use as per affidavit date | | | |
| 1 | | | | | | | |
| | | | | 0.10.2024) | Λ_1 | | |
| 3 | Type of occupancy | | | Residential Group A-1 | | | |
| 4 | Type | of case | R | enewal | DZ/2021/413 dated | 23.09.202 | |
| 5 | Detail | s of previous FSC | F | 6/DFS/MS/GH/N | DZ/2021/413 dated | | |
| 6 | Fire s | afety direction letter no. | N | | | | |
| 7 | | of inspection | | 9.10.2024 | o (GDI C | | |
| 8 | | e of the inspecting officers | s S | umit Kumar, ADO |) (SPM) | | |
| 9 | Name | e of the designation | of N | Iohd. Naimuddin | Sheikh (Owner) | | |
| , | office | er from the building side | | | | | |
| 10 | Vear | of construction | 2 | 001 | 202400251 | 1716 date | |
| 1772 | | icant's letter no. | (| Online application | n no. 202409251 | 4/40 date | |
| 11 | App | icant 5 icon | 2 | 5.09.2024 | | Remarks | |
| CN | N/in | imum Standards on fire | F | Requirement/ | Provided at Site | MR/ | |
| S.No | Prevention and fire safety | | 1 | Existing fire | | NMR | |
| | regu | irements U/R 33 | S | afety | 70. | | |
| | | | 2 | rrangements | | | |
| 1 | | ess To Building: | | NA (spl. Area) | 07 m | NA | |
| | | d width | | NA | NA | NA | |
| 11 | 10.4 | | | | | NA | |
| 11 | | e width | | NA | NA | 1471 | |
| | | 1 | Arran | NA | NA | III | |
| 2 | Wid Nu | ith of internal road mber, Width, Type and A | Arran | NA | | | |
| 2 | | Ith of internal road mber, Width, Type and A Number of staircases | Arran | NA | 01 no. | MR | |
| 2 | Wid Nu | of internal road mber, Width, Type and A Number of staircases a Upper floor | Arran | NA gement of Exits: | | | |
| 2 | Nui A | hth of internal road mber, Width, Type and A Number of staircases a Upper floor b Basement | Arran | NA gement of Exits: 01 no. NA | 01 no. / | MR NA | |
| 2 | Wid Nu | hth of internal road mber, Width, Type and A Number of staircases a Upper floor b Basement Width of staircases | Arran | NA gement of Exits: 01 no. NA 80 cms. | 01 no. / NA 105 cms. / | MR | |
| 2 | Nui A | Number of staircases a Upper floor b Basement Width of staircases a Upper floor b Basement Width of staircases b Basement | Arran | NA gement of Exits: 01 no. NA | 01 no. / | MR NA MR | |
| 2 | Nui A | Number of staircases a Upper floor b Basement Width of staircases a Upper floor b Basement Protection of exits | Arran | NA gement of Exits: 01 no. NA 80 cms. NA | 01 no. / NA 105 cms. / | MR NA MR NA | |
| 2 | Wid Num A B | Number of staircases a Upper floor b Basement Width of staircases a Upper floor b Basement Width of staircases a Upper floor b Basement Protection of exits a Fire check door | Arran | NA gement of Exits: 01 no. NA 80 cms. NA | 01 no. / NA 105 cms. / NA | MR NA MR NA | |
| 2 | Wice Num A B | Number of staircases a Upper floor b Basement Width of staircases a Upper floor b Basement Protection of exits a Fire check door b Pressurization | | NA gement of Exits: 01 no. NA 80 cms. NA | 01 no. NA 105 cms. NA | MR NA MR NA | |
| 2 | Wid Num A B | Number of staircases a Upper floor b Basement Width of staircases a Upper floor b Basement Protection of exits a Fire check door b Pressurization No. of continuous staircases | | NA gement of Exits: 01 no. NA 80 cms. NA NA NA NA O1 no. | 01 no. NA 105 cms. NA NA NA NA O1 no. | MR NA MR NA NA NA MR | |
| 2 | Wice Number A B C D | Number of staircases a Upper floor b Basement Width of staircases a Upper floor b Basement Protection of exits a Fire check door b Pressurization No. of continuous staircases to terrace | | NA gement of Exits: 01 no. NA 80 cms. NA | 01 no. NA 105 cms. NA NA NA NA NA NA NA NA NA | MR NA MR NA NA NA NA NA NA NA | |
| 2 | Wice Number A B C D E | Number of staircases a Upper floor b Basement Width of staircases a Upper floor b Basement Protection of exits a Fire check door b Pressurization No. of continuous stairc to terrace Width of corridor | | NA gement of Exits: 01 no. NA 80 cms. NA NA NA NA O1 no. | 01 no. NA 105 cms. NA NA NA NA O1 no. | MR NA MR NA NA NA MR | |
| | Wice Number A B C D E F | Number of staircases a Upper floor b Basement Width of staircases a Upper floor b Basement Protection of exits a Fire check door b Pressurization No. of continuous stairc to terrace Width of corridor Door size | | NA gement of Exits: 01 no. NA 80 cms. NA NA NA NA 1.0 mtr. | 01 no. / NA 1.0 mtr. / | MR NA MR NA NA NA NA NA NA NA | |
| 3 | Wice Number A B C D E F | Number of staircases a Upper floor b Basement Width of staircases a Upper floor b Basement Protection of exits a Fire check door b Pressurization No. of continuous staircase Width of corridor Door size mpartmentation: Fire check door | cases | NA gement of Exits: 01 no. NA 80 cms. NA NA NA 1.0 mtr. | 01 no. / NA | MR NA MR NA NA NA NA MR NA MR | |
| | Wice Number A B C C F C C C C C C C C C C C C C C C C | Number of staircases a Upper floor b Basement Width of staircases a Upper floor b Basement Protection of exits a Fire check door b Pressurization No. of continuous stairc to terrace Width of corridor Door size mpartmentation: Fire check door Sealing of electrical share | cases | NA gement of Exits: 01 no. NA 80 cms. NA NA NA 1.0 mtr. | 01 no. NA 105 cms. NA NA NA NA 1.0 mtr. NA NA | MR NA MR NA NA NA NA MR NA NA NA MR | |
| | Wice Number A B C C A B C C | Number of staircases a Upper floor b Basement Width of staircases a Upper floor b Basement Protection of exits a Fire check door b Pressurization No. of continuous stairc to terrace Width of corridor Door size mpartmentation: Fire check door Sealing of electrical shaft food | cases | NA gement of Exits: 01 no. NA 80 cms. NA NA NA 1.0 mtr. | 01 no. / NA | MR NA MR NA | |
| | Wice Number of N | Number of staircases a Upper floor b Basement Width of staircases a Upper floor b Basement Protection of exits a Fire check door b Pressurization No. of continuous stairce to terrace Width of corridor Door size mpartmentation: Fire check door Sealing of electrical shaft door Water curtain | cases | NA gement of Exits: 01 no. NA 80 cms. NA NA NA 1.0 mtr. | 01 no. NA 105 cms. NA NA NA 01 no. NA 1.0 mtr. NA NA NA | MR NA MR NA | |
| 3 | Wice Number of N | Number of staircases a Upper floor b Basement Width of staircases a Upper floor b Basement Protection of exits a Fire check door b Pressurization No. of continuous stairc to terrace Width of corridor Door size mpartmentation: Fire check door Sealing of electrical shaft from the staircase of th | eases | NA gement of Exits: 01 no. NA 80 cms. NA NA NA 1.0 mtr. NA NA NA NA NA NA NA NA NA N | 01 no. NA 105 cms. NA NA NA 1.0 mtr. NA NA NA NA NA NA NA NA NA N | MR NA MR NA | |
| | Wice Number of N | Number of staircases a Upper floor b Basement Width of staircases a Upper floor b Basement Protection of exits a Fire check door b Pressurization No. of continuous stairce to terrace Width of corridor Door size mpartmentation: Fire check door Sealing of electrical shaft frie dampers moke Management System Non b Pressurization Non of continuous stairce to terrace Width of corridor Door size mpartmentation: Fire check door Sealing of electrical shaft door Water curtain Fire dampers moke Management System | eases | NA gement of Exits: 01 no. NA 80 cms. NA NA 01 no. NA NA 1.0 mtr. | 01 no. NA 105 cms. NA NA NA 01 no. NA 1.0 mtr. NA NA NA NA NA NA | MR NA MR NA | |

| 5. | | tinguisher: Total numbers | 08 nos. | 08 nos. | MR | | |
|----|--|--------------------------------|-----------------------|-----------------------|----------|--|--|
| | A B | Types | CO ₂ & ABC | Provided | MR | | |
| 8 | | ISI marking | Required | Provided | MR | | |
| _ | C ISI marking Required Provided MR First-Aid-Hose Reels: | | | | | | |
| 6 | | Total numbers of each | 01 no. | 01 no. / | MR | | |
| | A | floor | 01 110. | or no. | IVAL | | |
| | В | Length of hose reel hose | 30 m | 30 m | MR | | |
| | C | Nozzle diameter | 05 mm | 05 mm | MR | | |
| 7 | Automatic Fire Detection And Alarming System: | | | | | | |
| | A | Type of detectors (CO type) | Required | Provided | MR | | |
| - | В | Location of main panel | Required | Provided at reception | MR | | |
| | С | Location of repeater panel | NA | NA | NA | | |
| | D | Alternate source of power | Required | Provided / | MR | | |
| | E | Hooters | Required | Provided / | MR | | |
| 8 | MOEF | A: | NA | NA | NA | | |
| 9 | | Address System: | Required | Provided | MR | | |
| 10 | Autom | atic Sprinkler System: | | | | | |
| | A | Basement | NA | NA | NA | | |
| | В | Upper floor | NA | NA | NA | | |
| | C | Sprinkler above false ceiling | NA | NA | NA | | |
| 11 | Internal Hydrants: | | | | | | |
| | A | size of riser/down-comer | NA | NA | NA | | |
| | В | Number of hydrants per floor | NA | NA | NA | | |
| | C | Hose box | NA | NA | NA | | |
| 12 | Yard l | Hydrants: | | | | | |
| | A | Total number of hydrants | NA | NA | NA | | |
| | В | Hose box | NA | NA | NA | | |
| 13 | Pump | ing Arrangements: | | | | | |
| | A | Ground level | | | | | |
| | a) | Discharge of main pump | NA | NA | NA | | |
| | b) | Head of main pump | NA | NA | NA | | |
| 74 | c) | Number of main pumps | NA | NA | NA | | |
| 17 | d) | Jockey pump out put | NA | NA | NA | | |
| | e) | Jockey pump head | NA | NA | NA | | |
| | f) | Standby pump out put | NA | NA | NA | | |
| | g) · | Standby pump head | NA | NA | NA | | |
| | h) | Auto starting /manual stopping | NA | NA | NA | | |
| - | <u>i)</u> | Pump house access | NA | NA | NA | | |
| - | В | | | | | | |
| | a) | Discharge of pump | 225 LPM | 225 LPM | MR | | |
| | | Head of the numn | 1 30 m | 30 m | BATT. | | |
| | b) | Head of the pump Power supply | 30 m Required | 30 m | MR MR | | |

| 4 | Car | otive Water Storage For Fire F | ighting: | | | |
|----|---------------------|---|-------------|---------------|----------|--|
| - | A | Underground tank capacity | NA | NA | Tari | |
| - | В | Draw-off connection | NA | NA NA | NA | |
| | C | Fire service inlet | NA | | NA | |
| | D | Access to tank | NA | NA | NA | |
| Ī | E | Overhead tank capacity | | NA | NA | |
| 5 | | t Signage: | 2,500 ltrs. | 4,000 ltrs. | MR * | |
| 6 | | | Required | Provided | MR | |
| 10 | Provision of Lifts: | | | | | |
| | A | Pressurization of lift shaft | NA | NA | NA | |
| | В | Pressurization of lift lobby | NA | NA | NA NA | |
| | C | Communication in lift car | NA | NA | NA NA | |
| | D | Firemen's grounding switch | NA | NA NA | NA | |
| | E | Lift signage | NA | NA | NA | |
| 17 | Sta | andby Power Supply: | Required | Provided | MR | |
| 18 | Re | efuge Area: | | Trovided IVIA | 1724 | |
| | A | Total area | NA | NA | NA | |
| | B | Location | NA | NA | NA | |
| 19 | Fire Control Room: | | | | | |
| | A | Detector system panel | NA | NA | NA | |
| | В | Flow switch panel | NA | NA | NA | |
| | C | Pa system panel | NA | NA | NA | |
| | D | | NA | NA | NA | |
| | E | Building floor plans | NA | NA | NA | |
| 20 | 25 (1) (2) | Special Fire Protection Systems F Special Risks, If Any: | NA | NA | | |

The fire protection systems provided in the building were tested, checked at randomly and found functional at the time of inspection.

Shortcomings communicated vide letter No.F6/DFS/MS/GH/NDZ/2024/511 dated

21/08/2024 has been rectified.

Keeping in view of the deemed compliance of minimum standards of fire prevention and fire safety measures as required under the Rules, the FSC issued vide letter No F6/DFS/MS/GH/NDZ/2021/413 dated 23.09.2021 is recommended to be renewed upto 3rd floor only, under Rule 35 of the Delhi Fire Service Rules 2010.

Signature of the Inspecting Officer

Name

Sumit Kumar

Designation ADO (SPM)

Directo