

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CONNAUGHT PLACE NEW DELHI-110001

No.F.6/DFS/MS/GH/2024/SZ/441

FIRE SAFETY CERTIFICATE

International located at C-5/32, Safdarjung development Area, New Delhi- 110016 comprised of Basement, Ground plus three upper floors with 23 guest rooms was issued Fire Safety Certificate by this department vide letter No. F6/DFS/MS/GH/2021/SZ/317 dated 13/08/2021. The premise was re-inspected by the officer concerned of this department on 19/10/2024 in the presence of Mr. Adil (Manager) and found that the said premises have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class "Residential, Group-A" (Guest House running at Ground plus three upper floors with 23 Guest Rooms only) and Validity upto 31/03/2027 in accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under Rule 38 of the Delhi Fire Service Rules, 2010

Issued on 28 10./2024 at New Delhi by

DIRECTOR HI FIRE SERVICE

Copy to: -

- The Addl. Commissioner of Police (Lic.), 1st Floor, P.S. Defence Colony, New Delhi-110049 (Ref. MHA Portal ID 2024092814974 dated 07/10/2024)
- The Executive engineer (Bldg Department) MCD, Green Park zone, New Delhi 110016 (with request to check & verify basement for further action in the matter.

Conditions for the validity of Fire Safety Certificate: -

All the means of escape/entry/exit shall be kept free from any obstruction.

All the fire safety arrangement provided therein shall be maintained in good working condition at all time as seen during inspection. Any loss of life property due to nonfunctional fire safety measures shall be at the responsibility of the management.

3. The basement shall be used as per the provisions of BBL/NBC Part- IV.

- All the staff members must know the correct method of operation of fire fighting system.
- 5. The owner/occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- This fire safety certificate may not in any way be treated as regularization (Clause 2.8 of UBBL-2016) of unauthorized construction or Alteration (Clause 1.4.3 of UBBL-2016), if any.
- "The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry



/	INSPECTIO	N REPORT				
1	Name & Address of the Building	M/s Shyama International located at C-5/32,				
2	Type of Occupancy Residential "Group A" (Group A" (Group A")					
3		L TIME OIUUD A II MIGH LIA				
4	Type of Case	Basement, Ground plus 3 Upper floors Renewal				
5						
6	Fire Safety Directives Letter No	F6/DFS/MS/GH/2021/SZ/317 dated 13/08/2021 Nil				
7	Date of Inspection	nspection 19/10/2024				
8	Name of the Inspecting Officers	ADO (BCP)				
9	Name & Designation of Officers from the building side	Mr. Adil Manager)				
10	Year of construction	1991 Total 23 Guest room				
11	Applicant letter No.	MHA Portal ID 2024092814974 dated 07/10/2024				
S. No.	Minimum standards on Fire Prevention	Old NOC	OLINOC D III			
6-	and Fire Safety U/R 33	requirements	110vided at Site	Remarks MR/NMR		
71	Access to Building.	- Squitteness		MINIMIK		
	Road width	Required	15mtr	MR		
	Gate width	-NA-	-NA-	-NA-		
	Width of internal road	-NA-	-NA-	-NA-		
2	Number, width, type & arrangement of exits.	1	TIM	-NA-		
100	a) Number of Staircase					
	> Upper floors.	Required	02 Nos	MR		
E 24	> Basement floor.	Required	02 Nos	MR		
0.75	b) Width of Staircase	Required	02 1405	IVIK		
2.0	> Upper floors	Required	1.22 mtr each	MR (old case		
17	➤ Basement floor			MR (old case		
1		Required	1.22 mtr each	IVIX (Old Case		
	c) Protection of exits > Fire check door	-NA-	NECT CHANGE	NIA.		
117			-NA-	-NA-		
10.7	> Pressurization	-NA-	-NA-	-NA-		
104	d) No. of continuous staircase to terrac		One	MR		
W.	e) Width of corridor	-NA-	-NA-	-NA-		
-	n Door size	lm .	1 m (final exit)	MR		
-	Compartmentation. Fire check door.	-NA-	-NA-	-NA-		
	The state of the s	-NA-	-NA-	-NA-		
	Sealing of electrical shafts. Fire rating of shaft door.	-NA-	-NA-	-NA-		
	Water curtain	-NA-	-NA-	-NA-		
13.0	Fire dampers.	-NA-	-NA-	-NA-		
-	4 Smoke Management system.	7.000	As per clause 7.31 of UBBL 2016			
	Basement		30 ACPH Exhaust fan provided Mi			
	Upper floors	12 ACPH	Exhaust fan provided			
	5 Fire Extinguishers.					
	Total numbers	15 Nos	Provided	MR		
	Types	ABC / CO2	ABC & CO2	MR		
-	ISI Marking	ISI marked	Provided	MR		
	6 First Aid Hose Reels.					
	Total numbers on each floor.	One	Provided	MR		
+	Management of the state of the	U.S. 4763.C	Provided	MR		
	 Length of hose-reel hose. 	30 mtr				
	Length of hose-reel hose. Nozzle Diameter	30 mtr 5 mm	Provided	MR		
	Length of hose-reel hose. Nozzle Diameter Automatic fire detection & alarming systems.	5 mm		MR		

d)	N			
	Location of Main Panel	Required	Provided	MF
	Location of Repeater Panel	-NA-	-NA-	-NA-
	 Alternate source of power 	Required	Provided	MR
_	Hooter's location	Required	Provided	MR
8	MOEFA	Required	Provided	MR
9	Public Address System	-NA-	NA	-NA-
10	Automatic Sprinkler System			14/1
	Basement	-NA-	NA	-NA-
	Upper floors.	-NA-	-NA-	-NA-
	Sprinkler above false ceiling	-NA-	-NA-	-NA-
11	Internal Hydrants.	141	178A. VA. A. Z.	-INA-
	Size of Riser/Down-comer	-NA-	NA	-NA-
	Number of Hydrant per floor	-NA-	-NA-	
	Hose box.	-NA-		-NA-
12	Yard Hydrants.	-INA-	-NA-	-NA-
	Total number of hydrants.	NIA I		- A. Haller
2021	Hose box.	-NA-	-NA-	-NA-
13	Pumping arrangements.	-NA-	-NA-	-NA-
	Ground Level			
	Discharge of main pump			
	Head of main nump	-NA-	-NA-	-NA-
	Number of main number	-NA-	-NA-	-NA-
	Jockey Pump output	-NA-	-NA-	-NA-
	Jockey Pump head	-NA-	-NA-	-NA-
	Standby Pump output.	-NA-	-NA-	-NA-
	Standby Pump head.	-NA-	-NA-	-NA-
	- Lato Starting/Manual Stopping	-NA-	-NA-	-NA-
	r ump nouse access.	-NA-	-NA-	-NA-
	Terrace Level	-IVA-	-NA-	-NA-
	Discharge of pump.	Boosting pump		
	Head of pump.	16m	180 LPM	MR
	- ovici supply.	Provided	16 m	MR
14	Captive The Auto starting of pump.	Provided	Provided	MR
	Captive water storage for fire fighting.	- I O FIELD	Provided	MR
	Oliderground tank canacity	-NA-		
	Draw-off connection.	-NA-	NA	-NA-
	Fire Service Inlet. Access to tank.	-NA-	-NA-	-NA-
	Overhead tank capacity.	-NA-	-NA-	-NA-
15	E-14 C	2500 ltr	-NA-	-NA-
16	Exit Signage.	Required	5,000 ltrs	MR
10	Provision of Lifts.	Required	Provided	MR
	 Pressurization of lift shaft. 	-NA-		WIII
	Pressurization of lift lobby.	-NA-	-NA-	-NA-
	Communication in lift car	-NA-	-NA-	-NA-
	• Fireman's switch.	-NA-	-NA-	-NA-
17	Lift signage. Standby D.	-NA-	-NA-	-NA-
18	Standby Power Supply	Required	-NA-	-NA-
	Refuge Area	quired	Provided (DG Set)	MR
	Total area	-NA-		.,
10	Location		-NA-	-NA-
19	Fire Control Room.	-NA-	-NA-	-NA-
	Detector system panel.	27.4	TOTAL TOTAL	-IVA-
E	Flow switch panel.	-NA-	-NA-	-NA-
				-131 /3

ादा का मृत महोत्सव -NA--NA-

-NA-PA system panel. -NA--NA--NA-Battery backup. -NA--NA--NA-Building floor plan. Special Fire Protection System for the Protection of special Risk, if any. -NA-

Note: As per MHA Portal Application details per floor occupancy is below mentioned.

1. Ground floor 02 Room

02 Nos of Bed

2. First Floor: 08 Rooms 3. Second Floor: 08 Rooms

08 Nos of Bed 08 Nos of Bed

4. Third floor: 05 Rooms The occupancy per person at per floor is less than of 10 people hence the FCD requirements under 05 Nos of Bed clause 7.31 of UBBL is not applicable.

The fire protection system provided in the building were randomly checked and found functional at the time of inspection.

urther, the party has complied all the observation / Shortcoming already issued &

communicated by this department vide letter of even no 525 dated 28/08/2024.

Keeping in view of the deemed compliance of the minimum standard on fire prevention and fire safety measures as required under the rules, the FSC issued vide letter no F6/DFS/MS/GH/2021/SZ/317 dated 13/08/2021, renewal under rule 37 of the Delhi Fire Service rules, 2010 is recommended.

Accordingly DFA is put up for approval and signature please.

Signature of the Inspecting Officer Name: Sh. Rajesh Kumar Design: ADO (BCP)

DO (South)

ynature,