



GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: CONNAUGHT PLACE NEW DELHI-110001

No.F.6 DFS/MS/School/2024/SZ/1101

Dated: 08/ 11/2024

FIRE SAFETY CERTIFICATE

Certified that the D.T.E.A Senior Secondary School located at R. K. Puram, New Delhi- 110022 comprised of Ground plus Two upper floors owner/occupied by D.T.E.A Senior Secondary School was issued Fire Safety Certificate by this department vide letter No. F6/DFS/MS/School/2021/SZ/933 dated 12/11/2021. The said premise was re-inspected by officer concerned of this department on 30/10/2024 in presence of Mrs. Jayasree Prasad (HOS) and found that the said school building have deemed complied with the fire prevention and fire safety requirements in accordance with Directorate of Education Circular No 262-362 dated 17/01/2005 issued by Director of Education, Govt. of NCT of Delhi and that the building is fit for occupancy class "Educational Building Group - B" with effect from 08/11/2024 for a period of Three years in accordance with rule 36 unless renewed under rule37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of Delhi Fire Service Rules 2010.

Issued on <u>08/11/2024</u> at New Delhi by

Copy to: -

1. The Principal, D.T.E.A Senior Secondary School, R.K Puram, New Delhi- 110022.

2. The Director of Education, Govt. of NCT of Delhi, Old Secretariat, New Delhi-54.

Conditions for the validity of Fire Safety Certificate:-

1. All the fire safety arrangements provided therein shall be maintained in good working condition at all time as seen during inspection. Any loss of life or property due to nonfunctional fire safety measures shall be at the responsibility of the management.

2. All the staff members must know the correct method of operation of firefighting system.

- 3. This certificate cannot be treated as regularization of unauthorized construction, if
- 4. The owner/ occupier shall submit a declaration every year in Form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 5. This fire safety certificate may not in any way be treated as regularization (Clause 2.8 of UBBL-2016) of unauthorized construction or Alteration (Clause 1.4.3 of UBBL-2016), if any.
- 6. "The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six months prior to its expiry."



1	Name & Address of the Building	D.T.E.A Senior Secondary School, R.K Puram, New Delhi- 110022			
2	Type of Occupancy	Educational, Group-B (School)			
3	Building Comprised of	Ground + Two upper floors			
4	Type of Case	Ground + Two upper floors. Renewal			
5	Details of Previous NOC				
6	Fire Safety Directives Letter No.	F6/DFS/MS/School/2021/SZ/933 dated 12/11/2021			
7	Date of Inspection	DOE Circular dated 17/01/2005 30/10/2024			
8	Name of the Inspecting Officers				
9	Name & Designation of Officers from the building side	Sh. Rajesh Kumar ADO (BCP) Mrs. Jayasree Prasad (HOS)			
10	Year of construction	1976		_	
11	Applicant letter No.		0200 1-4-1 24/10/202		
S. No.	Minimum standards on Fire Prevention	Outdoor diary no 8288 dated 24/10/2024 DOE Circular Provided at Site Remarks			
entava v = til	and Fire Safety U/R 33		Provided at Site	Remarks	
1.	Access to Building.	dt 2005		MR/NMR	
	Road width	9 mtr	9 mtr	MR	
	Gate width				
		5 mtr	5 mtr	MR	
_	Width of internal road	-NA-	-NA-	-NA-	
2.	Number, width, type & arrangement of ex	its.			
	a) Number of Staircase				
	Upper floors.	02 Nos	Provided	MR	
	➢ Basement floor.	-NA-	-NA-	-NA-	
	b) Width of Staircase	1000000		147	
	➤ Upper floors	02 Exit	1.50 m x 2	MR	
	▶ Basement floor	-NA-	-NA-	-NA-	
	c) Protection of exits	and the second		-14/4-	
	➤ Fire check door	-NA-	-NA-	-NA-	
	> Pressurization	-NA-	-NA-	-NA-	
	d) No. of continuous staircase to terrace	Required	01 Nos	MR	
	e) Width of corridor	-NA-	-NA-		
•	f) Door size	1.20 m	Provided	-NA-	
3.	Compartmentation.		Tioridad	MR	
	Fire check door.	-NA-	-NA-	NA	
	 Sealing of electrical shafts. 	-NA-	-NA-	-NA-	
	 Fire rating of shaft door. 	-NA-	-NA-	-NA-	
	Water curtain	-NA-	-NA-	-NA-	
	Fire dampers.	-NA-	-NA-	-NA-	
4.	Smoke Management system.		-1VA-	-NA-	
	Basement	30 ACPH	N/4		
	Upper floors	12 ACPH	-NA-	-NA-	
5.	Fire Extinguishers.	12 ACPH	-NA-	-NA-	
	Total numbers	D			
	Types	Required	15 Nos	MR	
	1-17	ABC / CO2	ABC & CO2	MR	
6.	ISI Marking First Add II	ISI marked	Provided		
0.	First Aid Hose Reels.		1 TOYIGEG	MR	
	Total numbers on each floor.	01 Nos	D		
	 Length of hose-reel hose. 	30 m	Provided	MR	
	Nozzle Diameter		Provided	MR	
7.	Automatic fire detection & alarming system.	5mm	Provided	MR	

7/-	
आज़ादी अमृत	HETE.

	Type of detectors	-NA-	-NA-	-NA-
	55.	-NA-	-NA-	-NA-
	Location of Main Panel	-NA-	-NA-	-NA-
	Location of Repeater Panel	-NA-	-NA-	-NA-
	Alternate source of power Hooter's location	-NA-	-NA-	-NA-
8.	Hooter's location MOEFA	-NA-	NA	-NA-
9.	Public Address System	-NA-	NA	-NA-
0.	Automatic Sprinkler System		.,,,	
	Basement	-NA-	-NA-	-NA-
	Upper floors	-NA-	-NA-	-NA-
	Sprinkler above false ceiling	-NA-	-NA-	-NA-
11.	Internal Hydrants.			
	Size of Riser/Down-comer	100mm	Provided	MR
	Number of Hydrant per floor	01	Provided	MR
	Hose box.	01	Provided	MR
12.	Yard Hydrants.			
	Total number of hydrants.	-NA-	-NA-	-NA-
	Hose box.	-NA-	-NA-	-NA-
13.	Pumping arrangements.			
10.	Ground Level			
	Discharge of main pump.	-NA-	-NA-	-NA-
	> Head of main pump.	-NA-	-NA-	-NA-
	➤ Number of main pumps.	-NA-	-NA-	-NA-
	➤ Jockey Pump output.	-NA-	-NA-	-NA-
	➤ Jockey Pump head.	-NA-	-NA-	-NA-
	➤ Standby Pump output.	-NA-	-NA-	-NA-
	Standby Pump head.	-NA-	-NA-	-NA-
	Auto Starting/Manual Stopping.	-NA-	-NA-	-NA-
	➤ Pump house access.	-NA-	-NA-	-NA-
	Terrace Level			
	Discharge of pump.	450 LPM	Provided	MR
	Head of pump.	40 mtr	Provided	MR
	Power supply.	Required	Provided	MR
	> Auto starting of pump.	Required	Provided	MR
14.	Captive water storage for fire fighting.			
	Underground tank capacity.	-NA-	-NA-	-NA-
	> Draw-off connection.	-NA-	-NA-	-NA-
	 Fire Service Inlet. Access to tank. 	-NA-	-NA-	-NA-
	Overhead tank capacity.	5,000 ltrs	10,000 ltrs	MR
15.	Exit Signage.	Required	Provided	MR
16.	Provision of Lifts.	- Acquired	Tionidea	IVIX
10.	Pressurization of lift shaft.	-NA-	-NA-	-NA-
	Pressurization of lift lobby.	-NA-	-NA-	-NA-
	Communication in lift car.	-NA-	-NA-	-NA-
	Fireman's switch.	-NA-	-NA-	
	Lift signage.			-NA-
-	- AN 181	-NA-	-NA-	-NA-
17.	Standby Power Supply	-NA-	-NA-	-NA-
18.	Refuge Area	-NA-	NA	N/A
	Total area		-NA-	-NA-
	Location	-NA-	-NA-	-NA-



•	Detector system panel.	Detector system panelNA-			
	Flow switch panel.	-IVA-	-NA-	-NA-	
	PA system panel.	-NA-	-NA-	-NA-	
	Battery backup.	-NA-	-NA-	-NA-	
	Building floor plan.	-NA-	-NA-	-NA-	
	, see	-NA-	-NA-	-NA-	
20.	Special Fire Protection System for the Protection of special Risk, if any.			-NA-	

The Fire protection systems provided in the building were test checked at random and found functional at the time of inspection.

Keeping in view of the deemed compliance of the minimum standard on fire prevention and fire safety measures as required under the rules, the FSC issued vide letter no F6/DFS/MS/School/2021/SZ/933 dated 12/11/2021, renewal under rule 37 of the Delhi Fire Service rules, 2010 is recommended.

Accordingly DFA is put up for approval and signature please.

Signature of the Inspecting Officer

Name: Sh. Rajesh Kumar Design: ADO (BCP)

approved F.T. (elter is putup for , ML synature Pl