## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE, CONNAUGHT PLACE NEW DELHI

No.F6/DFS/MS/SZ/2024/EH 369

Dated: 08/1/2024

## FIRE SAFETY CERTIFICATE

Certified that M/s Haldiram Products Pvt. Ltd. Located at Shop No 11A, Ground Floor, Pusa Road, Karol Bagh, New Delhi, in a building comprised of Basement + Ground + 03 Upper Floors was issued FSC vide letter No. F6/DFS/MS/EH/2021/SZ/312, dated 28/10/2021. The premises was inspected by the officer concerned of this department on 28/10/2024 in the presence of Sh. Sudhir Sharma (Licensing Officer) and found that premises have deem complied with the fire prevention and fire safety requirements in accordance with Rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Assembly" Group D (Ground Floor) with effect from 

OS 1112224 for a period of three years in accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under Rule 38 of the Delhi Fire Service Rules, 2010.

Issued on ... 08/11/2024. at New Delhi by.

Copy to:

- 1. The Joint Commissioner Police, Licensing, 1st Floor, PS, Defence Colony, New Delhi.
- 2. The Executive Engineer (Building), MCD, Civic Centre, Minto Road, New Delhi.
- 3. The Manager, M/s Haldiram Products Pvt. Ltd. Located at Shop No 11A, Ground Floor, Pusa Road, Karol Bagh, New Delhi.

## Condition for the validity of fire safety certificate:-

- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.
- 3. The trained staff should be available round the clock.
- Any deviations w.r.t. construction shall be verified by the concerned building sanctioning agency.
- The certificate may not be treated in any case for the regularization of the unauthorized construction, if any.
- 6. Basement shall be used as per building bye laws.
- The owner/occupier shall submit a declaration every year in the form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on <a href="www.dfs.delhigovt.nic.in">www.dfs.delhigovt.nic.in</a>.
- 8. The owner/ occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its expiry.

## INSPECTION REPORT

 Name & address of the building: M/s Haldiram Products Pvt. Ltd. Located at Shop No 11A, Ground Floor, Pusa Road, Karol Bagh, New Delhi.

2. Type of Occupancy: Class-D (Assembly)(At Ground Floor in a building comprised of Basement, Ground + 3 Upper Floors)

3. Type of Case

: Renewal

 Details of previous NOC: F6/DFS/MS/EH/2021/SZ/312, dated 28/10/2021

Basement=Office(Now vacant)

G.F= Haldiram

F.F= Institute S.F=Shops

T.F - Restaurant

5. Fire Safety directives L. No. :Nil

6. Date of inspection

: 28/10/2024

7. Name of the Inspecting Officer; ADO (DWK)

8. Name and designation of Officer from the building side Sh. Sudhir Sharma (Licensing Officer)

9. Year of Construction.

: 2021

10. Applicant's letter No.: 2024100415207, dated 04/10/2024

S No	Minimum standards on fire prevention and fire safety U/I		As per N/3 & N/3	1, N/2	Provided at site	Remarks MR/NMR	
1.	Access of building	Legiturgivi		Provided	MR		
	Road width     Gate width	1,20	06 mtr	Din	ectly accessible fro	m road MR	
		100	CONTRACT CON		NA	NA	
	Width of internal road		NA	0.21	NA .	1.00	
2.	Number, width, Type & Arra	s of exits		1.0			
	<ul> <li>a. Number of staircases</li> </ul>	•	NA	Dectaurant runi	ning at GF only		
	Upper floors     Basements		NA		Restaurant run	ning at GF only	
		NA .	NA	Restaurant run	Las and some time to the		
	b. Width of staircases			TATA	Doctourant r	unning at GF only	
	<ul> <li>Upper floors</li> <li>Basements</li> <li>Protection of exits</li> </ul>		NA			nning at GF only	
		NA	NA	Restaurant	unning at Of only		
	Fire check door				150	NA NA	
	Pressurization     d. No of continuous staircase to terrace     e. Width Of Corridor		NA		NA	NA NA	
		NA		NA MA	NA NA		
		NA		NA	NA NA		
		NA		NA			
	f. Door Size		2m & 1.5m		Provided MI	K .	
3.	Compartmentation		P 1,	Magua	L. 10234	VO	
3.	Fire check door	Required		Provided	MR		
	Sealing of electrical s	hafts	NA		NA	NA	
	Fire Rating of shaft department of the shaft depa	NA		NA .	NA		
140	<ul> <li>Water Curtain</li> </ul>	. NA		NA	NA NA		
	Fire Dampers  Sustam		NA		NA	NA.	
						de la min	
4.	Smoke managements System  Basements NA  12 a/a				NA	NA YY	
			per hour	Med	chanical ventilation	1/0	
	<ul> <li>Upper floors</li> </ul>	12 00	per nour	1,100	Jimilear Ventration	ii iviii	

	Fire Extinguishers											
	Total numbers 6 nos.			Pro	ovided					MR		
	1		CO2	Pro	vided					MR		
	IS marking	ISI ma	rked	Pro	vided					MR		
6.	First - Aid Hose Reel											
	Total numbers on each floor			01 No Provided						MR		
	Length of hose reel hose		30 n		F1 /	Pı	rovided			MR		
	<ul> <li>Nozzle diameter</li> </ul>		5	mm		2002	ovided	7.5		MR	•	
7.	Automatic fire detection and alarming			20070		- 1	0.1000	6				
	Type of detectors		Smoke Provided				rided		М	R		
	Location of Main Panel		Required with in			Provided			M			
			restaurant area		•	Trovided						
	<ul> <li>Location of Repeater</li> </ul>		NA				NA			NA	V - 1	
	<ul> <li>Alternate source of p</li> </ul>	ower	Required				25000 -01	2500 500		MR		
	<ul> <li>Hooters' Location</li> </ul>		Requ	Illib tota			The series of the	Provided		MR		
	MOEFA	MOFFA			•		Provided Provided					
	Public Address System		Requi			Provid	(Care All All All All All All All All All Al	7.4.3.5.5		MR		
0.	Automatic Sprinkler System		requi	ıcu		TIOVIC	ucu		M	IX .		
270	Basements	T		NA				Provided	I	NA		
	Upper Floor     Sprinkler above false ceiling		NA		A		Provided NA		<b>d</b> 1	NA		
										NA		
1,	Internal Hydrants:							574.4		. 1/1		
	Number of hydrants per floor     Hose Box		100 m	m	T	150 mr	n	MI	2		*	
			01 No.		Prov					-		
			01 No.				IVIIC				<u> </u>	
						Provided		· MR		+	· ·	
2.	Yard Hydrants							+				
			NA NA		VΑ	NA						
4			NA		N	NA		NA				
١.	Pumping Arrangements:					191					8	
	Ground Level			114								
	<ul> <li>Discharge of main pum</li> <li>Head of main pump</li> </ul>	7	IA	NA					NA		-	
	Number of main pumps		A	NA			NN.		NA			
	Jockey pump out put		A A	NA					NA			
	Jockey pump head		A	NA NA					NA		Spy II _ N.	
10	Standby Pump out put	N		NA NA		-			NA			
	> Auto Staring/Manual stopping N				NA				NA NA			
			NA NA		NA				NA NA		V	
					NA				NA	- N		
	Terrace level								1	1		
		45	1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 -		Provid	rided		MR				
	Discharge of pump	-			Provided				MR	145		
	<ul> <li>Discharge of pump</li> <li>Head of the pump</li> <li>Power supply</li> </ul>	40	Sept.		-	4.00	THE STATE OF THE S					
	<ul><li>Discharge of pump</li><li>Head of the pump</li></ul>	40 Re	quired		Provid				MR	1		
	<ul> <li>Discharge of pump</li> <li>Head of the pump</li> <li>Power supply</li> </ul>	40 Re	Sept.		-		•		MR MR			
	<ul> <li>Discharge of pump</li> <li>Head of the pump</li> <li>Power supply</li> <li>Auto starting of pump</li> </ul>	Re Re	quired		Provid				049-9-042		_ ^ A	
	<ul> <li>Discharge of pump</li> <li>Head of the pump</li> <li>Power supply</li> <li>Auto starting of pump</li> </ul> Captive water Storage for fire fig <ul> <li>Under ground tank capac</li> </ul>	40 Re Re	quired quired		Provid Provid	ed	•		049-9-042		_	
	<ul> <li>Discharge of pump</li> <li>Head of the pump</li> <li>Power supply</li> <li>Auto starting of pump</li> </ul> Captive water Storage for fire fig <ul> <li>Under ground tank capac</li> <li>Draw off connection</li> </ul>	40 Re Re shting:	quired quired		Provide Provide NA	ed		NA	049-9-042			
	<ul> <li>Discharge of pump</li> <li>Head of the pump</li> <li>Power supply</li> <li>Auto starting of pump</li> </ul> Captive water Storage for fire fig <ul> <li>Under ground tank capac</li> <li>Draw off connection</li> <li>Fire service inlet</li> </ul>	A0 Re Re phting: ity NA NA	quired quired		Provide Provide NA NA	ed	*	NA	049-9-042			
. (	<ul> <li>Discharge of pump</li> <li>Head of the pump</li> <li>Power supply</li> <li>Auto starting of pump</li> </ul> Captive water Storage for fire fig <ul> <li>Under ground tank capac</li> <li>Draw off connection</li> <li>Fire service inlet</li> <li>Access to tank</li> </ul>	40 Re Re shting:	quired quired		Provide Provide NA NA NA	ed		NA NA	049-9-042			
	<ul> <li>Discharge of pump</li> <li>Head of the pump</li> <li>Power supply</li> <li>Auto starting of pump</li> </ul> Captive water Storage for fire fig <ul> <li>Under ground tank capac</li> <li>Draw off connection</li> <li>Fire service inlet</li> <li>Access to tank</li> <li>Overhead Tank capacity</li> </ul>	ty NA NA NA	quired quired		Provide Provide NA NA NA NA	ed		NA NA NA	049-9-042			
E	<ul> <li>Discharge of pump</li> <li>Head of the pump</li> <li>Power supply</li> <li>Auto starting of pump</li> </ul> Captive water Storage for fire fig <ul> <li>Under ground tank capac</li> <li>Draw off connection</li> <li>Fire service inlet</li> <li>Access to tank</li> </ul>	thting: ity NA NA NA NA 20,	quired quired		Provide Provide NA NA NA	rided		NA NA	049-9-042			

/	Pressurization of lift lobby	NA	NA	NA	
/	Communication in lift Car Fireman's Grounding Switch Lift Signage	NA	NA	NA	- 1
/		NA	NA	NA	
		NA	NA	NA	
/	Standby power supply	Required	Provided	MR	
Y	Refuge Area				
1	<ul><li>➤ Total area</li><li>➤ Location</li></ul>	NA NA NA			
		NA	NA	NA	
9.	Fire control room				
	<ul> <li>➢ Flow Switch Panel</li> <li>➢ PA System Panel</li> <li>➢ Battery backup</li> <li>➢ Building Floor Plans</li> </ul>	NA	NA	NA	
		NA	· NA	NA	
		NA	NA	NA	
		NA	NA	NA	
		NA	NA	NA	
).	Special Fire Protection Systems for Protection of special Risks, if any;	Required	02 ABC type fire ex found provided near	MR	

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

In view of the deemed compliance of minimum standards on fire prevention and fire safety as required under the rules the FSC issued vide letter No F6/DFS/MS/EH/2021/SZ/312, dated 28/10/2021 renewal under Rule 37 of the Delhi Fire Service Rules 2010 is recommended.

Signature of the Inspecting Officer

Name: Udai Vir Singh

Designation: ADO/DWK

Fo (52) As desmed

6 11 20ry

Director 1911/