GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE, CONNAUGHT PLACE

NEW DELHI

No. F6/DFS/MS/2024/GH 445

Dated: 06/11/2024

FIRE SAFETY CERTIFICATE

Certified that the building of M/s Hotel Gold Souk located at 7A/35, WEA Channa Market, Karol Bagh, New Delhi - 110005, in a building comprised of Basement, stilt + ground plus three upper floors using Basement (storage), stilt (parking & reception), ground & second floor (04 guest rooms each floor) first & third floor (05 guest rooms each floor), (Total=18 guest rooms) & a pantry for staff in temporary shed on terrace (now sealed/closed) was issued FSC vide Letter No. F6/DFS/MS/GH/SZ/2021/260, dated 27/07/21. The premises was re inspected by the officer concerned of this department on 02/11/2024 in the presence of Sh. Rajesh Kumar Jha (Occupier) and observed that all the fire prevention and fire safety arrangements provided in the premises found in good working condition. The premises have therefore deemed complied with the fire prevention and fire safety requirements in accordance with Rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class "Residential" (guest house) at ground & second floor (04 guest rooms each floor) first & third floor (05 guest rooms each floor), (Total=18 guest rooms) with effect from O6/11/2024 for a period of three years in accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under Rule 38 of the Delhi Fire Service Rules, 2010.

Issued on ...06./11/2024.. at New Delhi by.

Copy to:

- The Joint. Commissioner of Police (Lic), 1st Floor, Licensing Unit, Police Station, Defence Colony, New Delhi.
- 2. The Manager, M/s Hotel Gold Souk located at 7A/35, WEA Channa Market, Karol Bagh, New Delhi 110005.
- 3. The Executive Engineer (Building), MCD, Civic Centre, Minto Road, New Delhi for information w.r.t. the use of the basement.

Condition for the validity of fire safety certificate

- 1. Terrace floor shall not be used for any purpose as undertaking given by owner.
- 2. The stairs/ passage shall be kept clear from any obstruction & free from lock & key, as seen during the inspection otherwise the FSC shall be null & void.
- 3. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.
- 5. The trained staff should be available round the clock.
- 6. Any deviations w.r.t. construction shall be verified by the concerned building sanctioning agency.
- 7. The certificate may not be treated in any case for the regularization of the unauthorized construction, if any.
- 8. The basement shall be used as per building bye laws.
- 9. The owner/ occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its expiry.
- 10. The owner/occupier shall submit a declaration every year in the form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on www.dfs.delhigovt.nic.in

INSPECTION REPORT

 Name & address of the building: M/s Hotel Gold Souk located at 7A/35, WEA Channa Market, Karol Bagh, New Delhi - 110005

2. Type of Occupancy

:Residential (Guest house)

 Type of Case : Renewal (Running at Ground, 1st, 2nd & 3rd floor in a building comprised of Basement, Stilt + Ground + 3 Upper Floor) & a pantry for staff in temporary shed on terrace (now sealed/closed

4. Details of previous NOC: F6/DFS/MS/GH/SZ/2021/260, dated 27/07/21

5. Fire Safety directives Letter No.: Nil

Date of inspection

: 02/11/2024

7. Name of the Inspecting Officer: ADO (DWK)

8. Name and designation of Officer

from the building side

: Sh. Rajesh Kumar Jha (Occupier)

9. Year of Construction

: Before 2009-10

10. Applicant's letter No.

: 2024102115943, dated 21/10/2024

S No	Minimum standards on fire prevention and fire safety U/R		s pe	er N/16. & N/18	7 Tage	ovided e	100000000000000000000000000000000000000	Rema MR/N		
1.	Access of building	6 mtr			Provi	ded			MR	
	Road widthGate widthWidth of internal road		NA Direct access NA NA			ssible from road			MR NA	
2.	Number, width, Type & Arrang	gement	s o	exits		1		-		
	a. Number of staircases • Upper floors • Basements b. Width of staircases • Upper floors • Basements c. Protection of exits • Fire check door • Pressurization d. No of continuous staircase to terrace e. Width Of Corridor f. Door Size	01			01 02 Nos	MR (Being olds. MR		d case)		
		1.25n 1.25n	$\overline{}$	1.48-1 1.31m	.55m & 1.20i	m	MR (MR (Being old case MR (Being old case		
		1421			JA .		NA NA			
		NA 01			NA 01		MR			
		Old c	_		1.21m 0.86 m	N	IR (Be	ing ol	MR d case)	
3.	Compartmentation	NIA		N/					NA	
	 Fire check door Sealing of electrical shafts Fire Rating of shaft door 	NA NA			Sealed		NA			
		NA .			NA		NA			
		NA			NA		NA			
	Water CurtainFire Dampers	NA			NA		NA			

N/28

4.	Smoke management Basements	ner hou	per hour Provided			MR				
	Basements Upper floors	per hour Provided					MR			
5.	Fire Extinguishers	12 00	P 31 1100	1.01						
<i>J</i> .				20 Nos.		Provided		MR		
	Types			& CO2	C	CO ₂ & ABC Provided		MR		
	IS marking		Requi					MR		
6.	First - Aid Hose Red				n (1.1		MR			
	Total number	Control of the Contro		1,000 1 01	Provided Provided		MR			
	 Length of ho 	e	30 mtr	114			MR			
	Nozzle diam		5 MM	F	UTIMUS.					
7	Automatic fire detec		arming	ng system O detectors Provided				MR		
	Type of dete	CO detectors		755	Provided		MR			
	 Location of Main Panel 		Required		1	Flovided				
	Location of Repeater Panel		NA NA		A			NA		
	Alternate sou power	Requi	red D	DG set 125 KVA		MR				
	Hooters' Loc	NA		N/	NA		NA			
8.	MOEFA		Requi	red P	ovided			MR		
9.	Public Address Syst	em	Requi		ovided			MR		
10.	Automatic Sprinkler		1104-							
	Basements	2,000	Requi	red		Provided		MR		
	Upper Floor		NA	V.00 (11)		NA		NA		
	Sprinkler above false			NA NA				NA		
11.	ceiling Internal Hydrants:									
	Size of riser/	ner	NA		NA		NA			
	Number of hydrants per fl			AND		WORKSTON		NIA		
	Hose Box		NA NA		NA		NA			
12.	Yard Hydrants			INA		NA		NA		
	Total number	rof	NA	NA NA				NA		
	hydrants		752767	MA MA			-			
	Hose Box		NA NA					NA		
13.	Pumping Arrangeme	ents:	1000			1.636.9	*(11/1		
	Ground Level									
		Discharge of main pump				NA		NIA		
	 Head of main pump Number of main pumps 			NA NA		NA NA		NA		
			100	and the second s		NA NA		NA		
	> Jockey pump out put							NA		
	 Jockey pump head 			NA .		NA		NA		
	Standby Pump out put			NA		NA		NA		
	Standby Pump Head			NA		NA		NA		
				IA		NA		NA		
	stopping		N	NA		NA		NA		
	 Pump House Access Terrace level Discharge of pump Head of the pump 		N	NA _		NA		NA		
				11120						
			4			rovided		MR		
			4	0 mtrs	mtrs Provided					
	- rower supply	Power supply						MR		
	 Auto starting 	Auto starting of pump				rovided Provided		MR		
	B	or pump	F	Required	Prov	rided		MR		

Ja/

N/29

	Under ground tank capacity	111		NA	NA			
	Draw off connection	NA		NA	NA MR NA			
	Fire service inlet	Req	uired .	Provided				
	 Access to tank Overhead Tank capacity 	NA		NA				
		5000 ltr		Provided	MR			
15		quire	d Provided	-	MR			
16.	Provision of Lifts							
	Pressurization of Lift S.	haft	NA	NA	NA			
	Pressurization of lift lol	NA	NA	NA				
	Communication in lift 0	Required	Provided	MR				
	 Fireman's Grounding Switch 		NA	NA	Old lif			
	➤ Lift Signage		Required	Provided	MR			
			Required Provided		MR			
17.	Standby power supply Required							
18.	Refuge Area		NA	NA	NA			
	> Total area > Location		NA .	NA	NA			
10	Fire control room		NA					
19.	> Detector system panel	NA		NA	NA NA			
	> Flow Switch Panel	NA		NA	NA NA			
	PA Custom Panel			NA	NA NA			
	> PA System Panel	NA NA		NA	NA			
	Battery backupBuilding Floor Plans	NA		NA NA	NA NA			
20.	Special Fire Protection System Protection of special Risks, if	s for	NA	INA	10000			

The fire protection systems provided in the building were test checked and found

In view of the deemed compliance of minimum standards on fire prevention and fire functional at the time of inspection. safety as required under the rules the FSC issued vide letter No. F6/DFS/MS/GH/SZ/2021/260, dated 27/07/21 renewal under Rule 37 of the Delhi Fire Service Rules 2010 is recommended. If

approved the FSC may be issued.

Hole: - Photographs of undertaling are photod at

Signature of the Inspecting Officer

Name: Sh. Udaivir Singh Designation: ADO (DWK)