

## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: NEW DELHI-110001

F.6/DFS/MS/Metro/2024/SZ/ 65 8 No.

Dated: 04/11/2024

## FIRE SAFETY CERTIFICATE

Certified that the "Qutab Minar Metro Station Line-2" located at Gurgaon Corridor, New Delhi comprised of Ground Floor & platform was issued Fire Safety Certificate by this department vide letter no F6/DFS/MS/2022/SZ/08 dated 06.01.2022. The premise was re-inspected by the officer concerned of this department on 24/10/2024 in the presence of Mr. Omkar Kumar (Fire-inspector) and found that the said metro station building have deemed complied with the fire prevention and fire safety requirements in accordance with Rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class-D "Assembly Occupancy" (Metro Station) as above with effect from 04/11/2024 for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

Issued on 64 / 11 /2024 at New Delhi by

DELHI FIRE SERVICE

Copy to: -

1. Mr. Rajesh Aggarwal (GM/E&M) Delhi Metro Rail Corporation, Metro Bhawan, 13, Fire Brigade Lane, New Delhi-110001.

## Conditions for the validity of Fire Safety Certificate: -

- 1. All the fire safety arrangement provided therein shall be maintained in good working condition at all time as seen during inspection. Any loss of life property due to non-functional fire safety measures shall be at the responsibility of the management.
- 2. All the staff members must know the correct method of operation of fire fighting
- The basement shall be used strictly as per the provision of Building Bye Laws.
- The owner/occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 5. This fire safety certificate may not in any way be treated as regularization (Clause UBBL-2016) of unauthorized construction or alteration (Clause 1.4.3 of UBBL-2016), if any.
- 6. "The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six





## INSPECTION REPORT

1. Name & address of the building: Qutab Minar, Metro Station Line-2, Gurgaon Corridor, New Delhi.

2. Type of Occupancy : Assembly D-7 (Metro Station)

Type of Case :Renewal (Ground Level + Platform Level)
 Details of previous NOC : F6/DFS/MS/2022/SZ/08 dated 06.01.2022
 Fire Safety directives letter No : F6/DFS/MS/BP/2010/1303 dated 04.05.2010

6. Date of inspection : 24.10.2024

7. Name of the Inspecting Officers : Sh. Rajesh Kumar, ADO (BCP)

8. Name and designation of officers

from the building side : Mr. Omkar Kumar, Fire Inspector

9. Year of Construction :2010

10. Applicant's letter No. : DMRC/OADM/FIRE/NOC/L-2/2024/10/02 dated 04/10/2024

No	Minimum Standards on fire prevention and fire safety U/R 33	NBC Requirement		Remarks IR/NMR			
	Access to building						
	Road width	As per PWD	Provided	MR			
	Gate width	Required	Approx 06 mtr	MR			
	Width of internal road	As per NBC	6 mtr	MR			
:	Number, Width, Type & Arrangement of Exits						
	a. Number of staircases						
	Upper Floors	04nos Ground to platform	Provided	MR			
	Basements	NA	NA	NA			
	b. Width of staircases						
	Upper Floors concourse to platform	As per NBC	PF to CC- 3.55 mtr (02 Nos) 1.65 r (02 Nos) 02 -escalator (1 mtr each				
	Basements	NA	NA	NA			
	c. Protection of exits						
	Fire check door	Required	Provided	MR			
	Pressurization	NA	NA	NA			
	d. No. of continuous staircases to	02	Provided	MR			
	e. Width of Corridor	2 m	2 m	MR			
	f. Door Size	Required	1.9m	MR			
3	Compartmentation.	SC 11461R I	A TO DAY COMED BY				
	Fire check door	Required	Provided	MR			
	Sealing of electrical shafts	Required	Provided	MR			
	Fire Rating of shaft door	Required	Provided	MR			
	Water Curtain	NA	NA	NA			
	Fire Dampers	N/A	Total In the N/A	N/A			
4	Smoke Management System.		- Andrea - 1 (a) (-12)				
	Basements	30АСРН	NA	NA			
5	Upper floors Fire Extinguishers	12ACPH	NA	NA			
-	Total						
	Total numbers	24nos	24nos	MR			
L	Types	ISI marked	Provided	MR			





	IS marking	Required	Provided	M		
6	First-Aid Hose Reels.					
	Total numbers on each floor	04 - platform level	04 – platform level	MR		
	Length of hose reel hose	02 – concourse level	02 – concourse level 45m	MF		
	Nozzle diameter	45m		MF		
	140221C diameter	5mm	5mm	1411		
7	Automatic fire detection and alarming system.					
	Type of detectors	Smoke	Provided	MF		
	Location of Main Panel	Required	Provided NA	NA NA		
	Location of Repeater Panel	NA Provinced	Provided	MF		
	Alternate source of power	Required		MR		
	Hooters' Location	Required	Provided	MIR		
3	MOEFA	Required	Provided	MR		
)	Public Address System.	Required	Provided	MR		
0						
U	Automatic Sprinkler System.  Basement	NA NA	NA	NA		
		NA NA	NA	NA		
	Upper Floor		NA	NA		
11	Sprinkler above false ceiling NA NA NA  Internal Hydrants  NA NA NA  NA NA NA NA  NA NA NA NA  NA NA NA NA  NA NA NA NA  NA NA NA NA  NA NA NA NA  NA NA NA NA NA  NA NA NA NA NA NA  NA NA NA NA NA NA NA NA NA NA NA NA NA N					
1	Size of riser/down-comer	150mm	Provided	MR		
		Required	Platform each-02	MR		
	Number of hydrants per floor	Required	Concourse - 02 Platform each-02	MR		
	Hose Box	Required	Concourse - 02			
12	Yard Hydrants.					
-	Total number of hydrants	02 Nos	02 Nos	MR		
	Hose Box	02 Nos	02 Nos	MR		
13	Pumping Arrangements					
	> Ground Level					
	> Discharge of main Pump	1800 Lpm	1800 LPM	MR		
	> Head of Main pump	60 mtr	60m	MR		
	Number of main pumps	01	01	MR		
	> Jockey Pump out put	180 LPM	180 LPM	MR		
		60 m	60m	M/R		
	<ul> <li>Jockey pump head</li> <li>Standby Pump out put</li> </ul>	1800LPM	1800 LPM	MR		
		60 mtr	60m	MR		
	> Standby Pump Head	Required	Provided	MR		
	> Auto Starting/ Manual stopping	Required	Provided	MR		
	> Pump House Access					
	Terrace level	NA	NA	NA		
	> Discharge of pump	NA	NA NA			
	> Head of the pump	NA	NA NA	NA		
	➤ Power Supply			NA		
	> Auto Starting of pump	NA	NA	NA		
4	Captive Water Storage for fire fighting.					
	Underground tank capacity	50,000ltrs	50,000ltrs	MR		

Required

Required

Draw-off connection

Fire service inlet



Provided

Provided

MR

MR

4			ममृत मही	त्याव		
-	Access to tank	Required	Provided	MR		
	Overhead Tank capacity	NA	NA	NA		
5	Exit Signage.	Required	Provided	MR		
6	Provision of Lifts.					
	Pressurization of Lift Shaft	NA NA	NA	NA		
	Pressurization of Lift lobby	NA	NA	NA		
	Communication In lift Car	Required	Provided	MR		
	Fireman's Grounding Switch	Required	Provided	MR		
	Lift Signage	Required	Provided	MR		
7	Standby power supply	Required	Provided	MR		
8	Refuge Area.					
-	> Total Area	NA	NA	NA		
	> Location	NA	NA	NA		
19	Fire Control Room					
_	Detector System Panel	Required	Provided	MR		
	Flow Switch Panel	NA	NA	NA		
	PA System Panel	Required	Provided	MR		
	Battery backup	Required	Provided	MR		
	Building Floor Plans	NA	NA	NA		
20	Special Fire Protection Systems for Protection of special Risks, if any:	r Required	Provided	MR		

The fire protection system provided in the building were randomly checked and found functional at the time of inspection.

Keeping in view of the deemed compliance of the minimum standard on fire prevention and fire safety measures as required under the rules, the FSC issued vide letter no F6/DFS/MS/2022/SZ/08 dated 06.01.2022, renewal under rule 37 of the Delhi Fire Service rules, 2010 is recommended.

Accordingly, DFA is put up for approval and signature please.

Signature of the Inspecting Officer Name: Sh. Rajesh Kumar

Design: ADO (BCP)

(fo) (Ms) | Vmgs

is prilip for

210