C-205

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: NEW DELHI - 110001

No.F6/DFS/MS/NDZ/2024/ 681

Dated:-20/.11/2024

FIRE SAFETY CERTIFICATE

Certified that Russian Federation located at 25, Barakhamba Road, New Delhi comprised of 3 Basement + Lower Ground + Upper Ground + 10 Upper floors owned /occupied by Russian Federation was earlier granted FSC vide letter No F6/DFS/MS/NDZ/2021/481 dated 04/10/21. Now, the premises was re-inspected by the officers concerned of this department on dated 13/11/24 in presence of Sh. Amardeep Singh and found that the said premises has deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class -Business Building with effect from 20.11.4..... 2024 for period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

Issued on ... 20 at New Delhi by.

DIRECTOR Delhi Fire Service

Copy to:-

1. The Chief Architect, NDMC, Palika kendra, New Delhi.

2. The Estate Manager, Russian Federation at 25, Barakhamba Road, New Delhi.

Conditions for the validity of fire safety certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of

3. The trained fire fighting staff should be available round the clock.

4. Any deviation w.r.t. construction, electrical installation, set back area etc. shall be verified by the concerned building sanctioning authority.

5. This fire safety certificate may not be treated in any case for regularization of unauthorized

6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in

7. The means of escape such as staircase, passage way, exits, etc shall be kept unobstructed / unlocked for unhindered evacuation in case of an emergency. 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J'

[sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".

N151

INSPECTION REPORT

1. Name & address of the building:- Russian Federation, 25, Barakhamba

Road, New Delhi

2. Type of occupancy:- Business Building (3 Basement, L.Ground

+ upper ground +10 upper Floors)

3. Type of case:- Renewal

4. Details of previous FSC:- F6/DFS/MS/NDZ/2021/481 dated 04/10/21.

Fire safety directives No. F6/DFS/MS/2001/1617 dated

08/08/2001.

Date of inspection:- 13/11/24.

7. Name of the inspecting officer:- Sh. Ravinder Singh (ADO/CC) Sh. Rajinder Atwal (DO (CD)

Name & designation of officer
 From the building side:-

Sh. Amardeep, Estate Manager

9. Year of construction:-

Old

10. Applicant's letter No:-

Letter no. nil dated 21/10/24.

S.No.	Minimum Standards on fire Prevention and fire safety U/R 33	Requirements Existing fire safety arrangements	/ Provided at site	Remarks MR/NMR	
1.	Access to Building			н	
1) Road width	12 mtr.	35 mtr. /	MR	
2) Gate width	4.5 mtr.	7.50 mtr.	MR	
3)Width of internal road	06 mtr.	Provided	MR	
	lumber, Width Type & Arra		11011.000	1440	
A	. Number of staircases	J		+	
1	. Upper floors	03 Nos.	03 Nos.	MR	
	. Basements .	06 Nos.	06 Nos. /	MR	
В	. Width of staircase		00 1103.	IVIIC	
	. Upper floors	1.25 mtr.	1.25 x 2 & .90 mtr	MR	
	. Basements	1.25 mtr.	1.25 x 2 & .90 mtr. x 4	MR	
_	. Protection of exits		/		
	Fire check door	Required	Provided	MR	
	Pressurization	Required	Provided	MR	
	. No. of continuous staircase to terrace	02 no.	02no.	MR	
	. Width of corridor	1.5 mtr.	Provided	MR	
	Door size	1.25 mtr.	1.25 mtr.	MR	
	ompartmentation			T.IIC	
	Fire check door	Required	Provided	MR	
2)	Sealing of electrical shafts	Required	Provided	MR	
	Fire rating of shaft door	N/A	N/A	N/A	
	Water curtain	N/A	N/A	N/A	
	Fire Dampers	N/A	N/A	N/A	
. Sr	noke Management System			IWA	
	Basements	12 ACPH	Provided	MR	
	Upper floors	12 ACPH	Provided	MR	
	ire Extinguishers		1 201	1111	
	Total numbers	120 Nos.	130 Nos.	MR	
2)	Types	ABC & CO2	ABC & CO2	MR	
3)	ISI marking	ISI	Yes	MR	

70	1		
.,	1	[2	
N	ı	26	

. 1	First-Aid Hose Reel			0
	1) Total number of each floor			MR
) Length of Leng	2 no.	2 no.	MR
-	2) Length of hose reel hose	30 m	30 m	MR
	3) Nozzle diameter	5 mm	5 mm	
1.	Automatic Fire Detection & Ala	rming System		MR
	1) Type of detectors	Smoke	Provided	MR
	2) Location of main panel	Ground floor	Ground floor	MR
	3) Location of repeater panel	Security	Provided	11
		Room		MR
Γ	4) Alternate source of power	Required	Provided	MR
	5) Hooter's Location	Every floor	Every floor	MR
8.	MOEFA	Required	Provided	
9.	Public Address System	Required	Provided	MR
10.	Automatic Sprinkler System	1104		
10.	1) Basement	Required	Provided	MR
Į.	2) Upper floors	Required	Provided	MR
	3) Sprinkler above false ceiling	Required	Provided	MR
11	Internal Hydrants	required	1	
11.		150 mm.	150 mm.	MR
	1) Size of riser/down-comer		2 Nos.	MR
	2) Number of hydrants per floor	2 Nos.	2 Nos.	MR
	3) Hose box at each floor	Z NOS.	2 1103.	
12.		04 Nos.	04 Nos.	MR
	1) Total number of hydrants	04 Nos.	04 Nos.	MR
	2) Hose box	04 NOS.	04 1403.	
13.				
	1) Ground level	2050 1 534	2050 1 DV	MR
1	a) Discharge of main	2850 LPM	2850 LPM	MIK
	pump	150	150	MR
W.	 b) Head of main pump 	150 mtr.	150 mtr.	
1	c) Number of main pump	2 Nos.	2 Nos.	MR
	d) Jockey pump out put	280 LPM	280 LPM	MR
	e) Jockey pump head	150 mtr.	150 mtr.	MR
	f) Stand by pump output	2850 LPM	2850 LPM	MR
1	g) Stand by pump head	150 mtr.	150 mtr.	MR
	h) Auto starting/Manual	Required	Provided	MR
1	stopping			
	Terrace level			1
1	 a) Discharge of pump 	N/A	N/A	N/A
	b) Head of pump	N/A	N/A	N/A
	c) Power supply	N/A	N/A	N/A
	d) Auto starting of pump	N/A	N/A	N/A
14		ire Fighting		7
-	Under ground tank	3,00,000 ltr	s. 3,00,000 ltrs.	MR
	capacity	5. 5.		9
	a) Draw-off connection	Required	Provided	MR
	b) Fire service inlet	Required	Provided	MR
	c) Access to tank	Required	Provided	MR
	d) Over head tank capacity	25,000 ltrs.	. 25,000 ltrs. oprovided	MR





4	xit Signage.	Required	Provided	MR
- E	-ovision of Lines.			
+	a) Pressurization of lift	Required	Provided	MR
-	shaft b) Pressurization of lift	Required	Provided	MR
-	lobby (basement) c) Communication in	Required	Provided	MR
	lift car	Required	Provided	MR
	d) Fireman's switch	Required	Provided	MR
	e) Lift signage	Required	Provided	MR
	tand by Power Supply	N/A	Provided	N/A
	efuge Area		Provided	N/A
T	otal area location	N/A	11011404	
		Required	Provided	MR
F	ire Control Room	Required	Desvided	MR

Required

Required

Required

Required

Required

Special Fire Protection System for Protection of special

The fire protection systems provided in the building were randomly tested, checked and found functional at the time of inspection.

Keeping in view the compliance of the minimum standards on fire prevention and fire safety required under the rules the FSC issued vide letter no. F6/DFS/MS/NDZ/2021/481 dated 04/10/21, renewal under rule 35(6) of the Delhi Fire Service rules 2010, Accordingly, DFA is put up for kind perusal and signature please.

Signature of the Inspecting Officer

a) Detector system panel

b) Flow switch panel

c) PA system panel

e) Building floor plan

Risk, if any: Co2, ABC Type Extinquiser

d) Battery backup

Name :- Sh. Rajinder Atwal Designation :- DO (CD)

Signature of the Inspecting Officer

MR

MR

MR

MR

MR

MR

Provided

Provided

Provided

Provided

Provided

Name :- Sh. Ravinder Singh Designation: ADO (CC)

19.

20.